

## Product Compliance Statement


January 20, 2016

Molex is committed to managing the use of chemical substances in accordance with governmental regulations, industry standards, and customer-specific requirements in order to protect the environment. For each part listed, this document provides:

- **EU RoHS Compliance Status.** EU RoHS status is declared per Directive 2011/65/EU and its subsequent amendments. Homogeneous materials of parts that are compliant to this legislation have less than 0.1% by weight each of lead, mercury, hexavalent chromium, PBB, and PBDE, and 0.01% by weight of cadmium. In situations where an exemption applies, the preceding limits, corresponding to the exempted substance(s), may be higher.

Molex's sole liability for incorrectly certifying a product shall be either replacement of the Molex product or, alternatively and in the sole discretion of Molex, return of the purchase price paid for the relevant Molex product.

For additional information regarding Molex's environmental initiatives and further explanation of this information, please visit [www.molex.com](http://www.molex.com)



Joel F. Eurich  
Director, Global Environmental, Health & Safety (EH&S)

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>
10-18-1041	2.36mm Diameter Standard .093" Pin and Socket Header, Shrouded, 4 Circuits, 4 Male Terminals	Compliant
10-18-1061	2.36mm Diameter Standard .093" Pin and Socket Header, Shrouded, 6 Circuits, 6 Male Terminals	Compliant
1051330011	Micro-USB B Receptacle, Vertical, Surface Mount, Lead-Free	Compliant
10-89-7401	2.54mm Pitch C-Grid® Breakaway Header, Dual Row, Vertical, High Temperature, 40 Circuits, Tin (Sn) Plating, 2.72mm PC Tail Length	Compliant
15-24-4557	5.08mm Pitch Disk Drive Power Connection System Header, Vertical, Through Hole, 4 Circuits, Lead-Free, 2.12mm PC Tail Length, without PCB Locator Peg	Compliant
15-91-0080	2.54mm Pitch C-Grid® Header, Surface Mount, Dual Row, Vertical, 8 Circuits, 0.38µm Gold (Au) Selective Plating	Compliant
22-05-2031	KK® 254 Wire-to-Board Header, Single Row, Right Angle, 3 Circuits, PA Polyamide Nylon, Tin (Sn) Plating	Compliant
22-05-3041	KK® 254 Solid Header, Right Angle, with Friction Lock, 4 Circuits, Tin (Sn) Plating	Compliant
22-05-3061	KK® 254 Solid Header, Right Angle, with Friction Lock, 6 Circuits, Tin (Sn) Plating	Compliant
22-05-3081	KK® 254 Solid Header, Right Angle, with Friction Lock, 8 Circuits, Tin (Sn) Plating	Compliant
22-23-2031	KK® 254 Solid Header, Vertical, with Friction Lock, 3 Circuits, Tin (Sn) Plating	Compliant
22-23-2041	KK® 254 Solid Header, Vertical, with Friction Lock, 4 Circuits, Tin (Sn) Plating	Compliant
22-27-2031	KK® 254 Wire-to-Board Header, Vertical, with Friction Lock, 3 Circuits, Tin (Sn) Plating	Compliant
22-27-2041	KK® 254 Wire-to-Board Header, Vertical, with Friction Lock, 4 Circuits, Tin (Sn) Plating	Compliant
22-28-0020	KK® 254 Breakaway Header, Vertical, with Friction Lock, 2 Circuits, Tin (Sn) Plating	Compliant
22-28-4023	KK® 254 Breakaway Header, Vertical, 2 Circuits, 0.38µm Gold (Au) Selective Plating, Mating Pin Length 6.09mm	Compliant

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>
22-28-4033	KK® 254 Breakaway Header, Vertical, 3 Circuits, 0.38µm Gold (Au) Selective Plating, Mating Pin Length 6.09mm	Compliant
22-28-4063	KK® 254 Breakaway Header, Vertical, 6 Circuits, 0.38µm Gold (Au) Selective Plating, Mating Pin Length 6.09mm	Compliant
26-61-4030	KK® 396 Header, Vertical, Friction Lock, 3 Circuits, Gold (Au) Plating	Compliant
35363-0460	2.00mm Pitch Sherlock™ Wire-to-Board Header, Right Angle, with Positive Lock, 4 Circuits	Compliant
38760-0112	CB BTS STD 12 ASY	Compliant
39-28-1063	Mini-Fit® Jr. Vertical Header, 4.20mm Pitch, Dual Row, 6 Circuits, without Snap-in Plastic Peg PCB Lock, Tin, Natural	Compliant
39-28-1203	Mini-Fit® Jr. Vertical Header, 4.20mm Pitch, Dual Row, 20 Circuits, without Snap-in Plastic Peg PCB Lock, Tin, Natural	Compliant
39-29-1068	Mini-Fit® Jr. Header, Dual Row, Right Angle, with PCB Mounting Flange, 6 Circuits, PA Polyamide Nylon 6/6 94V-2, Tin (Sn) Plating	Compliant
43045-2012	Micro-Fit 3.0™ Vertical Header, 3.00mm Pitch, Dual Row, 20 Circuits, with PCB Polarizing Peg, Tin, Glow Wire Compliant, Black	Compliant
43202-8817	Modular Jack, Right Angle, Low Profile, Shielded, Top Panel Grounding Tabs, without Bottom Grounding Tab, Front Position PCB Ground Tab, 8/8	Compliant
43650-0215	Micro-Fit 3.0™ Vertical Header, 3.00mm Pitch, Single Row, 2 Circuits, with PCB Polarizing Peg, Tin, Glow Wire Compliant, Black	Compliant
43650-0315	Micro-Fit 3.0™ Vertical Header, 3.00mm Pitch, Single Row, 3 Circuits, with PCB Polarizing Peg, Tin, Glow Wire Compliant, Black	Compliant
43650-0401	Micro-Fit 3.0™ Right Angle Header, 3.00mm Pitch, Single Row, 4 Circuits, with Snap-in Plastic Peg PCB Lock, Gold, Glow Wire Compliant, Black	Compliant
43650-0415	Micro-Fit 3.0™ Vertical Header, 3.00mm Pitch, Single Row, 4 Circuits, with PCB Polarizing Peg, Tin, Glow Wire Compliant, Black	Compliant

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>
43650-0416	Micro-Fit 3.0™ Vertical Header, 3.00mm Pitch, Single Row, 4 Circuits, with PCB Polarizing Peg, Gold, Glow Wire Compliant, Black	Compliant
43650-0615	Micro-Fit 3.0™ Vertical Header, 3.00mm Pitch, Single Row, 6 Circuits, with PCB Polarizing Peg, Tin, Glow Wire Compliant, Black	Compliant
43860-0010	Modular Jack, Right Angle, Low Profile, Inverted, Shielded, All Panel Grounding Tabs, Lightpipes, 8/8	Compliant
44248-0029	Modular Jack, Right Angle, Low Profile, Inverted, Lightpipes, 8/8, 2 Ports	Compliant
44248-0030	Modular Jack, Right Angle, Low Profile, Inverted, Lightpipes, 8/8, 4 Ports	Compliant
44914-0201	Micro-Fit CPI™ Header, Compliant Pin Interface, Dual Row, Vertical, 2 Circuits, Tin (Sn) Plating, Glow Wire Compatible	Compliant
44914-0401	Micro-Fit CPI™ Header, Compliant Pin Interface, Dual Row, Vertical, 4 Circuits, Tin (Sn) Plating, Glow Wire Compatible	Compliant
46765-0001		Compliant
500873-0806	1.10mm Pitch microSD* Memory Card Connector, Normal Mount Surface Mount	Compliant
502570-0893	1.10mm Pitch microSD* Memory Card Connector, Normal Mount Surface Mount, Push-Push Type	Compliant
52018-4416	Modular Jack Hsg Assy 4Ckt	Compliant
53047-0310	1.25mm Pitch PicoBlade™ Wire-to-Board Header, Vertical, with Friction Lock, 3 Circuits	Compliant
53109-0410	5.08mm Pitch Disk Drive Power Connection System Header, Right Angle, with Strap Standard Polarization, 4 Circuits	Compliant
53258-0229	3.50mm Pitch Header, Vertical, 2 Circuits, Brass (CuZn) Contact	Compliant
53258-0829	3.50mm Pitch Header, Vertical, 8 Circuits, Brass (CuZn) Contact	Compliant
53258-1029	3.50mm Pitch Header, Vertical, 10 Circuits, Brass (CuZn) Contact	Compliant
53398-0371	1.25mm Pitch PicoBlade™ Header, Surface Mount, Vertical, 3 Circuits	Compliant
68301-1010	2.54mm Pitch Header, Surface Mount, Single Row, Vertical, without Shroud, 4 Circuits, with 6.10mm Mating Pin Length	Compliant

**Table A**

Molex P/N	Part Description	RoHS Compliance Status
68301-1054	2.54mm Pitch Header, Surface Mount, Single Row, Vertical, without Shroud, 2 Circuits, with 6.10mm Mating Pin Length	Compliant
71430-0006	0.80mm Pitch Ultra+™ VHDCI Receptacle, Right Angle, with or without Enhanced Shield, 68 Circuits	Compliant with Exemption 6(c)
71430-0008	0.80mm Pitch Ultra+™ VHDCI Receptacle, Right Angle, with or without Enhanced Shield, 68 Circuits	Compliant with Exemption 6(c)
73101-0120	75 Ohms, BNC Right-Angle PCB Bulkhead Jack Receptacle with Board Locks, Low Profile	Compliant with Exemption 6(c)
73776-0201	0.80mm Pitch Ultra+™ VHDCI Receptacle, Vertical, SMT	Compliant with Exemption 6(b)
74337-0011	0.80mm Pitch Ultra+™ VHDCI Wire-to-Board Receptacle, Stacked, Right Angle, with Enhanced Shield, Version 1 Footprint, 136 Circuits	Compliant with Exemption 6(c)
75586-0011	0.80mm Pitch, iPass™ I/O Surface Mount Receptacle, Right Angle, External Application, 38 Circuit, 0.76µm Gold (Au), Supports QSFP14 / FDR	Compliant
78171-0004	Pico-EZmate™ Wire-to-Board Header, Vertical, Housing Height: 1.55mm, with side-Friction Locks, 4 Circuits	Compliant
87332-3420	2.00mm Pitch Milli-Grid™ Header, Surface Mount, Vertical, Shrouded, 34 Circuits, 0.38µm Gold (Au) Selective Plating, with Slot, Stand-off, with PCB Locator	Not Compliant
87831-1020	2.00mm Pitch Milli-Grid™ Header, Vertical, Through Hole, Shrouded, 10 Circuits, 0.38µm Gold (Au) Plating, Center Polarization Slot, without Locking Window, without PCB Locator, Tube	Compliant
87831-1620	2.00mm Pitch Milli-Grid™ Header, Vertical, Through Hole, Shrouded, 16 Circuits, 0.38µm Gold (Au) Plating, Center Polarization Slot, with Locking Windows, without PCB Locator, Tube	Compliant
87831-4020	2.00mm Pitch Milli-Grid™ Header, Vertical, Through Hole, Shrouded, 40 Circuits, 0.38µm Gold (Au) Plating, Center Polarization Slot, with Locking Windows, without PCB Locator, Tube	Compliant
87832-1020	Milli-Grid™ Header, Surface Mount, Vertical, Shrouded, Lead-Free, 10 Circuits, 0.38µm Gold (Au) Plating, without Locking Window, with Centre Polarization Slot, PCB Locator, Tube	Compliant

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>
87832-1620	Milli-Grid™ Header, Surface Mount, Vertical, Shrouded, Lead-Free, 16 Circuits, 0.38µm Gold (Au) Plating, with Locking Windows and Centre Polarization Slot, PCB Locator, Tube	Compliant
87833-0831	Milli-Grid™ Header, Right Angle, Shrouded, Lead-Free, 8 Circuits, 0.38µm Gold (Au) Plating, without PCB Locator, with Locking Window, without Center Polarization Slot, Tube	Compliant
87833-1420	Milli-Grid™ Header, Right Angle, Shrouded, Lead-Free, 14 Circuits, 0.38µm Gold (Au) Plating, without PCB Locator, with Locking Windows, Center Polarization Slot, Tube	Compliant
87898-0204	C-Grid® / SL™ Header, Surface Mount, Breakaway, Vertical, 2 Circuits, 0.38µm Gold (Au) Plating, Tray Packaging, without Cap, Lead-Free	Compliant
90059-0009	2.54mm Pitch C-Grid® Micro Shunt, Low Profile, 0.381µm Select Gold (Au) with Gold (Au) Flash Plating	Compliant