

# **Product Compliance Declaration**

Please see <a href="https://www.molex.com">www.molex.com</a> for the most up-to-date information.

#### **Contact Information**

Name Molex Product Compliance E-Mail Product.Compliance@molex.com

#### **Part Information**

Part Number 0026624030 Part Weight 0.934G

Part Name KK 156 Hdr Assy FrLk 03 Ckt Tin

# **Product Composition**

Name	Туре	CAS Number	Proportion (% Total)	Mass (Grams)
KK 156 Hdr Assy FrLk 03 Ckt Tin	Assembly		100	0.934
KK.045 Sq Pin Bando .720 (197) Sn	Assembly		40.257	0.376
KK.045 Sq Pin Bando .720 (999) unplt	Component		39.4004	0.368
Cartridge Brass 70% Unplated	Material		39.4004	0.368
Copper	Substance	7440-50-8	27.5803	0.2576
Zinc (metal)	Substance	7440-66-6	11.8201	0.1104
Tin Plating	Material		0.3854	0.0036
Tin	Substance	7440-31-5	0.3854	0.0036
Nickel Plating	Material		0.4711	0.0044
Nickel	Substance	7440-02-0	0.471	0.0044
Further Additives	Substance	system	5E-5	4E-7
KK 156 Header FrLk 03 Ckt	Component		59.743	0.558
PBT GF NATURAL	Material		59.743	0.558

#### Form Rev - F

Limitation of this Product Compliance Declaration: This declaration is based on the state of knowledge and belief of Molex as of the date that it is provided. Molex bases its knowledge and belief on information provided by numerous sources, including third parties, and in certain circumstances laboratory test results. Molex has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and substances. Molex represents that to the best of its knowledge that the information provided in this declaration is accurate. Molex's sole liability shall be to either replace the product or refund the purchase price of the product if it does not meet the requirement of this declaration.

Name	Туре	CAS Number	Proportion (% Total)	Mass (Grams)
PBT	Substance		38.4062	0.358714
Antimonytrioxide	Substance	1309-64-4	3.4992	0.032683
Flame Retardant, ISO 1043-4 FR(17)	Substance		13.2288	0.123557
Further Additives	Substance	system	0.5121	0.004783
GF-Fiber	Substance		4.0967	0.038263

#### **ROHS Declaration Information**

Regulatory Revision 2011/65/EU

Compliance Status Compliant

**Contained Substances Exceeding Threshold** 

None

**Exemptions** 

None

# **REACH-SVHC Declaration Information**

Regulatory Revision ED/30/2017 (7 July 2017)

**Contained Substances Exceeding Threshold** 

None

#### **GADSL Declaration Information**

Regulatory Revision GADSL imported from IMDS

# **Contained Substances Exceeding Threshold**

Substance Group	Substance Location	Threshold (PPM)	Concentration (PPM)	Intentionally Added
Lead	Cartridge Brass 70% (CA260)	*Note	350	Yes
Lead	e-plate Sn (electrodeposited Tin	*Note	150	Yes

#### Form Rev - F

Limitation of this Product Compliance Declaration: This declaration is based on the state of knowledge and belief of Molex as of the date that it is provided. Molex bases its knowledge and belief on information provided by numerous sources, including third parties, and in certain circumstances laboratory test results. Molex has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and substances. Molex represents that to the best of its knowledge that the information provided in this declaration is accurate. Molex's sole liability shall be to either replace the product or refund the purchase price of the product if it does not meet the requirement of this declaration.

Substance Group	Substance Location	Threshold (PPM)	Concentration (PPM)	Intentionally Added
Antimonytrioxide	PBT GF NATURAL	*Note	70,000	Yes
Nickel	Ep-Ni	*Note	997,500	Yes
Copper	Cartridge Brass 70% (CA260)	*Note	700,000	Yes
Glass fibres	PBT GF NATURAL	*Note	80,000	Yes

<sup>\*</sup>Note: For GADSL substance declarable/prohibited threshold values, please reference http://www.gadsl.org/

## **Exemptions**

Part Name	Exemption
Cartridge Brass 70% (CA260)	44 Concentration within acceptable GADSL limits
e-plate Sn (electrodeposited Tin Coatings, bright and matt)	44 Concentration within acceptable GADSL limits
Ep-Ni	33 Other application (Surface not routinely touched or nickel release rate < 0.5µg/cm2/week)

# **HFLH Declaration Information**

Regulatory Revision IEC 61249-2-21

## **Contained Substances Exceeding Threshold**

Substance Group	Substance Location	Threshold (PPM)	Concentration (PPM)	Intentionally Added
Bromine and its compounds	PBT GF NATURAL	900	250,000	Yes
Bromine and Chlorine combined	PBT GF NATURAL	1,500	250,000	Yes

## **China ROHS Declaration Information**

Part Number	0026624030							
Part Name	KK 156 Hdr Assy FrLk 03 Ckt Tin	<del>(e)</del>						
Part Information	n			Ha	zardous \$	Substance	es	
Components			Lead	Mercury	Cadmium	Hex. Chromium	PBB	PBDE
KK 156 Hdr A	ssy FrLk 03 Ckt Tin		0	0	0	0	0	0
KK.045 Sq Pii	n Bando .720 (197) Sn		0	0	0	0	0	0

#### Form Rev - F

Limitation of this Product Compliance Declaration: This declaration is based on the state of knowledge and belief of Molex as of the date that it is provided. Molex bases its knowledge and belief on information provided by numerous sources, including third parties, and in certain circumstances laboratory test results. Molex has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and substances. Molex represents that to the best of its knowledge that the information provided in this declaration is accurate. Molex's sole liability shall be to either replace the product or refund the purchase price of the product if it does not meet the requirement of this declaration.

Components	Lead	Mercury	Cadmium	Hex. Chromium	PBB	PBDE
KK.045 Sq Pin Bando .720 (999) unplt	0	0	0	0	0	0
KK 156 Header FrLk 03 Ckt	0	0	0	0	0	0

# **Process Information**

Component Plating / Surface Finish	MSn-RNi
Termination Base Alloy	Brass
Solder Alloy	N/A
Process Capability	WAVE
Maximum Exposure Time (seconds)	005
Maximum Process Temperature (C)	235
Maximum Cycles at Reflow Temperature	001
J-STD-020 Moisture Sensitivity Level	N/A

Sep 6, 2017