

## Product Compliance Statement

February 04, 2018

Molex is committed to managing the use of chemical substances in accordance with governmental regulations, industry standards, and customer-specific requirements in order to protect the environment. For each part listed, this document provides:

- **EU RoHS Compliance Status.** EU RoHS status is declared per Directive 2011/65/EU and its subsequent amendments. Homogeneous materials of parts that are compliant to this legislation have less than 0.1% by weight each of lead, mercury, hexavalent chromium, PBB, and PBDE, and 0.01% by weight of cadmium. In situations where an exemption applies, the preceding limits, corresponding to the exempted substance(s), may be higher.

Molex's sole liability for incorrectly certifying a product shall be either replacement of the Molex product or, alternatively and in the sole discretion of Molex, return of the purchase price paid for the relevant Molex product.

For additional information regarding Molex's environmental initiatives and further explanation of this information, please visit [www.molex.com](http://www.molex.com)



Haim Eliyahu  
Manager, Global Product Compliance

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>
5011903017	1.00mm Pitch Pico-Clasp Wire-to-Board Header, Surface Mount, Dual Row, Vertical, 0.10µm Gold Plated, with Inner Positive Lock, with Pick-and-Place Tape, 30 Circuits	Compliant
5033981892	1.10mm Pitch microSD Memory Card Connector, Normal Mount Surface Mount, Push-Push Type, 1.28mm Height	Compliant
5037722410	0.40mm Pitch SlimStack B8 Board-to-Board Receptacle, Surface Mount, Dual Row, Vertical, 0.80mm Stacking Height, 24 Circuits	Compliant
5037762410	0.40mm Pitch SlimStack B8 Board-to-Board Plug, Surface Mount, Dual Row, Vertical, 0.80mm Stacking Height, 24 Circuits	Compliant
432238122	Modular Jack, Right Angle, Low Profile, 8/8, 2 Ports	Compliant
878330631	Milli-Grid Header, Right Angle, Shrouded, Lead-Free, 6 Circuits, 0.38µm Gold (Au) Plating, without PCB Locator, with Locking Window, without Center Polarization Slot, Tube	Compliant
5052781533	0.50mm Pitch Easy-On FFC/FPC Connector, 1.90mm Height, Single Bottom Contact (FS19), Right Angle, Surface Mount, ZIF, 15 Circuits	Compliant
2005280060	1.00mm Pitch Easy-On FFC/FPC Connector, 1.90mm Height, Double Bottom Contact Type (FD19 Series), Right Angle, Surface Mount, ZIF, 6 Circuits	Compliant