

# **Product Compliance Declaration**

Please see www.molex.com for the most up-to-date information.

**Contact Information** 

Name Molex Product Compliance E-Mail Product.Compliance@molex.com

**Part Information** 

Part Name 2.54mm KK Hdr RA FricLK 5Sn 3Ckt

## **Product Composition**

| Name                                     | Туре      | CAS Number | Proportion<br>(% Total) | Mass<br>(Grams) |
|--|-----------|------------|-------------------------|-----------------|
| 2.54mm KK Hdr RA FricLK 5Sn 3Ckt         | Assembly  |            | 100                     | 0,456012        |
| .740 x .0261 Sq Brass Bando Pin Tin      | Assembly  |            | 44,7383                 | 0,204012        |
| .740 x .0261 Sq Brass Bando Pin Unplated | Component |            | 43,4199                 | 0,198           |
| Cartridge Brass 70% Unplated             | Material  |            | 43,4199                 | 0,198           |
| Copper                                   | Substance | 7440-50-8  | 30,3939                 | 0,1386          |
| Zinc (metal)                             | Substance | 7440-66-6  | 13,026                  | 0,0594          |
| Tin Plating                              | Material  |            | 0,5948                  | 0,002712        |
| Tin                                      | Substance | 7440-31-5  | 0,5948                  | 0,002712        |
| Nickel Plating                           | Material  |            | 0,7237                  | 0,0033          |
| Nickel                                   | Substance | 7440-02-0  | 0,7236                  | 0,0033          |
| Further Additives                        | Substance | system     | 7E-5                    | 3E-7            |
| KK100 FR LOCK WAFER 6410-03 3 CKT        | Component |            | 55,2617                 | 0,252           |
| PA66 UF WHITE                            | Material  |            | 55,2617                 | 0,252           |

Form Rev - F

Limitation of this Product Compliance Declaration: This declaration is based on the state of knowledge and belief of Molex as of the date that it is provided. Molex bases its knowledge and belief on information provided by numerous sources, including third parties, and in certain circumstances laboratory test results. Molex has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and substances. Molex represents that to the best of its knowledge that the information provided in this declaration is accurate. Molex's sole liability shall be to either replace the product or refund the purchase price of the product if it does not meet the requirement of this declaration.

| Name                               | Туре      | CAS Number | Proportion<br>(% Total) | Mass<br>(Grams) |
|------------------------------------|-----------|------------|-------------------------|-----------------|
| PA66                               | Substance |            | 46,9724                 | 0,2142          |
| Further Additives                  | Substance | system     | 2,7631                  | 0,0126          |
| Flame Retardant, ISO 1043-4 FR(30) | Substance |            | 5,5262                  | 0,0252          |

## **ROHS Declaration Information**

Regulatory Revision EU 2015/863

Compliance Status Compliant

**Contained Substances Exceeding Threshold** 

None

**Exemptions** 

None

## **REACH-SVHC Declaration Information**

Regulatory Revision ED/71/2019 (16 July 2019)

**Contained Substances Exceeding Threshold** 

None

## **GADSL Declaration Information**

Regulatory Revision GADSL imported from IMDS

## **Contained Substances Exceeding Threshold**

| Substance Group | Substance Location  | Threshold<br>(PPM) | Concentration (PPM) | Intentionally<br>Added |
|-----------------|---|--------------------|---------------------|------------------------|
| Lead            | Cartridge Brass 70% (CA260)                                 | *Note              | 350                 | Yes                    |
|                 | e-plate Sn (electrodeposited Tin Coatings, bright and matt) | *Note              | 150                 | Yes                    |
| Nickel          | Ep-Ni   | *Note              | 997,500             | Yes                    |
| Copper          | Cartridge Brass 70% (CA260)                                 | *Note              | 700,000             | Yes                    |

#### Form Rev - F

Limitation of this Product Compliance Declaration: This declaration is based on the state of knowledge and belief of Molex as of the date that it is provided. Molex bases its knowledge and belief on information provided by numerous sources, including third parties, and in certain circumstances laboratory test results. Molex has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and substances. Molex represents that to the best of its knowledge that the information provided in this declaration is accurate. Molex's sole liability shall be to either replace the product or refund the purchase price of the product if it does not meet the requirement of this declaration.

\*Note: For GADSL substance declarable/prohibited threshold values, please reference http://www.gadsl.org/

## **Exemptions**

| Part Name   | Exemption  |
|---|--|
| Cartridge Brass 70% (CA260)                                 | 44 Concentration within acceptable GADSL limits  |
| e-plate Sn (electrodeposited Tin Coatings, bright and matt) | 44 Concentration within acceptable GADSL limits  |
| Ep-Ni   | 33 Other application (Surface not routinely touched or nickel release rate < 0.5µg/cm2/week) |

## **HFLH** Declaration Information

Regulatory Revision IEC 61249-2-21

## **Contained Substances Exceeding Threshold**

None

## **China ROHS Declaration Information**

| Part Number 0022057038                     |            |      |         |           |                  |     |      |
|--|------------|------|---------|-----------|------------------|-----|------|
| Part Name 2.54mm KK Hdr RA FricLK 5Sn 3Ckt | <b>(e)</b> |      |         |           |                  |     |      |
| Part Information                           |            |      | Ha      | zardous S | Substance        | s   |      |
| Components                                 |            | Lead | Mercury | Cadmium   | Hex.<br>Chromium | PBB | PBDE |
| 2.54mm KK Hdr RA FricLK 5Sn 3Ckt           |            | 0    | 0       | 0         | 0                | 0   | 0    |
| .740 x .0261 Sq Brass Bando Pin Tin        |            | 0    | 0       | 0         | 0                | 0   | 0    |
| .740 x .0261 Sq Brass Bando Pin Unplated   |            | 0    | 0       | 0         | 0                | 0   | 0    |
| KK100 FR LOCK WAFER 6410-03 3 CKT          |            | 0    | 0       | 0         | 0                | 0   | 0    |

# **Process Information**

| Component Plating / Surface Finish | MSn-RNi |
|------------------------------------|---------|
| Termination Base Alloy             | Brass   |
| Solder Alloy                       | N/A     |
| Process Capability                 | WAVE    |

Form Rev - F

Limitation of this Product Compliance Declaration: This declaration is based on the state of knowledge and belief of Molex as of the date that it is provided. Molex bases its knowledge and belief on information provided by numerous sources, including third parties, and in certain circumstances laboratory test results. Molex has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and substances. Molex represents that to the best of its knowledge that the information provided in this declaration is accurate. Molex's sole liability shall be to either replace the product or refund the purchase price of the product if it does not meet the requirement of this declaration.

| Maximum Exposure Time (seconds)      | 005 |
|--------------------------------------|-----|
| Maximum Process Temperature (C)      | 235 |
| Maximum Cycles at Reflow Temperature | 001 |
| J-STD-020 Moisture Sensitivity Level | N/A |

Oct 22, 2019