

Product Compliance Statement

March 04, 2020

Molex is committed to managing the use of chemical substances in accordance with governmental regulations, industry standards, and customer-specific requirements in order to protect the environment. For each part listed, this document provides:

- **EU RoHS Compliance Status.** EU RoHS status is declared per Directive 2011/65/EU and its subsequent amendments, including the Directive EU 2015/863 which additionally prohibited four phthalates. Homogeneous materials of parts that are compliant to this legislation have less than 0.1% by weight each of lead, mercury, hexavalent chromium, PBB, PBDE, DBP, BBP, DIBP, DEHP, and 0.01% by weight of cadmium. In situations where an exemption applies, the preceding limits, corresponding to the exempted substance(s), may be higher.

- **EU REACH SVHC Content.** Substances of Very High Concerns (SVHCs) are declared if above 0.1% of the article per Regulation (EC) No. 1907/2006 and its subsequent amendments. The Candidate List of SVHCs is continually updated at <https://echa.europa.eu/candidate-list-table>.

- **Low-Halogen Status.** Homogeneous materials of parts that are considered Low-Halogen have less than 0.09% by weight each of bromine and chlorine, and less than 0.15% by weight of the sum of bromine and chlorine.

Molex's sole liability for incorrectly certifying a product shall be either replacement of the Molex product or, alternatively and in the sole discretion of Molex, return of the purchase price paid for the relevant Molex product.

For additional information regarding Molex's environmental initiatives and further explanation of this information, please visit www.molex.com



Haim Eliyahu
Director, Global Product Stewardship

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1511194112	2.00mm Pitch, Milli-Grid PCB Header, Dual Row, Right-Angle, Through Hole, 0.05µm Gold (Au) Plating, without Peg, 3.60mm PC Tail Length, without Pick and Place Tape, 12 Circuits, Glow-Wire Capable, Tube	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Low-Halogen
0936000073	GWconnect Metal Adapter, Male Pg11 Thread to Female 3/8" NPT Thread	Compliant	Not Contained Per -ED/71/2019 (16 July 2019)	Not Reviewed
0936012613	GWconnect STD - Standard, Single Lever Hood, Die-cast Aluminum, with 2 Pegs, Top Entry, Size 16B «77x27», Pg29 Thread, High Construction, Grey	Not Reviewed	Not Reviewed	Not Reviewed
0936010779		Not Reviewed	Not Reviewed	Not Reviewed
1060253000	LC Duplex Connector, Multimode, 128µm Ceramic Ferrule, 1.60mm Duplex Cable, Beige Housing, Straight	Compliant	Not Contained Per -ED/71/2019 (16 July 2019)	Not Low-Halogen
0438794000	Mini-Fit BMI Header Compliant Pin Interface, Dual Row, Vertical, 6 Circuits, Circuit 1 Voided, 2.54µm Tin (Sn) over Nickel Plating	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Not Low-Halogen
0936000474	GWconnect Plastic Nut, Polyamide, Pg9 Thread, Light Grey RAL 7035	Compliant	Not Contained Per -ED/71/2019 (16 July 2019)	Not Reviewed
1060535100	FC Connector, Singlemode, 126µm Ferrule, 1.60mm / 2.00mm Cable Diameter, Yellow Boot	Compliant with Exemption 6(c)	Not Contained Per -ED/01/2018 (15 January 2018)	Not Low-Halogen
0936000124	GWconnect Plastic Spiral Top Gland, with Gasket and Nut, M12x1.5 Thread, Grey RAL 7001	Compliant	Not Reviewed	Not Reviewed
0150221050	0.50mm Pitch Premo-Flex LVDS Jumper, 0.25m Cable Length, Gold Plated, 50 Circuits	Compliant	Not Contained Per -ED/88/2018 (15 January 2019)	Not Low-Halogen
1060533000	FC Connector, Multimode, 128µm Ferrule, 3.00mm Cable Diameter, Metal Coupling Nut, Black Boot	Compliant with Exemption 6(c)	Contained Per - ED/88/2018 (15 January 2019)	Not Low-Halogen
1552300168	Flamar Control Cable, PUR Jacket, Unshielded, 3 Circuits, 1.00mm² with Green-Yellow Ground / 18 AWG with Green-Yellow Ground, 7.10mm (.280") Diameter, 1000.0m (3280.83') Length, Gray	Compliant	Not Reviewed	Not Reviewed
1552110025	Flamar Sensor Cable, PVC Jacket, Braided Shielding Overall, 5 Circuits, 0.34mm² / 22 AWG, 6.10mm (.240") Diameter, 300.0m (984.25') Length, Black	Not Reviewed	Not Reviewed	Not Reviewed

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1552200069	Flamar Sensor Cable, WSOR Jacket, Unshielded, 4 Circuits, 0.34mm ² / 22 AWG, 5.10mm (.201") Diameter, 1500.0m (4921.26') Length, Gray	Not Reviewed	Not Reviewed	Not Reviewed
1502070007	Ditto Wire-to-Wire Interconnects, Single-Ended Pigtail Harness, 2.50mm Pitch, 0.30m Length, 8 Circuits	Compliant	Not Contained Per -ED/88/2018 (15 January 2019)	Not Low-Halogen
1552100137	Flamar Control Cable, PVC Jacket, Unshielded, 2 Circuits, 0.75mm ² / 19 AWG, 6.00mm (.236") Diameter, 500.0m (1640.42') Length, Gray	Not Reviewed	Not Reviewed	Not Reviewed
0014600074	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 3.81µm Tin/Lead (SnPb), 7 Circuits	Not Reviewed	Not Reviewed	Not Reviewed
1552200020	Flamar Sensor Cable, WSOR Jacket, Unshielded, 4 Circuits, 0.25mm ² / 24 AWG, 4.80mm (.189") Diameter, 800.0m (2624.67') Length, Yellow	Not Reviewed	Not Reviewed	Not Reviewed
1511194312	2.00mm Pitch, Milli-Grid PCB Header, Dual Row, Right-Angle, Through Hole, 0.75µm Gold (Au) Plating, without Peg, 3.60mm PC Tail Length, without Pick and Place Tape, 12 Circuits, Glow-Wire Capable, Tube	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Low-Halogen
1552100144	Flamar Control Cable, PVC Jacket, Unshielded, 3 Circuits, 0.75mm ² with Green-Yellow Ground / 19 AWG with Green-Yellow Ground, 6.40mm (.252") Diameter, 1000.0m (3280.83') Length, Gray	Not Reviewed	Not Reviewed	Not Reviewed
0638237870		Compliant	Not Reviewed	Not Relevant
0733861570	50 Ohms, SMA Jack to SMP-MAX Plug Slide-on, Straight, 16.00mm Length	Compliant with Exemption 6(c)	Contained Per -ED/71/2019 (16 July 2019)	Low-Halogen
1300170011	Mini-Change Field Attachable, Male Connector, 3 Pole, Cable Range: 5.08-11.43mm Outside Diameter with External Threads	Compliant with Exemption 6(c)	Contained Per -ED/71/2019 (16 July 2019)	Not Low-Halogen
0639019500	FineAdjust Applicator for 3.7 LED Connector Plug Crimp Terminal	Not Reviewed	Not Reviewed	Not Reviewed
1552200119	Flamar Control Cable, WSOR Jacket, Unshielded, 4 Circuits, 0.50mm ² with Green-Yellow Ground / 21 AWG with Green-Yellow Ground, 5.90mm (.232") Diameter, 500.0m (1640.42') Length, Gray	Not Reviewed	Not Reviewed	Not Reviewed
0638812200	Mini-Mac Applicator	Not Reviewed	Not Reviewed	Not Reviewed
0638160700	Air Powered Crimp Adapter to be used with Module Crimp Headers with Air Powered Tool	Compliant	Not Contained Per -ED/30/2017 (7 July 2017)	Not Relevant

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1552100117	Flamar Control Cable, PVC Jacket, Unshielded, 4 Circuits, 0.50mm ² with Green-Yellow Ground / 21 AWG with Green-Yellow Ground, 5.90mm (.232") Diameter, 1000.0m (3280.83') Length, Black	Not Reviewed	Not Reviewed	Not Reviewed
1212080040	mPm DIN Valve Connector, Form B-11mm, External Thread, 2 Pole Plus Ground with A1 Circuit, 24V, Red LED, Transparent, Nitrile Gasket	Not Reviewed	Not Reviewed	Not Reviewed
0638136100	Extraction Tool	Not Reviewed	Not Reviewed	Not Reviewed
0152660279	0.50mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 26 Circuits, 0.127m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
0639001300	FineAdjust for Low Force Crimp Terminal, 26-30 AWG Wire	Not Reviewed	Not Reviewed	Not Relevant
0797580016	Pre-Crimped Lead Pico-SPOX Female-to-Pico-SPOX Female, 300mm, 24 AWG	Compliant	Not Contained Per -ED/01/2018 (15 January 2018)	Not Low-Halogen
0639020900	FineAdjust Applicator for 2.00mm (.079") Grid Wire-to-Board Crimp Terminal	Not Reviewed	Not Reviewed	Not Relevant
0638953000	Mini-Mac Applicator Mechanical Feed Dual Carrier Metal Strip	Not Reviewed	Not Reviewed	Not Relevant
1300680019	BradPower D-Size (1 3/8"-M35) AC Male to Micro-Change Female Pass Thru, 4-Pole	Not Reviewed	Not Reviewed	Not Reviewed
0639120200	T2 Terminator for insulation OD 1.10-1.30mm - 22-28 AWG	Not Reviewed	Not Reviewed	Not Reviewed
0638910080	Anvil	Not Reviewed	Not Reviewed	Not Relevant
0638255000	Hand Crimp Tool for 2.50mm Pitch Floating Wire-to-Board Plug Crimp Terminal	Compliant	Not Contained Per -ED/30/2017 (7 July 2017)	Not Relevant
0152660829	0.50mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 13 Circuits, 0.254m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
0638245010	Unlatching Tool for TermiMate 505071 Plug Terminal for removal of TermiMate 505073 Crimp Terminal Receptacle	Not Reviewed	Not Reviewed	Not Relevant
0639120700	T2 Terminator for .070 Female Crimp Terminal	Not Reviewed	Not Reviewed	Not Reviewed
0638197500	Hand Crimp Tool 3.96mm Pitch Wire-to-Wire and 6.50mm Pitch Wire-to-BoardCrimp Terminals, 16-18 AWG	Compliant	Not Contained Per -ED/30/2017 (7 July 2017)	Not Relevant

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
0459851362	EXTreme LPHPower Header, Right-Angle, 10 Power Contacts, 32 Signal Contacts, Select Gold (Au) Plating, for 2.36mm Thick PC Board, with Press-fit Plastic Pegs	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Low-Halogen
1300170024	Mini-Change Field Attachable, Female Connector, 5 Pole, Cable Range: 5.08-11.43mm Outside Diameter with Internal Threads, Stainless Steel	Compliant with Exemption 6(c)	Contained Per -ED/71/2019 (16 July 2019)	Not Low-Halogen
0638243500	Extractor Tool for MX120G Terminals	Not Reviewed	Not Reviewed	Not Relevant
0622030301	EdgeLine ESP Press-In Tool	Not Reviewed	Not Contained Per -ED/01/2018 (15 January 2018)	Not Relevant
0638912000	Mini-Mac Applicator	Not Reviewed	Not Reviewed	Not Relevant
0639007500	FineAdjust Applicator for Crimp Terminals, 14-20 AWG Wire with 2.08-2.50mm Diameter Insulation	Not Reviewed	Not Reviewed	Not Relevant
0387006325	8.26mm Pitch Beau PCB Terminal Strip, without Mounting Ends, 25 Circuits	Not Reviewed	Not Reviewed	Not Reviewed
0639014600	FineAdjust Applicator for Crimp Terminal, Male, 22 AWG Wire	Not Reviewed	Not Reviewed	Not Relevant
0638259600	Hand Crimp Tool for 4.0mm Pitch Motor Crimp Terminals	Not Reviewed	Not Reviewed	Not Reviewed
0192000011	Avikrimp Seamless Butt Splice for 18-22 AWG Wire, Super Duty	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Low-Halogen
0639013800	FineAdjust Applicator for NSCC 1.5 Receptacle Terminals 0.35mm ² Metric	Not Reviewed	Not Reviewed	Not Reviewed
0398801027	5.08mm Pitch Beau Eurostyle High Profile, Three Level Terminal Block, Modular, 27 Circuits	Not Reviewed	Not Reviewed	Not Reviewed
0640160036	ServiceGrade Hand Crimp Tool	Compliant	Not Contained Per -ED/30/2017 (7 July 2017)	Not Relevant
0152670446	1.00mm Pitch Premo-Flex FFC Jumper, Opposite Side Contacts (Type D), 28 Circuits, 0.051m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
0638243000	Imperium Extractor Tool for TPA, HVIL Header	Not Reviewed	Not Reviewed	Not Relevant
0638253400	Hand Crimp Tool for Solar Shingle Receptacle Terminals	Not Reviewed	Not Reviewed	Not Reviewed
0622007400	Tool Kit for Standard Manual Press FFC	Not Reviewed	Not Reviewed	Not Reviewed

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1300170012	Mini-Change Field Attachable, Male Connector, 3 Pole, Cable Range: 5.08-11.43mm Outside Diameter with External Threads, Stainless Steel	Not Reviewed	Not Reviewed	Not Reviewed
0639118500	T2 Terminator for 2.50mm Pitch Crimp Terminal	Not Reviewed	Not Reviewed	Not Reviewed
1212080080	mPm DIN Valve Connector, Form B-11mm, External Thread, 2 Pole Plus Ground with C4 Circuit, 24V, Amber LED, Transparent, Nitrile Gasket	Compliant with Exemption 6(c)	Contained Per -ED/71/2019 (16 July 2019)	Low-Halogen
0639015900	FineAdjust Applicator for 2.8 UCC2 Receptacle Terminal	Not Reviewed	Not Reviewed	Not Reviewed
0152670867	1.00mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 17 Circuits, 0.178m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
0640018100	Hand Crimp Tool InsulKrimp Male Q.D.	Compliant	Not Contained Per -ED/30/2017 (7 July 2017)	Not Relevant
0152660283	0.50mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 26 Circuits, 0.178m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
1300630201	BradPower D-Size (1 3/8"-M35) Single-Ended Cordset, 3 Poles, Male (90°) to Pigtail with Alternate Key, 10 AWG, PVC Cable, 2.0m (6.56') Length	Not Reviewed	Not Reviewed	Not Reviewed
0387007324	8.26mm Pitch Beau PCB Terminal Strip, with Mounting Ends, 24 Circuits, with Screw Clamp Washer	Not Reviewed	Not Reviewed	Not Reviewed
1300100106	Mini-Change A-Size Double-Ended Cordset, 5 Poles, Male (Straight) to Female (Straight), 16 AWG, TPE Cable, 10.0m (32.81') Length	Compliant with Exemption 6(c)	Not Contained Per - ECHA_01_2020 (16 January 2020)	Not Low-Halogen
0152680727	1.25mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 5 Circuits, 0.076m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
1300640356	BradPower D-Size (1 3/8"-M35) Double-Ended Cordset, 4 Poles, Female (Straight) to Male (Straight) with Alternate Key, 10 AWG, PVC Cable, 2.0m (6.56') Length	Not Reviewed	Not Reviewed	Not Reviewed
0152680423	1.25mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 34 Circuits, 0.203m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
1300100867	Mini-Change A-Size Double-Ended Cordset, 4 Poles, Male (Straight) to Female (Straight), 16 AWG, TPE Cable, 4.0m (13.12') Length	Compliant with Exemption 6(c)	Not Contained Per -ED/01/2018 (15 January 2018)	Not Low-Halogen

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1300101744	Mini-Change A-Size Double-Ended Cordset, 4 Poles, Male (90°) to Female (90°), 16 AWG, TPE Cable, 2.0m (6.56') Length	Not Reviewed	Not Reviewed	Not Reviewed
0152680485	1.25mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 40 Circuits, 0.152m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
1300080279	Mini-Change C-Size Single-Ended Cordset, 12 Poles, Female (90°) to Pigtail, 18 & 22 AWG, PVC Cable, 5.0m (16.40') Length	Not Reviewed	Not Reviewed	Not Low-Halogen
0395430221	5.00mm Pitch Eurostyle 45° Wire Entry Fixed Mount PCB Terminal Block, with Screw Pressure Clamp, 21 Circuits	Not Reviewed	Not Reviewed	Not Reviewed
1300061412	Mini-Change A-Size Single-Ended Cordset, 5 Poles, Female (90°) to Pigtail, 20 AWG, PVC Cable, 10.0m (32.81') Length	Not Reviewed	Not Reviewed	Not Reviewed
0190700039	InsulKrimp Ring Tongue Terminal for 18-22 AWG Wire	Not Reviewed	Not Contained Per -ED/30/2017 (7 July 2017)	Not Low-Halogen
0787261012	DDR4 DIMM Socket, Vertical Through-Hole, 0.38µm Gold Plating, 288 Circuits, PCB Thickness 1.57mm, Tail Length 2.67mm, Black Housing, Black Latch	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Low-Halogen
1300100159	Mini-Change A-Size Double-Ended Cordset, 2 Poles, Male (Straight) to Female (Straight), 16 AWG, PVC Cable, 6.10m (20.0') Length	Not Reviewed	Not Reviewed	Not Reviewed
0440671801	Micro-Fit 3.0 Wire-to-Board Header, Dual Row, Vertical for up to 3.56mm Thick PCB, 18 Circuits, Tin (Sn) Plating	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Low-Halogen
1300240080	Mini-Change Single-Ended Cordset, 5 Poles, Female (Straight) to DeviceNet Thick (Trunk) Pigtail Cable, 15 and 18 AWG, 5.0m (15.40') Length	Compliant with Exemption 6(c)	Not Reviewed	Not Low-Halogen
1300080338	Mini-Change C-Size Single-Ended Cordset, 9 Poles, Female (Straight) to Pigtail, 16 AWG, PVC Cable, 10.67m (35.0') Length	Not Reviewed	Not Reviewed	Not Reviewed
1300610135	BradPower A-Size (7/8"-M22) Single-Ended Cordset, 4 Poles, Male (Straight) to Pigtail, 16 AWG, PVC Cable, 2.0m (6.56') Length	Not Reviewed	Not Reviewed	Not Reviewed
1000151543	zQSFP+ 1x2 Cage Assembly with Spring Fingers, Open Top, 1 Rear Pin, PCI Heat Sink, 2 Light Pipes	Compliant	Not Contained Per -ED/71/2019 (16 July 2019)	Not Low-Halogen

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
0152680875	1.25mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 17 Circuits, 0.305m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
1300240028	Mini-Change Single-Ended Cordset, 5 Poles, Male (Straight) to DeviceNet Thick (Trunk) Pigtail Cable, 15 and 18 AWG, 1.0m (3.28') Length	Compliant with Exemption 6(c)	Contained Per - ECHA_01_2020 (16 January 2020)	Not Low-Halogen
0152660814	0.50mm Pitch Premo-Flex FFC Jumper, Opposite Side Contacts (Type D), 13 Circuits, 0.076m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
1300061453	Mini-Change A-Size Single-Ended Cordset, 5 Poles, Male (Straight) to Pigtail, 16 AWG, PVC Cable, 6.10m (20.0') Length	Not Reviewed	Not Reviewed	Not Reviewed
0526101833	Easy-On FFC/FPC Connector, 1.00mm Pitch, Slider Series, Vertical, 5.75mm Height, 18 Circuits, Tin-Silver-Bismuth Plating	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Not Low-Halogen
1300680045	BradPower D-Size (1 3/8"-M35) 3-Pole Trunk Tee, with 3-Pole BradPower D-Size (1 3/8"-M35) Drop, Gray	Not Reviewed	Not Reviewed	Not Reviewed
0026504121	KK 156 Header Assy FrLk Break 12 Ckt Gol	Not Reviewed	Not Reviewed	Not Reviewed
1300061312	Mini-Change A-Size Single-Ended Cordset, 5 Poles, Female (Straight) to Pigtail, 16 AWG, Rubber Cable, 1.83m (6.0') Length	Not Reviewed	Not Reviewed	Not Reviewed
0622020480	Crimp Die, Crimp Stake Tool 1394B	Not Reviewed	Not Reviewed	Not Reviewed
1300610168	BradPower A-Size (7/8"-M22) Single-Ended Cordset, 4 Poles, Male (90°) to Pigtail, 16 AWG, PVC Cable, 2.0m (6.56') Length	Not Reviewed	Not Reviewed	Not Reviewed
0194270021	MX150L Gasket for 6 Circuit Plug Housing with Flange	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Low-Halogen
1300101316	Mini-Change A-Size Double-Ended Cordset, 6 Poles, Male (Straight) to Female (Straight), 16 AWG, PVC Cable, 1.83m (6.0') Length	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed
1300130423	Mini-Change A-Size Receptacle, 5 Poles, 1/2" - 14 NPT Threads, Female (Straight) to 16 AWG, 1.83m (6.0') Length	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Not Reviewed
0194260002	MOLEX P/N NOT RECOGNIZED	-	-	-
0397000708	3.50mm Pitch, Eurostyle Fixed-Mount Push-Button Terminal Block, 45° Modular, 5A, 20-16 AWG, Light Gray, 8 Circuits	Not Reviewed	Not Reviewed	Not Reviewed

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1300240136	Mini-Change Single-Ended Cordset, 5 Poles, Female (90°) to DeviceNet Thick (Trunk) Pigtail Cable, 15 and 18 AWG, 3.0m (9.84') Length	Not Reviewed	Not Reviewed	Not Reviewed
0387068010	8.26mm Pitch Beau PCB Terminal Strip, without Mounting Ends, Dual Level Terminal Block, 10 Circuits	Not Reviewed	Not Reviewed	Not Reviewed
1042660110	Bottom-Entry Lite-Trap SMT Wire-to-Board Connector, Push-Button Type, 1 Circuit	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Low-Halogen
1300131001	Mini-Change A-Size Bulkhead Feed-Through, 4 Poles, 7/8-16UN, Stainless Steel, 0.049m (1.94") Length	Not Reviewed	Not Reviewed	Not Reviewed
0152680788	1.25mm Pitch Premo-Flex FFC Jumper, Opposite Side Contacts (Type D), 11 Circuits, 0.03m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
0783590001	1.00mm Pitch DDR3 DIMM Socket, Very Low Profile, 25° Angle, Through Hole, with Beveled Metal Pins, Black Housing and Latches, 0.76µm Gold (Au) Plating, 2.79mm Solder Tail Length, 1.57mm PCB Thickness, 1.5V Center Voltage Key,	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Not Low-Halogen
0634540019	Punch	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Not Relevant
1708140036	NeoScale High-Speed Mezzanine Receptacle, 2.80mm Pitch, 4x18, 72 Triads (216 Circuits), 8.00mm Connector Height, 0.76µm Gold (Au) Plating	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Low-Halogen
0622018893	Installation Press-In Tool for Impact Daughtercard Signal Module Assembly and Daughtercard Orthogonal Assembly (5-Pair by 8 Column Assemblies)	Not Reviewed	Not Reviewed	Not Reviewed
1300080218	Mini-Change C-Size Single-Ended Cordset, 12 Poles, Female (90°) to Pigtail, 16 AWG, PVC Cable, 6.10m (20.0') Length	Not Reviewed	Not Reviewed	Not Reviewed
0848548021	DeviceNet Micro-Change Single-Ended, 5 Poles, Male (Straight) to Pigtail, NMEA 2000 Style Cable, 0.50m (1.64') Length, meets NMEA 2000	Compliant with Exemption 6(c)	Contained Per - ECHA_01_2020 (16 January 2020)	Not Low-Halogen
1300069048	Mini-Change A-Size Single-Ended Cordset, 4 Poles, Female (90°) to Straight, 16 AWG, TPE Cable, 20.0m (65.62') Length	Not Reviewed	Not Reviewed	Not Reviewed

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1300100875	Mini-Change A-Size Double-Ended Cordset, 4 Poles, Male (Straight) to Female (Straight), 16 AWG, TPE Cable, 12.0m (6.56') Length	Compliant with Exemption 6(c)	Not Contained Per -ED/01/2018 (15 January 2018)	Not Low-Halogen
1300062122	Mini-Change A-Size Single-Ended Cordset, 4 Poles, Female (Straight) to Pigtail, 16 AWG, PVC Cable, 7.62m (25.0') Length, Stainless Steel Coupling Nut	Not Reviewed	Not Reviewed	Not Reviewed
0152671091	1.00mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 37 Circuits, 0.229m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
1300061404	Mini-Change A-Size Single-Ended Cordset, 5 Poles, Female (90°) to Pigtail, 20 AWG, PVC Cable, 2.0m (6.56') Length	Not Reviewed	Not Reviewed	Not Reviewed
1300080187	Mini-Change C-Size Single-Ended Cordset, 12 Poles, Female (Straight) to Pigtail, 16 AWG, PVC Cable, 5.0m (16.40') Length	Not Reviewed	Not Reviewed	Not Reviewed
0190700110	InsulKrimp Ring Tongue Terminal for 10-12 AWG Wire, Stud Size 1/2" (M12), Length 39.90mm, Mylar Tape Carrier	Not Reviewed	Not Contained Per -ED/01/2018 (15 January 2018)	Not Low-Halogen
1300061320	Mini-Change A-Size Single-Ended Cordset, 5 Poles, Female (Straight) to Pigtail, 16 AWG, Rubber Cable, 7.62m (25.0') Length	Not Reviewed	Not Reviewed	Not Reviewed
0787261023	DDR4 DIMM Socket, Vertical Through-Hole, 0.76µm Gold Plating, 288 Circuits, PCB Thickness 2.36mm, Tail Length 3.18mm, Blue Housing, White Latch	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Low-Halogen
1300062444	MC 4P M/MP 6M ST #16-4 TPE	Not Reviewed	Not Reviewed	Not Reviewed
1300660160	BradPower D-Size (1 3/8"-M35) Female, 1/2" NPT 2, 4 Poles, Receptacle, Female (Straight) to 10 AWG Leads, 2.0m (6.56') Length	Not Reviewed	Not Reviewed	Not Reviewed
0982680338	1.25mm Pitch Premo-Flex FFC Jumper, Opposite Side Contacts (Type D), 26 Circuits, 0.229m Cable Length, Tin(Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
0152670493	1.00mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 32 Circuits, 0.102m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
0982680354	1.25mm Pitch Premo-Flex FFC Jumper, Opposite Side Contacts (Type D), 28 Circuits, 0.152m Cable Length, Tin(Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
0753414774	GbX 4 Pair Backplane Connector System, Power Module, 8 Circuits, 1.27µm Gold (Au)	Product not active	Product not active	Product not active

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
0982680371	1.25mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 30 Circuits, 0.102m Cable Length, Tin(Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
0936011111	GWconnect HP-HE - High Performance-Harsh Environment, Surface Mount Housing, Toggle Locking, Zinc Alloy, Side Entry, Size 10B «57x27», M32x2 Thread, Black	Not Reviewed	Not Reviewed	Not Reviewed
0152680322	1.25mm Pitch Premo-Flex FFC Jumper, Opposite Side Contacts (Type D), 26 Circuits, 0.03m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
1300190023	Die Block 4 Pole Cast Receptacle, Orange	Not Reviewed	Not Reviewed	Not Reviewed
0623003000	Hawk Ribbon Cable Terminator without Break-off	Not Reviewed	Not Reviewed	Not Reviewed
1204800528	Brad M23 Power Single-Ended Cordset, 6 Poles, Female (Straight) to Pigtail, 16 AWG, Shielded WSOR Cable, 5.0m (16.40') Length	Not Reviewed	Not Reviewed	Not Reviewed
1552400260	Flamar Control Cable, TPE Jacket, Unshielded, 12 Circuits, 2.50mm ² with Green-Yellow Ground / 14 AWG with Green-Yellow Ground, 18.40mm (.724") Diameter, 250.0m (820.21') Length, Gray	Not Reviewed	Not Reviewed	Not Reviewed
0011184977	Cut-off Punch	Not Reviewed	Not Reviewed	Not Relevant
1301190002	Flat PVC Festoon Cable #12/8C	Not Reviewed	Not Reviewed	Not Reviewed
0152660932	0.50mm Pitch Premo-Flex FFC Jumper, Opposite Side Contacts (Type D), 23 Circuits, 0.178m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
1552400217	Flamar Control Cable, TPE Jacket, Unshielded, 25 Circuits, 1.50mm ² with Green-Yellow Ground / 16 AWG with Green-Yellow Ground, 20.00mm (.787") Diameter, 350.0m (1148.29') Length, Gray	Not Reviewed	Not Reviewed	Not Reviewed
0982670723	1.00mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 5 Circuits, 0.03m Cable Length, Tin(Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
1552400252	Flamar Control Cable, TPE Jacket, Unshielded, 11 Circuits, 2.50mm ² with Green-Yellow Ground / 14 AWG with Green-Yellow Ground, 18.40mm (.724") Diameter, 500.0m (1640.42') Length, Black	Not Reviewed	Not Reviewed	Not Reviewed
1300980026	MAX-LOC Strain Relief Cord-Sealing Grip, 1/4" NPT, Straight Male, Cable Diameter 5.08-6.73mm (.200-.265")	Not Reviewed	Not Reviewed	Not Reviewed
1300062095	Mini-Change Female Connector, 2 Pole, for 1/2" Liquid-Tite Conduit	Not Reviewed	Not Reviewed	Not Reviewed

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
0459851462	EXTreme LPHPower Header, Right-Angle, 10 Power Contacts, 32 Signal Contacts, Select Gold (Au) Plating, for 2.36mm Thick PC Board, with Guide Pockets, with Press-fit Plastic Pegs	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Low-Halogen
1552400170	Flamar Control Cable, TPE Jacket, Unshielded, 3 Circuits, 1.50mm ² with Green-Yellow Ground / 16 AWG with Green-Yellow Ground, 8.50mm (.335") Diameter, 500.0m (1640.42') Length, Gray	Not Reviewed	Not Reviewed	Not Reviewed
0330014023	MX150 Female Terminal for Unsealed Connectors, Silver Plating, 22 AWG, Right Reel Payoff. Not suitable for MX150 Sealed Connectors.	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Not Relevant
1552400007	Flamar Sensor Cable, TPE Jacket, Unshielded, 3 Circuits, 0.34mm ² / 22 AWG, 5.10mm (.201") Diameter, 600.0m (1968.50') Length, Yellow	Not Reviewed	Not Reviewed	Not Reviewed
0348269126	Mini50 Unsealed Right-Angle Header, Dual Row, 12 Circuit, Polarization Option C, Dark Gray, Tube	Not Reviewed	Not Reviewed	Not Reviewed
1552100196	Flamar Control Cable, PVC Jacket, Unshielded, 12 Circuits, 1.00mm ² with Green-Yellow Ground / 18 AWG with Green-Yellow Ground, 11.50mm (.453") Diameter, 100.0m (328.08') Length, Gray	Not Reviewed	Not Reviewed	Not Reviewed
0559351110	2.00mm Pitch MicroClasp Wire-to-Board Header, Single Row, Right Angle, 11 Circuits, with PCB Locator	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Not Low-Halogen
1300990173	MAX-LOC/Watertite Cord Grips, 3/4" NPT, Straight Male, Body Size F3, Cable Diameter 12.70-15.88mm (.500-.625")	Not Reviewed	Not Reviewed	Not Reviewed
0395100019	3.81mm Pitch Eurostyle Horizontal Plug, 19 Circuits	Not Reviewed	Not Reviewed	Not Reviewed
1300990181	MAX-LOC/Watertite Cord Grips, 1" NPT, Straight Male, Body Size F4, Cable Diameter 19.05-22.23mm (.750-.875")	Not Reviewed	Not Reviewed	Not Reviewed
0459858422	EXTreme LPHPower Header, Right-Angle, 8 Power Contacts, 16 Signal Contacts, Select Gold (Au) Plating, for 2.36mm Thick PC Board, with Guide Pockets, with Press-fit Plastic Pegs	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Low-Halogen
1552400159	Flamar Control Cable, TPE Jacket, Unshielded, 25 Circuits, 1.00mm ² with Green-Yellow Ground / 18 AWG with Green-Yellow Ground, 18.00mm (.709") Diameter, 500.0m (1640.42') Length, Gray	Not Reviewed	Not Reviewed	Not Reviewed

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
0152670227	1.00mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 8 Circuits, 0.076m Cable Length, Tin (Sn) Plating	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Not Low-Halogen
0936011141	GWconnect STD - Standard, Single Lever Surface Mount Housing, Die-cast Aluminum, with 1 Lever, Size 10A «49x16», Pg21 Thread, Grey	Compliant	Not Contained Per -ED/71/2019 (16 July 2019)	Not Reviewed
0399700304	10.16mm Beau Eurostyle Fixed Mount PCB Terminal Block, High Power 40A, 4 Circuits	Compliant with Exemption 6(c)	Contained Per - ED/88/2018 (15 January 2019)	Not Low-Halogen
1300621050	BP A 3P M/MFE SK ST #14 BK TPE 30M	Not Reviewed	Not Reviewed	Not Reviewed
1212070087	mPm DIN Valve Connector, Form A-18mm, External Threads, 2 Pole Plus Ground with C3 Circuit, 24V, Green LED, Transparent, Nitrile Gasket	Compliant with Exemption 6(c)	Contained Per -ED/71/2019 (16 July 2019)	Low-Halogen
0152680384	1.25mm Pitch Premo-Flex FFC Jumper, Opposite Side Contacts (Type D), 30 Circuits, 0.254m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
1552400265	Flamar Control Cable, TPE Jacket, Unshielded, 17 Circuits, 2.50mm ² with Green-Yellow Ground / 14 AWG with Green-Yellow Ground, 21.40mm (.843") Diameter, 350.0m (1148.29') Length, Gray	Not Reviewed	Not Reviewed	Not Reviewed
1552400048	Flamar Sensor Cable, TPE Jacket, Unshielded, 5 Circuits, 0.34mm ² with Green-Yellow Ground / 22 AWG with Green-Yellow Ground, 5.80mm (.228") Diameter, 1000.0m (3280.83') Length, Orange	Not Reviewed	Not Reviewed	Not Reviewed
0395260002	5.00mm Pitch Eurostyle Horizontal PCB Header, with Threaded Retention Inserts, 2 Circuits	Compliant with Exemption 6(c)	Contained Per - ECHA_01_2020 (16 January 2020)	Low-Halogen
1201090004	Ultra-Lock (M12) Ethernet Receptacle, FPM PG9, Female (Straight), Panel Mount, 4 Poles, D-Code	Compliant with Exemption 7(c)-I,6(c)	Contained Per - ECHA_01_2020 (16 January 2020)	Not Low-Halogen
0545500933	0.50mm Pitch Easy-On FFC/FPC Connector, 1.20mm Height, Right-Angle, Surface Mount, ZIF, Top Contact Style, 9 Circuits	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Not Low-Halogen
1122190012	Woodhead ArcArrest Receptacle, Switch-Rated, 30.0A, 600V AC, 2-Pole+Ground, Insulator Keying Position 14	Not Reviewed	Contained Per - ED/01/2018 (15 January 2018)	Not Reviewed
1204800535	Brad M23 Power Single-Ended Cordset, 6 Poles, Male (Straight) to Pigtail, 16 AWG, Shielded WSOR Cable, 4.0m (13.12') Length	Not Reviewed	Not Reviewed	Not Reviewed

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
0395021008	3.50mm Pitch Eurostyle Horizontal PCB Header, 8 Circuits	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Low-Halogen
1201080285	Micro-Change (M12) to Standard RJ-45 Double-Ended Cordset, 4 Poles, Male (Straight) to Male (Straight), 22 AWG, Shielded PUR Cable, 6.0m (19.68') Length, 6.70mm (.264") Diameter, Green	Not Reviewed	Not Reviewed	Not Reviewed
1552100149	Flamar Control Cable, PVC Jacket, Unshielded, 4 Circuits, 0.75mm² with Green-Yellow Ground / 19 AWG with Green-Yellow Ground, 7.00mm (.276") Diameter, 500.0m (1640.42') Length, Gray	Not Reviewed	Not Reviewed	Not Reviewed
0152671089	1.00mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 37 Circuits, 0.203m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
0936011161		Not Reviewed	Not Reviewed	Not Reviewed
0395283012	5.00mm Pitch Eurostyle Vertical PCB Dual Level Header, Closed Ends, 12 Circuits	Not Reviewed	Not Reviewed	Not Reviewed
1122190013	Woodhead ArcArrest Receptacle, Switch-Rated, 30.0A, 600V AC, 3-Pole+Ground, Insulator Keying Position 14	Not Reviewed	Contained Per - ED/01/2018 (15 January 2018)	Not Reviewed
1300500170	Brad RJ-Lnxx RJ-45 Double-Ended Cordset, 8 Poles, Male (Straight) to Male (Straight), Shielded Cable, 1.0m (3.28') Length , 26 AWG	Not Reviewed	Not Reviewed	Not Reviewed
0334710202	MX150 Mat-Sealed Female Connector Assembly, Single Row, 2 Circuits, Keying Option B, Light Gray	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Not Relevant
1552100227	Flamar Control Cable, PVC Jacket, Unshielded, 4 Circuits, 1.50mm² / 16 AWG, 7.90mm (.311") Diameter, 500.0m (1640.42') Length, Gray	Not Reviewed	Not Reviewed	Not Reviewed
0152680407	1.25mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 32 Circuits, 0.305m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
1552100147	Flamar Control Cable, PVC Jacket, Unshielded, 4 Circuits, 0.75mm² with Green-Yellow Ground / 19 AWG with Green-Yellow Ground, 7.00mm (.276") Diameter, 1000.0m (3280.83') Length, Black	Not Reviewed	Not Reviewed	Not Reviewed
0347072030	Stac64 2 Bay Vertical Headers, 20 Circuits, Bay A 10 Circuit Power Header, Polarization B, Gray; Bay B 10 Circuit Power Header, Polarization A, Black, Tray	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Not Relevant

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1552100244	Flamar Control Cable, PVC Jacket, Unshielded, 7 Circuits, 1.50mm ² with Green-Yellow Ground / 16 AWG with Green-Yellow Ground, 10.50mm (.413") Diameter, 100.0m (328.08') Length, Gray	Not Reviewed	Not Reviewed	Not Reviewed
1552100211	Flamar Control Cable, PVC Jacket, Unshielded, 2 Circuits, 1.50mm ² / 16 AWG, 7.10mm (.280") Diameter, 300.0m (984.25') Length, Black	Compliant	Not Reviewed	Not Reviewed
1552100191	Flamar Control Cable, PVC Jacket, Unshielded, 11 Circuits, 1.00mm ² with Green-Yellow Ground / 18 AWG with Green-Yellow Ground, 11.50mm (.453") Diameter, 500.0m (1640.42') Length, Gray	Not Reviewed	Not Reviewed	Not Reviewed
0395133003	3.81mm Pitch Eurostyle Vertical Plug, Front Wire Entry, 3 Circuits	Compliant with Exemption 6(c)	Contained Per -ED/71/2019 (16 July 2019)	Low-Halogen
1552400164	Flamar Control Cable, TPE Jacket, Unshielded, 2 Circuits, 1.50mm ² / 16 AWG, 8.00mm (.315") Diameter, 500.0m (1640.42') Length, Gray	Not Reviewed	Not Reviewed	Not Reviewed
0395433105	5.00mm Pitch Eurostyle Horizontal Fixed Mount PCB Terminal Block, 5 Circuits	Not Reviewed	Not Reviewed	Not Reviewed
1552400222	Flamar Control Cable, TPE Jacket, Unshielded, 2 Circuits, 2.50mm ² / 14 AWG, 9.80mm (.385") Diameter, 1000.0m (3280.83') Length, Black	Not Reviewed	Not Reviewed	Not Reviewed
0152670578	1.00mm Pitch Premo-Flex FFC Jumper, Opposite Side Contacts (Type D), 40 Circuits, 0.051m Cable Length, Tin (Sn) Plating	Not Reviewed	Not Reviewed	Not Reviewed
1122190011	Woodhead ArcArrest Receptacle, Switch-Rated, 30.0A, 277/480V AC, 3-Pole+Neutral+Ground, Insulator Keying Position 4	Not Reviewed	Contained Per -ED/01/2018 (15 January 2018)	Not Reviewed
0194351214	MX150L 12 Circuit Rear Mount Flange Plug for 18-22 AWG Wire, without Gasket, Black	Compliant	Not Contained Per -ECHA_01_2020 (16 January 2020)	Low-Halogen
1553119011	Flamar Feedback Cable, PVC Jacket, Braided Shielding Overall, 16 Circuits, 3x(2x0.14mm ² with Spiral Shield) + 2x(0.50mm ²) + 4x(0.14mm ²) + 4x(0.25mm ²) / 3x(2x26 AWG with Spiral Shield) + 2x(21 AWG) + 4x(26 AWG) + 4x(24 AWG), 10.00mm (.394") Diameter, 500.0m (1640.42') Length, Green	Not Reviewed	Not Reviewed	Not Reviewed
1301460100	Watertite Extreme Extra Hard Outdoor Connector with Locking Blade, 2 Pole/3 Wire, NEMA L5-15, 125V, Cord Grip Body Size F2, Black, Silicone Husk	Not Reviewed	Not Reviewed	Not Reviewed

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
0194280016	5.84mm Pitch MX150L Vertical PCB Header, Dual Row, Low Profile, 16 Circuits	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Low-Halogen
1552400190	Flamar Control Cable, TPE Jacket, Unshielded, 7 Circuits, 1.50mm ² with Green-Yellow Ground / 16 AWG with Green-Yellow Ground, 11.80mm (.465") Diameter, 100.0m (328.08') Length, Black	Compliant	Not Contained Per -ED/88/2018 (15 January 2019)	Not Reviewed
0391001803	8.00mm Pitch Beau Eurostyle Two-Screw Terminal Strips, 3 Circuits	Compliant with Exemption 6(c)	Contained Per - ECHA_01_2020 (16 January 2020)	Low-Halogen
0936011163	GWconnect HE - Harsh Environment, Single Lever Bulkhead Mount Housing, Die-cast Aluminum, with 1 Lever, Size 10A «49x16», Black	Compliant	Not Contained Per -ED/71/2019 (16 July 2019)	Not Reviewed
0461146121	1.27mm, 12.00mm Pitch, EXTreme LPHPower Receptacle Header, Vertical, 6 Power Contacts, 12 Signal Contacts, Select Gold (Au) Plating, without BMI Guides	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Low-Halogen
1552400236	Flamar Control Cable, TPE Jacket, Unshielded, 4 Circuits, 2.50mm ² with Green-Yellow Ground / 14 AWG with Green-Yellow Ground, 11.60mm (.457") Diameter, 500.0m (1640.42') Length, Gray	Not Reviewed	Not Reviewed	Not Reviewed