

## Product Compliance Statement

August 24, 2020

Molex is committed to managing the use of chemical substances in accordance with governmental regulations, industry standards, and customer-specific requirements in order to protect the environment. For each part listed, this document provides:

- **EU RoHS Compliance Status.** EU RoHS status is declared per Directive 2011/65/EU and its subsequent amendments, including the Directive EU 2015/863 which additionally prohibited four phthalates. Homogeneous materials of parts that are compliant to this legislation have less than 0.1% by weight each of lead, mercury, hexavalent chromium, PBB, PBDE, DBP, BBP, DIBP, DEHP, and 0.01% by weight of cadmium. In situations where an exemption applies, the preceding limits, corresponding to the exempted substance(s), may be higher.

- **EU REACH SVHC Content.** Substances of Very High Concerns (SVHCs) are declared if above 0.1% of the article per Regulation (EC) No. 1907/2006 and its subsequent amendments. The Candidate List of SVHCs is continually updated at <https://echa.europa.eu/candidate-list-table>.

- **Low-Halogen Status.** Homogeneous materials of parts that are considered Low-Halogen have less than 0.09% by weight each of bromine and chlorine, and less than 0.15% by weight of the sum of bromine and chlorine.

Molex's sole liability for incorrectly certifying a product shall be either replacement of the Molex product or, alternatively and in the sole discretion of Molex, return of the purchase price paid for the relevant Molex product.

For additional information regarding Molex's environmental initiatives and further explanation of this information, please visit [www.molex.com](http://www.molex.com)



Haim Eliyahu  
Director, Global Product Stewardship

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>   | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b>                                 | <b>Low-Halogen Status</b> |
|------------------|---|-------------------------------|---|---------------------------|
| 0879751011       |   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0449146803       | Micro-Fit CPI Header, Dual Row, Vertical, Compliant Pin Interface, 18 Circuits, LCP, Glass-Filled, UL 94V-0, 0.76µm Gold (Au) Selective Contact Plating, Tin (Sn) Plated Tails, Glow-Wire Capable | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0428203228       | 10.00mm Pitch Mini-Fit Sr. Header, Single Row, Right-Angle, 2.36mm PCB Thickness, 0.76µm Gold (Au) Selective Plating, 3 Circuits  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0955222667       | Modular Jack, Vertical, Top Entry, Through Hole, 6/6, High Profile, with Ribs, Tray   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0010894147       | 2.54mm Pitch C-Grid Breakaway Header, High Profile, Dual Row, Right-Angle, 14 Circuits, 8.13mm Mating Pin Length, 0.76µm Gold (Au) Selective Plating  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0010897103       | 2.54mm Pitch C-Grid Breakaway Header, Dual Row, Vertical, High Temperature, 10 Circuits, 0.76µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating, 2.79mm PC Tail                             | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0050841065       | 2.13mm Diameter MLX Power Crimp Housing Plug, 6 Circuits, Natural   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0050842032       | 2.13mm Diameter MLX Pin and Socket Receptacle, 3 Circuits, Natural  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0015247101       | Mini-Fit BMI Receptacle Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-In Plastic Pegs, Post 2.54µm Tin (Sn), UL 94V-0, 10 Circuits  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0015247143       | Mini-Fit BMI Receptacle Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-In Plastic Pegs, 0.80µm Gold (Au), UL 94V-0, 14 Circuits  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0022552101       | 2.54mm Pitch SL Crimp Housing, Dual Row, Version A, Non-polarized, 10 Circuits, Black   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0874270802       | Mini-Fit Jr. Header, 4.20mm Pitch, Right-Angle, without Flange, 8 Circuits, Tin (Sn) over Nickel (Ni) Plating   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0874270842       | Mini-Fit Jr. Header, 4.20mm Pitch, Vertical, without Flange, 8 Circuits, Tin (Sn) over Nickel (Ni) Plating, Bulk Packaging  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>   | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b>                                 | <b>Low-Halogen Status</b> |
|------------------|---|-------------------------------|---|---------------------------|
| 0717423003       | 1.00mm Mezz (IEEE 1386) Receptacle, Surface Mount, Dual Row, Vertical Stacking, 84 Circuits   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0714361864       | 1.00mm Mezz (IEEE 1386) Plug, Surface Mount, Dual Row, Vertical Stacking, 64 Circuits, 7.35mm Unmated Height, without PCB Locator Pegs, with Robotic Placement Metal Cap, Embossed Tape on Reel Packaging | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0714390864       | 1.00mm Mezz (IEEE 1386) Receptacle, Surface Mount, Dual Row, Vertical Stacking, Embossed Tape on Reel, 0.76µm Gold (Au), 64 Circuits Pick and Place Cap   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0736421000       | HDM Board-to-Board Backplane Header, Vertical, Press-Fit, Open End, 144 Circuits  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0736431000       | HDM Board-to-Board Backplane Header, Vertical, Press-Fit, Closed End, 144 Circuits  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0432498104       | Modular Jack, Right-Angle, Low Profile, 8/8, Panel Stops  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0713492091       | 2.54mm Pitch C-Grid Header, Surface Mount, Dual Row, Vertical, Shrouded, 50 Circuits, 0.76µm Gold (Au) Selective Plating, with Press-fit Plastic Pegs   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0438100103       | Mini-Fit BMI Header, Dual Row, Right-Angle, for 3.18mm PCB, 10 Circuits, Gold (Au) Plating, 260C Wave Solderable, with Retention Clip   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0836129020       | 1.27mm Pitch Commercial Micro D, PCB Mount, Right-Angle Plug, 15 Circuits   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0008500187       | KK Trifurcon Crimp Terminal 6838, 18-20 AWG, Reel, Brass Tin (Sn)   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0015916062       | 2.54mm Pitch C-Grid Breakaway Header, Surface Mount, Dual Row, Vertical, 6 Circuits, 0.38µm Gold (Au) Selective Plating, without PCB Locator Pegs, Tape and Reel  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0438790058       | Mini-Fit BMI Header Compliant Pin Interface, Dual Row, Vertical, 10 Circuits, 0.76µm Gold (Au) Selective Contact Plating, Tin (Sn) Press-fit Tail Plating   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>   | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b>                                 | <b>Low-Halogen Status</b> |
|------------------|---|-------------------------------|---|---------------------------|
| 0679100002       |   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0873686140       | Milli-Grid Receptacle, Surface Mount, Side Entry, 0.38µm Gold (Au) Plating, 50 Circuits, Lead-Free, Tape and Reel   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0541323062       | Easy-On FFC/FPC Connector, 0.50mm Pitch, Slider Series, Right-Angle, Bottom Contact, 2.00mm Height, 30 Circuits, Gold Plating   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0955012661       | Modular Jack, Right-Angle, Through Hole, 6/6, Low Profile, Tray   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0541324062       | Easy-On FFC/FPC Connector, 0.50mm Pitch, Slider Series, Right-Angle, Bottom Contact, 2.00mm Height, 40 Circuits, Gold Plating   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0879751001       | 1.27mm Signal Pitch, 0.80mm SCSI Pitch, 1.27mm Power Pitch SAS-2 Receptacle, Right-Angle, Surface Mount, Fork Lock, "Z" Height of 2.85mm, with Beveled Metal Pins, 29 Circuits, Lead-Free | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0015246183       | Mini-Fit BMI Header, Dual Row, Right-Angle, with Snap-in Plastic Peg PCB Lock, 18 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, with Select Gold (Au) Plating                               | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0438790027       | Mini-Fit BMI Header Compliant Pin Interface, Dual Row, Vertical, 14 Circuits, Tin (Sn) Plating  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0016020083       | SL Crimp Terminal, Series 70058, Female, 24-30 AWG, with 0.76µm Selective Gold (Au) Plated Contact, Reel  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0438600026       | Modular Jack, Right-Angle, Low Profile, Inverted, 6/6, without Shield Panel Grounding Tabs  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0713494091       | 2.54mm Pitch C-Grid Header, Surface Mount, Dual Row, Vertical, Shrouded, 50 Circuits, 0.76µm Gold (Au) Selective Plating, with Press-fit Plastic Pegs                                     | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0955016889       | Modular Jack, Right-Angle, Surface Mount, 8/8, Low Profile, Tube  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0751010001       | 2.54mm Pitch C-Grid Header, Dual Row, Vertical, Shrouded, with Compliant Pin Interface, Version A, 6 Circuits, 0.76µm Gold (Au) Selective Plating   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>  | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b>                                 | <b>Low-Halogen Status</b> |
|------------------|--|-------------------------------|---|---------------------------|
| 0527460671       | Easy-On FFC/FPC Connector, 0.50mm Pitch, Slider Series, Right-Angle, Bottom Contact, 2.00mm Height, 6 Circuits, Gold Plating   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0702471051       | 2.54mm Pitch C-Grid Header, Dual Row, Low Profile, Right Angle, Shrouded, 10 Circuits, 0.38µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating                              | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0533980571       | 1.25mm Pitch, PicoBlade PCB Header, Single Row, Vertical, Surface Mount, Tin (Sn) Plating, Friction Lock, 5 Circuits, Tape and Reel, 0.60mm PC Tail Length                       | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0010897102       | 2.54mm Pitch C-Grid Breakaway Header, Dual Row, Vertical, High Temperature, 10 Circuits, 0.38µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating, 2.72mm PC Tail            | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0010897162       | 2.54mm Pitch C-Grid Breakaway Header, Dual Row, Vertical, High Temperature, 16 Circuits, 0.38µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating, 2.72mm PC Tail            | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0010897502       | 2.54mm Pitch C-Grid Breakaway Header, Dual Row, Vertical, High Temperature, 50 Circuits, 0.38µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating, 2.72mm PC Tail            | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0755860011       | 0.80mm Pitch, iPass I/O Surface Mount Receptacle, Right-Angle, External Application, 38 Circuit, 0.76µm Gold (Au), Supports QSFP14 / FDR   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 5034801000       | Easy-On FFC/FPC Connector, 0.50mm Pitch, FBH1 Series, Right-Angle, Dual Contact, 1.00mm Height, 10 Circuits, Gold over Nickel Plating  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0528921633       | 0.50mm Pitch Easy-On FFC/FPC Connector, Right-Angle, Surface Mount, ZIF, Bottom Contact Style, Cable Retention Guide, 16 Circuits  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 1062840050       | CXP Optical Cable Assembly (iPass+ ), MTP-to-MTP, Multimode, 50/125µm, Round Cable Assembly, Straight Boot, Standard Bandwidth, OFNP, Cable Diameter 5.40mm, Cable Length 50.00m | Compliant with Exemption 6(c) | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0039537104       | QIK Flecs Wafer Assy RA 10Ckt  | Compliant                     | Not Contained Per -ED/88/2018 (15 January 2019)   | Not Low-Halogen           |
| 0019092156       | 2.36mm Diameter Standard .093" Pin and Socket Plug Housing with Positive Latch, UL 94V-0, without Panel Mount, 15 Circuits   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>  | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b>                                 | <b>Low-Halogen Status</b> |
|------------------|--|-------------------------------|---|---------------------------|
| 0432236022       | Modular Jack, Right-Angle, Low Profile, 6/4, 2 Ports   | Compliant                     | Not Contained Per -ED/71/2019 (16 July 2019)      | Low-Halogen               |
| 0015249185       | Mini-Fit BMI Header, Dual Row, Right-Angle, with Snap-in Plastic Peg PCB Lock, 18 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, with Overall Gold (Au) Plating   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0438790036       | Mini-Fit BMI Header Compliant Pin Interface, Dual Row, Vertical, 10 Circuits, Gold (Au) Selective Contact Plating, Tin/Lead (Sn/Pb) Press-fit Tail Plating   | Product not active            | Product not active                                | Product not active        |
| 0520892010       | 1.0 FPC Conn ZIF RA Assy 20Ckt   | Product not active            | Product not active                                | Product not active        |
| 0894000320       | 2.00mm Pitch Wire-to-Board Header, Vertical, 3 Circuits, with Kinked PC Tail   | Compliant                     | Contained Per - D(2020)4578-DC (25 June 2020)     | Not Low-Halogen           |
| 0039267108       | 10CKT RT ANG HEADER ASSY BLK 534210GS1   | Product not active            | Product not active                                | Product not active        |
| 0942080011       | 1.27mm Pitch PC Card - Header, Single Port, Flush Profile Vertical, Top Mount Through Hole   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0520186645       | 6/6 MODULAR JACK ASSY  | Product not active            | Product not active                                | Product not active        |
| 0709282000       | 1.27mm Pitch LFH Matrix 50 Receptacle, Shielded, Right-Angle, 2.01mm PC Tail Length, Screw Hole M3 Thread, Gold Plating, 60 Circuits   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0528921690       | 0.5 FPC AssyZIF SMT RA EO 16CktEmbsTpPkg   | Product not active            | Product not active                                | Product not active        |
| 0950222667       | Modular Jack, Vertical, 8/8, Panel Stops, without Ribs, Tray   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0449141803       | Micro-Fit CPI Header, Dual Row, Vertical, Compliant Pin Interface, 18 Circuits, LCP, Glass-Filled, UL 94V-0, 0.76µm Gold (Au) Selective Contact Plating, Tin/Lead (Sn/Pb) Plated Tails, Glow-Wire Capable            | Product not active            | Product not active                                | Product not active        |
| 0482016063       | D-Subminiature Shielded I/O PCB Female Receptacle, Right-Angle, Through Hole, 9 Circuits, #4-40 Flush Insert, 2 #4-40 Hex Internal Thread Screws Assembled, Gold (Au) Flash Plating, PCB Thickness 1.60mm, Lead-Free | Product not active            | Product not active                                | Product not active        |
| 0520184446       | Modular Jack Hsg Assy 4Ckt   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>  | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b>  | <b>Low-Halogen Status</b> |
|------------------|--|-------------------------------|--|---------------------------|
| 0536431474       | 0.635 BtB Plg Hsg<br>CvrAssy140CktEmbsTpPkg  | Compliant                     | Not Contained<br>Per -<br>D(2020)4578-DC<br>(25 June 2020) | Low-Halogen               |
| 0097000445       | KK Cat Ear Crimp Terminal 40445,<br>Bag Tin (Sn)   | Compliant                     | Not Contained<br>Per -<br>D(2020)4578-DC<br>(25 June 2020) | Low-Halogen               |
| 0900591007       | 2.54mm Pitch C-Grid Micro Shunt,<br>Low Profile, 5.08µm Tin (Sn) Plating   | Compliant                     | Not Contained<br>Per -<br>D(2020)4578-DC<br>(25 June 2020) | Not Low-Halogen           |
| 0438790038       | Mini-Fit BMI Header Compliant Pin<br>Interface, Dual Row, Vertical, 14<br>Circuits, Gold (Au) Selective Contact<br>Plating, Tin/Lead (Sn/Pb) Press-fit<br>Tail Plating   | Product<br>not active         | Product<br>not active                                      | Product<br>not active     |
| 0432496501       | Modular Jack, Right-Angle, Low<br>Profile, 6/6, Flangeless   | Compliant                     | Not Contained<br>Per -<br>D(2020)4578-DC<br>(25 June 2020) | Low-Halogen               |
| 0432238192       | Modular Jack, Right-Angle, Low<br>Profile, 8/4, 4 Ports  | Compliant                     | Not Contained<br>Per -<br>D(2020)4578-DC<br>(25 June 2020) | Low-Halogen               |
| 0432238197       | Modular Jack, Right-Angle, Low<br>Profile, 8/8, 4 Ports  | Compliant                     | Not Contained<br>Per -<br>D(2020)4578-DC<br>(25 June 2020) | Low-Halogen               |
| 0875872050       | 1.27mm Pitch DIMM 8-Byte Socket,<br>Low Profile (25°), Multi-Key, with<br>Beveled Metal Pins and Plastic Peg,<br>Right Function Key, 2.79mm Tail<br>Length, 0.38µm Gold (Au) Selective<br>Plating, 168 Circuits, Lead-Free | Compliant                     | Not Contained<br>Per -<br>D(2020)4578-DC<br>(25 June 2020) | Not Low-Halogen           |
| 0520892019       | 1.0 FPC ZIF RA Hsg Assy 20Ckt  | Compliant                     | Not Contained<br>Per -<br>D(2020)4578-DC<br>(25 June 2020) | Not Low-Halogen           |
| 0526020679       | 1.00mm Pitch Receptacle, Dual Row<br>Surface Mount, Vertical Stacking,<br>Mated Stacking Height 20.00mm, 60<br>Circuits  | Compliant                     | Not Contained<br>Per -<br>D(2020)4578-DC<br>(25 June 2020) | Low-Halogen               |
| 0525592872       | Easy-On FFC/FPC Connector,<br>0.50mm Pitch, Slider Series, Vertical,<br>3.90mm Height, 28 Circuits, Tin-<br>Bismuth Plating  | Compliant                     | Not Contained<br>Per -<br>D(2020)4578-DC<br>(25 June 2020) | Not Low-Halogen           |
| 0524372572       | Easy-On FFC/FPC Connector,<br>0.50mm Pitch, Slider Series, Right-<br>Angle, Bottom Contact, 2.00mm<br>Height, 25 Circuits, Tin-Bismuth<br>Plating  | Compliant                     | Not Contained<br>Per -<br>D(2020)4578-DC<br>(25 June 2020) | Not Low-Halogen           |
| 0525592570       | Easy-On FFC/FPC Connector,<br>0.50mm Pitch, Slider Series, Vertical,<br>3.90mm Height, 25 Circuits, Tin-<br>Bismuth Plating  | Compliant                     | Not Contained<br>Per -<br>D(2020)4578-DC<br>(25 June 2020) | Not Low-Halogen           |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>   | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b>                                 | <b>Low-Halogen Status</b> |
|------------------|---|-------------------------------|---|---------------------------|
| 0528921695       | 0.50mm Pitch Easy-On Type FFC/ FPC Connector, Right-Angle, Surface Mount, ZIF, Bottom Contact Style, Cable Retention Guide, 16 Circuits                                   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0015244745       | 5.08mm Pitch Disk Drive Power Connection System Header, Vertical, Through Hole, 4 Circuits, Lead-Free, 3.58mm PC Tail Length, without PCB Locator Peg                     | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0470183000       | 1.27mm Pitch Serial ATA Host Receptacle, Mating Height 4.70mm, Gold (Au) Flash, Light Tin Solder Area, Surface Mount, Right-Angle, Top Mount Type, 22 Circuits, Lead-Free | Product not active            | Product not active                                | Product not active        |
| 5008730816       | TFR Card Assy Normal Type 8Ckt EmbsTpPkg  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 1062841100       |   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0955027883       | Modular Jack, Vertical, Bottom Entry, Through Hole, 8/8, Tray   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0739982023       | HDM DC Vertical Power SLS 3.5PF LF  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0351890110       | 4.75mm Tab, MP-Lock Housing, 1 Circuit, UL94V-2, Natural  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0528921533       | 0.50mm Pitch Easy-On FFC/FPC Connector, Right-Angle, Surface Mount, ZIF, Bottom Contact Style, Cable Retention Guide, 15 Circuits   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0190020025       | Avikrimp Fully Insulated Quick Disconnect, Female, for 14-16 AWG Wire, Mylar Tape   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0022288035       | KK 254 Breakaway Header, Right-Angle Surface Mount Compatible, 3 Circuits, 0.76µm Gold (Au) Selective Plating, Mating Pin Length 8.23mm                                   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Not Low-Halogen           |
| 0855025006       | Modular Jack, Right-Angle, Surface Mount, 6/4, Low Profile, Tape & Reel   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |
| 0426081435       |   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020) | Low-Halogen               |



**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>  | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b>                                  | <b>Low-Halogen Status</b> |
|------------------|--|-------------------------------|--|---------------------------|
| 0441500005       | Modular Jack, Right-Angle, Low Profile, 8/8, 2 Ports   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020)  | Not Low-Halogen           |
| 0190020045       | Avikrimp Quick Disconnect, Female, for 10-12 (5.00-3.30mm <sup>2</sup> ) Wire, Mylar Tape, Tab 6.35 x 0.81mm   | Compliant                     | Not Contained Per - ECHA_01_2020 (16 January 2020) | Low-Halogen               |
| 0747290001       | SFP Cage Lightpipe Cover Assembly, 1-by-5, Rear Mount  | Compliant                     | Not Contained Per - ED/108/2014 (17 Dec 2014)      | Not Low-Halogen           |
| 0432238191       | Modular Jack, Right-Angle, Low Profile, 8/6, 2 Ports   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020)  | Low-Halogen               |
| 0432238193       | Modular Jack, Right-Angle, Low Profile, 8/4, 3 Ports   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020)  | Low-Halogen               |
| 0210200161       | 0.50mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 16 Circuits, 30.00mm Cable Length, Tin(Sn) Plating  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020)  | Not Low-Halogen           |
| 1700177001       | Small Form-factor Pluggable Plus (SFP+) Stacked 2-by-8 Multi-Port Press Fit Connector with 4 Lightpipe Ports (2 Inner/2 Outer), Elastomeric Gasket, 608 Circuits, Tin (Sn), Enhanced EMI | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020)  | Low-Halogen               |
| 0534080679       | 1.00mm Pitch Plug, Surface Mount, Dual Row, Vertical Stacking, Mated Stack Height 20.00mm, 60 Circuits   | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020)  | Low-Halogen               |
| 0350689822       | MP-Lock Quick Disconnect, Female, for 16-20 AWG (1.31-0.52mm <sup>2</sup> ), Metal Strip, Tab 4.75 x 0.80mm, Pre-Tin Plated  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020)  | Low-Halogen               |
| 0190020044       | Avikrimp Quick Disconnect, Female, for 10-12 (5.00-3.30mm <sup>2</sup> ) Wire, Box, Tab 6.35 x 0.81mm  | Compliant                     | Not Contained Per - D(2020)4578-DC (25 June 2020)  | Low-Halogen               |