

Product Compliance Statement

August 20, 2020

Molex is committed to managing the use of chemical substances in accordance with governmental regulations, industry standards, and customer-specific requirements in order to protect the environment. For each part listed, this document provides:

- **EU RoHS Compliance Status.** EU RoHS status is declared per Directive 2011/65/EU and its subsequent amendments, including the Directive EU 2015/863 which additionally prohibited four phthalates. Homogeneous materials of parts that are compliant to this legislation have less than 0.1% by weight each of lead, mercury, hexavalent chromium, PBB, PBDE, DBP, BBP, DIBP, DEHP, and 0.01% by weight of cadmium. In situations where an exemption applies, the preceding limits, corresponding to the exempted substance(s), may be higher.

- **EU REACH SVHC Content.** Substances of Very High Concerns (SVHCs) are declared if above 0.1% of the article per Regulation (EC) No. 1907/2006 and its subsequent amendments. The Candidate List of SVHCs is continually updated at <https://echa.europa.eu/candidate-list-table>.

- **Low-Halogen Status.** Homogeneous materials of parts that are considered Low-Halogen have less than 0.09% by weight each of bromine and chlorine, and less than 0.15% by weight of the sum of bromine and chlorine.

Molex's sole liability for incorrectly certifying a product shall be either replacement of the Molex product or, alternatively and in the sole discretion of Molex, return of the purchase price paid for the relevant Molex product.

For additional information regarding Molex's environmental initiatives and further explanation of this information, please visit www.molex.com



Haim Eliyahu
Director, Global Product Stewardship

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1705251118	Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Unguided, Left Endwall, 10 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727080104	Mini-Fit TPA2 Receptacle Housing, 4.20mm Pitch, Dual Row, UL 94V-2, Glow-Wire Capable, 4 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1719771209	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.75µm Selective Gold (Au) Plating, 9 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722871204	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 4 Circuits, with Solder Clips, 0.38µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1726723004	7.50mm Pitch Super Sabre Receptacle Crimp Housing, UL 94V-2, Glow-Wire Capable, 4 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1713203038	Impel 90 Ohm, 4 Pair Right-Angle Daughtercard, 1.90mm Pitch, Left Guided, 8 Columns, 64 Circuits, Plated Through Hole Dimension 0.36mm	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722982308	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 8 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1726723003	7.50mm Pitch Super Sabre Receptacle Crimp Housing, UL 94V-2, Glow-Wire Capable, 3 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1720651006	Mega-Fit Vertical Header, Through Hole, 5.70mm Pitch, Dual Row, 6 Circuits, 0.76µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722871205	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 5 Circuits, with Solder Clips, 0.38µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1715739604	Impact 100 Ohm 3 Pair Right-Angle Orthogonal Direct Header, Bottom Guide, Top Endwall, with Outtrigger, 6 Column, 90#Mate Position, Pin Length 4.90mm, Plated Through- Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1719771208	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.75µm Selective Gold (Au) Plating, 8 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1721590209	3.96mm Pitch EdgeMate Wire- to-Board Edge Card Connector, Female, Nylon 6/6, White, UL94-V2, without Lock, 9 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705251825	Impact 3x8 85 Ohm Dual Wall BP 5.5 .46	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1721590610	3.96mm Pitch EdgeMate Wire- to-Board Edge Card Connector, Female, Nylon 6/6, White, UL94-V2, with Positive Lock, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1717223062	zQuad Small Form Factor Pluggable Plus (zQSFP+) Stacked Integrated 2-by-3 Connector and Cage with Metal EMI Gasket, Gold (Au) Over Nickel Plated, with Internal Heat Sinks, Open Top	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1721730006	KK 396 Breakaway Header, Right- Angle Square Pin, 6 Circuits, Matte Tin (Sn) Plating, Mating Pin Length 11.43mm	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1700714011	zSFP+ Stacked Ganged Assembly with Elastomeric Gasket, 2-by-4 with 4 Light Pipes, 160 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1718564007	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 12.95mm, Tape and Reel, 7 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727080110	Mini-Fit TPA2 Receptacle Housing, 4.20mm Pitch, Dual Row, UL 94V-2, Glow-Wire Capable, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1718131010	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 17.02mm, Bag, 10 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1729520801	Micro-Fit TPA Receptacle Housing, Dual Row, 8 Circuits, UL 94V-0, Low-Halogen, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1700010110	Mega-Fit Receptacle Housing, Dual Row, 10 Circuit, Glow-Wire Capable, Bag	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1727090104	Mini-Fit TPA2 Terminal Position Assurance (TPA) Retainer, 4.20mm Pitch, UL 94V-2, Glow-Wire Capable, 4 Circuits, White	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1719710103	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 3 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722642007	Ultra-Fit Terminal Position Assurance (TPA) Wire-to-Board Retainer, 3.50mm Pitch, 7 Circuits, Natural	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718561106	KK RPC 100 Hdr FrLk Vert 06 Ckt 15Au	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719750208	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Through Hole, with Pegs, 0.75µm Selective Gold (Au) Plating, 8 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705259608	Impact BP 3X16 85ohm GR Endwall 5.5 0.39	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719770124	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.38µm Selective Gold (Au) Plating, 24 Circuits, Tube	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718131005	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 17.02mm, Bag, 5 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710221	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 21 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703359407	Impact 85 Ohm Plus 4 Pair Vertical Header, Right Guide, Left End Wall, 14 Columns, 168 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1726460512	MiniFitJrPlg SR PnlMnt V-2 5Ckt	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1718564012	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 12.95mm, Tape and Reel, 12 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1703353207	Impact 85 Ohm Plus 4 Pair Vertical Header, Left Guide, Open End Walls, 12 Columns, 144 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705251625	Impact 3x16 85 Ohm Dual Wall BP 5.5 .46	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710216	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 16 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722564107	Ultra-Fit Tangless Receptacle Housing, 3.50mm Pitch, Single Row, 7 Circuits, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1715739605	Impact 100 Ohm 3 Pair Right-Angle Orthogonal Direct Header, Bottom Guide, Top Endwall, with Outtrigger, 6 Column, 90#Mate Position, Pin Length 5.50mm, Plated Through- Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1727656121	Mini-Fit TPA2 Male Crimp Terminal, Brass, Pre-Plated Tin (Sn), 22-24 AWG, 1.65-2.38mm Insulation Diameter, Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720420806	Super Sabre Vertical Header, 8 Circuit, Long Solder Tail with Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705303022	Impact 85 Ohm Plus 3 Pair Right- Angle Daughtercard, Left Guide, 12 Columns, 108 Circuits, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705251818	Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Unguided, Left Endwall, 8 Columns, 72 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718563004	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, Tin (Sn) Plating, Pin Length 12.95mm, Tape and Reel, 4 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719730605	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Surface Mount, Matte Tin (Sn) Plating, 5 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719740102	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 2 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722533112	Ultra-Fit Crimp Terminal, Female, 0.76µm Gold (Au) Plating, 20-22 AWG	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703903000	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 18.00mm, Left Guided, 10 Columns, 120 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1716920110	Mega-Fit Receptacle Housing, Dual Row, 10 Circuit, UL 94 V-0, Bag	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1703351227	Impact 85 Ohm Plus 4 Pair Vertical Header, Unguided, Dual End Walls, 12 Columns, 144 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722982314	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 14 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1718141003	3.96mm Pitch, KK 396 RPC Wire- to-Board Right-Angle Header with Friction Lock, 15µm Gold (Au) Plating, Bag, 3 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1721731008	KK 396 Breakaway Header, Right- Angle Square Pin, 8 Circuits, 0.38µm Gold (Au) Plating, Mating Pin Length 11.43mm	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1722981306	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 6 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703901020	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 25.00mm, Unguided, 10 Columns, 120 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722991112	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 12 Circuits, with Solder Clips, Tin (Sn) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703357905	Impact 85 Ohm Plus 4 Pair Vertical Header, Left Guide, Right End Wall, 18 Columns, 216 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718131004	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 17.02mm, Bag, 4 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703903030	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 37.00mm, Left Guided, 10 Columns, 120 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720420502	Super Sabre Vertical Header, 5 Circuit, Short Solder Tail with Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710220	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 20 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710018	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, Matte Tin (Sn) Plating, 18 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722862102	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 2 Circuits, with Kinked Pins, Tin (Sn) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718563005	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, Tin (Sn) Plating, Pin Length 12.95mm, Tape and Reel, 5 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719771015	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, Matte Tin (Sn) Plating, 15 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719771102	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.38µm Selective Gold (Au) Plating, 2 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723162314	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Dual Row, 14 Circuits, 0.76µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727656122	Mini-Fit TPA2 Male Crimp Terminal, Brass, Pre-Plated Tin (Sn), 22-24 AWG, 1.65-2.38mm Insulation Diameter, Bag	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722564108	Ultra-Fit Tangless Receptacle Housing, 3.50mm Pitch, Single Row, 8 Circuits, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1718131006	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 17.02mm, Bag, 6 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710215	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 15 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718563010	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, Tin (Sn) Plating, Pin Length 12.95mm, Tape and Reel, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719771020	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, Matte Tin (Sn) Plating, 20 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723161308	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Dual Row, 8 Circuits, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718564011	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 12.95mm, Tape and Reel, 11 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1726460513	Mini-Fit Jr. Plug Housing, Single Row without Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, Glow-Wire Capable, 5 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1719710222	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 22 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703355807	Impact 85 Ohm Plus 4 Pair Vertical Header, Right Guide, Open End Walls, 8 Columns, 96 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719770123	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.38µm Selective Gold (Au) Plating, 23 Circuits, Tube	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703355106	Impact 85 Ohm Plus 4 Pair Vertical Header, Right Guide, Open End Walls, 10 Columns, 120 Circuits, Pin Length 4.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705259607	Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Right Guide with Endwall, 16 Columns, 144 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718130109	KK RPC 156 Hdr Assy FrLk 09 Ckt Tin	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722991306	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 6 Circuits, with Solder Clips, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722642006	Ultra-Fit Terminal Position Assurance (TPA) Wire-to-Board Retainer, 3.50mm Pitch, 6 Circuits, Natural	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710104	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 4 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727090105		Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1724470210	Mini-Fit Jr. Header, Dual Row, Vertical, without Snap-in Plastic Peg PCB Lock, 10 Circuits, PA Polyamide Nylon 6/6 94V-2, Tin (Sn) Plating, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1729520802	Micro-Fit TPA Receptacle Housing, Dual Row, 8 Circuits, UL 94V-2, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1727620010	Mini-Fit TPA2 Plug Housing, 4.20mm Pitch, Dual Row, UL 94V-0, Low- Halogen, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718131011	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 17.02mm, Bag, 11 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703905036	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 37.00mm, Right Guided, 16 Columns, 192 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720651010	Mega-Fit Vertical Header, Through Hole, 5.70mm Pitch, Dual Row, 10 Circuits, 0.76µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1712941804	Impact 100 Ohm 4 Pair Vertical Backplane Header, Unguided, Open Endwall, 8 Columns, 96 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.46mm, Matte Tin, 0.254µm Gold	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722681006	Ultra-Fit Terminal Position Assurance (TPA) Wire-to-Board Retainer, 3.50mm Pitch, 6 Circuits, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1722991212	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 12 Circuits, with Solder Clips, 0.38µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722982214	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 14 Circuits, with Kinked Pins, 0.38µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710124	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 24 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718144012	KK 396 RPC Wire-to-Board Right- Angle Header with Friction Lock, 12 Circuits, 15µm Gold (Au)	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703351827	Impact 85 Ohm Plus 4 Pair Vertical Header, Unguided, Dual End Walls, 8 Columns, 96 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720420402	Super Sabre Vertical Header, 4 Circuit, Short Solder Tail with Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710006	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, Matte Tin (Sn) Plating, 6 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1713203022	Impel 90 Ohm, 4 Pair Right-Angle Daughtercard, 1.90mm Pitch, Left Guided, 12 Columns, 96 Circuits, Plated Through Hole Dimension 0.36mm	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718571003	2.54mm Pitch, KK 254 RPC Wire- to-Board Right-Angle Header with Friction Lock, 15µm Gold (Au) Plating, Bag, 3 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703901032	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 37.00mm, Unguided, 12 Columns, 144 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1705253618	Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Left Guide, Open Endwall, 16 Columns, 144 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Polarizing Key Position A, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1712947607	Impact 100 Ohm 4 Pair Vertical Backplane Header, Left Guided, Endwall, 16 Columns, 192 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723101307	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Single Row, 7 Circuits, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1721850010	EXTreme EnergetiC Modular Right- Angle Plug Assembly, 4 Power Circuits with Solder Tail Mounting, without Guide	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727670124	Mini-Fit TPA2 Plug Housing, 4.20mm Pitch, Dual Row, UL 94V-2 Glow- Wire Capable, 24 Circuits, Panel Mount	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1718133004	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, Tin (Sn) Plating, Pin Length 17.02mm, Tape and Reel, 4 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1725123618	EXTreme Ten60Power Panel-to- Board Receptacle Housing, 18 Signal Circuits, 6 Power Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1727186122	Mini-Fit TPA2 Female Crimp Terminal, Brass, Pre-Plated Tin (Sn), 22-24 AWG, 1.65-2.38mm Insulation Diameter, Bag	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1717222003	zQuad Small Form Factor Pluggable Plus (zQSFP+) Stacked Integrated 2-by-2 Connector and Cage with Metal EMI Gasket, 152 Circuit, Gold (Au) Over Nickel Plated, Down/Up Light Pipe Indicators	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722872108	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 8 Circuits, with Solder Clips, Tin (Sn) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722582106	Ultra-Fit TPA Receptacle Housing, 3.50mm Pitch, Dual Row, 6 Circuits, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1706722294	EdgeLine Vertical Connector, 12.5 Gbps, 0.80mm Pitch, 2.36mm PCB Thickness, 2 Bays, 294 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720430602	Super Sabre Right-Angle Header, 6 Circuit, Short Solder Tail with Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722561104	Ultra-Fit TPA Receptacle Housing, 3.50mm Pitch, Single Row, 4 Circuits, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719770108	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.38µm Selective Gold (Au) Plating, 8 Circuits, Tube	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727184111	Mini-Fit TPA2 Female Crimp Terminal, Phosphor Bronze, Pre- Plated Tin (Sn), 18-20 AWG, 2.10-2.85mm Insulation Diameter, Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1713151828	Impel 90 Ohm, 4 Pair Vertical Backplane Header, 1.90mm Pitch, Unguided, Dual Endwalls, 8 Columns, 64 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.36mm	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1722861307	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 7 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1713203138	Impel 4x8 DC Left GD 1.9mm Pitch Key A	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1726750813	Mini-Fit Plus HCS Header, Dual Row, Vertical, 8 Circuits, with Snap-in Plastic Peg PCB Lock, PA Polyamide Nylon 6/6, UL 94V-2, Glow-Wire Capable, Tin (Sn) Plating	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1703351605	Impact 85 Ohm Plus 4 Pair Vertical Header, Unguided, Open End Walls, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703405010	Impact 85 Ohm Plus 4 Pair, Right- Angle Daughtercard, Right Guided, 10 Columns, 120 Circuits, Plated Through Hole Dimension 0.46mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1710970012	EXTreme EnergetiC Right-Angle Plug Assembly, 27 Circuits (25 Signal/2 Power) with Press-Fit and Pegs Mounting	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705255207	Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Right Guide, Open Endwall, 12 Columns, 108 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1717226002	zQSFP+Stkd 2x2wEMI Sprg Fgrs 4 Int LP Dn	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1726460413	Mini-Fit Jr. Plug Housing, Single Row without Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, Glow-Wire Capable, 4 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1727185111	Mini-Fit TPA2 Female Crimp Terminal, Phosphor Bronze, Pre- Plated Tin (Sn), 22-24 AWG, 1.07-1.65mm Insulation Diameter, Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723162106	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Dual Row, 6 Circuits, Tin (Sn) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1715737605	Impact 100 Ohm 3 Pair Right- Angle Orthogonal Direct Header, Top Guide, Bottom Endwall, with Outrigger, 6 Column, 90#Mate Position, Pin Length 5.50mm, Plated Through-Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1719710012	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, Matte Tin (Sn) Plating, 12 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727080122	Mini-Fit TPA2 Receptacle Housing, 4.20mm Pitch, Dual Row, UL 94V-2, Glow-Wire Capable, 22 Circuit	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1722862307	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 7 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722562002	Ultra-Fit Receptacle Housing, 3.50mm Pitch, Single Row, 2 Circuits, Natural	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703901026	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 25.00mm, Unguided, 16 Columns, 192 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1729531001	Micro-Fit Terminal Position Assurance (TPA) Retainer, 10 Circuits, 3.00mm Pitch, UL 94V-0, Low-Halogen, Natural	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1720420602	Super Sabre Vertical Header, 6 Circuit, Short Solder Tail with Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1700712013	zSFP+ Stacked Ganged Assembly with Elastomeric Gasket, 2-by-2 with Outer Down/Up Light Pipes, 80 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1718134004	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 17.02mm, Tape and Reel, 4 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719771109	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.38µm Selective Gold (Au) Plating, 9 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723161212	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Dual Row, 12 Circuits, 0.38µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722871108	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 8 Circuits, with Solder Clips, Tin (Sn), Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720650212	Mega-Fit Slim Vertical Header, Through Hole, 5.70mm Pitch, Dual Row, 12 Circuits, 0.38µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1714461112	SpeedStack Vertical Plug, 0.80mm Pitch, 3.90mm Height, 60 Circuits, UL94V-0, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1725123624	EXTreme Ten60Power Panel-to- Board Receptacle Housing, 24 Signal Circuits, 6 Power Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1720420405	Super Sabre Vertical Header, 4 Circuit, Long Solder Tail without Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703351127	Impact 85 Ohm Plus 4 Pair Vertical Header, Unguided, Dual End Walls, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1715653003	zQuad Small Form Factor Pluggable Plus (zQSFP+) Stacked Integrated 2-by-3 Connector and Cage with Elastomeric Gasket, Gold (Au) Over Nickel Plated, Down/Up Light Pipe	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723102307	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Single Row, 7 Circuits, 0.76µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723102203	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Single Row, 3 Circuits, 0.38µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1708070037	NeoScale High-Speed Mezzanine Plug, 2.80mm Pitch, 4x8, 32 Triads-85 Ohm (96 Circuits), 12.00mm Connector Height	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727182122	Mini-Fit TPA2 Female Crimp Terminal, Brass, Pre-Plated Tin (Sn), 16 AWG, 2.55-3.14mm Insulation Diameter, Bag	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1703353107	Impact 85 Ohm Plus 4 Pair Vertical Header, Left Guide, Open End Walls, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718571011	2.54mm Pitch, KK 254 RPC Wire- to-Board Right-Angle Header with Friction Lock, 15µm Gold (Au) Plating, Bag, 11 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727670012	Mini-Fit TPA2 Plug Housing, 4.20mm Pitch, Dual Row, UL 94V-0, Low- Halogen, 12 Circuits, Panel Mount	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710121	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 21 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1717226003		Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1704151918	Impact 100 Ohm 3 Pair Mezzanine Receptacle, Unguided, 18.00mm Stack Height, 16 Columns, 144 Circuits, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1708072017	NeoScale High-Speed Mezzanine Plug, 2.80mm Pitch, 6x20, 120 Triads-100 Ohm (360 Circuits), 18.00mm Connector Height	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710119	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 19 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722862203	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 3 Circuits, with Kinked Pins, 0.38µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722992212	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 12 Circuits, with Solder Clips, 0.38µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718144007	KK 396 RPC Wire-to-Board Right- Angle Header with Friction Lock, 7 Circuits, 15µm Gold (Au)	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710203	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 3 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710116	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 16 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718139998	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, Tin (Sn) Plating, Pin Length 18.29mm, Bag, 3 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1715747805	Impact 100 Ohm 4 Pair Right- Angle Orthogonal Direct Header, Top Guide, Bottom Endwall, with Outtrigger, 8 Column, 90#Mate Position, Pin Length 5.50mm, Plated Through-Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1722582112	Ultra-Fit TPA Receptacle Housing, 3.50mm Pitch, Dual Row, 12 Circuits, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727620104	Mini-Fit TPA2 Plug Housing, 4.20mm Pitch, Dual Row, UL 94V-2, Glow- Wire Capable, 4 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1715759105	Impact 100 Ohm 5 Pair Right-Angle Orthogonal Direct Header, Bottom Guide, Top Endwall, with Outtrigger, 10 Column, 90#Mate Position, Pin Length 5.50mm, Plated Through- Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1722641006	Ultra-Fit Terminal Position Assurance (TPA) Wire-to-Board Retainer, 3.50mm Pitch, 6 Circuits, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705251816	Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Unguided, Left Endwall, 8 Columns, 72 Circuits, Pin Length 4.50mm, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718560105	KK RPC 100 Hdr FrLk Vert 05 Ckt Tin	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1712981717	Impact 100 Ohm 6 Pair Vertical Backplane Header, Unguided, Left Endwall, 14 Columns, 252 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, MAPS, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722564105	Ultra-Fit Tangless Receptacle Housing, 3.50mm Pitch, Single Row, 5 Circuits, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1720430305	Super Sabre Right-Angle Header, 3 Circuit, Long Solder Tail without Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722583104	Ultra-Fit Tangless Receptacle Housing, 3.50mm Pitch, Dual Row, 4 Circuits, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1714003020	Impel 90 Ohm, 6 Pair Right-Angle Daughtercard, 1.90mm Pitch, Left Guided, 10 Columns, 120 Circuits, Plated Through Hole Dimension 0.36mm	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722992204	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 4 Circuits, with Solder Clips, 0.38µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1717223001	zQuad Small Form Factor Pluggable Plus (zQSFP+) Stacked Integrated 2-by-3 Connector and Cage with Metal EMI Gasket, 228 Circuit, Gold (Au) Over Nickel Plated, No Light Pipe	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723162308	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Dual Row, 8 Circuits, 0.76µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703403038	Impact 85 Ohm Plus 4 Pair, Right- Angle Daughtercard, Left Guided, 8 Columns, 96 Circuits, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718564010	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 12.95mm, Tape and Reel, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718562003	KK RPC 100 Hdr FrLk Vert 03 Ckt 30Au	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703903002	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 18.00mm, Left Guided, 12 Columns, 144 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719770122	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.38µm Selective Gold (Au) Plating, 22 Circuits, Tube	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1718564005	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 12.95mm, Tape and Reel, 5 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722981304	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 4 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723161304	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Dual Row, 4 Circuits, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703359207	Impact 85 Ohm Plus 4 Pair Vertical Header, Right Guide, Left End Wall, 12 Columns, 144 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722981314	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 14 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720650304	Mega-Fit Slim Vertical Header, Through Hole, 5.70mm Pitch, Dual Row, 4 Circuits, 0.76µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722992112	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 12 Circuits, with Solder Clips, Tin (Sn) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1731620338	Nano-Pitch I/O Receptacle, Straight, Extra Duty Through Hole, 3.00mm Tail Length, with Cap, 80 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718574010	2.54mm Pitch, KK 254 RPC Wire- to-Board Right-Angle Header with Friction Lock, 15µm Gold (Au) Plating, Tape and Reel, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1715757107	Impact 100 Ohm 5 Pair Right- Angle Orthogonal Direct Header, Top Guide, Bottom Endwall, with Outtrigger, 10 Column, 90#Mate Position, Pin Length 4.90mm, Plated Through-Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1705251118	Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Unguided, Left Endwall, 10 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727080104	Mini-Fit TPA2 Receptacle Housing, 4.20mm Pitch, Dual Row, UL 94V-2, Glow-Wire Capable, 4 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1719771209	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.75µm Selective Gold (Au) Plating, 9 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722871204	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 4 Circuits, with Solder Clips, 0.38µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1726723004	7.50mm Pitch Super Sabre Receptacle Crimp Housing, UL 94V-2, Glow-Wire Capable, 4 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1713203038	Impel 90 Ohm, 4 Pair Right-Angle Daughtercard, 1.90mm Pitch, Left Guided, 8 Columns, 64 Circuits, Plated Through Hole Dimension 0.36mm	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722982308	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 8 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1726723003	7.50mm Pitch Super Sabre Receptacle Crimp Housing, UL 94V-2, Glow-Wire Capable, 3 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1720651006	Mega-Fit Vertical Header, Through Hole, 5.70mm Pitch, Dual Row, 6 Circuits, 0.76µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722871205	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 5 Circuits, with Solder Clips, 0.38µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1715739604	Impact 100 Ohm 3 Pair Right-Angle Orthogonal Direct Header, Bottom Guide, Top Endwall, with Outtrigger, 6 Column, 90#Mate Position, Pin Length 4.90mm, Plated Through- Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1719771208	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.75µm Selective Gold (Au) Plating, 8 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1721590209	3.96mm Pitch EdgeMate Wire- to-Board Edge Card Connector, Female, Nylon 6/6, White, UL94-V2, without Lock, 9 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705251825	Impact 3x8 85 Ohm Dual Wall BP 5.5 .46	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1721590610	3.96mm Pitch EdgeMate Wire- to-Board Edge Card Connector, Female, Nylon 6/6, White, UL94-V2, with Positive Lock, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1717223062	zQuad Small Form Factor Pluggable Plus (zQSFP+) Stacked Integrated 2-by-3 Connector and Cage with Metal EMI Gasket, Gold (Au) Over Nickel Plated, with Internal Heat Sinks, Open Top	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1721730006	KK 396 Breakaway Header, Right- Angle Square Pin, 6 Circuits, Matte Tin (Sn) Plating, Mating Pin Length 11.43mm	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1700714011	zSFP+ Stacked Ganged Assembly with Elastomeric Gasket, 2-by-4 with 4 Light Pipes, 160 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1718564007	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 12.95mm, Tape and Reel, 7 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727080110	Mini-Fit TPA2 Receptacle Housing, 4.20mm Pitch, Dual Row, UL 94V-2, Glow-Wire Capable, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1718131010	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 17.02mm, Bag, 10 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1729520801	Micro-Fit TPA Receptacle Housing, Dual Row, 8 Circuits, UL 94V-0, Low-Halogen, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1700010110	Mega-Fit Receptacle Housing, Dual Row, 10 Circuit, Glow-Wire Capable, Bag	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1727090104	Mini-Fit TPA2 Terminal Position Assurance (TPA) Retainer, 4.20mm Pitch, UL 94V-2, Glow-Wire Capable, 4 Circuits, White	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1719710103	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 3 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722642007	Ultra-Fit Terminal Position Assurance (TPA) Wire-to-Board Retainer, 3.50mm Pitch, 7 Circuits, Natural	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718561106	KK RPC 100 Hdr FrLk Vert 06 Ckt 15Au	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719750208	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Through Hole, with Pegs, 0.75µm Selective Gold (Au) Plating, 8 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705259608	Impact BP 3X16 85ohm GR Endwall 5.5 0.39	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719770124	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.38µm Selective Gold (Au) Plating, 24 Circuits, Tube	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718131005	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 17.02mm, Bag, 5 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710221	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 21 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703359407	Impact 85 Ohm Plus 4 Pair Vertical Header, Right Guide, Left End Wall, 14 Columns, 168 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1726460512	MiniFitJrPlg SR PnlMnt V-2 5Ckt	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1718564012	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 12.95mm, Tape and Reel, 12 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1703353207	Impact 85 Ohm Plus 4 Pair Vertical Header, Left Guide, Open End Walls, 12 Columns, 144 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705251625	Impact 3x16 85 Ohm Dual Wall BP 5.5 .46	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710216	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 16 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722564107	Ultra-Fit Tangless Receptacle Housing, 3.50mm Pitch, Single Row, 7 Circuits, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1715739605	Impact 100 Ohm 3 Pair Right-Angle Orthogonal Direct Header, Bottom Guide, Top Endwall, with Outtrigger, 6 Column, 90#Mate Position, Pin Length 5.50mm, Plated Through- Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1727656121	Mini-Fit TPA2 Male Crimp Terminal, Brass, Pre-Plated Tin (Sn), 22-24 AWG, 1.65-2.38mm Insulation Diameter, Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720420806	Super Sabre Vertical Header, 8 Circuit, Long Solder Tail with Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705303022	Impact 85 Ohm Plus 3 Pair Right- Angle Daughtercard, Left Guide, 12 Columns, 108 Circuits, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705251818	Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Unguided, Left Endwall, 8 Columns, 72 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718563004	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, Tin (Sn) Plating, Pin Length 12.95mm, Tape and Reel, 4 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719730605	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Surface Mount, Matte Tin (Sn) Plating, 5 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719740102	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 2 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722533112	Ultra-Fit Crimp Terminal, Female, 0.76µm Gold (Au) Plating, 20-22 AWG	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703903000	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 18.00mm, Left Guided, 10 Columns, 120 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1716920110	Mega-Fit Receptacle Housing, Dual Row, 10 Circuit, UL 94 V-0, Bag	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1703351227	Impact 85 Ohm Plus 4 Pair Vertical Header, Unguided, Dual End Walls, 12 Columns, 144 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722982314	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 14 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1718141003	3.96mm Pitch, KK 396 RPC Wire- to-Board Right-Angle Header with Friction Lock, 15µm Gold (Au) Plating, Bag, 3 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1721731008	KK 396 Breakaway Header, Right- Angle Square Pin, 8 Circuits, 0.38µm Gold (Au) Plating, Mating Pin Length 11.43mm	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1722981306	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 6 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703901020	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 25.00mm, Unguided, 10 Columns, 120 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722991112	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 12 Circuits, with Solder Clips, Tin (Sn) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703357905	Impact 85 Ohm Plus 4 Pair Vertical Header, Left Guide, Right End Wall, 18 Columns, 216 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718131004	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 17.02mm, Bag, 4 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703903030	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 37.00mm, Left Guided, 10 Columns, 120 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720420502	Super Sabre Vertical Header, 5 Circuit, Short Solder Tail with Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710220	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 20 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710018	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, Matte Tin (Sn) Plating, 18 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722862102	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 2 Circuits, with Kinked Pins, Tin (Sn) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718563005	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, Tin (Sn) Plating, Pin Length 12.95mm, Tape and Reel, 5 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719771015	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, Matte Tin (Sn) Plating, 15 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719771102	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.38µm Selective Gold (Au) Plating, 2 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723162314	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Dual Row, 14 Circuits, 0.76µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727656122	Mini-Fit TPA2 Male Crimp Terminal, Brass, Pre-Plated Tin (Sn), 22-24 AWG, 1.65-2.38mm Insulation Diameter, Bag	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722564108	Ultra-Fit Tangless Receptacle Housing, 3.50mm Pitch, Single Row, 8 Circuits, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1718131006	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 17.02mm, Bag, 6 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710215	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 15 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718563010	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, Tin (Sn) Plating, Pin Length 12.95mm, Tape and Reel, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719771020	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, Matte Tin (Sn) Plating, 20 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723161308	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Dual Row, 8 Circuits, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718564011	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 12.95mm, Tape and Reel, 11 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1726460513	Mini-Fit Jr. Plug Housing, Single Row without Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, Glow-Wire Capable, 5 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1719710222	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 22 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703355807	Impact 85 Ohm Plus 4 Pair Vertical Header, Right Guide, Open End Walls, 8 Columns, 96 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719770123	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.38µm Selective Gold (Au) Plating, 23 Circuits, Tube	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703355106	Impact 85 Ohm Plus 4 Pair Vertical Header, Right Guide, Open End Walls, 10 Columns, 120 Circuits, Pin Length 4.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705259607	Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Right Guide with Endwall, 16 Columns, 144 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718130109	KK RPC 156 Hdr Assy FrLk 09 Ckt Tin	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722991306	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 6 Circuits, with Solder Clips, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722642006	Ultra-Fit Terminal Position Assurance (TPA) Wire-to-Board Retainer, 3.50mm Pitch, 6 Circuits, Natural	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710104	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 4 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727090105		Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1724470210	Mini-Fit Jr. Header, Dual Row, Vertical, without Snap-in Plastic Peg PCB Lock, 10 Circuits, PA Polyamide Nylon 6/6 94V-2, Tin (Sn) Plating, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1729520802	Micro-Fit TPA Receptacle Housing, Dual Row, 8 Circuits, UL 94V-2, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1727620010	Mini-Fit TPA2 Plug Housing, 4.20mm Pitch, Dual Row, UL 94V-0, Low- Halogen, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718131011	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 17.02mm, Bag, 11 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703905036	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 37.00mm, Right Guided, 16 Columns, 192 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720651010	Mega-Fit Vertical Header, Through Hole, 5.70mm Pitch, Dual Row, 10 Circuits, 0.76µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1712941804	Impact 100 Ohm 4 Pair Vertical Backplane Header, Unguided, Open Endwall, 8 Columns, 96 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.46mm, Matte Tin, 0.254µm Gold	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722681006	Ultra-Fit Terminal Position Assurance (TPA) Wire-to-Board Retainer, 3.50mm Pitch, 6 Circuits, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1722991212	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 12 Circuits, with Solder Clips, 0.38µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722982214	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 14 Circuits, with Kinked Pins, 0.38µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710124	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 24 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718144012	KK 396 RPC Wire-to-Board Right- Angle Header with Friction Lock, 12 Circuits, 15µm Gold (Au)	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703351827	Impact 85 Ohm Plus 4 Pair Vertical Header, Unguided, Dual End Walls, 8 Columns, 96 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720420402	Super Sabre Vertical Header, 4 Circuit, Short Solder Tail with Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710006	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, Matte Tin (Sn) Plating, 6 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1713203022	Impel 90 Ohm, 4 Pair Right-Angle Daughtercard, 1.90mm Pitch, Left Guided, 12 Columns, 96 Circuits, Plated Through Hole Dimension 0.36mm	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718571003	2.54mm Pitch, KK 254 RPC Wire- to-Board Right-Angle Header with Friction Lock, 15µm Gold (Au) Plating, Bag, 3 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703901032	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 37.00mm, Unguided, 12 Columns, 144 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1705253618	Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Left Guide, Open Endwall, 16 Columns, 144 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Polarizing Key Position A, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1712947607	Impact 100 Ohm 4 Pair Vertical Backplane Header, Left Guided, Endwall, 16 Columns, 192 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723101307	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Single Row, 7 Circuits, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1721850010	EXTreme EnergetiC Modular Right- Angle Plug Assembly, 4 Power Circuits with Solder Tail Mounting, without Guide	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727670124	Mini-Fit TPA2 Plug Housing, 4.20mm Pitch, Dual Row, UL 94V-2 Glow- Wire Capable, 24 Circuits, Panel Mount	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1718133004	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, Tin (Sn) Plating, Pin Length 17.02mm, Tape and Reel, 4 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1725123618	EXTreme Ten60Power Panel-to- Board Receptacle Housing, 18 Signal Circuits, 6 Power Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1727186122	Mini-Fit TPA2 Female Crimp Terminal, Brass, Pre-Plated Tin (Sn), 22-24 AWG, 1.65-2.38mm Insulation Diameter, Bag	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1717222003	zQuad Small Form Factor Pluggable Plus (zQSFP+) Stacked Integrated 2-by-2 Connector and Cage with Metal EMI Gasket, 152 Circuit, Gold (Au) Over Nickel Plated, Down/Up Light Pipe Indicators	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722872108	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 8 Circuits, with Solder Clips, Tin (Sn) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722582106	Ultra-Fit TPA Receptacle Housing, 3.50mm Pitch, Dual Row, 6 Circuits, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1706722294	EdgeLine Vertical Connector, 12.5 Gbps, 0.80mm Pitch, 2.36mm PCB Thickness, 2 Bays, 294 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720430602	Super Sabre Right-Angle Header, 6 Circuit, Short Solder Tail with Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722561104	Ultra-Fit TPA Receptacle Housing, 3.50mm Pitch, Single Row, 4 Circuits, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719770108	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.38µm Selective Gold (Au) Plating, 8 Circuits, Tube	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727184111	Mini-Fit TPA2 Female Crimp Terminal, Phosphor Bronze, Pre- Plated Tin (Sn), 18-20 AWG, 2.10-2.85mm Insulation Diameter, Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1713151828	Impel 90 Ohm, 4 Pair Vertical Backplane Header, 1.90mm Pitch, Unguided, Dual Endwalls, 8 Columns, 64 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.36mm	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1722861307	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 7 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1713203138	Impel 4x8 DC Left GD 1.9mm Pitch Key A	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1726750813	Mini-Fit Plus HCS Header, Dual Row, Vertical, 8 Circuits, with Snap-in Plastic Peg PCB Lock, PA Polyamide Nylon 6/6, UL 94V-2, Glow-Wire Capable, Tin (Sn) Plating	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1703351605	Impact 85 Ohm Plus 4 Pair Vertical Header, Unguided, Open End Walls, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703405010	Impact 85 Ohm Plus 4 Pair, Right- Angle Daughtercard, Right Guided, 10 Columns, 120 Circuits, Plated Through Hole Dimension 0.46mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1710970012	EXTreme EnergetiC Right-Angle Plug Assembly, 27 Circuits (25 Signal/2 Power) with Press-Fit and Pegs Mounting	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705255207	Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Right Guide, Open Endwall, 12 Columns, 108 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1717226002	zQSFP+Stkd 2x2wEMI Sprg Fgrs 4 Int LP Dn	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1726460413	Mini-Fit Jr. Plug Housing, Single Row without Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, Glow-Wire Capable, 4 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1727185111	Mini-Fit TPA2 Female Crimp Terminal, Phosphor Bronze, Pre- Plated Tin (Sn), 22-24 AWG, 1.07-1.65mm Insulation Diameter, Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723162106	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Dual Row, 6 Circuits, Tin (Sn) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1715737605	Impact 100 Ohm 3 Pair Right- Angle Orthogonal Direct Header, Top Guide, Bottom Endwall, with Outrigger, 6 Column, 90#Mate Position, Pin Length 5.50mm, Plated Through-Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1719710012	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, Matte Tin (Sn) Plating, 12 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727080122	Mini-Fit TPA2 Receptacle Housing, 4.20mm Pitch, Dual Row, UL 94V-2, Glow-Wire Capable, 22 Circuit	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1722862307	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 7 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722562002	Ultra-Fit Receptacle Housing, 3.50mm Pitch, Single Row, 2 Circuits, Natural	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703901026	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 25.00mm, Unguided, 16 Columns, 192 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1729531001	Micro-Fit Terminal Position Assurance (TPA) Retainer, 10 Circuits, 3.00mm Pitch, UL 94V-0, Low-Halogen, Natural	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1720420602	Super Sabre Vertical Header, 6 Circuit, Short Solder Tail with Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1700712013	zSFP+ Stacked Ganged Assembly with Elastomeric Gasket, 2-by-2 with Outer Down/Up Light Pipes, 80 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1718134004	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 17.02mm, Tape and Reel, 4 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719771109	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.38µm Selective Gold (Au) Plating, 9 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723161212	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Dual Row, 12 Circuits, 0.38µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722871108	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 8 Circuits, with Solder Clips, Tin (Sn), Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720650212	Mega-Fit Slim Vertical Header, Through Hole, 5.70mm Pitch, Dual Row, 12 Circuits, 0.38µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1714461112	SpeedStack Vertical Plug, 0.80mm Pitch, 3.90mm Height, 60 Circuits, UL94V-0, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1725123624	EXTreme Ten60Power Panel-to- Board Receptacle Housing, 24 Signal Circuits, 6 Power Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1720420405	Super Sabre Vertical Header, 4 Circuit, Long Solder Tail without Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703351127	Impact 85 Ohm Plus 4 Pair Vertical Header, Unguided, Dual End Walls, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1715653003	zQuad Small Form Factor Pluggable Plus (zQSFP+) Stacked Integrated 2-by-3 Connector and Cage with Elastomeric Gasket, Gold (Au) Over Nickel Plated, Down/Up Light Pipe	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723102307	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Single Row, 7 Circuits, 0.76µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723102203	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Single Row, 3 Circuits, 0.38µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1708070037	NeoScale High-Speed Mezzanine Plug, 2.80mm Pitch, 4x8, 32 Triads-85 Ohm (96 Circuits), 12.00mm Connector Height	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727182122	Mini-Fit TPA2 Female Crimp Terminal, Brass, Pre-Plated Tin (Sn), 16 AWG, 2.55-3.14mm Insulation Diameter, Bag	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1703353107	Impact 85 Ohm Plus 4 Pair Vertical Header, Left Guide, Open End Walls, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718571011	2.54mm Pitch, KK 254 RPC Wire- to-Board Right-Angle Header with Friction Lock, 15µm Gold (Au) Plating, Bag, 11 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727670012	Mini-Fit TPA2 Plug Housing, 4.20mm Pitch, Dual Row, UL 94V-0, Low- Halogen, 12 Circuits, Panel Mount	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710121	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 21 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1717226003		Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1704151918	Impact 100 Ohm 3 Pair Mezzanine Receptacle, Unguided, 18.00mm Stack Height, 16 Columns, 144 Circuits, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1708072017	NeoScale High-Speed Mezzanine Plug, 2.80mm Pitch, 6x20, 120 Triads-100 Ohm (360 Circuits), 18.00mm Connector Height	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710119	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 19 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722862203	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 3 Circuits, with Kinked Pins, 0.38µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722992212	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 12 Circuits, with Solder Clips, 0.38µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718144007	KK 396 RPC Wire-to-Board Right- Angle Header with Friction Lock, 7 Circuits, 15µm Gold (Au)	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710203	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 3 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710116	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 16 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718139998	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, Tin (Sn) Plating, Pin Length 18.29mm, Bag, 3 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1715747805	Impact 100 Ohm 4 Pair Right- Angle Orthogonal Direct Header, Top Guide, Bottom Endwall, with Outtrigger, 8 Column, 90#Mate Position, Pin Length 5.50mm, Plated Through-Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1722582112	Ultra-Fit TPA Receptacle Housing, 3.50mm Pitch, Dual Row, 12 Circuits, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727620104	Mini-Fit TPA2 Plug Housing, 4.20mm Pitch, Dual Row, UL 94V-2, Glow- Wire Capable, 4 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1715759105	Impact 100 Ohm 5 Pair Right-Angle Orthogonal Direct Header, Bottom Guide, Top Endwall, with Outtrigger, 10 Column, 90#Mate Position, Pin Length 5.50mm, Plated Through- Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1722641006	Ultra-Fit Terminal Position Assurance (TPA) Wire-to-Board Retainer, 3.50mm Pitch, 6 Circuits, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705251816	Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Unguided, Left Endwall, 8 Columns, 72 Circuits, Pin Length 4.50mm, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718560105	KK RPC 100 Hdr FrLk Vert 05 Ckt Tin	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1712981717	Impact 100 Ohm 6 Pair Vertical Backplane Header, Unguided, Left Endwall, 14 Columns, 252 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, MAPS, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722564105	Ultra-Fit Tangless Receptacle Housing, 3.50mm Pitch, Single Row, 5 Circuits, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1720430305	Super Sabre Right-Angle Header, 3 Circuit, Long Solder Tail without Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722583104	Ultra-Fit Tangless Receptacle Housing, 3.50mm Pitch, Dual Row, 4 Circuits, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1714003020	Impel 90 Ohm, 6 Pair Right-Angle Daughtercard, 1.90mm Pitch, Left Guided, 10 Columns, 120 Circuits, Plated Through Hole Dimension 0.36mm	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722992204	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 4 Circuits, with Solder Clips, 0.38µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1717223001	zQuad Small Form Factor Pluggable Plus (zQSFP+) Stacked Integrated 2-by-3 Connector and Cage with Metal EMI Gasket, 228 Circuit, Gold (Au) Over Nickel Plated, No Light Pipe	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723162308	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Dual Row, 8 Circuits, 0.76µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703403038	Impact 85 Ohm Plus 4 Pair, Right- Angle Daughtercard, Left Guided, 8 Columns, 96 Circuits, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718564010	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 12.95mm, Tape and Reel, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718562003	KK RPC 100 Hdr FrLk Vert 03 Ckt 30Au	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703903002	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 18.00mm, Left Guided, 12 Columns, 144 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719770122	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.38µm Selective Gold (Au) Plating, 22 Circuits, Tube	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1718564005	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 12.95mm, Tape and Reel, 5 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722981304	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 4 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723161304	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Dual Row, 4 Circuits, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703359207	Impact 85 Ohm Plus 4 Pair Vertical Header, Right Guide, Left End Wall, 12 Columns, 144 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722981314	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 14 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720650304	Mega-Fit Slim Vertical Header, Through Hole, 5.70mm Pitch, Dual Row, 4 Circuits, 0.76µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722992112	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 12 Circuits, with Solder Clips, Tin (Sn) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1731620338	Nano-Pitch I/O Receptacle, Straight, Extra Duty Through Hole, 3.00mm Tail Length, with Cap, 80 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718574010	2.54mm Pitch, KK 254 RPC Wire- to-Board Right-Angle Header with Friction Lock, 15µm Gold (Au) Plating, Tape and Reel, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1715757107	Impact 100 Ohm 5 Pair Right- Angle Orthogonal Direct Header, Top Guide, Bottom Endwall, with Outtrigger, 10 Column, 90#Mate Position, Pin Length 4.90mm, Plated Through-Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1705251118	Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Unguided, Left Endwall, 10 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727080104	Mini-Fit TPA2 Receptacle Housing, 4.20mm Pitch, Dual Row, UL 94V-2, Glow-Wire Capable, 4 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1719771209	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.75µm Selective Gold (Au) Plating, 9 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722871204	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 4 Circuits, with Solder Clips, 0.38µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1726723004	7.50mm Pitch Super Sabre Receptacle Crimp Housing, UL 94V-2, Glow-Wire Capable, 4 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1713203038	Impel 90 Ohm, 4 Pair Right-Angle Daughtercard, 1.90mm Pitch, Left Guided, 8 Columns, 64 Circuits, Plated Through Hole Dimension 0.36mm	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722982308	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 8 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1726723003	7.50mm Pitch Super Sabre Receptacle Crimp Housing, UL 94V-2, Glow-Wire Capable, 3 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1720651006	Mega-Fit Vertical Header, Through Hole, 5.70mm Pitch, Dual Row, 6 Circuits, 0.76µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722871205	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 5 Circuits, with Solder Clips, 0.38µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1715739604	Impact 100 Ohm 3 Pair Right-Angle Orthogonal Direct Header, Bottom Guide, Top Endwall, with Outtrigger, 6 Column, 90#Mate Position, Pin Length 4.90mm, Plated Through- Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1719771208	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.75µm Selective Gold (Au) Plating, 8 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1721590209	3.96mm Pitch EdgeMate Wire- to-Board Edge Card Connector, Female, Nylon 6/6, White, UL94-V2, without Lock, 9 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705251825	Impact 3x8 85 Ohm Dual Wall BP 5.5 .46	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1721590610	3.96mm Pitch EdgeMate Wire- to-Board Edge Card Connector, Female, Nylon 6/6, White, UL94-V2, with Positive Lock, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1717223062	zQuad Small Form Factor Pluggable Plus (zQSFP+) Stacked Integrated 2-by-3 Connector and Cage with Metal EMI Gasket, Gold (Au) Over Nickel Plated, with Internal Heat Sinks, Open Top	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1721730006	KK 396 Breakaway Header, Right- Angle Square Pin, 6 Circuits, Matte Tin (Sn) Plating, Mating Pin Length 11.43mm	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1700714011	zSFP+ Stacked Ganged Assembly with Elastomeric Gasket, 2-by-4 with 4 Light Pipes, 160 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1718564007	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 12.95mm, Tape and Reel, 7 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727080110	Mini-Fit TPA2 Receptacle Housing, 4.20mm Pitch, Dual Row, UL 94V-2, Glow-Wire Capable, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1718131010	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 17.02mm, Bag, 10 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1729520801	Micro-Fit TPA Receptacle Housing, Dual Row, 8 Circuits, UL 94V-0, Low-Halogen, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1700010110	Mega-Fit Receptacle Housing, Dual Row, 10 Circuit, Glow-Wire Capable, Bag	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1727090104	Mini-Fit TPA2 Terminal Position Assurance (TPA) Retainer, 4.20mm Pitch, UL 94V-2, Glow-Wire Capable, 4 Circuits, White	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1719710103	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 3 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722642007	Ultra-Fit Terminal Position Assurance (TPA) Wire-to-Board Retainer, 3.50mm Pitch, 7 Circuits, Natural	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718561106	KK RPC 100 Hdr FrLk Vert 06 Ckt 15Au	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719750208	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Through Hole, with Pegs, 0.75µm Selective Gold (Au) Plating, 8 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705259608	Impact BP 3X16 85ohm GR Endwall 5.5 0.39	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719770124	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.38µm Selective Gold (Au) Plating, 24 Circuits, Tube	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718131005	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 17.02mm, Bag, 5 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710221	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 21 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703359407	Impact 85 Ohm Plus 4 Pair Vertical Header, Right Guide, Left End Wall, 14 Columns, 168 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1726460512	MiniFitJrPlg SR PnlMnt V-2 5Ckt	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1718564012	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 12.95mm, Tape and Reel, 12 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1703353207	Impact 85 Ohm Plus 4 Pair Vertical Header, Left Guide, Open End Walls, 12 Columns, 144 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705251625	Impact 3x16 85 Ohm Dual Wall BP 5.5 .46	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710216	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 16 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722564107	Ultra-Fit Tangless Receptacle Housing, 3.50mm Pitch, Single Row, 7 Circuits, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1715739605	Impact 100 Ohm 3 Pair Right-Angle Orthogonal Direct Header, Bottom Guide, Top Endwall, with Outtrigger, 6 Column, 90#Mate Position, Pin Length 5.50mm, Plated Through- Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1727656121	Mini-Fit TPA2 Male Crimp Terminal, Brass, Pre-Plated Tin (Sn), 22-24 AWG, 1.65-2.38mm Insulation Diameter, Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720420806	Super Sabre Vertical Header, 8 Circuit, Long Solder Tail with Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705303022	Impact 85 Ohm Plus 3 Pair Right- Angle Daughtercard, Left Guide, 12 Columns, 108 Circuits, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705251818	Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Unguided, Left Endwall, 8 Columns, 72 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718563004	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, Tin (Sn) Plating, Pin Length 12.95mm, Tape and Reel, 4 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719730605	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Surface Mount, Matte Tin (Sn) Plating, 5 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719740102	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 2 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722533112	Ultra-Fit Crimp Terminal, Female, 0.76µm Gold (Au) Plating, 20-22 AWG	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703903000	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 18.00mm, Left Guided, 10 Columns, 120 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1716920110	Mega-Fit Receptacle Housing, Dual Row, 10 Circuit, UL 94 V-0, Bag	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1703351227	Impact 85 Ohm Plus 4 Pair Vertical Header, Unguided, Dual End Walls, 12 Columns, 144 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722982314	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 14 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1718141003	3.96mm Pitch, KK 396 RPC Wire- to-Board Right-Angle Header with Friction Lock, 15µm Gold (Au) Plating, Bag, 3 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1721731008	KK 396 Breakaway Header, Right- Angle Square Pin, 8 Circuits, 0.38µm Gold (Au) Plating, Mating Pin Length 11.43mm	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1722981306	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 6 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703901020	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 25.00mm, Unguided, 10 Columns, 120 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722991112	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 12 Circuits, with Solder Clips, Tin (Sn) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703357905	Impact 85 Ohm Plus 4 Pair Vertical Header, Left Guide, Right End Wall, 18 Columns, 216 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718131004	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 17.02mm, Bag, 4 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703903030	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 37.00mm, Left Guided, 10 Columns, 120 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720420502	Super Sabre Vertical Header, 5 Circuit, Short Solder Tail with Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710220	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 20 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710018	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, Matte Tin (Sn) Plating, 18 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722862102	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 2 Circuits, with Kinked Pins, Tin (Sn) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718563005	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, Tin (Sn) Plating, Pin Length 12.95mm, Tape and Reel, 5 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719771015	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, Matte Tin (Sn) Plating, 15 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719771102	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.38µm Selective Gold (Au) Plating, 2 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723162314	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Dual Row, 14 Circuits, 0.76µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727656122	Mini-Fit TPA2 Male Crimp Terminal, Brass, Pre-Plated Tin (Sn), 22-24 AWG, 1.65-2.38mm Insulation Diameter, Bag	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722564108	Ultra-Fit Tangless Receptacle Housing, 3.50mm Pitch, Single Row, 8 Circuits, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1718131006	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 17.02mm, Bag, 6 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710215	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 15 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718563010	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, Tin (Sn) Plating, Pin Length 12.95mm, Tape and Reel, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719771020	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, Matte Tin (Sn) Plating, 20 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723161308	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Dual Row, 8 Circuits, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718564011	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 12.95mm, Tape and Reel, 11 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1726460513	Mini-Fit Jr. Plug Housing, Single Row without Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, Glow-Wire Capable, 5 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1719710222	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 22 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703355807	Impact 85 Ohm Plus 4 Pair Vertical Header, Right Guide, Open End Walls, 8 Columns, 96 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719770123	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.38µm Selective Gold (Au) Plating, 23 Circuits, Tube	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703355106	Impact 85 Ohm Plus 4 Pair Vertical Header, Right Guide, Open End Walls, 10 Columns, 120 Circuits, Pin Length 4.50mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705259607	Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Right Guide with Endwall, 16 Columns, 144 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718130109	KK RPC 156 Hdr Assy FrLk 09 Ckt Tin	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722991306	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 6 Circuits, with Solder Clips, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722642006	Ultra-Fit Terminal Position Assurance (TPA) Wire-to-Board Retainer, 3.50mm Pitch, 6 Circuits, Natural	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710104	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 4 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727090105		Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1724470210	Mini-Fit Jr. Header, Dual Row, Vertical, without Snap-in Plastic Peg PCB Lock, 10 Circuits, PA Polyamide Nylon 6/6 94V-2, Tin (Sn) Plating, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1729520802	Micro-Fit TPA Receptacle Housing, Dual Row, 8 Circuits, UL 94V-2, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1727620010	Mini-Fit TPA2 Plug Housing, 4.20mm Pitch, Dual Row, UL 94V-0, Low- Halogen, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718131011	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 17.02mm, Bag, 11 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703905036	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 37.00mm, Right Guided, 16 Columns, 192 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720651010	Mega-Fit Vertical Header, Through Hole, 5.70mm Pitch, Dual Row, 10 Circuits, 0.76µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1712941804	Impact 100 Ohm 4 Pair Vertical Backplane Header, Unguided, Open Endwall, 8 Columns, 96 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.46mm, Matte Tin, 0.254µm Gold	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722681006	Ultra-Fit Terminal Position Assurance (TPA) Wire-to-Board Retainer, 3.50mm Pitch, 6 Circuits, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1722991212	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 12 Circuits, with Solder Clips, 0.38µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722982214	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 14 Circuits, with Kinked Pins, 0.38µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710124	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 24 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718144012	KK 396 RPC Wire-to-Board Right- Angle Header with Friction Lock, 12 Circuits, 15µm Gold (Au)	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703351827	Impact 85 Ohm Plus 4 Pair Vertical Header, Unguided, Dual End Walls, 8 Columns, 96 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720420402	Super Sabre Vertical Header, 4 Circuit, Short Solder Tail with Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710006	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, Matte Tin (Sn) Plating, 6 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1713203022	Impel 90 Ohm, 4 Pair Right-Angle Daughtercard, 1.90mm Pitch, Left Guided, 12 Columns, 96 Circuits, Plated Through Hole Dimension 0.36mm	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718571003	2.54mm Pitch, KK 254 RPC Wire- to-Board Right-Angle Header with Friction Lock, 15µm Gold (Au) Plating, Bag, 3 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703901032	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 37.00mm, Unguided, 12 Columns, 144 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1705253618	Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Left Guide, Open Endwall, 16 Columns, 144 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.39mm, Polarizing Key Position A, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1712947607	Impact 100 Ohm 4 Pair Vertical Backplane Header, Left Guided, Endwall, 16 Columns, 192 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723101307	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Single Row, 7 Circuits, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1721850010	EXTreme EnergetiC Modular Right- Angle Plug Assembly, 4 Power Circuits with Solder Tail Mounting, without Guide	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727670124	Mini-Fit TPA2 Plug Housing, 4.20mm Pitch, Dual Row, UL 94V-2 Glow- Wire Capable, 24 Circuits, Panel Mount	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1718133004	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, Tin (Sn) Plating, Pin Length 17.02mm, Tape and Reel, 4 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1725123618	EXTreme Ten60Power Panel-to- Board Receptacle Housing, 18 Signal Circuits, 6 Power Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1727186122	Mini-Fit TPA2 Female Crimp Terminal, Brass, Pre-Plated Tin (Sn), 22-24 AWG, 1.65-2.38mm Insulation Diameter, Bag	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1717222003	zQuad Small Form Factor Pluggable Plus (zQSFP+) Stacked Integrated 2-by-2 Connector and Cage with Metal EMI Gasket, 152 Circuit, Gold (Au) Over Nickel Plated, Down/Up Light Pipe Indicators	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722872108	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 8 Circuits, with Solder Clips, Tin (Sn) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722582106	Ultra-Fit TPA Receptacle Housing, 3.50mm Pitch, Dual Row, 6 Circuits, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1706722294	EdgeLine Vertical Connector, 12.5 Gbps, 0.80mm Pitch, 2.36mm PCB Thickness, 2 Bays, 294 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720430602	Super Sabre Right-Angle Header, 6 Circuit, Short Solder Tail with Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722561104	Ultra-Fit TPA Receptacle Housing, 3.50mm Pitch, Single Row, 4 Circuits, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719770108	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.38µm Selective Gold (Au) Plating, 8 Circuits, Tube	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727184111	Mini-Fit TPA2 Female Crimp Terminal, Phosphor Bronze, Pre- Plated Tin (Sn), 18-20 AWG, 2.10-2.85mm Insulation Diameter, Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1713151828	Impel 90 Ohm, 4 Pair Vertical Backplane Header, 1.90mm Pitch, Unguided, Dual Endwalls, 8 Columns, 64 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.36mm	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1722861307	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 7 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1713203138	Impel 4x8 DC Left GD 1.9mm Pitch Key A	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1726750813	Mini-Fit Plus HCS Header, Dual Row, Vertical, 8 Circuits, with Snap-in Plastic Peg PCB Lock, PA Polyamide Nylon 6/6, UL 94V-2, Glow-Wire Capable, Tin (Sn) Plating	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1703351605	Impact 85 Ohm Plus 4 Pair Vertical Header, Unguided, Open End Walls, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703405010	Impact 85 Ohm Plus 4 Pair, Right- Angle Daughtercard, Right Guided, 10 Columns, 120 Circuits, Plated Through Hole Dimension 0.46mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1710970012	EXTreme EnergetiC Right-Angle Plug Assembly, 27 Circuits (25 Signal/2 Power) with Press-Fit and Pegs Mounting	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705255207	Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Right Guide, Open Endwall, 12 Columns, 108 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1717226002	zQSFP+Stkd 2x2wEMI Sprg Fgrs 4 Int LP Dn	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1726460413	Mini-Fit Jr. Plug Housing, Single Row without Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, Glow-Wire Capable, 4 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1727185111	Mini-Fit TPA2 Female Crimp Terminal, Phosphor Bronze, Pre- Plated Tin (Sn), 22-24 AWG, 1.07-1.65mm Insulation Diameter, Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723162106	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Dual Row, 6 Circuits, Tin (Sn) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1715737605	Impact 100 Ohm 3 Pair Right- Angle Orthogonal Direct Header, Top Guide, Bottom Endwall, with Outrigger, 6 Column, 90#Mate Position, Pin Length 5.50mm, Plated Through-Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1719710012	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, Matte Tin (Sn) Plating, 12 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727080122	Mini-Fit TPA2 Receptacle Housing, 4.20mm Pitch, Dual Row, UL 94V-2, Glow-Wire Capable, 22 Circuit	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1722862307	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 7 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722562002	Ultra-Fit Receptacle Housing, 3.50mm Pitch, Single Row, 2 Circuits, Natural	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703901026	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 25.00mm, Unguided, 16 Columns, 192 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1729531001	Micro-Fit Terminal Position Assurance (TPA) Retainer, 10 Circuits, 3.00mm Pitch, UL 94V-0, Low-Halogen, Natural	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1720420602	Super Sabre Vertical Header, 6 Circuit, Short Solder Tail with Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1700712013	zSFP+ Stacked Ganged Assembly with Elastomeric Gasket, 2-by-2 with Outer Down/Up Light Pipes, 80 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1718134004	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 17.02mm, Tape and Reel, 4 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719771109	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.38µm Selective Gold (Au) Plating, 9 Circuits, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723161212	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Dual Row, 12 Circuits, 0.38µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722871108	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 8 Circuits, with Solder Clips, Tin (Sn), Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720650212	Mega-Fit Slim Vertical Header, Through Hole, 5.70mm Pitch, Dual Row, 12 Circuits, 0.38µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1714461112	SpeedStack Vertical Plug, 0.80mm Pitch, 3.90mm Height, 60 Circuits, UL94V-0, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1725123624	EXTreme Ten60Power Panel-to- Board Receptacle Housing, 24 Signal Circuits, 6 Power Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1720420405	Super Sabre Vertical Header, 4 Circuit, Long Solder Tail without Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703351127	Impact 85 Ohm Plus 4 Pair Vertical Header, Unguided, Dual End Walls, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1715653003	zQuad Small Form Factor Pluggable Plus (zQSFP+) Stacked Integrated 2-by-3 Connector and Cage with Elastomeric Gasket, Gold (Au) Over Nickel Plated, Down/Up Light Pipe	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723102307	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Single Row, 7 Circuits, 0.76µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723102203	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Single Row, 3 Circuits, 0.38µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1708070037	NeoScale High-Speed Mezzanine Plug, 2.80mm Pitch, 4x8, 32 Triads-85 Ohm (96 Circuits), 12.00mm Connector Height	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727182122	Mini-Fit TPA2 Female Crimp Terminal, Brass, Pre-Plated Tin (Sn), 16 AWG, 2.55-3.14mm Insulation Diameter, Bag	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1703353107	Impact 85 Ohm Plus 4 Pair Vertical Header, Left Guide, Open End Walls, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718571011	2.54mm Pitch, KK 254 RPC Wire- to-Board Right-Angle Header with Friction Lock, 15µm Gold (Au) Plating, Bag, 11 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727670012	Mini-Fit TPA2 Plug Housing, 4.20mm Pitch, Dual Row, UL 94V-0, Low- Halogen, 12 Circuits, Panel Mount	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710121	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 21 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1717226003		Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1704151918	Impact 100 Ohm 3 Pair Mezzanine Receptacle, Unguided, 18.00mm Stack Height, 16 Columns, 144 Circuits, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1708072017	NeoScale High-Speed Mezzanine Plug, 2.80mm Pitch, 6x20, 120 Triads-100 Ohm (360 Circuits), 18.00mm Connector Height	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710119	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 19 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722862203	Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 3 Circuits, with Kinked Pins, 0.38µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722992212	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 12 Circuits, with Solder Clips, 0.38µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718144007	KK 396 RPC Wire-to-Board Right- Angle Header with Friction Lock, 7 Circuits, 15µm Gold (Au)	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710203	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.75µm Selective Gold (Au) Plating, 3 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719710116	2.54mm Pitch SL Header, Single Row, Vertical, LCP, Shrouded, Through Hole, 0.38µm Selective Gold (Au) Plating, 16 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718139998	3.96mm Pitch, KK 396 RPC Vertical Header with Friction Lock, Tin (Sn) Plating, Pin Length 18.29mm, Bag, 3 Circuits, without Pegs	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1715747805	Impact 100 Ohm 4 Pair Right- Angle Orthogonal Direct Header, Top Guide, Bottom Endwall, with Outtrigger, 8 Column, 90#Mate Position, Pin Length 5.50mm, Plated Through-Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1722582112	Ultra-Fit TPA Receptacle Housing, 3.50mm Pitch, Dual Row, 12 Circuits, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727620104	Mini-Fit TPA2 Plug Housing, 4.20mm Pitch, Dual Row, UL 94V-2, Glow- Wire Capable, 4 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1715759105	Impact 100 Ohm 5 Pair Right-Angle Orthogonal Direct Header, Bottom Guide, Top Endwall, with Outtrigger, 10 Column, 90#Mate Position, Pin Length 5.50mm, Plated Through- Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1722641006	Ultra-Fit Terminal Position Assurance (TPA) Wire-to-Board Retainer, 3.50mm Pitch, 6 Circuits, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1705251816	Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Unguided, Left Endwall, 8 Columns, 72 Circuits, Pin Length 4.50mm, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718560105	KK RPC 100 Hdr FrLk Vert 05 Ckt Tin	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1712981717	Impact 100 Ohm 6 Pair Vertical Backplane Header, Unguided, Left Endwall, 14 Columns, 252 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, MAPS, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722564105	Ultra-Fit Tangless Receptacle Housing, 3.50mm Pitch, Single Row, 5 Circuits, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1720430305	Super Sabre Right-Angle Header, 3 Circuit, Long Solder Tail without Board Lock, Complies with UL1977 Finger Proof Standards, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722583104	Ultra-Fit Tangless Receptacle Housing, 3.50mm Pitch, Dual Row, 4 Circuits, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen
1714003020	Impel 90 Ohm, 6 Pair Right-Angle Daughtercard, 1.90mm Pitch, Left Guided, 10 Columns, 120 Circuits, Plated Through Hole Dimension 0.36mm	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722992204	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 4 Circuits, with Solder Clips, 0.38µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1717223001	zQuad Small Form Factor Pluggable Plus (zQSFP+) Stacked Integrated 2-by-3 Connector and Cage with Metal EMI Gasket, 228 Circuit, Gold (Au) Over Nickel Plated, No Light Pipe	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723162308	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Dual Row, 8 Circuits, 0.76µm Gold (Au) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703403038	Impact 85 Ohm Plus 4 Pair, Right- Angle Daughtercard, Left Guided, 8 Columns, 96 Circuits, Plated Through Hole Dimension 0.39mm, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718564010	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 12.95mm, Tape and Reel, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718562003	KK RPC 100 Hdr FrLk Vert 03 Ckt 30Au	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703903002	Impact 85 Ohm Plus 4 Pair Mezzanine Receptacle, Stack Height 18.00mm, Left Guided, 12 Columns, 144 Circuits, Lead Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1719770122	2.54mm Pitch SL Header, Single Row, Right-Angle, LCP, Shrouded, Surface Mount, with Pegs, 0.38µm Selective Gold (Au) Plating, 22 Circuits, Tube	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low- Halogen Status
1718564005	2.54mm Pitch, KK 254 RPC Vertical Header with Friction Lock, 15µm Gold (Au) Plating, Pin Length 12.95mm, Tape and Reel, 5 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722981304	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 4 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1723161304	Ultra-Fit Right-Angle Header, 3.50mm Pitch, Dual Row, 4 Circuits, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1703359207	Impact 85 Ohm Plus 4 Pair Vertical Header, Right Guide, Left End Wall, 12 Columns, 144 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722981314	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 14 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Black, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1720650304	Mega-Fit Slim Vertical Header, Through Hole, 5.70mm Pitch, Dual Row, 4 Circuits, 0.76µm Gold (Au) Plating, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1722992112	Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 12 Circuits, with Solder Clips, Tin (Sn) Plating, Natural, Glow-Wire Capable	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1731620338	Nano-Pitch I/O Receptacle, Straight, Extra Duty Through Hole, 3.00mm Tail Length, with Cap, 80 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718574010	2.54mm Pitch, KK 254 RPC Wire- to-Board Right-Angle Header with Friction Lock, 15µm Gold (Au) Plating, Tape and Reel, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1715757107	Impact 100 Ohm 5 Pair Right- Angle Orthogonal Direct Header, Top Guide, Bottom Endwall, with Outtrigger, 10 Column, 90#Mate Position, Pin Length 4.90mm, Plated Through-Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low- Halogen