

Product Compliance Statement

November 06, 2020

Molex is committed to managing the use of chemical substances in accordance with governmental regulations, industry standards, and customer-specific requirements in order to protect the environment. For each part listed, this document provides:

- **EU RoHS Compliance Status.** EU RoHS status is declared per Directive 2011/65/EU and its subsequent amendments, including the Directive EU 2015/863 which additionally prohibited four phthalates. Homogeneous materials of parts that are compliant to this legislation have less than 0.1% by weight each of lead, mercury, hexavalent chromium, PBB, PBDE, DBP, BBP, DIBP, DEHP, and 0.01% by weight of cadmium. In situations where an exemption applies, the preceding limits, corresponding to the exempted substance(s), may be higher.

- **EU REACH SVHC Content.** Substances of Very High Concerns (SVHCs) are declared if above 0.1% of the article per Regulation (EC) No. 1907/2006 and its subsequent amendments. The Candidate List of SVHCs is continually updated at <https://echa.europa.eu/candidate-list-table>.

- **Low-Halogen Status.** Homogeneous materials of parts that are considered Low-Halogen have less than 0.09% by weight each of bromine and chlorine, and less than 0.15% by weight of the sum of bromine and chlorine.

Molex's sole liability for incorrectly certifying a product shall be either replacement of the Molex product or, alternatively and in the sole discretion of Molex, return of the purchase price paid for the relevant Molex product.

For additional information regarding Molex's environmental initiatives and further explanation of this information, please visit www.molex.com



Haim Eliyahu
Director, Global Product Stewardship

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
0151660104	0.50mm Pitch Premo-Flex FFC Jumper, Opposite Side Contacts (Type D), 127.00mm Cable Length, Tin (Sn) Plating, 10 Circuits	Compliant	Not Reviewed	Not Reviewed
0151670235	1.00mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 178.00mm Cable Length, Tin (Sn) Plating, 8 Circuits	Compliant	Not Reviewed	Not Reviewed
0151670250	1.00mm Pitch Premo-Flex FFC Jumper, Opposite Side Contacts (Type D), 76.00mm Cable Length, Tin (Sn) Plating, 10 Circuits	Compliant	Not Reviewed	Not Reviewed
0348268126	Mini50 Unsealed Right-Angle Header, Dual Row, 12 Circuit, Polarization Option C, 2.80mm Pin Length, Dark Gray, Tape and Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
0349587340	Mini50 Unsealed Vertical Hybrid Header, 3 Rows, 34 Circuits, Polarization Option A, Black, Tube	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
0349601200	Mini50 Unsealed 2 Bay Vertical Headers, 68 Circuits, Bay A 34 Circuit Hybrid Header, Polarization Option A, Black; Bay B 34 Circuit Hybrid Header, Polarization Option B, Gray; Tray	Compliant	Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
0349610342	Mini50 Unsealed Right-Angle Hybrid Header, 3 Rows, 34 Circuits, Polarization Option C, Dark Gray, Tray	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
0349617342	Mini50 Unsealed Right-Angle Hybrid Header, 3 Rows, 34 Circuits, Polarization Option C, Dark Gray, Tube	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
0349674002	Mini50 Sealed Receptacle, Single Row, with CPA, 4 Circuits, Polarization Option B, Light Gray	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
0395105004	3.81mm Pitch Eurostyle Horizontal Plug, Green Housing, 4 Circuits	Compliant with Exemption 6(c)	Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
0395105005	3.81mm Pitch Eurostyle Horizontal Plug, Green Housing, 5 Circuits	Compliant with Exemption 6(c)	Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
0395305008	5.08mm Pitch Eurostyle Horizontal Plug, Green Housing, 8 Circuits	Compliant with Exemption 6(c)	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
0395431202	5.00mm Pitch Eurostyle 45° Wire Entry Fixed Mount PCB Terminal Block, with Screw Pressure Clamp, with Standard Imprinting, 2 Circuits	Compliant with Exemption 6(c)	Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
0395937004	5.00mm Pitch Eurostyle Vertical Fixed Mount PCB Terminal Block, with Reverse Imprinting, Green Housing, 4 Circuits	Compliant with Exemption 6(c)	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
0428203224	10.00mm Pitch Mini-Fit Sr. Header, Single Row, Right-Angle, 2.36mm PCB Thickness, Silver (Ag) Plating, 3 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
0430315005	Micro-Fit TPA Crimp Terminal, Male, with 0.76µm Select Gold (Au) Plated Phosphor Bronze Contact, 20-24 AWG, Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
0430315006	Micro-Fit TPA Crimp Terminal, Male, with 2.54µm Matte Tin Plated Phosphor Bronze Contact, 20-24 AWG, Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
0430315009	Micro-Fit TPA Crimp Terminal, Male, with 0.76µm Select Gold (Au) Plated Phosphor Bronze Contact, 26-30 AWG, Reel	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
0747630010	QSFP+ Universal Loopback Adapter, 100 Ohms Impedance, Serial ID, 0dB	Compliant	Not Reviewed	Not Reviewed
0747630030	QSFP+ 14Gb Universal Loopback Adapter, 100 Ohms Impedance, Serial ID, 0dB	Compliant	Not Reviewed	Not Reviewed
0845860019	Micro-Change (M12) Terminator Resistor, Female 5 Poles, meets NMEA 2000	Compliant with Exemption 6(c)	Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
0848569114	Mini-Change Single-Ended Cordset, 4 Poles, Female (Straight) to Pigtail, 16 AWG, PVC Cable, 5.0m (16.40') Length, meets NMEA 2000	Not Compliant	Not Reviewed	Not Reviewed
0930700512	Appli-Mate RAST 2.5 Header, Vertical, 4 Circuits, Tin (Sn) Plating, Glow-Wire Capable, Positioning Key D	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
0930700517	Appli-Mate RAST 2.5 Header, Vertical, 4 Circuits, Tin (Sn) Plating, Glow-Wire Capable, Positioning Key D	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
0936010868	GWconnect STD - Standard, Single Lever Hood, Die-cast Aluminum, with 2 Pegs, Top Entry, Size 6B «44x27», M32 Thread, High Construction, Grey	Compliant	Not Reviewed	Not Reviewed
0936040043	GWconnect Enclosure, Die-cast Aluminum, S-8000 Series, with External Mounting Flanges, 407 x 313 x 157mm Outside Dimensions, Black RAL 9005	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1200868657	Nano-Change (M8) Single-Ended Cordset with Knurled Hexnut, 3 Poles, Female (Straight) to Pigtail, 24 AWG, WSOR Cable, 5.0m (16.40') Length	Compliant with Exemption 6(c)	Contained Per - D(2020)4578-DC (25 June 2020)	Not Relevant

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1200868660	Nano-Change (M8) Single-Ended Cordset with Knurled Hexnut, 4 Poles, Female (Straight) to Pigtail, 24 AWG, WSOR Cable, 2.0m (6.56') Length	Compliant with Exemption 6(c)	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Relevant
1200870491	Nano-Change (M8) to Micro-Change (M12) Double-Ended Cordset, 3 Poles, Female (Straight) to Male (Straight), 22 AWG, TPE Cable, 0.60m (1.97') Length	Compliant with Exemption 6(c)	Not Reviewed	Not Low-Halogen
1200910025	Nano-Change (M8) Field Attachable Connector, 4 Poles, Straight, Male, Unshielded, Screw Termination, Cable Diameter 3.50-5.00mm	Compliant with Exemption 6(c)	Not Contained Per -ED/21/2016 (20 June 2016)	Not Low-Halogen
1200910026	Nano-Change (M8) Field Attachable Connector, 4 Poles, Straight, Female, Unshielded, Screw Termination, Cable Diameter 3.50-5.00mm	Compliant with Exemption 6(c)	Not Contained Per -ED/01/2018 (15 January 2018)	Not Low-Halogen
1201080237	Micro-Change (M12) Double-Ended Cordset, 4 Poles, Male (Straight) to Male (Straight), 22 AWG, Shielded PUR Cable, 3.0m (9.84') Length	Compliant with Exemption 6(c)	Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1201080559	ENET RJ45/RJ45 2PR 3M TPE TEAL	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Relevant
1300680104	BradPower D-Size (1 3/8"-M35) 3-Pole Trunk Tee, with 3-Pole BradPower D-Size (1 3/8"-M35) Drop, Red	Compliant with Exemption 6(c)	Not Reviewed	Not Low-Halogen
1300970201	Deluxe Cord Grips Strain Relief, 3/4" NPT, 45° Angle Male, Cable Diameter 6.35-9.53mm (.250-.375")	Compliant	Not Reviewed	Not Reviewed
1300980082	MAX-LOC Strain Relief Cord-Sealing Grip, 1/2" NPT, Straight Male, Cable Diameter 12.70-14.27mm (.500-.562")	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Reviewed
1300980153	MAX-LOC Strain Relief Cord-Sealing Grip, 1" NPT, 90° Angle Male, Cable Diameter 17.45-20.62mm (.687-.812")	Compliant	Contained Per -ED/21/2016 (20 June 2016)	Not Reviewed
1300990141	MAX-LOC Lock Nut 1/4" NPT	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1302090063	Micro-Change Stranded Cable, TPE, 22 AWG, 3 Conductors, 76.20m Length, Yellow	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1302110061	Mini-Change Stranded Cable, PVC, 20 AWG, 76.20m Length, Yellow	Compliant	Not Reviewed	Not Relevant
1302110066	Micro-Change / Mini-Change Stranded Cable, TPE, 18 AWG, 5 Conductors, 76.20m Length, Yellow	Compliant	Not Reviewed	Not Reviewed

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
0151670811	1.00mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 30.00mm Cable Length, Tin (Sn) Plating, 13 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
0151670815	1.00mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 76.00mm Cable Length, Tin (Sn) Plating, 13 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
0151670859	1.00mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 76.00mm Cable Length, Tin (Sn) Plating, 17 Circuits	Compliant	Not Reviewed	Not Reviewed
0151670862	1.00mm Pitch Premo-Flex FFC Jumper, Opposite Side Contacts (Type D), 127.00mm Cable Length, Tin (Sn) Plating, 17 Circuits	Compliant	Not Reviewed	Not Reviewed
0151670865	1.00mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 152.00mm Cable Length, Tin (Sn) Plating, 17 Circuits	Compliant	Not Reviewed	Not Reviewed
1552100001	Flamar Sensor Cable, PVC Jacket, Unshielded, 3 Circuits, 0.25mm ² / 24 AWG, 4.50mm (.177") Diameter, 600.0m (1968.50') Length, Black	Compliant	Not Reviewed	Not Relevant
1552110005	Flamar Sensor Cable, PVC Jacket, Braided Shielding Overall, 3 Circuits, 0.34mm ² / 22 AWG, 5.40mm (.213") Diameter, 800.0m (2624.67') Length, Gray	Compliant	Not Reviewed	Not Reviewed
1552110006	Flamar Sensor Cable, PVC Jacket, Braided Shielding Overall, 3 Circuits, 0.34mm ² / 22 AWG, 5.40mm (.213") Diameter, 1500.0m (4921.26') Length, Gray	Compliant	Not Reviewed	Not Reviewed
1552200073	Flamar Sensor Cable, WSOR Jacket, Unshielded, 4 Circuits, 0.34mm ² / 22 AWG, 5.10mm (.201") Diameter, 600.0m (1968.50') Length, Orange	Compliant	Not Reviewed	Not Relevant
1552200082	Flamar Sensor Cable, WSOR Jacket, Unshielded, 5 Circuits, 0.34mm ² / 22 AWG, 5.50mm (.217") Diameter, 600.0m (1968.50') Length, Yellow	Compliant	Not Reviewed	Not Relevant
1552200084	Flamar Sensor Cable, WSOR Jacket, Unshielded, 5 Circuits, 0.34mm ² / 22 AWG, 5.50mm (.217") Diameter, 1500.0m (4921.26') Length, Yellow	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Not Relevant
1552200100	Flamar Control Cable, WSOR Jacket, Unshielded, 2 Circuits, 0.50mm ² / 21 AWG, 5.20mm (.205") Diameter, 600.0m (1968.50') Length, Black	Compliant	Not Reviewed	Not Relevant

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1552200102	Flamar Control Cable, WSOR Jacket, Unshielded, 2 Circuits, 0.50mm ² / 21 AWG, 5.20mm (.205") Diameter, 1500.0m (4921.26') Length, Black	Compliant	Not Reviewed	Not Low-Halogen
1552200143	Flamar Control Cable, WSOR Jacket, Unshielded, 3 Circuits, 0.75mm ² with Green-Yellow Ground / 19 AWG with Green-Yellow Ground, 6.40mm (.252") Diameter, 500.0m (1640.42') Length, Gray	Compliant	Not Reviewed	Not Reviewed
1552200144	Flamar Control Cable, WSOR Jacket, Unshielded, 3 Circuits, 0.75mm ² with Green-Yellow Ground / 19 AWG with Green-Yellow Ground, 6.40mm (.252") Diameter, 1000.0m (3280.83') Length, Gray	Compliant	Not Reviewed	Not Reviewed
1552200157	Flamar Control Cable, WSOR Jacket, Unshielded, 2 Circuits, 1.00mm ² / 18 AWG, 6.70mm (.264") Diameter, 300.0m (984.25') Length, Black	Compliant	Not Reviewed	Not Relevant
1552200159	Flamar Control Cable, WSOR Jacket, Unshielded, 2 Circuits, 1.00mm ² / 18 AWG, 6.70mm (.264") Diameter, 1000.0m (3280.83') Length, Black	Compliant	Not Reviewed	Not Low-Halogen
1552200163	Flamar Control Cable, WSOR Jacket, Unshielded, 3 Circuits, 1.00mm ² with Green-Yellow Ground / 18 AWG with Green-Yellow Ground, 7.10mm (.280") Diameter, 300.0m (984.25') Length, Black	Compliant	Not Reviewed	Not Relevant
1552200165	Flamar Control Cable, WSOR Jacket, Unshielded, 3 Circuits, 1.00mm ² with Green-Yellow Ground / 18 AWG with Green-Yellow Ground, 7.10mm (.280") Diameter, 1000.0m (3280.83') Length, Black	Compliant	Not Reviewed	Low-Halogen
1552200171	Flamar Control Cable, WSOR Jacket, Unshielded, 4 Circuits, 1.00mm ² with Green-Yellow Ground / 18 AWG with Green-Yellow Ground, 7.60mm (.299") Diameter, 1000.0m (3280.83') Length, Black	Compliant	Not Contained Per -ED/71/2019 (16 July 2019)	Not Low-Halogen
1552200236	Flamar Control Cable, WSOR Jacket, Unshielded, 5 Circuits, 1.50mm ² with Green-Yellow Ground / 16 AWG with Green-Yellow Ground, 8.60mm (.339") Diameter, 500.0m (1640.42') Length, Black	Compliant	Not Reviewed	Not Reviewed
1552200239	Flamar Control Cable, WSOR Jacket, Unshielded, 5 Circuits, 1.50mm ² with Green-Yellow Ground / 16 AWG with Green-Yellow Ground, 8.60mm (.339") Diameter, 500.0m (1640.42') Length, Gray	Compliant	Not Reviewed	Not Reviewed

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1552200240	Flamar Control Cable, WSOR Jacket, Unshielded, 5 Circuits, 1.50mm ² with Green-Yellow Ground / 16 AWG with Green-Yellow Ground, 8.60mm (.339") Diameter, 1000.0m (3280.83') Length, Gray	Compliant	Not Reviewed	Not Reviewed
1552200259	Flamar Control Cable, WSOR Jacket, Unshielded, 17 Circuits, 1.50mm ² with Green-Yellow Ground / 16 AWG with Green-Yellow Ground, 14.70mm (.579") Diameter, 100.0m (328.08') Length, Black	Compliant	Not Reviewed	Not Relevant
1552200283	Flamar Control Cable, WSOR Jacket, Unshielded, 4 Circuits, 2.50mm ² with Green-Yellow Ground / 14 AWG with Green-Yellow Ground, 10.10mm (.398") Diameter, 100.0m (328.08') Length, Black	Compliant	Not Reviewed	Not Relevant
1552200285	Flamar Control Cable, WSOR Jacket, Unshielded, 4 Circuits, 2.50mm ² with Green-Yellow Ground / 14 AWG with Green-Yellow Ground, 10.10mm (.398") Diameter, 1000.0m (3280.83') Length, Black	Compliant	Not Reviewed	Not Relevant
1552210013	Flamar Sensor Cable, WSOR Jacket, Braided Shielding Overall, 4 Circuits, 0.34mm ² / 22 AWG, 5.70mm (.224") Diameter, 300.0m (984.25') Length, Black	Compliant	Not Reviewed	Not Relevant
1552210015	Flamar Sensor Cable, WSOR Jacket, Braided Shielding Overall, 4 Circuits, 0.34mm ² / 22 AWG, 5.70mm (.224") Diameter, 1000.0m (3280.83') Length, Black	Compliant	Not Reviewed	Not Relevant
1552300133	Flamar Control Cable, PUR Jacket, Unshielded, 2 Circuits, 0.75mm ² / 19 AWG, 6.00mm (.236") Diameter, 300.0m (984.25') Length, Black	Compliant	Not Reviewed	Not Relevant
1552300135	Flamar Control Cable, PUR Jacket, Unshielded, 2 Circuits, 0.75mm ² / 19 AWG, 6.00mm (.236") Diameter, 1000.0m (3280.83') Length, Black	Compliant	Not Reviewed	Not Relevant
1552300160	Flamar Control Cable, PUR Jacket, Unshielded, 2 Circuits, 1.00mm ² / 18 AWG, 6.70mm (.264") Diameter, 300.0m (984.25') Length, Gray	Compliant	Not Reviewed	Not Relevant
1552300162	Flamar Control Cable, PUR Jacket, Unshielded, 2 Circuits, 1.00mm ² / 18 AWG, 6.70mm (.264") Diameter, 1000.0m (3280.83') Length, Gray	Compliant	Not Reviewed	Not Relevant
1552300172	Flamar Control Cable, PUR Jacket, Unshielded, 4 Circuits, 1.00mm ² with Green-Yellow Ground / 18 AWG with Green-Yellow Ground, 7.60mm (.299") Diameter, 300.0m (984.25') Length, Gray	Compliant	Not Reviewed	Not Relevant

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1552300174	Flamar Control Cable, PUR Jacket, Unshielded, 4 Circuits, 1.00mm ² with Green-Yellow Ground / 18 AWG with Green-Yellow Ground, 7.60mm (.299") Diameter, 1000.0m (3280.83') Length, Gray	Compliant	Not Reviewed	Not Relevant
1552310013	Flamar Sensor Cable, PUR Jacket, Braided Shielding Overall, 4 Circuits, 0.34mm ² / 22 AWG, 5.70mm (.224") Diameter, 300.0m (984.25') Length, Black	Compliant	Not Reviewed	Not Reviewed
1552310015	Flamar Sensor Cable, PUR Jacket, Braided Shielding Overall, 4 Circuits, 0.34mm ² / 22 AWG, 5.70mm (.224") Diameter, 1000.0m (3280.83') Length, Black	Compliant	Not Reviewed	Not Reviewed
1552400001	Flamar Sensor Cable, TPE Jacket, Unshielded, 3 Circuits, 0.34mm ² / 22 AWG, 5.10mm (.201") Diameter, 600.0m (1968.50') Length, Black	Compliant	Not Reviewed	Not Relevant
1552400003	Flamar Sensor Cable, TPE Jacket, Unshielded, 3 Circuits, 0.34mm ² / 22 AWG, 5.10mm (.201") Diameter, 1500.0m (4921.26') Length, Black	Compliant	Not Reviewed	Not Relevant
1552400064	Flamar Control Cable, TPE Jacket, Unshielded, 4 Circuits, 0.50mm ² with Green-Yellow Ground / 21 AWG with Green-Yellow Ground, 6.40mm (.252") Diameter, 300.0m (984.25') Length, Black	Compliant	Not Reviewed	Not Relevant
1552400184	Flamar Control Cable, TPE Jacket, Unshielded, 5 Circuits, 1.50mm ² with Green-Yellow Ground / 16 AWG with Green-Yellow Ground, 10.00mm (.394") Diameter, 100.0m (328.08') Length, Black	Compliant	Not Reviewed	Not Relevant
1552400186	Flamar Control Cable, TPE Jacket, Unshielded, 5 Circuits, 1.50mm ² with Green-Yellow Ground / 16 AWG with Green-Yellow Ground, 10.00mm (.394") Diameter, 1000.0m (3280.83') Length, Black	Compliant	Not Reviewed	Not Relevant
1552410025	Flamar Sensor Cable, TPE Jacket, Braided Shielding Overall, 5 Circuits, 0.34mm ² / 22 AWG, 6.40mm (.252") Diameter, 300.0m (984.25') Length, Black	Compliant	Not Reviewed	Not Reviewed
1552410026	Flamar Sensor Cable, TPE Jacket, Braided Shielding Overall, 5 Circuits, 0.34mm ² / 22 AWG, 6.40mm (.252") Diameter, 500.0m (1640.42') Length, Black	Compliant	Not Reviewed	Not Reviewed
1552410027	Flamar Sensor Cable, TPE Jacket, Braided Shielding Overall, 5 Circuits, 0.34mm ² / 22 AWG, 6.40mm (.252") Diameter, 1000.0m (3280.83') Length, Black	Compliant	Not Reviewed	Not Reviewed

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1553110001	Flamar Power Cable, PVC Jacket, Braided Shielding Overall, 4 Circuits, 1.50mm ² with Green-Yellow Ground / 16 AWG with Green-Yellow Ground, 9.00mm (.354") Diameter, 200.0m (656.17') Length, Orange	Compliant	Not Reviewed	Not Reviewed
1553110003	Flamar Power Cable, PVC Jacket, Braided Shielding Overall, 4 Circuits, 1.50mm ² with Green-Yellow Ground / 16 AWG with Green-Yellow Ground, 9.00mm (.354") Diameter, 1000.0m (3280.83') Length, Orange	Compliant	Not Reviewed	Not Reviewed
1553210004	Flamar Power Cable, WSOR Jacket, Braided Shielding Overall, 4 Circuits, 2.50mm ² with Green-Yellow Ground / 14 AWG with Green-Yellow Ground, 10.60mm (.417") Diameter, 100.0m (328.08') Length, Orange	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Not Reviewed
1553210006	Flamar Power Cable, WSOR Jacket, Braided Shielding Overall, 4 Circuits, 2.50mm ² with Green-Yellow Ground / 14 AWG with Green-Yellow Ground, 10.60mm (.417") Diameter, 1000.0m (3280.83') Length, Orange	Compliant	Not Contained Per - ECHA_01_2020 (16 January 2020)	Not Reviewed
1553211010	Flamar Power Cable, WSOR Jacket, Braided Shielding Overall, 6 Circuits, 4x(6.00mm ²) with Green-Yellow Ground + (2x1.50mm ² with Braided Shield) / 4x(10 AWG) with Green-Yellow Ground + (2x16 AWG with Braided Shield), 16.20mm (.244") Diameter, 100.0m (328.08') Length, Orange	Compliant	Not Reviewed	Not Relevant
1553211012	Flamar Power Cable, WSOR Jacket, Braided Shielding Overall, 6 Circuits, 4x(6.00mm ²) with Green-Yellow Ground + (2x1.50mm ² with Braided Shield) / 4x(10 AWG) with Green-Yellow Ground + (2x16 AWG with Braided Shield), 16.20mm (.244") Diameter, 500.0m (1640.42') Length, Orange	Compliant	Not Reviewed	Not Relevant
1553212010	Flamar Power Cable, WSOR Jacket, Braided Shielding Overall, 8 Circuits, 4x(6.00mm ²) with Green-Yellow Ground + 2x(2x1.50mm ² with Braided Shield) / 4x(10 AWG) with Green-Yellow Ground + 2x(2x16 AWG with Braided Shield), 17.90mm (.311") Diameter, 100.0m (328.08') Length, Orange	Compliant	Not Reviewed	Not Relevant
1553212012	Flamar Power Cable, WSOR Jacket, Braided Shielding Overall, 8 Circuits, 4x(6.00mm ²) with Green-Yellow Ground + 2x(2x1.50mm ² with Braided Shield) / 4x(10 AWG) with Green-Yellow Ground + 2x(2x16 AWG with Braided Shield), 17.90mm (.311") Diameter, 500.0m (1640.42') Length, Orange	Compliant	Not Reviewed	Not Relevant

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1553219007	Flamar Feedback Cable, WSOR Jacket, Braided Shielding Overall, 12 Circuits, 4x(2x0.34mm ²) + 4x(0.50mm ²) / 4x(2x22 AWG) + 4x(21 AWG), 9.50mm (.374") Diameter, 200.0m (656.17') Length, Green	Compliant	Not Reviewed	Not Reviewed
1553219009	Flamar Feedback Cable, WSOR Jacket, Braided Shielding Overall, 12 Circuits, 4x(2x0.34mm ²) + 4x(0.50mm ²) / 4x(2x22 AWG) + 4x(21 AWG), 9.50mm (.374") Diameter, 1000.0m (3280.83') Length, Green	Compliant	Not Reviewed	Not Reviewed
1553219010	Flamar Feedback Cable, WSOR Jacket, Braided Shielding Overall, 16 Circuits, 3x(2x0.14mm ² with Spiral Shield) + 2x(0.50mm ²) + 4x(0.14mm ²) + 4x(0.25mm ²) / 3x(2x26 AWG with Spiral Shield) + 2x(21 AWG) + 4x(26 AWG) + 4x(24 AWG), 10.00mm (.394") Diameter, 100.0m (328.08') Length, Green	Compliant	Not Reviewed	Not Relevant
1553219012	Flamar Feedback Cable, WSOR Jacket, Braided Shielding Overall, 16 Circuits, 3x(2x0.14mm ² with Spiral Shield) + 2x(0.50mm ²) + 4x(0.14mm ²) + 4x(0.25mm ²) / 3x(2x26 AWG with Spiral Shield) + 2x(21 AWG) + 4x(26 AWG) + 4x(24 AWG), 10.00mm (.394") Diameter, 1000.0m (3280.83') Length, Green	Compliant	Not Reviewed	Not Reviewed
1553319007	Flamar Feedback Cable, PUR Jacket, Braided Shielding Overall, 12 Circuits, 4x(2x0.34mm ²) + 4x(0.50mm ²) / 4x(2x22 AWG) + 4x(21 AWG), 9.50mm (.374") Diameter, 200.0m (656.17') Length, Green	Compliant	Not Reviewed	Not Reviewed
1553319009	Flamar Feedback Cable, PUR Jacket, Braided Shielding Overall, 12 Circuits, 4x(2x0.34mm ²) + 4x(0.50mm ²) / 4x(2x22 AWG) + 4x(21 AWG), 9.50mm (.374") Diameter, 1000.0m (3280.83') Length, Green	Compliant	Not Reviewed	Not Reviewed
1554115001	Flamar PROFINET* C Network Cable, PVC Jacket, Braided Shielding Overall, 4 Circuits, 2x(2x0.34mm ²) / 2x(2x22 AWG), 6.80mm (.268") Diameter, 300.0m (984.25') Length, Green	Compliant	Not Reviewed	Not Reviewed
1554115002	Flamar PROFINET* C Network Cable, PVC Jacket, Braided Shielding Overall, 4 Circuits, 2x(2x0.34mm ²) / 2x(2x22 AWG), 6.80mm (.268") Diameter, 500.0m (1640.42') Length, Green	Compliant	Not Reviewed	Not Reviewed

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1554115003	Flamar PROFINET* C Network Cable, PVC Jacket, Braided Shielding Overall, 4 Circuits, 2x(2x0.34mm ²) / 2x(2x22 AWG), 6.80mm (.268") Diameter, 100.0m (328.08') Length, Green	Compliant	Not Reviewed	Not Reviewed
1554215002	Flamar PROFINET* C Network Cable, WSOR Jacket, Braided Shielding Overall, 4 Circuits, 2x(2x0.34mm ²) / 2x(2x22 AWG), 6.80mm (.268") Diameter, 500.0m (1640.42') Length, Green	Compliant	Not Reviewed	Not Reviewed
1554215003	Flamar PROFINET* C Network Cable, WSOR Jacket, Braided Shielding Overall, 4 Circuits, 2x(2x0.34mm ²) / 2x(2x22 AWG), 6.80mm (.268") Diameter, 100.0m (328.08') Length, Green	Compliant	Not Reviewed	Not Reviewed
1554315001	Flamar PROFINET* C Network Cable, PUR Jacket, Braided Shielding Overall, 4 Circuits, 2x(2x0.34mm ²) / 2x(2x22 AWG), 6.80mm (.268") Diameter, 300.0m (984.25') Length, Green	Compliant	Not Reviewed	Not Reviewed
1554315002	Flamar PROFINET* C Network Cable, PUR Jacket, Braided Shielding Overall, 4 Circuits, 2x(2x0.34mm ²) / 2x(2x22 AWG), 6.80mm (.268") Diameter, 500.0m (1640.42') Length, Green	Compliant	Not Reviewed	Not Relevant
1554315003	Flamar PROFINET* C Network Cable, PUR Jacket, Braided Shielding Overall, 4 Circuits, 2x(2x0.34mm ²) / 2x(2x22 AWG), 6.80mm (.268") Diameter, 1000.0m (3280.83') Length, Green	Compliant	Not Reviewed	Not Reviewed
1554316001	Flamar Ethernet 5e Network Cable, PUR Jacket, Braided Shielding Overall, 4 Circuits, 2x(2x0.14mm ²) / 2x(2x26 AWG), 6.50mm (.256") Diameter, 300.0m (984.25') Length, Teal	Compliant	Not Reviewed	Not Relevant
1554316003	Flamar Ethernet 5e Network Cable, PUR Jacket, Braided Shielding Overall, 4 Circuits, 2x(2x0.14mm ²) / 2x(2x26 AWG), 6.50mm (.256") Diameter, 1000.0m (3280.83') Length, Teal	Compliant	Not Reviewed	Not Reviewed
1554316010	Flamar Ethernet 5e Network Cable, PUR Jacket, Braided Shielding Overall, 8 Circuits, 4x(2x0.25mm ²) / 4x(2x24 AWG), 7.80mm (.307") Diameter, 300.0m (984.25') Length, Teal	Compliant	Not Reviewed	Not Reviewed
1600290011	stAK50h Hybrid Receptacle, 27 Circuits, Key 1, Black, Bag	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Relevant

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1600290012	stAK50h Hybrid Receptacle, 27 Circuits, Key 2, Light Green, Bag	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1712961617	Impact 100 Ohm 5 Pair Vertical Backplane Header, Unguided, Left Endwall, 16 Columns, 240 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Matte Tin, 0.254µm Gold	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1712961627	Impact 100 Ohm 5 Pair Vertical Backplane Header, Unguided, Dual Endwall, 16 Columns, 240 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Matte Tin, 0.254µm Gold	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1713205022	Impel 4Px12C Gd Right DC Assy	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1715731614	Impact 100 Ohm 3 Pair Right-Angle Orthogonal Direct Header, Unguided, Dual Endwall, with Outrigger, 6 Column, 90#Mate Position, Pin Length 4.90mm, Plated Through-Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1715731615	Impact 100 Ohm 3 Pair Right-Angle Orthogonal Direct Header, Unguided, Dual Endwall, with Outrigger, 6 Column, 90#Mate Position, Pin Length 5.50mm, Plated Through-Hole Dimension 0.46mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1715741817	Impact 100 Ohm 4 Pair Right-Angle Orthogonal Direct Header, Unguided, Dual Endwall, with Outrigger, 8 Column, 90#Mate Position, Pin Length 4.90mm, Plated Through-Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1715761217	Impact 100 Ohm 6 Pair Right-Angle Orthogonal Direct Header, Unguided, Dual Endwall, with Outrigger, 12 Column, 90#Mate Position, Pin Length 4.90mm, Plated Through-Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1715761218	Impact 100 Ohm 6 Pair Right-Angle Orthogonal Direct Header, Unguided, Dual Endwall, with Outrigger, 12 Column, 90#Mate Position, Pin Length 5.50mm, Plated Through-Hole Dimension 0.39mm, Lead-Free	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1718562006	KK RPC 100 Hdr FrLk Vert 06 Ckt 30Au	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718570008	2.54mm Pitch, KK 254 RPC Wire-to-Board Right-Angle Header with Friction Lock, Tin (Sn) Plating, Bag, 8 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1718570010	2.54mm Pitch, KK 254 RPC Wire-to-Board Right-Angle Header with Friction Lock, Tin (Sn) Plating, Bag, 10 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718571002	2.54mm Pitch, KK 254 RPC Wire-to-Board Right-Angle Header with Friction Lock, 15µm Gold (Au) Plating, Bag, 2 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1718573009	2.54mm Pitch, KK 254 RPC Wire-to-Board Right-Angle Header with Friction Lock, Tin (Sn) Plating, Tape and Reel, 9 Circuits	Compliant	Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1725123612	EXTreme Ten60Power Panel-to-Board Receptacle Housing, 12 Signal Circuits, 6 Power Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1727040033	FCT Mixed Layout D-Sub Housing, Male, Tin-plated Shell with Dimples, 5 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
1727040098	FCT Metal Backshell for D-Sub Connector, Shell Size 2, Straight Cable Outlet, Large Inner Chamber, with Rubber Bushing and Locking Screws	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Reviewed
1729520602	Micro-Fit TPA Receptacle Housing, Dual Row, 6 Circuits, UL 94V-2, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1729520802	Micro-Fit TPA Receptacle Housing, Dual Row, 8 Circuits, UL 94V-2, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1729521002	Micro-Fit TPA Receptacle Housing, Dual Row, 10 Circuits, UL 94V-2, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1729521202	Micro-Fit TPA Receptacle Housing, Dual Row, 12 Circuits, UL 94V-2, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1729520402	Micro-Fit TPA Receptacle Housing, Dual Row, 4 Circuits, UL 94V-2, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1729521402	Micro-Fit TPA Receptacle Housing, Dual Row, 14 Circuits, UL 94V-2, Glow-Wire Capable, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1729530402	Micro-Fit Terminal Position Assurance (TPA) Retainer, 4 Circuits, 3.00mm Pitch, UL 94V-2, Glow-Wire Capable, Natural	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1729530802	Micro-Fit Terminal Position Assurance (TPA) Retainer, 8 Circuits, 3.00mm Pitch, UL 94V-2, Glow-Wire Capable, Natural	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1729531002	Micro-Fit Terminal Position Assurance (TPA) Retainer, 10 Circuits, 3.00mm Pitch, UL 94V-2, Glow-Wire Capable, Natural	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1729531202		Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1729531402	Micro-Fit Terminal Position Assurance (TPA) Retainer, 14 Circuits, 3.00mm Pitch, UL 94V-2, Glow-Wire Capable, Natural	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1730830007	KK 508 Header, Vertical, with Polarizing Backwall, Tin (Sn) Plating, Glow-Wire Capable, 7 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1730830009	KK 508 Header, Vertical, with Polarizing Backwall, Tin (Sn) Plating, Glow-Wire Capable, 9 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1730830011	KK 508 Header, Vertical, with Polarizing Backwall, Tin (Sn) Plating, Glow-Wire Capable, 11 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Low-Halogen
1731070119	FCT Mixed Layout D-Sub Connector, Female, Straight, Solder Cup, Gold over Nickel Phosphorus Plating, Tin-plated Shell without Dimples, 43 Circuits, 41 Signal Contacts Loaded	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed
1731090094	FCT Standard-Density D-Sub Connector, Female, Straight, Solder Cup, Gold Plating, 500 Mating Cycles, 4-40 UNC Clinch Nut, 9 Circuits	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed
1731090096	FCT Standard-Density D-Sub Connector, Female, Straight, Solder Cup, Gold Plating, 500 Mating Cycles, 4-40 UNC Clinch Nut, 25 Circuits	Compliant with Exemption 6(c),6(a)	Not Reviewed	Not Reviewed
1731090107	FCT Standard-Density D-Sub Connector, Female, Straight, Solder Cup, Gold Plating, 200 Mating Cycles, 4-40 UNC Clinch Nut, 37 Circuits	Compliant with Exemption 6(c),6(a)	Not Reviewed	Not Reviewed
1731090119	FCT Standard-Density D-Sub Connector, Male, Straight, PCB Through Hole, Gold Plating, 500 Mating Cycles, 50 Circuits	Compliant with Exemption 6(c)	Contained Per - D(2020)4578-DC (25 June 2020)	Not Reviewed
1731090146	FCT Standard-Density D-Sub Connector, Male, Straight, PCB Through Hole, Gold Plating, 200 Mating Cycles, 6.60mm Snap-in Bolt, 9 Circuits	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1731090149	FCT Standard-Density D-Sub Connector, Male, Straight, PCB Through Hole, Gold Plating, 200 Mating Cycles, 6.60mm Snap-in Bolt, 37 Circuits	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed
1731090153	FCT Standard-Density D-Sub Connector, Female, Straight, PCB Through Hole, Gold Plating, 200 Mating Cycles, 6.60mm Snap-in Bolt, 25 Circuits	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed
1731090177	FCT Standard-Density D-Sub Connector, Male, Right-Angle, PCB Through Hole, Gold Plating, 200 Mating Cycles, Riveted Metal Bracket and Clinch Nut, 15 Circuits	Compliant with Exemption 6(c),6(a)	Not Reviewed	Not Reviewed
1731090178	FCT Standard-Density D-Sub Connector, Male, Right-Angle, PCB Through Hole, Gold Plating, 200 Mating Cycles, Riveted Metal Bracket and Clinch Nut, 25 Circuits	Compliant with Exemption 6(c),6(a)	Not Reviewed	Not Reviewed
1731090184	FCT Standard-Density D-Sub Connector, Female, Right-Angle, PCB Through Hole, Gold Plating, 200 Mating Cycles, Riveted Metal Bracket and Clinch Nut, 37 Circuits	Compliant with Exemption 6(a),6(c)	Not Reviewed	Not Reviewed
1731090195	FCT Standard-Density D-Sub Connector, Female, Right-Angle, PCB Through Hole, Gold Plating, 50 Mating Cycles, Riveted Metal Bracket and Clinch Nut, 50 Circuits	Compliant with Exemption 6(a)-I,6(c)	Not Reviewed	Not Reviewed
1731090247	FCT Standard-Density D-Sub Connector, Male, Right-Angle, PCB Through Hole, Gold Plating, 200 Mating Cycles, 37 Circuits	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed
1731090426	FCT Standard-Density D-Sub Connector, Male, Straight, PCB Through Hole, Gold Plating, 200 Mating Cycles, 5.60mm Snap-in Bolt, 15 Circuits	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed
1731090427	FCT Standard-Density D-Sub Connector, Male, Straight, PCB Through Hole, Gold Plating, 200 Mating Cycles, 5.60mm Snap-in Bolt, 25 Circuits	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed
1731090428	FCT Standard-Density D-Sub Connector, Male, Straight, PCB Through Hole, Gold Plating, 200 Mating Cycles, 5.60mm Snap-in Bolt, 50 Circuits	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed
1731090783	FCT Standard-Density D-Sub Connector, Female, Right-Angle, PCB Through Hole, Gold Plating, 200 Mating Cycles, 9 Circuits	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1731091369	FCT Standard-Density D-Sub Connector, Female, Right-Angle, PCB Through Hole, Gold Plating, 200 Mating Cycles, Plastic Bracket with Snap-in Grounding Bracket and Clinch Nut, 15 Circuits	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed
1731091835	FCT Standard-Density D-Sub Connector, Male, Right-Angle, Surface Mount, 3.70mm Contact Height, 500 Mating Cycles, Diecast Bracket, 9 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Reviewed
1731091836	FCT Standard-Density D-Sub Connector, Male, Right-Angle, Surface Mount, 7.30mm Contact Height, 500 Mating Cycles, Diecast Bracket, 9 Circuits	Compliant	Not Reviewed	Not Reviewed
1731100022	FCT Standard-Density Waterproof D-Sub Connector, Male, Straight, Solder Cup, Gold Plating, Front Panel Mount, Plastic Watertight Frame, 15 Circuits	Compliant with Exemption 6(c)	Contained Per - D(2020)4578-DC (25 June 2020)	Not Reviewed
1731100116	FCT IP67 FWD SDR PLG 09 PN FMNT MTL	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed
1731100120	FCT IP67 FWD STR PC PLG 09 RMNT MTL	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed
1731100162	FCT IP67 FWD STR PC RCPT 09 RMNT MTL	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed
1731100247	FCT High-Density Waterproof D-Sub Connector, Female, Straight, PCB Through Hole, Gold Plating, Metal Watertight Frame, Snap-in Bolt, 15 Circuits	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed
1731110218	FCT HOOD S5 0 DEG MTL W/ SCRWLCK	Compliant with Exemption 6(a)-I	Not Reviewed	Not Reviewed
1731120270	FCT TERM HPWR STR PC PLG 20 AMP	Compliant with Exemption 6(c)	Contained Per - D(2020)4578-DC (25 June 2020)	Not Reviewed
1731130072	FCT High-Density D-Sub Crimp Housing, Male, 78 Circuits	Compliant	Not Reviewed	Not Reviewed
1731130075	FCT High-Density D-Sub Crimp Housing, Female, 44 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Reviewed
1731130077	FCT High-Density D-Sub Crimp Housing, Female, 78 Circuits	Compliant	Not Reviewed	Not Reviewed
1731130079	FCT High-Density D-Sub Connector, Male, Straight, PCB Through Hole, Gold Plating, 26 Circuits	Compliant	Not Reviewed	Not Reviewed
1731130083	FCT High-Density D-Sub Connector, Female, Straight, PCB Through Hole, Gold Plating, 15 Circuits	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Reviewed

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
1731130088	FCT High-Density D-Sub Connector, Male, Straight, PCB Through Hole, Gold Plating, 6.60mm Snap-in Bolt, 26 Circuits	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed
1731130198	FCT High-Density D-Sub Connector, Female, Straight, PCB Through Hole, Gold Plating, 5.60mm Snap-in Bolt, 26 Circuits	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed
1731130214	FCT High-Density D-Sub Connector, Male, Straight, PCB Through Hole, Gold Plating, 5.60mm Snap-in Bolt, 15 Circuits	Compliant with Exemption 6(c)	Not Reviewed	Not Reviewed
0190430011	FUSE BLOCK TAP ADAPTER (FTA-1) SPM	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2005010282	stAK50h Vertical Hybrid Header, 28 Circuits, Key 2, Green, Tube	Compliant	Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2005010284	stAK50h Vertical Hybrid Header, 28 Circuits, Key 4, Black, Tube	Compliant	Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2005020283	stAK50h Right-Angle Hybrid Header, 28 Circuits, Key 3, Gray, Tube	Compliant	Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2005020321	stAK50h Right-Angle Hybrid Header, 32 Circuits, Key 1, Black, Tube	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2005020323	stAK50h Right-Angle Hybrid Header, 32 Circuits, Key 3, Dark Gray, Tube	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2018440141	MultiCat High-Power Hermaphroditic Backshell, 4 Circuits, 12-18 AWG, Gray	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2023940110	Vertical Lite-Trap SMT Wire-to-Board Connector, 1 Circuit	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Not Reviewed
2036321401	Micro-Fit TPA Plug Housing, Dual Row, 14 Circuits, UL 94V-0, Low-Halogen, without Panel Mounts, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2036321600	Micro-Fit TPA Plug Housing, Dual Row, 16 Circuits, UL 94V-0, Low-Halogen, with Panel Mounts, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2036321601	Micro-Fit TPA Plug Housing, Dual Row, 16 Circuits, UL 94V-0, Low-Halogen, without Panel Mounts, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen

Table A

Molex P/N	Part Description	RoHS Compliance Status	REACH SVHC	Low-Halogen Status
2036321800	Micro-Fit TPA Plug Housing, Dual Row, 18 Circuits, UL 94V-0, Low-Halogen, with Panel Mounts, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2036322001	Micro-Fit TPA Plug Housing, Dual Row, 20 Circuits, UL 94V-0, Low-Halogen, without Panel Mounts, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2036322200	Micro-Fit TPA Plug Housing, Dual Row, 22 Circuits, UL 94V-0, Low-Halogen, with Panel Mounts, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2036322201	Micro-Fit TPA Plug Housing, Dual Row, 22 Circuits, UL 94V-0, Low-Halogen, without Panel Mounts, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2036322400	Micro-Fit TPA Plug Housing, Dual Row, 24 Circuits, UL 94V-0, Low-Halogen, with Panel Mounts, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2036322401	Micro-Fit TPA Plug Housing, Dual Row, 24 Circuits, UL 94V-0, Low-Halogen, without Panel Mounts, Black	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2042810050	Wi-Fi 6E Flex Cabled Side-Fed Balanced Antenna, 50.00mm Cable Length, Compatible with U.FL / I-PEX MHF Connectors	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2042810150	Wi-Fi 6E Flex Cabled Side-Fed Balanced Antenna, 150.00mm Cable Length, Compatible with U.FL / I-PEX MHF Connectors	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2042810200	Wi-Fi 6E Flex Cabled Side-Fed Balanced Antenna, 200.00mm Cable Length, Compatible with U.FL / I-PEX MHF Connectors	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2042810250	Wi-Fi 6E Flex Cabled Side-Fed Balanced Antenna, 250.00mm Cable Length, Compatible with U.FL / I-PEX MHF Connectors	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2042810300	Wi-Fi 6E Flex Cabled Side-Fed Balanced Antenna, 300.00mm Cable Length, Compatible with U.FL / I-PEX MHF Connectors	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen
2067640050	ISM 868/915MHz Dipole Flexible Antenna, 50.00mm Cable Length, Compatible with U.FL / I-PEX MHF Connectors	Compliant	Not Contained Per - D(2020)4578-DC (25 June 2020)	Low-Halogen