

Product Compliance Declaration

Please see www.molex.com for the most up-to-date information.

Contact Information

Name Molex Product Compliance E-Mail Product.Compliance@molex.com

Part Information

Part Number 0015913080 Part Weight 0.484437G

Part Name CGrid SMT Bkwy Hdr 30"SAu 8Ckt Tube

Product Composition

Name	Туре	CAS Number	Proportion (% Total)	Mass (Grams)
CGrid SMT Bkwy Hdr 30"SAu 8Ckt Tube	Assembly		100	0.484437
COMPONENT CGrid Bkwy Hsg 100Ckt	Component		33.995	0.164684
LCP GF30 BLACK	Material		33.995	0.164684
LCP	Substance		23.3545	0.113138
Carbon black	Substance	1333-86-4	0.3399	0.001647
GF-Fibre	Substance		10.1985	0.049405
Further Additives, not to declare	Substance	system	0.102	0.000494
.440 X .0255 Sq Pin 30GOLD Plate	Assembly		66.005	0.319753
.440 x .0255 Sq Bandolier Pin Unplated	Component		62.7533	0.304
Cartridge Brass 70% Unplated	Material		62.7533	0.304
Copper	Substance	7440-50-8	43.9273	0.2128
Zinc (metal)	Substance	7440-66-6	18.826	0.0912
Gold Plating	Material		0.7955	0.003854

Form Rev - F

Limitation of this Product Compliance Declaration: This declaration is based on the state of knowledge and belief of Molex as of the date that it is provided. Molex bases its knowledge and belief on information provided by numerous sources, including third parties, and in certain circumstances laboratory test results. Molex has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and substances. Molex represents that to the best of its knowledge that the information provided in this declaration is accurate. Molex's sole liability shall be to either replace the product or refund the purchase price of the product if it does not meet the requirement of this declaration.

Name	Туре	CAS Number	Proportion (% Total)	Mass (Grams)
Cobalt	Substance	7440-48-4	0.002	0.00001
Nickel	Substance	7440-02-0	0.002	0.00001
Gold	Substance	7440-57-5	0.7915	0.003834
Nickel Plating	Material		1.8165	0.0088
Nickel	Substance	7440-02-0	1.8164	0.008799
Further Additives, not to declare	Substance	system	0.0002	9E-07
Tin Plating	Material		0.6398	0.003099
Tin	Substance	7440-31-5	0.6398	0.003099

ROHS Declaration Information

Regulatory Revision EU 2015/863

Compliance Status Compliant

Contained Substances Exceeding Threshold

None

Exemptions

None

REACH-SVHC Declaration Information

Regulatory Revision D(2020)9139-DC (19 Jan 2021)

Contained Substances Exceeding Threshold

None

GADSL Declaration Information

Regulatory Revision GADSL imported from IMDS

Contained Substances Exceeding Threshold

Form Rev - F

Limitation of this Product Compliance Declaration: This declaration is based on the state of knowledge and belief of Molex as of the date that it is provided. Molex bases its knowledge and belief on information provided by numerous sources, including third parties, and in certain circumstances laboratory test results. Molex has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and substances. Molex represents that to the best of its knowledge that the information provided in this declaration is accurate. Molex's sole liability shall be to either replace the product or refund the purchase price of the product if it does not meet the requirement of this declaration.

Substance Group	Substance Location	Threshold (PPM)	Concentration (PPM)	Intentionally Added
lead	e-plate Sn (electrodeposited Tin Coatings, bright and matt)	*Note	500	Yes
lead	Cartridge Brass 70% (CA260)	*Note	350	Yes
nickel powder [particle diameter < 1 mm]	e-plate Au (Hardgold) (electrodeposited Hardgold	*Note	2,500	Yes
nickel powder [particle diameter < 1 mm]	Ep-Ni	*Note	997,500	Yes
Cobalt	e-plate Au (Hardgold) (electrodeposited Hardgold	*Note	2,500	Yes
copper	Cartridge Brass 70% (CA260)	*Note	700,000	Yes
glass, oxide, chemicals	LCP GF30 BLACK	*Note	300,000	Yes

^{*}Note: For GADSL substance declarable/prohibited threshold values, please reference http://www.gadsl.org/

Exemptions

Part Name	Exemption
e-plate Sn (electrodeposited Tin Coatings, bright and matt)	44 Concentration within acceptable GADSL limits
Cartridge Brass 70% (CA260)	44 Concentration within acceptable GADSL limits
e-plate Au (Hardgold) (electrodeposited Hardgold Coatings)	34 Not applicable
Ep-Ni	33 Other application (Surface not routinely touched or nickel release rate < 0.5µg/cm2/week)

HFLH Declaration Information

Regulatory Revision IEC 61249-2-21

Contained Substances Exceeding Threshold

None

China ROHS Declaration Information

Part Number	0015913080							
Part Name	CGrid SMT Bkwy Hdr 30"SAu 8Ckt Tube	(e)						
Part Information	on			Haz	zardous S	Substance	es	
Components			Lead	Mercury	Cadmium	Hex. Chromium	PBB	PBDE
CGrid SMT Bkwy Hdr 30"SAu 8Ckt Tube O O		0	0	0	0			

Form Rev - F

Limitation of this Product Compliance Declaration: This declaration is based on the state of knowledge and belief of Molex as of the date that it is provided. Molex bases its knowledge and belief on information provided by numerous sources, including third parties, and in certain circumstances laboratory test results. Molex has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and substances. Molex represents that to the best of its knowledge that the information provided in this declaration is accurate. Molex's sole liability shall be to either replace the product or refund the purchase price of the product if it does not meet the requirement of this declaration.

Components	Lead	Mercury	Cadmium	Hex. Chromium	PBB	PBDE
COMPONENT CGrid Bkwy Hsg 100Ckt	0	0	0	0	0	0
.440 X .0255 Sq Pin 30GOLD Plate	0	0	0	0	0	0
.440 x .0255 Sq Bandolier Pin Unplated	0	0	0	0	0	0

Process Information

Component Plating / Surface Finish	MSn-Ni
Termination Base Alloy	Brass
Solder Alloy	N/A
Process Capability	REFLOW
Maximum Exposure Time (seconds)	030
Maximum Process Temperature (C)	260
Maximum Cycles at Reflow Temperature	003
J-STD-020 Moisture Sensitivity Level	N/A

Mar 24, 2021