

# **Product Compliance Declaration**

Please see <a href="https://www.molex.com">www.molex.com</a> for the most up-to-date information.

**Contact Information** 

Name Molex Product Compliance E-Mail Product.Compliance@molex.com

**Part Information** 

Part Number 0026603040 Part Weight 1.368G

Part Name KK 156 Hdr Assy RtAn Tin 04 Ckt

### **Product Composition**

Name	Туре	CAS Number	Proportion (% Total)	Mass (Grams)
KK 156 Hdr Assy RtAn Tin 04 Ckt	Assembly		100	1.368
KK.045 Sq Pin Bando 1.000 (197) Sn	Assembly		75.1462	1.028
KK.045 Sq Pin Bando 1.000 (999) unplt	Component		73.6842	1.008
Cartridge Brass 70% Unplated	Material		73.6842	1.008
Copper	Substance	7440-50-8	51.5789	0.7056
Zinc (metal)	Substance	7440-66-6	22.1053	0.3024
Tin Plating	Material		0.6725	0.0092
Tin	Substance	7440-31-5	0.6725	0.0092
Nickel Plating	Material		0.7895	0.0108
Nickel	Substance	7440-02-0	0.7894	0.010799
Further Additives, not to declare	Substance	system	8E-05	0.000001
KK 156 Hdr Flat 04 Ckt 417700004	Component		24.8538	0.34
PBT GF NATURAL	Material		24.8538	0.34

Form Rev - F

Limitation of this Product Compliance Declaration: This declaration is based on the state of knowledge and belief of Molex as of the date that it is provided. Molex bases its knowledge and belief on information provided by numerous sources, including third parties, and in certain circumstances laboratory test results. Molex has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and substances. Molex represents that to the best of its knowledge that the information provided in this declaration is accurate. Molex's sole liability shall be to either replace the product or refund the purchase price of the product if it does not meet the requirement of this declaration.

Name	Туре	CAS Number	Proportion (% Total)	Mass (Grams)
PBT	Substance		15.9774	0.218571
GF-Fibre	Substance		1.7043	0.023314
Flame Retardant, ISO 1043-4 FR(17)	Substance		5.5034	0.075286
Antimonytrioxide	Substance	1309-64-4	1.4557	0.019914
Further Additives, not to declare	Substance	system	0.213	0.002914

#### **ROHS** Declaration Information

**Regulatory Revision** EU 2015/863

Compliance Status Compliant

**Contained Substances Exceeding Threshold** 

None

**Exemptions** 

None

## **REACH-SVHC Declaration Information**

Regulatory Revision D(2020)9139-DC (19 Jan 2021)

**Contained Substances Exceeding Threshold** 

None

#### **GADSL Declaration Information**

Regulatory Revision GADSL imported from IMDS

## **Contained Substances Exceeding Threshold**

Substance Group	Substance Location	Threshold (PPM)	Concentration (PPM)	Intentionally Added
lead	Cartridge Brass 70% (CA260)	*Note	350	Yes
lead		*Note	500	Yes

#### Form Rev - F

Limitation of this Product Compliance Declaration: This declaration is based on the state of knowledge and belief of Molex as of the date that it is provided. Molex bases its knowledge and belief on information provided by numerous sources, including third parties, and in certain circumstances laboratory test results. Molex has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and substances. Molex represents that to the best of its knowledge that the information provided in this declaration is accurate. Molex's sole liability shall be to either replace the product or refund the purchase price of the product if it does not meet the requirement of this declaration.

Substance Group	Substance Location	Threshold (PPM)	Concentration (PPM)	Intentionally Added
Antimonytrioxide	PBT GF NATURAL	*Note	70,000	Yes
nickel powder [particle diameter < 1 mm]	Ep-Ni	*Note	997,500	Yes
copper	Cartridge Brass 70% (CA260)	*Note	700,000	Yes
glass, oxide, chemicals	PBT GF NATURAL	*Note	80,000	Yes

<sup>\*</sup>Note: For GADSL substance declarable/prohibited threshold values, please reference http://www.gadsl.org/

## **Exemptions**

Part Name	Exemption
Cartridge Brass 70% (CA260)	44 Concentration within acceptable GADSL limits
	44 Concentration within acceptable GADSL limits
Ep-Ni	33 Other application (Surface not routinely touched or nickel release rate < 0.5µg/cm2/week)

## **HFLH Declaration Information**

Regulatory Revision IEC 61249-2-21

#### **Contained Substances Exceeding Threshold**

Substance Group	Substance Location	Threshold (PPM)	Concentration (PPM)	Intentionally Added
Bromine and its compounds	PBT GF NATURAL	900	250,000	Yes
Bromine and Chlorine combined	PBT GF NATURAL	1,500	250,000	Yes

## **China ROHS Declaration Information**

Part Number	0026603040							
Part Name	KK 156 Hdr Assy RtAn Tin 04 Ckt	<b>(e)</b>						
Part Information	on			Ha	zardous S	Substance	es	
Components			Lead	Mercury	Cadmium	Hex. Chromium	PBB	PBDE
KK 156 Hdr A	Assy RtAn Tin 04 Ckt		0	0	0	0	0	0
KK.045 Sq P	in Bando 1.000 (197) Sn		0	0	0	0	0	0

#### Form Rev - F

Limitation of this Product Compliance Declaration: This declaration is based on the state of knowledge and belief of Molex as of the date that it is provided. Molex bases its knowledge and belief on information provided by numerous sources, including third parties, and in certain circumstances laboratory test results. Molex has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and substances. Molex represents that to the best of its knowledge that the information provided in this declaration is accurate. Molex's sole liability shall be to either replace the product or refund the purchase price of the product if it does not meet the requirement of this declaration.

Components	Lead	Mercury	Cadmium	Hex. Chromium	PBB	PBDE
KK.045 Sq Pin Bando 1.000 (999) unplt	0	0	0	0	0	0
KK 156 Hdr Flat 04 Ckt 417700004	0	0	0	0	0	0

### **Process Information**

Component Plating / Surface Finish	MSn-RNi
Termination Base Alloy	Brass
Solder Alloy	N/A
Process Capability	WAVE
Maximum Exposure Time (seconds)	005
Maximum Process Temperature (C)	235
Maximum Cycles at Reflow Temperature	001
J-STD-020 Moisture Sensitivity Level	N/A

Mar 24, 2021