

Product Compliance Statement

July 18, 2021

Molex is committed to managing the use of chemical substances in accordance with governmental regulations, industry standards, and customer-specific requirements in order to protect the environment. For each part listed, this document provides:

- **EU RoHS Compliance Status.** EU RoHS status is declared per Directive 2011/65/EU and its subsequent amendments, including the Directive EU 2015/863 which additionally prohibited four phthalates. Homogeneous materials of parts that are compliant to this legislation have less than 0.1% by weight each of lead, mercury, hexavalent chromium, PBB, PBDE, DBP, BBP, DIBP, DEHP, and 0.01% by weight of cadmium. In situations where an exemption applies, the preceding limits, corresponding to the exempted substance(s), may be higher.

Molex's sole liability for incorrectly certifying a product shall be either replacement of the Molex product or, alternatively and in the sole discretion of Molex, return of the purchase price paid for the relevant Molex product.

For additional information regarding Molex's environmental initiatives and further explanation of this information, please visit www.molex.com



Haim Eliyahu
Director, Global Product Stewardship

Table A

Molex P/N	Part Description	RoHS Compliance Status
0008650121	KK Trifurcon Crimp Terminal 7258, 22-26 AWG, Reel, Phosphor Bronze Selective Gold (Au)	Compliant
0008650121	KK Trifurcon Crimp Terminal 7258, 22-26 AWG, Reel, Phosphor Bronze Selective Gold (Au)	Compliant
0015381024	2.54mm Pitch C-Grid Shunt Terminal Housings, Overall Tin (Sn), 2 Circuits, with Open End	Compliant
0026482075	KK 156 Hdr Assy FrLk Bkwy 07 ckt 20 Au	Compliant
0026482095	KK 156 Hdr Assy FrLk Bkwy 09 ckt 20 Au	Compliant
0026614060	KK 396 Header, Vertical, Friction Lock, 6 Circuits, Gold (Au) Plating	Compliant
0438600010	Modular Jack, Right-Angle, Low Profile, Inverted, Shielded, All Panel Grounding Tabs, Lightpipes, 8/8	Compliant
0438600006	Modular Jack, Right-Angle, Low Profile, Inverted, Shielded, All Panel Grounding Tabs, 6/4	Compliant
0039013023	Mini-Fit Jr. Plug Housing, Dual Row, 2 Circuits, UL 94V-2, without Panel Mounting Ears, Natural	Compliant
0432238122	Modular Jack, Right-Angle, Low Profile, 8/8, 2 Ports	Compliant
0455580003	Mini-Fit Jr. Header, Dual Row, Right-Angle, 6 Circuits, PA Polyamide Nylon 6/6 94V-0, Tin (Sn) Plating, without Drain Holes	Compliant
0467650301	0.40mm Pitch Micro HDMI Connector, Right-Angle Receptacle, Surface Mount, with Pick-and-Place Polyimide Tape, 19 Circuits, Lead-Free	Compliant
0528850674	SlimStack Board-to-Board Connector, 0.635mm Pitch, 0.635 Series, Receptacle, 6.00 to 10.00mm Mated Height, 6.40mm Mated Width, 60 Circuits	Compliant
0528851074	SlimStack Board-to-Board Connector, 0.635mm Pitch, 0.635 Series, Receptacle, 6.00 to 10.00mm Mated Height, 6.40mm Mated Width, 100 Circuits	Compliant
0522710669	Easy-On FFC/FPC Connector, 1.00mm Pitch, Slider Series, Right-Angle, Bottom Contact, 3.00mm Height, 6 Circuits, Gold Plating	Compliant
0522711179	Easy-On FFC/FPC Connector, 1.00mm Pitch, Slider Series, Right-Angle, Bottom Contact, 3.00mm Height, 11 Circuits, Tin-Bismuth Plating	Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
0550911074	SlimStack Board-to-Board Connector, 0.635mm Pitch, 0.635 Series, Plug, 6.00 or 12.00mm Mated Height, 6.40mm Mated Width, 100 Circuits	Compliant
0554600672	2.00mm Pitch Mi II System Wire-to-Board Header, Surface Mount, Single Row, Vertical, 6 Circuits	Compliant
0791077209	2.00mm Pitch Milli-Grid Receptacle, Vertical, Through Hole, Dual Row, 1.91mm Tail Length, 0.38µm Gold (Au) Selective Plating, 20 Circuits, Lead-Free	Compliant
0673298001	Universal Serial Bus (USB) Shielded I/O Receptacle, Type A Single Upright Right-Angle, Solder Tail Length 2.00mm, Kinked Pins, PCB Thickness 1.20mm and 1.60mm, 0.76µm Gold (Au) Plating, Lead-Free	Compliant
0731160035	MCRF-to-MCRF, 1.32mm Cable Diameter, Length 152.4mm, H25, 50 Ohms, One Piece Per Bag	Compliant
0791077208	2.00mm Pitch Milli-Grid Receptacle, Vertical, Through Hole, Dual Row, 1.91mm Tail Length, 0.38µm Gold (Au) Selective Plating, 18 Circuits, Lead-Free	Compliant
0878312020	2.00mm Pitch, Milli-Grid PCB Header, Dual Row, Vertical, Through Hole, Shrouded, 20 Circuits, 0.38µm Gold (Au) Plating, with Center Polarization Slot, with Locking Window, without PCB Locator, Tube	Compliant
0934443104	ML-XT Sealed 4 Circuit Receptacle Housing, Pre-Assembled with Small Rear Seal and Cover, Blue	Compliant
0956232881	Modular Jack, Top Entry, Through Hole, 8/8, Shielded, Tray	Compliant
0845240016	ML-XT / XRC Male (Pin) Terminal, 14 to 18 AWG, Terminal Size 16, Insulation Diameter 1.90 to 3.30mm, Selective Gold	Compliant