

## Product Compliance Statement

March 16, 2022

Molex is committed to managing the use of chemical substances in accordance with governmental regulations, industry standards, and customer-specific requirements in order to protect the environment. For each part listed, this document provides:

- **EU RoHS Compliance Status.** EU RoHS status is declared per Directive 2011/65/EU and its subsequent amendments, including the Directive EU 2015/863 which additionally prohibited four phthalates. Homogeneous materials of parts that are compliant to this legislation have less than 0.1% by weight each of lead, mercury, hexavalent chromium, PBB, PBDE, DBP, BBP, DIBP, DEHP, and 0.01% by weight of cadmium. In situations where an exemption applies, the preceding limits, corresponding to the exempted substance(s), may be higher.

- **EU REACH SVHC Content.** Substances of Very High Concerns (SVHCs) are declared if above 0.1% of the article per Regulation (EC) No. 1907/2006 and its subsequent amendments. The Candidate List of SVHCs is continually updated at <https://echa.europa.eu/candidate-list-table>.

- **Low-Halogen Status.** Homogeneous materials of parts that are considered Low-Halogen have less than 0.09% by weight each of bromine and chlorine, and less than 0.15% by weight of the sum of bromine and chlorine.

Molex's sole liability for incorrectly certifying a product shall be either replacement of the Molex product or, alternatively and in the sole discretion of Molex, return of the purchase price paid for the relevant Molex product.

For additional information regarding Molex's environmental initiatives and further explanation of this information, please visit [www.molex.com](http://www.molex.com)



Haim Eliyahu  
Director, Global Product Stewardship

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>	<b>REACH SVHC</b>	<b>Low-Halogen Status</b>
0014567062	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567067	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 22 AWG, 0.38µm Gold (Au), 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567069	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 22 AWG, 0.76µm Gold (Au), 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567071	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 7 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567079	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 22 AWG, 0.76µm Gold (Au), 7 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567081	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 8 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567089	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 22 AWG, 0.76µm Gold (Au), 8 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567091	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 9 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567100	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 10 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567101	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 10 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567102	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 10 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567104	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 22 AWG, 0.38µm Gold (Au), 10 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>	<b>REACH SVHC</b>	<b>Low-Halogen Status</b>
0014567111	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 11 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567121	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 12 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567131	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 13 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567139	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 22 AWG, 0.76µm Gold (Au), 13 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567141	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 14 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567147	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 22 AWG, 0.38µm Gold (Au), 14 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567149	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 22 AWG, 0.76µm Gold (Au), 14 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567151	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 15 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567159	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 22 AWG, 0.76µm Gold (Au), 15 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567161	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 16 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567162	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 16 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567171	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 17 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>	<b>REACH SVHC</b>	<b>Low-Halogen Status</b>
0014567181	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 18 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567191	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 19 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567201	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 20 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567207	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 22 AWG, 0.38µm Gold (Au), 20 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567211	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 21 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567220	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 22 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567221	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 22 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567222	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 22 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567231	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 23 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567241	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 24 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014567251	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 22 AWG, 3.81µm Tin/Lead (SnPb), 25 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014568022	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 22 AWG, 0.76µm Gold (Au), 2 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>	<b>REACH SVHC</b>	<b>Low-Halogen Status</b>
0014568062	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 22 AWG, 0.76µm Gold (Au), 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014568100	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 22 AWG, 0.76µm Gold (Au), 10 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014568110	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 22 AWG, 0.76µm Gold (Au), 11 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014600022	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 3.81µm Tin/Lead (SnPb), 2 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014600025	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 3.81µm Tin/Lead (SnPb), 2 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014600026	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 3.81µm Tin/Lead (SnPb), 2 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014600027	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 3.81µm Tin/Lead (SnPb), 2 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014600032	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 3.81µm Tin/Lead (SnPb), 3 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014600035	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version A, Non-polarized, Wire Size 28 AWG, 3.81µm Tin/Lead (SnPb), 3 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014600036	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 3.81µm Tin/Lead (SnPb), 3 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014600047	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 3.81µm Tin/Lead (SnPb), 4 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014600052	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 3.81µm Tin/Lead (SnPb), 5 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>	<b>REACH SVHC</b>	<b>Low-Halogen Status</b>
0014600054	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 3.81µm Tin/Lead (SnPb), 5 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014600056	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 3.81µm Tin/Lead (SnPb), 5 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014600058	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 24 AWG, 3.81µm Tin/Lead (SnPb), 5 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014600062	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 3.81µm Tin/Lead (SnPb), 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014600072	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 24 AWG, 3.81µm Tin/Lead (SnPb), 7 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014600096	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 28 AWG, 3.81µm Tin/Lead (SnPb), 9 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014600124	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 3.81µm Tin/Lead (SnPb), 12 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014600127	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version C, Front Ribs, Wire Size 24 AWG, 3.81µm Tin/Lead (SnPb), 12 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014600164	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 3.81µm Tin/Lead (SnPb), 16 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014600204	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 3.81µm Tin/Lead (SnPb), 20 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014601050	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 3.81µm Tin/Lead (SnPb), 5 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014601060	2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row, Version D, Back Ribs, Wire Size 26 AWG, 3.81µm Tin/Lead (SnPb), 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>	<b>REACH SVHC</b>	<b>Low-Halogen Status</b>
0014604033	SL IDT Hdr SR 15"SAu 3Ckt	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014604034	SL IDT Hdr SR 15"SAu 3Ckt	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014604036	SL IDT Hdr SR 15"SAu 3Ckt	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0014625022	SL IDT Hdr SR 15"SAu 2Ckt	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015040211	Mini-Fit Jr. Polarizing Key for Receptacles	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015040219	3.96mm Pitch KK Polarizing Key without Boss	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015040220	3.96mm Pitch KK Polarizing Peg with Boss	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015040292	Universal Polarizing Key, Black	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015040293	Universal Polarizing Key, White	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015040296	Mini-Fit Strain Relief, 6 Circuits, Natural	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015040297	Custom Polarizing Key	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015040343	Mini-Fit Jr. Strain Relief, 8 Circuits, Natural	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>	<b>REACH SVHC</b>	<b>Low-Halogen Status</b>
0015040802	Flat Blade Appliance Temperature Switch Crimp Housing, 6 Circuit	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015045042	2.54mm SL Interim Clip, 4 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045052	2.54mm SL Interim Clip, 5 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045061	2.54mm SL Interim Clip, 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045072	2.54mm SL Interim Clip, 7 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045084	2.54mm SL Interim Clip, 8 Circuits, Polarized	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045101	2.54mm SL Interim Clip, 10 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045104	2.54mm SL Interim Clip, 10 Circuits, Polarized	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045122	2.54mm SL Interim Clip, 12 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045124	2.54mm SL Interim Clip, 12 Circuits, Polarized	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045142	2.54mm SL Interim Clip, 14 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045144	2.54mm SL Interim Clip, 14 Circuits, Polarized	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen



**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>	<b>REACH SVHC</b>	<b>Low-Halogen Status</b>
0015045152	2.54mm SL Interim Clip, 15 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045161	2.54mm SL Interim Clip, 16 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045172	2.54mm SL Interim Clip, 17 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045181	2.54mm SL Interim Clip, 18 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045184	2.54mm SL Interim Clip, 18 Circuits, Polarized	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045201	2.54mm SL Interim Clip, 20 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045222	2.54mm SL Interim Clip, 22 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045224	2.54mm SL Interim Clip, 22 Circuits, Polarized	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045252	2.54mm SL Interim Clip, 25 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045261	2.54mm SL Interim Clip, 26 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045284	2.54mm SL Interim Clip, 28 Circuits, Polarized	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045301	2.54mm SL Interim Clip, 30 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>	<b>REACH SVHC</b>	<b>Low-Halogen Status</b>
0015045304	2.54mm SL Interim Clip, 30 Circuits, Polarized	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045361	2.54mm SL Interim Clip, 36 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045384	2.54mm SL Interim Clip, 38 Circuits, Polarized	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045401	2.54mm SL Interim Clip, 40 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045404	2.54mm SL Interim Clip, 40 Circuits, Polarized	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045424	2.54mm SL Interim Clip, 42 Circuits, Polarized	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045461	2.54mm SL Interim Clip, 46 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045484	2.54mm SL Interim Clip, 48 Circuits, Polarized	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045501	2.54mm SL Interim Clip, 50 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015045504	2.54mm SL Interim Clip, 50 Circuits, Polarized	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015049209	2.54mm Pitch KK Polarizing Key	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015049210	2.54mm Pitch KK Polarizing Peg	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>	<b>REACH SVHC</b>	<b>Low-Halogen Status</b>
0015049342	Mini-Fit Strain Relief, 6 Circuits, Black	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015049343	Mini-Fit Strain Relief, 8 Circuits, Natural	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015057044	3.96mm Pitch Black Polyester Strain Relief Cover, 4 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015057064	3.96mm Pitch Black Polyester Strain Relief Cover, 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015057125	5.08mm Pitch Black Polyester Strain Relief Cover, 12 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015057224	3.96mm Pitch Black Polyester Strain Relief Cover, 22 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058045	2.54mm Pitch Black Polyester IDT Cover, Feed-Through, 4 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058046	2.49mm Pitch Black Polyester IDT Cover, Feed-Through, 4 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058047	2.54mm Pitch Black Polyester IDT Cover, Feed-To, 4 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058048	2.49mm Pitch Black Polyester IDT Cover, Feed-To, 4 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058055	2.54mm Pitch Black Polyester IDT Cover, Feed-Through, 5 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058056	2.49mm Pitch Black Polyester IDT Cover, Feed-Through, 5 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>	<b>REACH SVHC</b>	<b>Low-Halogen Status</b>
0015058057	2.54mm Pitch Black Polyester IDT Cover, Feed-To, 5 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058065	2.54mm Pitch Black Polyester IDT Cover, Feed-Through, 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058067	2.54mm Pitch Black Polyester IDT Cover, Feed-To, 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058068	2.49mm Pitch Black Polyester IDT Cover, Feed-To, 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058075	2.54mm Pitch Black Polyester IDT Cover, Feed-Through, 7 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058087	2.54mm Pitch Black Polyester IDT Cover, Feed-To, 8 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058088	2.49mm Pitch Black Polyester IDT Cover, Feed-To, 8 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058095	2.54mm Pitch Black Polyester IDT Cover, Feed-Through, 9 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058097	2.54mm Pitch Black Polyester IDT Cover, Feed-To, 9 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058105	2.54mm Pitch Black Polyester IDT Cover, Feed-Through, 10 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058107	2.54mm Pitch Black Polyester IDT Cover, Feed-To, 10 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058108	2.49mm Pitch Black Polyester IDT Cover, Feed-To, 10 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>	<b>REACH SVHC</b>	<b>Low-Halogen Status</b>
0015058115	2.54mm Pitch Black Polyester IDT Cover, Feed-Through, 11 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058125	2.54mm Pitch Black Polyester IDT Cover, Feed-Through, 12 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058128	2.49mm Pitch Black Polyester IDT Cover, Feed-To, 12 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058135	2.54mm Pitch Black Polyester IDT Cover, Feed-Through, 13 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058145	2.54mm Pitch Black Polyester IDT Cover, Feed-Through, 14 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058147	2.54mm Pitch Black Polyester IDT Cover, Feed-To, 14 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058157	2.54mm Pitch Black Polyester IDT Cover, Feed-To, 15 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058165	2.54mm Pitch Black Polyester IDT Cover, Feed-Through, 16 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058167	2.54mm Pitch Black Polyester IDT Cover, Feed-To, 16 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015058205	2.54mm Pitch Black Polyester IDT Cover, Feed-Through, 20 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015060040	Mini-Fit BMI Receptacle Housing, 4.20mm Pitch, Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, 4 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060041	Mini-Fit BMI Receptacle Housing, 4.20mm Pitch, Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, 4 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>	<b>REACH SVHC</b>	<b>Low-Halogen Status</b>
0015060042	Mini-Fit BMI Receptacle Housing, 4.20mm Pitch, Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, 4 Circuits, 2.39mm max. PCB Thickness	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060045	Mini-Fit BMI Plug Housing, 4.20mm Pitch Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, 4 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060046	Mini-Fit BMI Plug Housing, 4.20mm Pitch Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, 4 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060060	Mini-Fit BMI Receptacle Housing, 4.20mm Pitch, Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060061	Mini-Fit BMI Receptacle Housing, 4.20mm Pitch, Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060065	Mini-Fit BMI Plug Housing, 4.20mm Pitch Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060066	Mini-Fit BMI Plug Housing, 4.20mm Pitch Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060080	Mini-Fit BMI Receptacle Housing, 4.20mm Pitch, Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, 8 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060085	Mini-Fit BMI Plug Housing, 4.20mm Pitch Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, 8 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060100	Mini-Fit BMI Receptacle Housing, 4.20mm Pitch, Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, 10 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060101	Mini-Fit BMI Receptacle Housing, 4.20mm Pitch, Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, 10 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060105	Mini-Fit BMI Plug Housing, 4.20mm Pitch Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, 10 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>	<b>REACH SVHC</b>	<b>Low-Halogen Status</b>
0015060106	Mini-Fit BMI Plug Housing, 4.20mm Pitch Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, 10 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060140	Mini-Fit BMI Receptacle Housing, 4.20mm Pitch, Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, 14 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060141	Mini-Fit BMI Receptacle Housing, 4.20mm Pitch, Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, 14 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060145	Mini-Fit BMI Plug Housing, 4.20mm Pitch Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, 14 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060146	Mini-Fit BMI Plug Housing, 4.20mm Pitch Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, 14 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060180	Mini-Fit BMI Receptacle Housing, 4.20mm Pitch, Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, 18 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060181	Mini-Fit BMI Receptacle Housing, 4.20mm Pitch, Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, 18 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060185	Mini-Fit BMI Plug Housing, 4.20mm Pitch Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, 18 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060186	Mini-Fit BMI Plug Housing, 4.20mm Pitch Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, 18 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060240	Mini-Fit BMI Receptacle Housing, 4.20mm Pitch, Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, 24 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060245	Mini-Fit BMI Plug Housing, 4.20mm Pitch Dual Row with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, 24 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015060246	Mini-Fit BMI Plug Housing, 4.20mm Pitch Dual Row with Panel Mount Ears, White, UL 94V-0, 24 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>	<b>REACH SVHC</b>	<b>Low-Halogen Status</b>
0015243048	Mini-Fit BMI Receptacle Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-In Plastic Pegs, 1.25µm Gold (Au), 4 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015244047	5.08mm Pitch Disk Drive Power Connection System, Male Crimp Housing, 4 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015244048	5.08mm Pitch Disk Drive Power Connection System, Female Crimp Housing	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015244745	5.08mm Pitch Disk Drive Power Connection System Header, Vertical, Through Hole, 4 Circuits, Lead-Free, 3.58mm PC Tail Length, without PCB Locator Peg	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Not Low- Halogen
0015246040	Mini-Fit BMI Header, Dual Row, Right-Angle, with Snap-in Plastic Peg PCB Lock, 4 Circuits, PA Polyamide Nylon 6/6, UL 94V-2, with Tin (Sn) Plating	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015246041	Mini-Fit BMI Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, 4 Circuits, PA Polyamide Nylon 6/6, UL 94V-2, Tin (Sn) Plating, without Drain Holes	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015246042	Mini-Fit BMI Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, 4 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) Plating, without Drain Holes	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015246043	Mini-Fit BMI Header, Dual Row, Right-Angle, with Snap-in Plastic Peg PCB Lock, 4 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, with Select Gold (Au) Plating	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015246047	Mini-Fit BMI Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, 4 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) Plating, with Drain Holes	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015246063	Mini-Fit BMI Header, Dual Row, Right-Angle, with Snap-in Plastic Peg PCB Lock, 6 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, with Select Gold (Au) Plating	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015246066	Mini-Fit BMI Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, 6 Circuits, PA Polyamide Nylon 6/6, UL 94V-2, Tin (Sn) Plating, with Drain Holes	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015246102	Mini-Fit BMI Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, 10 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) Plating, without Drain Holes	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen



**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>	<b>REACH SVHC</b>	<b>Low-Halogen Status</b>
0015246103	Mini-Fit BMI Header, Dual Row, Right-Angle, with Snap-in Plastic Peg PCB Lock, 10 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, with Select Gold (Au) Plating	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015246107	Mini-Fit BMI Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, 10 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) Plating, with Drain Holes	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015246142	Mini-Fit BMI Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, 14 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) Plating, without Drain Holes	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015246143	Mini-Fit BMI Header, Dual Row, Right-Angle, with Snap-in Plastic Peg PCB Lock, 14 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, with Select Gold (Au) Plating	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015246146	Mini-Fit BMI Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, 14 Circuits, PA Polyamide Nylon 6/6, UL 94V-2, Tin (Sn) Plating, with Drain Holes	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015246163	Mini-Fit BMI Header, Dual Row, Right-Angle, with Snap-in Plastic Peg PCB Lock, 16 Circuits, PA Polyamide Nylon 6/6 94V-0, with Select Gold (Au) Plating	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015246182	Mini-Fit BMI Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, 18 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) Plating, without Drain Holes	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015246240	Mini-Fit BMI Header, Dual Row, Right-Angle, with Snap-in Plastic Peg PCB Lock, 24 Circuits, PA Polyamide Nylon 6/6, UL 94V-2, with Tin (Sn) Plating	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015246241	Mini-Fit BMI Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, 24 Circuits, PA Polyamide Nylon 6/6, UL 94V-2, Tin (Sn) Plating, without Drain Holes	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015246242	Mini-Fit BMI Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, 24 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) Plating, without Drain Holes	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015246246	Mini-Fit BMI Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, 24 Circuits, PA Polyamide Nylon 6/6, UL 94V-2, Tin (Sn) Plating, with Drain Holes	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015246247	Mini-Fit BMI Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, 24 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) Plating, with Drain Holes	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>	<b>REACH SVHC</b>	<b>Low-Halogen Status</b>
0015247040	Mini-Fit BMI Receptacle Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-In Plastic Pegs, Post 2.54µm Tin (Sn), UL 94V-2, 4 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015247041	Mini-Fit BMI Receptacle Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-In Plastic Pegs, Post 2.54µm Tin (Sn), UL 94V-0, 4 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015247061	Mini-Fit BMI Receptacle Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-In Plastic Pegs, Post 2.54µm Tin (Sn), UL 94V-0, 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015247062	Mini-Fit BMI Receptacle Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-In Plastic Pegs, 0.80µm Gold (Au), UL 94V-2, 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015247063	Mini-Fit BMI Receptacle Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-In Plastic Pegs, 0.80µm Gold (Au), UL 94V-0, 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015247064	Mini-Fit BMI Receptacle Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-In Plastic Pegs, Post 2.54µm Tin (Sn), UL 94V-2, 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015247067	Mini-Fit BMI Receptacle Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-In Plastic Pegs, 0.80µm Gold (Au), UL 94V-0, 6 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen
0015247100	Mini-Fit BMI Receptacle Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-In Plastic Pegs, Post 2.54µm Tin (Sn), UL 94V-2, 10 Circuits	Compliant	Not Contained Per - D(2021)10043-DC (17 Jan 2022)	Low-Halogen