

Home: Cable >

Part Number: 98267-0230

1.00mm Pitch Premo-Flex™ FFC Jumper, Opposite Side Contacts (Type D), 8 Circuits, 0.102m Cable Length, 0.22mm Cable Thickness, Tin(Sn) Plating



Series image - Reference only

Status: Active
Series: [98267](#)
Category: Cable
Overview: [Premo-Flex™ Cable Jumpers](#)

Go to [Part Detail](#) ▼

CHECK DISTRIBUTOR INVENTORY

- [Add to My Parts](#)
- [Email this page](#)

Use With:

[Molex FFC – FPC connector](#). Be sure to match like plating

Specifications & Other Documents:

- [Part Details \(PDF\)](#)
- [Product Specification PS-98267-001.pdf](#)
- [Packaging Specification PK-98267-001.pdf](#)

Sales Drawings, 3D Models, and Brochures

Drawing (PDF)

Note - Please disable browser pop-up blockers to view documents on www.molex.com

Product Environmental Compliance

Questions on Product Environmental Compliance? Email productcompliance@molex.com

- [EU ELV](#): Not Relevant
- [EU RoHS](#): Not Reviewed
- [China RoHS](#):
- [REACH SVHC](#): Not Reviewed
- [Low-Halogen Status](#): Not Reviewed

- RoHS Certificate of Compliance (PDF)
- Multiple Part Product Compliance Form

Application Tooling

[FAQ](#)

Tooling specifications and manuals are found by selecting the products below.

Crimp Height Specifications are then contained in the Application Tooling Specification document.

Crimp Quality Equipment

[Molex also offers wire strippers, pull testers, shut-height gauges, micro-meters and more](#)

Previously Available Application Tooling

[Check our list of old tooling that used to be available for this part](#)

Part Detail

COLLAPSE ALL

▼ **General**

Status	Active
Category	Cable
Series	98267
Comments	Contacts on opposite sides, Type D
Overview	Premo-Flex™ Cable Jumpers
Product Name	Premo-Flex™ FFC Jumper
UPC	756054770504

▼ **Physical**

Cable Length	0.102m
Circuits (Loaded)	8
Net Weight	0.620/g
Packaging Type	Bag
Pitch - Termination Interface	1.00mm
Temperature Range - Operating	-40°C to +105°C

Wire Size AWG	N/A
Wire/Cable Type	Flat Flex Cable

▼ **Electrical**

(Please review the Product Specification for specific details.)

Current - Maximum per Contact	1.2A
Voltage - Maximum	60V AC

▼ **Material Info**

▼ **Reference - Drawing Numbers**

Packaging Specification	PK-98267-001
Product Specification	PS-98267-001
Sales Drawing	SD-98267-001

PRODUCTS

- Antennas
- Application Tooling
- Cable Assemblies
- Connectors
- Copper Flex
- Electrical Products
- Industrial Automation
- Membrane Switches
- Optical Solutions
- PCB Assemblies
- Solid State Lighting

QUICK LINKS

- Contact Molex
- Cross-Reference
- Industries
- Literature
- Press Room / Press Releases
- Product Index
- Sitemap

RESOURCES

- California Supply Chains Act
- Careers
- Compliance
- ecocare
- Feedback | Help
- Legal | Trademarks
- Mobile Site
- Supplier Portal
- Privacy Policy

STAY CONNECTED

