


NOTE

1. 嵌合相手：503764シリーズ
   MATES WITH : 503764 SERIES
2. 偶数極の製品に適用
   APPY EVEN CIRCUIT PRODUCTS.
3. 材質
   MATERIAL
   ハウジング ： 耐熱性樹脂 UL94-V0 BLACK
   HOUSING : HEATPROOF RESIN UL94-V0 BLACK
   ターミナル ： 銅合金
   TERMINAL : COPPER ALLOY
   ネール ： 銅合金
   NAIL : COPPER ALLOY
4. メッキ
   PLATING
   ターミナル ： 下地 ニッケルメッキ、コンタクト及びテール部 金メッキ
   TERMINAL : UNDER NICKEL PLATING ,
   CONTACT AND TAIL GOLD PLATING
   ネール ： 下地 ニッケルメッキ、錫メッキ
   NAIL : UNDER NICKEL PLATING , TIN
5. ELV及びRoHS適合品
   ELV AND RoHS COMPLIANT.
6. パターン禁止エリア
   PATTERN PROHIBITION AREA
7. ソルダーテールとネイルの平坦度：0．1mmMAX.
   SOLDER TAIL AND FITTING NAIL COPLANARITY : 0.1mmMAX.
8. コネクタの取扱いについては、AS-503764-001/002を参照
   PLEASE REFER TO AS-503764-001/002

3.0	7.8	5037630491	4
1.0	5.8	5037630291	2
B	A	EMBOSSED PACKAGE ORDER No.	CIRCUIT

CONNECTOR SERIES No. 503763 - **91

REVISED				REV
EC NO: J2014-1278	2014/03/03			
DRWN:YWAKE	2014/03/03			
CHKD:KASAKAWA	2014/03/03			
APPR:NUKITA	2014/03/05			
A				


GENERAL TOLERANCES (UNLESS SPECIFIED)

DESCRIPTION	
10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR ±1 °	


DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE	MM ONLY
SCALE	10:1
DESIGN UNITS	METRIC
	THIRD ANGLE PROJECTION
DRAWN BY / DATE	YWAKE 2014/03/03
CHECKED BY / DATE	KASAKAWA 2014/03/03
APPROVED BY / DATE	NUKITA 2014/03/05
MATERIAL NO.	SEE CHART
TITLE	1.0 WIRE TO BOARD CONN. R/A H=1.5MM HEADER ASS'Y
DOCUMENT NO.	SD-503763-001
SHEET NO.	1 OF 2
SIZE	A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



RECOMMENDED PATTERN LAYOUT (REF.)



MATED CONNECTORS

SEE SHEET 1	EC NO: J2014-1278	DRWN:YWAKE	2014/03/03
		CH'KD:KASAKAWA	2014/03/03
		APPR:NUKITA	2014/03/05
A		DESCRIPTION	

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±1 °


DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS


DIMENSION STYLE	MM ONLY
SCALE	10:1
DESIGN UNITS	METRIC
	THIRD ANGLE PROJECTION
DRAWN BY / DATE	YWAKE 2014/03/03
CHECKED BY / DATE	KASAKAWA 2014/03/03
APPROVED BY / DATE	NUKITA 2014/03/05
MATERIAL NO.	SEE SHEET 1
TITLE	1.0 WIRE TO BOARD CONN. R/A H=1.5MM HEADER ASS'Y
	molex
DOCUMENT NO.	SD-503763-001
SHEET NO.	2 OF 2
SIZE	A3


THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

ELV AND RoHS COMPLIANT

CONFIDENTIAL








DETAIL "D"


NOTE

1. 梱包数量： 3000個 ／リール
   NUMBER OF CONNECTORS : 3000 PIECES/REEL

2. リードテープ長さ
   LEAD TAPE LENGTH



3. トップテープの剥離強度：JES-59参照
   剥離方向は下記参照。
   <剥離速度：300mm/minute （参考）>
   PEELING OFF FORCE OF TOP TAPE : REFFER TO JES-59
   PEELING DIRECTION AS SHOWN IN FOLLOWING FIGURE.
   <PEELING OFF SPPED : 300mm/minute (REFERENCE)>



4. 材料 MATERIAL
   キャリアテープ (CARRIER TAPE)：PS
   トップテープ (TOP TAPE)：PE、PE、PET
   リール：PS （リサイクル材を含む RECYCLE MATERIAL CONTAINED）

5. 製品詳細寸法についてはSD-503763-001を参照ください。
   PLEASE REFER SD-503763-001 FOR THE DETAILED DIMENSION.

6. 環境負荷物質の管理の為「化学物質ガイドライン」の内容を満足する事。
   CHEMICAL SUBSTANCES GUIDELINE MANAGEMENT OF ENVIRONMENTAL HAZARDOUS MATERIALS.

C	B	A WIDTH OF TAPE	MATERIAL No.	CIRCUIT
25.5	11.5	24	503763-0491	4
17.5	7.5	16	503763-0291	2

RELEASED
EC NO: J2014-12278 2014/02/28
DRWN:YWAKE 2014/02/28
CH'KD:KASAKAWA 2014/03/05
APPR:NUKITA
DESCRIPTION
A
REV

GENERAL TOLERANCES (UNLESS SPECIFIED)


10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY	SCALE: 5:1	DESIGN UNITS: METRIC	THIRD ANGLE PROJECTION
DRAWN BY: YWAKE DATE: 2014/02/28	TITLE: EMBOSSED TAPE PACKAGE FOR 503763-**** (1.0WB CONN, H=1.5MM)		
CHECKED BY: KASAKAWA DATE: 2014/02/28			
APPROVED BY: NUKITA DATE: 2014/03/05	molex		
MATERIAL NO.: SEE CHART	DOCUMENT NO.: SD-503763-002		SHEET NO.: 1 OF 1

SIZE A2

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



NOTE

1. 嵌合相手：503763シリーズ
   MATES WITH : 503763 SERIES
2. 適合ターミナル：503765シリーズ
   APPLICABLE TERMINAL : 503765 SERIES
   偶数極に適用
   APPY EVEN CIRCUIT PRODUCTS
4. 材料
   MATERIAL
   耐熱性樹脂 UL94-V0 BLACK
   HEATPROOF RESIN UL94-V0 BLACK
5. ELV及びRoHS適合品
   ELV AND RoHS COMPLIANT
6. コネクタの取扱いについては、AS-503764-001/002を参照
   PLEASE REFER TO AS-503764-001/002

6.6	7	8.6	3.0	5037640401	4
4.6	5	6.6	1.0	5037640201	2
D	C	B	A	ORDER No.	CIRCUIT

RELEASED
EC NO: J2014-1278 2014/03/03
DRWN:YWAKE 2014/03/03
CH'KD:KASAKAWA 2014/03/03
APPR:NUKITA 2014/03/05
DESCRIPTION
REV A

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: 10:1
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: YWAKE DATE: 2014/03/03
CHECKED BY: KASAKAWA DATE: 2014/03/03
APPROVED BY: NUKITA DATE: 2014/03/05

TITLE: 1.0 WIRE TO BOARD CONN. R/A H=1.5MM REC CRIMP HOUSING

molex

MATERIAL NO.: SEE CHART
DOCUMENT NO.: SD-503764-001
SHEET NO.: 1 OF 1
SIZE: A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION