

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:0311010041

Status:Active

Overview:H-DAC 64 Unsealed Connector System

Description:H-DAC 64 2.54mm 4 Way Vertical Header Assembly, Polarization B

Documents:

[Drawing \(PDF\)](#)

[Product Specification PS-31100-0001-001 \(PDF\)](#)

[Application Specification AS-31067-100-001 \(PDF\)](#)

[Packaging Specification PK-31300-707 \(PDF\)](#)

[RoHS Certificate of Compliance \(PDF\)](#)

General

Product Family

Series

Application

Comments

Overview

Product Name

UPC

PCB Headers

31101

Power, Wire-to-Board

Polarization Option B, Gray

H-DAC 64 Unsealed Connector System

H-DAC 64

822350699808

Physical

Breakaway

Circuits (Loaded)

Circuits (maximum)

Color - Resin

Durability (mating cycles max)

First Mate / Last Break

Glow-Wire Capable

Guide to Mating Part

Keying to Mating Part

Lock to Mating Part

Material - Metal

Material - Plating Mating

Material - Plating Termination

Material - Resin

Net Weight

Number of Rows

Orientation

PC Tail Length

PCB Locator

PCB Retention

PCB Thickness - Recommended

Packaging Type

Pitch - Mating Interface

Pitch - Termination Interface

Plating min - Mating

Plating min - Termination

Polarized to Mating Part

Polarized to PCB

Shrouded

Stackable

Surface Mount Compatible (SMC)

Temperature Range - Operating

Termination Interface: Style

No

4

4

Gray

10

No

No

No

None

Yes

Brass

Tin

Nickel

Modified Polystyrene

1.754/g

1

Right Angle

3.68mm

Yes

Yes

1.57mm

Tray

2.54mm

2.54mm

1.524µm

1.524µm

Yes

Yes

Closed Ends

No

No

-40° to +100°C

Through Hole

Electrical

Current - Maximum per Contact

Voltage - Maximum

5.0A, 7.0A

500V DC



Series image - Reference only

EU ELV

Compliant

EU RoHS

Compliant

REACH SVHC

Not Contained Per - ED/61/2018 (27 June 2018)

Halogen-Free

Status

Not Relevant

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

Not Relevant

Compliant

Not Contained

Search Parts in this Series

31101 Series

Mates With

H-DAC 64, 4 Way Receptacle Assembly

Solder Process Data

Duration at Max. Process Temperature (seconds)	040
Lead-freeProcess Capability	SMC&WAVE
Max. Cycles at Max. Process Temperature	003
Process Temperature max. C	260

Material Info

Reference - Drawing Numbers

Application Specification	AS-31067-100-001
Packaging Specification	PK-31300-707
Product Specification	PS-31100-0001-001

This document was generated on 09/19/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION