

Part Number: 469940302

Product Description: Mini-Fit Jr. Receptacle Housing, Single Row, PA Polyamide Nylon 6/6, UL 94V-2, 3 Circuits, Positive Latch, First Mate/Last Break, Glow-Wire Capable, Beige

Series Number: 46994

Status: Active

Product Category: Connector Housings



Documents & Resources

Drawings

469940302_sd.pdf PK-5557-002-000.pdf

3D Models and Design Files

469940302_stp.zip

Specifications

55560001-AS-000.pdf 55560002-AS-000.pdf PS-45750-001-001.pdf PS-5556-001-001.pdf 55560001-TS-000.pdf TS-5556-002-001.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|--|
| China RoHS | © |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2- 21 |
| REACH SVHC | Not Contained per D(2024)6225-DC (07 Nov 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|--------------|---|
| Category | Connector Housings |
| Series | 46994 |
| Description | Mini-Fit Jr. Receptacle Housing, Single Row, PA Polyamide Nylon 6/6, UL 94V-2, 3 Circuits, Positive Latch, First Mate/Last Break, Glow- Wire Capable, Beige |
| Application | Power, Wire-to-Board, Wire-to-Wire |
| Product Name | Mini-Fit Jr. |
| UPC | 889056143295 |

Physical

| Circuits (maximum) | 3 |
|-----------------------|------------|
| Color - Resin | Beige |
| Gender | Receptacle |
| Glow-Wire Capable | Yes |
| Keying to Mating Part | None |
| Lock to Mating Part | Yes |
| Material - Resin | Nylon |
| Net Weight | 0.950/g |
| Number of Rows | 1 |
| Packaging Type | Bag |
| Panel Mount | No |
| | |

| Pitch - Mating Interface | 4.20mm |
|-------------------------------|----------------|
| Pitch - Termination Interface | 4.20mm |
| Polarized to Mating Part | Yes |
| Ports | 1 |
| Stackable | No |
| Temperature Range - Operating | -40° to +105°C |

Solder Process Data

| Lead-Free Process Capability | N/A |
|------------------------------|-----|
|------------------------------|-----|

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|--|---------------|
| Mini-Fit Jr. Single Row Plug Housings | <u>172646</u> |
| Mini-Fit Jr. Vertical Single Row Headers | <u>172647</u> |
| Mini-Fit Jr. Right-Angle Single Row Headers | 172648 |

Use with Part(s)

| Description | Part Number |
|---|--------------|
| Mini-Fit Female Crimp Terminals | <u>5556</u> |
| Mini-Fit Plus Female Crimp Terminals | <u>45750</u> |

This document was generated on Jan 22, 2025