

## Product Compliance Statement

July 25, 2013

Molex is committed to managing the use of chemical substances in accordance with governmental regulations, industry standards, and customer-specific requirements in order to protect the environment. For each part listed, this document provides:


- **EU RoHS Compliance Status.** EU RoHS status is declared per Directive 2011/65/EU and its subsequent amendments. Homogeneous materials of parts that are compliant to this legislation have less than 0.1% by weight each of lead, mercury, hexavalent chromium, PBB, and PBDE, and 0.01% by weight of cadmium. In situations where an exemption applies, the preceding limits, corresponding to the exempted substance(s), may be higher.

- **EU REACH SVHC Content.** Substances of Very High Concerns (SVHCs) are declared if above 0.1% of the article per Regulation (EC) No. 1907/2006 and its subsequent amendments. The Candidate List of SVHCs is continually updated at [http://echa.europa.eu/chem\\_data/authorisation\\_process/candidate\\_list\\_table\\_en.asp](http://echa.europa.eu/chem_data/authorisation_process/candidate_list_table_en.asp) . The current revision was used in this declaration.

- **Low-Halogen Status.** Homogeneous materials of parts that are considered Low-Halogen have less than 0.09% by weight each of bromine and chlorine, and less than 0.15% by weight of the sum of bromine and chlorine.

Molex's sole liability for incorrectly certifying a product shall be either replacement of the Molex product or, alternatively and in the sole discretion of Molex, return of the purchase price paid for the relevant Molex product.

For additional information regarding Molex's environmental initiatives and further explanation of this information, please visit [www.molex.com](http://www.molex.com)



Joel F. Eurich  
Director, Global Environmental, Health & Safety (EH&S)

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>   | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b> | <b>Low-Halogen Status</b> |
|------------------|---|-------------------------------|-------------------|---------------------------|
| 02-09-1102       | 2.36mm Diameter, Standard .093" Pin and Socket Crimp Terminal, Series 1189, Female, with Tin (Sn) Plated Brass Contact, 14-20 AWG, Reel         | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 02-09-1104       | 2.36mm Diameter, Standard .093" Pin and Socket Crimp Terminal, Series 1189, Female, with Tin (Sn) Plated Brass Contact, 14-20 AWG, Bag          | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 02-09-5142       | 2.36mm Diameter, Standard .093" Pin and Socket Crimp Terminal, Series 1381, Female, with Gold (Au) Plated Brass Contact, 18-22 AWG, Bag         | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 02-09-5143       | 2.36mm Diameter, Standard .093" Pin and Socket Crimp Terminal, Series 1381, Female, with Gold (Au) Plated Brass Contact, 18-22 AWG, Reel        | ELV and RoHS Compliant        | Contains SVHC: No | Not Reviewed              |
| 02-09-6106       | 2.36mm Diameter, Standard .093" Pin and Socket Crimp Terminal, Series 1190, Male, with Gold (Au) Plated Brass Contact, 14-20 AWG, Bag           | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 02-09-6110       | 2.36mm Diameter, Standard .093" Pin and Socket Crimp Terminal, Series 1190, Male, with Selective Gold (Au) Plated Brass Contact, 14-20 AWG, Bag | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 02-09-6122       | 2.36mm Diameter, Standard .093" Pin and Socket Crimp Terminal, Series 1380, Male, with Gold (Au) Plated Brass Contact, 18-22 AWG, Reel          | ELV and RoHS Compliant        | Contains SVHC: No | Not Reviewed              |
| 02-09-6123       | 2.36mm Diameter, Standard .093" Pin and Socket Crimp Terminal, Series 1380, Male, with Gold (Au) Plated Brass Contact, 18-22 AWG, Bag           | ELV and RoHS Compliant        | Contains SVHC: No | Not Reviewed              |
| 03-06-1241       | 1.57mm Diameter Standard .062" Pin and Socket Receptacle Housing, 24 Circuits, with Mounting Ears   | ELV and RoHS Compliant        | Contains SVHC: No | Not Reviewed              |
| 03-06-2024       | 1.57mm Diameter Standard .062" Pin and Socket Plug Housing, 2 Circuits, with Pre-bent Mounting Ears   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 08-50-0105       | 3.96mm Pitch KK® Crimp Terminal 2478, 18-24 AWG, Reel, Brass Tin (Sn)   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 08-50-0114       | KK® Crimp Terminal, 22-30 AWG, Bag, Hot Tin (Sn) Dip, Nickel (Ni) Under Plating   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 08-55-0102       | KK® Crimp Terminal, 22-30 AWG, Bag, Selective Gold (Au), Nickel (Ni) Under Plating  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>   | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b> | <b>Low-Halogen Status</b> |
|------------------|---|-------------------------------|-------------------|---------------------------|
| 09-50-3061       | 3.96mm Pitch KK® Crimp Terminal Housing, Friction Ramp, 6 Circuits  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 09-65-2088       | 3.96mm Pitch SPOX™ and KK® Wire-to-Board Header, Vertical, with Friction Lock, 8 Circuits   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 11-03-0044       | Extraction Tool   | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 14-56-2074       | 2.54mm Pitch SL™ Insulation Displacement Connector Assembly, Female, Single Row, Version G, Positive Lock, Wire Size 26 AWG, 0.38µm Gold (Au), 7 Circuits   | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 15-24-4449       | 5.08mm Pitch Disk Drive Power Connection System Header, Vertical, Through Hole, 4 Circuits, Lead-Free, 3.60mm PC Tail Length, without PCB Locator Peg   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 15-91-3033       | 2.54mm Pitch SL™ Wire-to-Board Header, Low Profile, Surface Mount, Single Row, Right Angle, 3.05mm Pocket, Shrouded, with Press-fit Plastic Peg, 3 Circuits, 0.76µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 15-92-2430       | 1.27mm Pitch EBBI™ 50D Plug, Vertical, without Latch, 30 Circuits, 2.79mm PC Tail Length  | ELV and RoHS Compliant        | Not Reviewed      | Low-Halogen               |
| 15-92-2440       | 1.27mm Pitch EBBI™ 50D Plug, Vertical, without Latch, 40 Circuits, 2.79mm PC Tail Length  | ELV and RoHS Compliant        | Not Reviewed      | Low-Halogen               |
| 15-92-2450       | 1.27mm Pitch EBBI™ 50D Plug, Vertical, without Latch, 50 Circuits, 2.79mm PC Tail Length  | ELV and RoHS Compliant        | Not Reviewed      | Low-Halogen               |
| 15-92-2460       | 1.27mm Pitch EBBI™ 50D Plug, Vertical, without Latch, 60 Circuits, 2.79mm PC Tail Length  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 15-92-2480       | 1.27mm Pitch EBBI™ 50D Plug, Vertical, without Latch, 80 Circuits, 2.79mm PC Tail Length  | ELV and RoHS Compliant        | Not Reviewed      | Low-Halogen               |
| 16-02-0083       | SL™ Crimp Terminal 70058, 24-30 AWG, Reel Selective Gold (Au)   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 16-02-0110       | SL™ Crimp Terminal, Series 70021, Male, with 0.76µm Selective Gold (Au) Plated Contact, 24-30 AWG, Bag  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 16-02-1113       | SL™ Crimp Terminal, Series 71851, Female, with 0.76µm Selective Gold (Au) Plated Contact, 24-30 AWG, Reel   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 19002-0009       | Avikrimp™ Fully Insulated Quick Disconnect, Female, for 18-22 AWG Wire, Box   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>  | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b> | <b>Low-Halogen Status</b> |
|------------------|--|-------------------------------|-------------------|---------------------------|
| 19002-0024       | Avikrimp™ Fully Insulated Quick Disconnect, Female, for 14-16 AWG Wire, Box  | ELV and RoHS Compliant        | Contains SVHC: No | Not Reviewed              |
| 190020044        | Avikrimp™ Quick Disconnect, Female, for 10-12 (5.00-3.30mm <sup>2</sup> ) Wire, Box, Tab 6.35 x 0.81mm                     | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 190030040        | InsulKrimp™ Female Quick Disconnect, for 14-16 AWG Wire  | ELV and RoHS Compliant        | Contains SVHC: No | Not Reviewed              |
| 19005-0010       | InsulKrimp™ Fully Insulated Female Quick Disconnect, for 10-12 AWG Wire, Box   | ELV and RoHS Compliant        | Not Reviewed      | Low-Halogen               |
| 19016-0085       | Krimptite™ Quick Disconnect, Female, for 12-14 (3.30-2.00mm <sup>2</sup> ) Wire, Box, Tab 6.35 x 0.81mm                    | ELV and RoHS Compliant        | Contains SVHC: No | Not Reviewed              |
| 22-05-3061       | 2.54mm Pitch KK® Solid Header, Right Angle, with Friction Lock, 6 Circuits, Tin (Sn) Plating                               | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 22-05-7025       | 2.50mm Pitch SPOX™ Wire-to-Board Header, Right Angle, Shrouded, Friction Lock, 2 Circuits                                  | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 22-11-2062       | 2.54mm Pitch KK® Solid Header, Vertical, with Friction Lock, 6 Circuits, Gold (Au) Plating                                 | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 22-11-2102       | 2.54mm Pitch KK® Solid Header, Vertical, with Friction Lock, 10 Circuits, Gold (Au) Plating                                | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 22-12-2024       | 2.54mm Pitch KK® Solid Header, Right Angle, with Friction Lock, 2 Circuits, 0.51µm Gold (Au) Plating                       | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 22-12-2034       | 2.54mm Pitch KK® Solid Header, Right Angle, with Friction Lock, 3 Circuits, 0.51µm Gold (Au) Plating                       | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 22-55-2102       | 2.54mm Pitch SL™ Crimp Housing, Dual Row, Version B, Polarized, 10 Circuits  | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 22-55-2142       | 2.54mm Pitch SL™ Crimp Housing, Dual Row, Version B, Polarized, 14 Circuits  | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 22-55-2242       | 2.54mm Pitch SL™ Crimp Housing, Dual Row, Version B, Polarized, 24 Circuits  | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 26-60-2020       | 3.96mm (.156") Pitch KK® Solid Header, Vertical, without Peg, 2 Circuits, Tin (Sn) Plating                                 | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 35728-0201       | 2.00mm Diameter Socket Terminal, Brass, 0.25mm Thickness, Wire Range 14-20 AWG (2.00-0.52mm <sup>2</sup> ), Pre-Tin Plated | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 38660-8802       | 12.70mm Pitch Beau™ PCB Tri-Barrier Terminal Strip, with Mounting Ends, 600V, 2 Circuits                                   | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>   | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b> | <b>Low-Halogen Status</b> |
|------------------|---|-------------------------------|-------------------|---------------------------|
| 38660-8803       | 12.70mm Pitch Beau™ PCB Tri-Barrier Terminal Strip, with Mounting Ends, 600V, 3 Circuits  | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 39-00-0021       | SPOX™ Crimp Terminal 5194, 18-24 AWG, Phosphor Bronze, Reel   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 39-00-0089       | Mini-Fit® Female Crimp Terminal, Gold (Au) over Brass, 16 AWG, Reel   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 39-00-0096       | Mini-Fit® Male Crimp Terminal, Selective Gold (Au) and Selective Tin (Sn) over Nickel (Ni), 16 AWG, Bag   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 39-00-0428       | Mini-Fit® Female Crimp Terminal, Selective Gold (Au) and Selective Tin (Sn) over Nickel (Ni), 18-24 AWG, Reel   | ELV and RoHS Compliant        | Not Reviewed      | Low-Halogen               |
| 39-00-0429       | Mini-Fit® Female Crimp Terminal, Selective Gold (Au) and Selective Tin (Sn) over Nickel (Ni), 18-24 AWG, Bag  | ELV and RoHS Compliant        | Not Reviewed      | Low-Halogen               |
| 39-01-2085       | Mini-Fit Jr.™ Receptacle Housing, 4.20mm Pitch, Dual Row, UL 94V-0, 8 Circuits,   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 39-01-3042       | Mini-Fit Jr.™ Receptacle Housing, 4.20mm Pitch, Dual Row, PA Polyamide Nylon 6/6, UL 94V-2, 4 Circuits  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 39-29-1028       | Mini-Fit® Jr. Header, 4.20mm Pitch, Dual Row, Right Angle, with PCB Mounting Flange, 2 Circuits, PA Polyamide Nylon 6/6 94V-2, Tin (Sn) Plating   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 39-29-1068       | Mini-Fit® Jr. Header, 4.20mm Pitch, Dual Row, Right Angle, with PCB Mounting Flange, 6 Circuits, PA Polyamide Nylon 6/6 94V-2, Tin (Sn) Plating   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 39-29-1088       | Mini-Fit® Jr. Header, 4.20mm Pitch, Dual Row, Right Angle, with PCB Mounting Flange, 8 Circuits, PA Polyamide Nylon 6/6 94V-2, Tin (Sn) Plating   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 39-29-4069       | Mini-Fit® Jr. Header, 4.20mm Pitch, Dual Row, Right Angle, with PCB Mounting Flange, 6 Circuits, PA Polyamide Nylon 6/6 94V-0, Gold (Au) Plating  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 39-29-6068       | Mini-Fit® Jr. Header, 4.20mm Pitch, Dual Row, Vertical, without Snap-in Plastic Peg PCB Lock, 6 Circuits, PA Polyamide Nylon 6/6 94V-0, 0.76µm Gold (Au) Selective Plating, without Drain Holes | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |

**Table A**

| Molex P/N  | Part Description   | RoHS Compliance Status | REACH SVHC        | Low-Halogen Status |
|------------|--|------------------------|-------------------|--------------------|
| 39-29-6208 | Mini-Fit® Jr. Header, 4.20mm Pitch, Dual Row, Vertical, without Snap-in Plastic Peg PCB Lock, 20 Circuits, PA Polyamide Nylon 6/6 94V-0, 0.76µm Gold (Au) Selective Plating, without Drain Holes | ELV and RoHS Compliant | Contains SVHC: No | Low-Halogen        |
| 39-29-9084 | Mini-Fit® Jr. Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, 8 Circuits, PA Polyamide Nylon 6/6 94V-2, 0.76µm Gold (Au) Selective Plating, with Drain Holes        | ELV and RoHS Compliant | Contains SVHC: No | Low-Halogen        |
| 395431006  | 5.00mm Pitch Eurostyle™ Vertical Fixed Mount PCB Terminal Block, with Screw Pressure Clamp, with Standard Imprinting, 6 Circuits   | ELV and RoHS Compliant | Not Reviewed      | Not Reviewed       |
| 395431006  | 5.00mm Pitch Eurostyle™ Vertical Fixed Mount PCB Terminal Block, with Screw Pressure Clamp, with Standard Imprinting, 6 Circuits   | ELV and RoHS Compliant | Not Reviewed      | Not Reviewed       |
| 42815-0012 | Mini-Fit Sr.™ Crimp Terminal, Female, 10 to 12 AWG Gold (Au)   | ELV and RoHS Compliant | Contains SVHC: No | Low-Halogen        |
| 42819-2212 | 10.00mm Pitch Mini-Fit Sr.™ Header, Single Row, Vertical, 2 Circuits, 1.57mm PCB Thickness, Tin (Sn) Plating   | ELV and RoHS Compliant | Contains SVHC: No | Not Low-Halogen    |
| 43025-1200 | 3.00mm Pitch Micro-Fit 3.0™ Receptacle Housing, Dual Row, 12 Circuits  | ELV and RoHS Compliant | Not Reviewed      | Not Low-Halogen    |
| 43045-0411 | 3.00mm Pitch Micro-Fit 3.0™ Header, Surface Mount, Dual Row, Right Angle, with Solder Tab, 4 Circuits, 0.76µm Gold (Au) Selective Plating, Glow Wire Compatible                                  | ELV and RoHS Compliant | Contains SVHC: No | Low-Halogen        |
| 43045-0820 | 3.00mm Pitch Micro-Fit 3.0™ Header, Surface Mount, Dual Row, Vertical, with Solder Tab, 8 Circuits, 0.76µm Gold (Au) Selective Plating, Glow Wire Compatible                                     | ELV and RoHS Compliant | Contains SVHC: No | Low-Halogen        |
| 43045-1411 | 3.00mm Pitch Micro-Fit 3.0™ Header, Surface Mount, Dual Row, Right Angle, with Solder Tab, 14 Circuits, 0.76µm Gold (Au) Selective Plating, Glow Wire Compatible                                 | ELV and RoHS Compliant | Contains SVHC: No | Low-Halogen        |
| 43650-0215 | 3.00mm Pitch Micro-Fit 3.0™ Header, Surface Mount Compatible, Single Row, Vertical, with PCB Polarizing Peg, 2 Circuits, Tin (Sn) Plating, Glow Wire Compatible                                  | ELV and RoHS Compliant | Contains SVHC: No | Low-Halogen        |
| 43650-0404 | 3.00mm Pitch Micro-Fit 3.0™ Header, Surface Mount Compatible, Single Row, Right Angle, with Press-fit Metal Retention Clip, 4 Circuits, 0.38µm Gold (Au) Selective Plating, Glow Wire Compatible | ELV and RoHS Compliant | Contains SVHC: No | Low-Halogen        |
| 47219-2001 | 1.10mm Pitch microSD Card Connector, Hinge Type, Lead-Free   | ELV and RoHS Compliant | Contains SVHC: No | Low-Halogen        |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>  | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b> | <b>Low-Halogen Status</b> |
|------------------|--|-------------------------------|-------------------|---------------------------|
| 50-36-1673       | Mini-Fit Jr.™ Receptacle Housing, 4.20mm Pitch, Dual Row, PA Polyamide Nylon 6/6, UL 94V-0, 2 Circuits, Glow Wire Compatible     | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 500075-1517      | USB On-The-Go (OTG) Mini-B Receptacle, Vertical, Through Hole Solder Tails and Shell Tabs, Lead-Free                             | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 50147-8100       | 2.50mm Pitch Mizu-P25™ Crimp Terminal, 50147, Bag  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 50148-8100       | 2.50mm Pitch Mizu-P25™ Crimp Terminal, 50148, Bag  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 50351-8100       | 2.50mm Pitch Mini-Lock™ Wire-to-Board and Wire-to-Wire Crimp Terminal, Phosphor Bronze, Bag, for 51102, 51103 and 51163 Housings | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 50372-8000       | 2.00mm Pitch Crimp Terminal 50372, Female, 22-26 AWG, Reel   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 50641-8041       | PanelMate™ Crimp Receptacle Terminal, 28-30 AWG, Reel Gold (Au)  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 50753-8041       | PanelMate™ Crimp Terminal 50753, 30-32 AWG, Reel   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 51021-0500       | 1.25mm Pitch PicoBlade™ Wire-to-Wire and Wire-to-Board Housing, Female, 5 Circuits   | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 51021-1100       | 1.25mm Pitch PicoBlade™ Wire-to-Wire and Wire-to-Board Housing, Female, 11 Circuits  | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 51103-0200       | 2.50mm Pitch Wire-to-Wire and Wire-to-Board Housing, Positive Lock, 2 Circuits   | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 51103-0500       | 2.50mm Pitch Wire-to-Wire and Wire-to-Board Housing, Positive Lock, 5 Circuits   | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 51103-0600       | 2.50mm Pitch Wire-to-Wire and Wire-to-Board Housing, Positive Lock, 6 Circuits   | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 51110-0650       | 2.00mm Pitch, Milli-Grid™ Crimp Housing, 6 Circuits, without Center Polarization Key, without Locking Ramp, Lead-Free            | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 51110-0660       | 2.00mm Pitch, Milli-Grid™ Crimp Housing, 6 Circuits, without Center Polarization Key, with Locking Ramp, Lead-Free               | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 51110-0860       | 2.00mm Pitch, Milli-Grid™ Crimp Housing, 8 Circuits, without Center Polarization Key, with Locking Ramp, Lead-Free               | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>   | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b> | <b>Low-Halogen Status</b> |
|------------------|---|-------------------------------|-------------------|---------------------------|
| 51110-1060       | 2.00mm Pitch, Milli-Grid™ Crimp Housing, 10 Circuits, without Center Polarization Key, with Locking Ramp, Lead-Free                                     | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 51110-2651       | 2.00mm Pitch, Milli-Grid™ Crimp Housing, 26 Circuits, with Center Polarization Key, with Locking Ramp, Lead-Free  | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 51191-0200       | 2.50mm Pitch Wire-to-Wire and Wire-to-Board Receptacle Housing, with Guide Rails, 2 Circuits  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 52435-2872       | FFC/FPC Connector, Right-Angle, SMT, 28 Circuits  | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 52974-0404       | 0.50mm Pitch Receptacle, Surface Mount, Dual Row, Vertical Stacking, 40 Circuits  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 52991-0208       | 0.50mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical, 3.00 and 4.00mm Stacking Heights, Lower Circuit Size Version, White, 20 Circuits | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 53748-0208       | 0.50mm Pitch SlimStack™ Plug, Surface Mount, Dual Row, Vertical, 3.00mm Stack Height, 20 Circuits, without Vacuum Pick-up Tape                          | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 53748-0608       | 0.50mm Pitch SlimStack™ Plug, Surface Mount, Dual Row, Vertical, 3.00mm Stack Height, 60 Circuits, without Vacuum Pick-up Tape                          | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 54393-3981       | 0.30mm Pitch Easy-On™ Type, Right Angle, SMT, ZIF, Bottom Contact, 39 Circuits, Lead-Free, Gold (Au) Contact Plating                                    | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 543935182        | 0.30mm Pitch Easy-On™ Type, Right Angle, SMT, ZIF, Bottom Contact, 51 Circuits, Lead-Free   | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 54596-0410       | MINI MI2 REC. ASSY (SN)   | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 54596-0810       | MINI MI2 REC. ASSY (SN)   | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 54819-0572       | USB On-The-Go (OTG) Mini-B Receptacle, Right Angle, SMT Solder Tails and Shell Tabs, with Cover Tape, Lead-Free   | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 54819-1572       | USB On-The-Go (OTG) Mini-B Receptacle, Right Angle, SMT Solder Tails and Shell Tabs, with Cover Tape, Lead-Free, LCP Housing                            | ELV and RoHS Compliant        | Not Reviewed      | Low-Halogen               |
| 55650-0488       | 0.50mm Pitch SlimStack™ Plug, Surface Mount, Dual Row, Vertical, 2.00mm Stack Height, with Solder Tab, 40 Circuits, Lead-Free                           | ELV and RoHS Compliant        | Not Reviewed      | Low-Halogen               |



**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>  | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b> | <b>Low-Halogen Status</b> |
|------------------|--|-------------------------------|-------------------|---------------------------|
| 55917-1010       | 2.00mm Pitch MicroClasp™ Wire-to-Board Header, Dual Row, Vertical, 10 Circuits, with PCB Locator | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 55917-1210       | 2.00mm Pitch MicroClasp™ Wire-to-Board Header, Dual Row, Vertical, 12 Circuits, with PCB Locator | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 55917-1610       | 2.00mm Pitch MicroClasp™ Wire-to-Board Header, Dual Row, Vertical, 16 Circuits, with PCB Locator | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 55917-1810       | 2.00mm Pitch MicroClasp™ Wire-to-Board Header, Dual Row, Vertical, 18 Circuits, with PCB Locator | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 55917-2010       | 2.00mm Pitch MicroClasp™ Wire-to-Board Header, Dual Row, Vertical, 20 Circuits, with PCB Locator | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 55917-2210       | 2.00mm Pitch MicroClasp™ Wire-to-Board Header, Dual Row, Vertical, 22 Circuits, with PCB Locator | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 55917-2410       | 2.00mm Pitch MicroClasp™ Wire-to-Board Header, Dual Row, Vertical, 24 Circuits, with PCB Locator | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 55917-2610       | 2.00mm Pitch MicroClasp™ Wire-to-Board Header, Dual Row, Vertical, 26 Circuits, with PCB Locator | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 55917-2810       | 2.00mm Pitch MicroClasp™ Wire-to-Board Header, Dual Row, Vertical, 28 Circuits, with PCB Locator | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 55917-3210       | 2.00mm Pitch MicroClasp™ Wire-to-Board Header, Dual Row, Vertical, 32 Circuits, with PCB Locator | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 55917-3610       | 2.00mm Pitch MicroClasp™ Wire-to-Board Header, Dual Row, Vertical, 36 Circuits, with PCB Locator | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 55917-3810       | 2.00mm Pitch MicroClasp™ Wire-to-Board Header, Dual Row, Vertical, 38 Circuits, with PCB Locator | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 55917-4010       | 2.00mm Pitch MicroClasp™ Wire-to-Board Header, Dual Row, Vertical, 40 Circuits, with PCB Locator | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 63811-5200       | Hand Crimp Tool for Crimp Terminals  | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 63811-8200       | Hand Crimp Tool  | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 63811-8700       | Hand Crimp Tool  | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 63812-0000       | Insertion Tool   | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 63812-0800       | Insertion Tool for Crimp Terminal  | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 63813-2700       | Extraction Tool  | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>   | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b> | <b>Low-Halogen Status</b> |
|------------------|---|-------------------------------|-------------------|---------------------------|
| 63819-0000       | Hand Crimp Tool   | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 63819-0100       | Hand Crimp Tool for Crimp Terminals   | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 63819-0300       | Hand Crimp Tool for 1.25mm Pitch Crimp Terminals, 26-32 AWG Wire  | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 63819-0500       | Hand Crimp Tool for 2.00mm Pitch Terminal, 24-30 AWG  | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 63819-0900       | Hand Crimp Tool for Male and Female Crimp Terminals, 16-24 AWG Wire   | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 63819-1000       | Hand Crimp Tool for Crimp Terminals   | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 63819-1100       | Hand Crimp Tool   | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 63819-1500       | Hand Crimp Tool for 1.00mm Wire-to-Board Crimp Terminal, 28-32 AWG Wire   | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 63819-2900       | Hand Crimp Tool for Low Force Crimp Terminals   | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 63823-9900       | Hand Crimp Tool For SATA Power Cable Crimp Receptacles  | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 64001-2800       | Hand Crimp Tool   | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 64001-7400       | PremiumGrade™ Hand Crimp Tool   | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 67581-0000       | 1.27mm Pitch Serial ATA Crimp Terminal for Power Cable Receptacle, Gold (Au) Flash Plating, with Reel Direction - Type 1, Lead free     | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 67581-0010       | 1.27mm Pitch Serial ATA Crimp Terminal for Power Cable Receptacle, Gold (Au) Flash Plating, with Reel Direction - Type 2, Lead free     | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 70928-2008       | 1.27mm Pitch LFH™ Matrix 50 Receptacle, Shielded, Right Angle, 2.34mm PC Tail Length, 4-40 Hex Screw Kit, Gold Plating, 60 Circuits     | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 70929-2009       | 1.27mm Pitch LFH™ Matrix 50 Plug Cable Kit, Subassembly, 60 Circuits, Bright Nickel (Ni) Front Shell Plating                            | ELV and RoHS Compliant        | Not Reviewed      | Low-Halogen               |
| 71430-0013       | 0.80mm Pitch Ultra+™ VHDCI Receptacle, Right Angle, 68 Circuits, PC Tail Length 2.08mm, Shield with Enhanced Ground Tabs, No Screwlocks | RoHS Compliant by Exemption   | Not Reviewed      | Low-Halogen               |
| 73251-2201       | 50 Ohms, SMA Jack, Right Angle PCB, Gold  | RoHS Compliant RF Product     | Contains SVHC: No | Low-Halogen               |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>   | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b> | <b>Low-Halogen Status</b> |
|------------------|---|-------------------------------|-------------------|---------------------------|
| 78171-0004       | 1.20mm Pitch Pico-EZmate™ Wire-to-Board Header, Vertical, Housing Height: 1.55mm, with side-Friction Locks, 4 Circuits, Lead-Free   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 78171-5006       | 1.20mm Pitch Pico-EZmate™ Wire-to-Board Header, Vertical, Housing Height: 1.65mm, with side-Friction Locks, 6 Circuits, Lead-Free   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 84729-0001       | USB Type A Panel Mount Receptacle 5/C Pigtail 0.152m Length, 28 AWG   | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 85508-5001       | Modular Jack, Vertical, Shielded, 8/8, Cat 5e, Through Hole, Gold (Au), Tin (Sn) over Nickel (Ni)                                   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 85543-7001       | Modular Jack, Right Angle, Fully Shielded, SMT, 8 Circuits, Palladium Nickel (PdNi)   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 87438-0343       | 1.50mm Pitch Pico-SPOX™ Wire-to-Board Header, Surface Mount, Right Angle, Shrouded, 3 Circuits, Embossed Tape on Reel, Lead-Free    | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
| 89400-0420       | 2.00mm Pitch Wire-to-Board Header, Vertical, 4 Circuits, with Kinked PC Tail, Lead-Free   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 90119-0122       | C-Grid III™ Crimp Terminal, 26-28 AWG, Reel, 0.76µm Selective Gold (Au)   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 90120-0762       | 2.54mm Pitch C-Grid III™ Header, Single Row, Vertical, 2 Circuits, 0.38µm Gold (Au) Selective Plating                               | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 90130-1210       | 2.54mm Pitch C-Grid III™ Header, Dual Row, Vertical, Shrouded, Fully Loaded, 10 Circuits, Black, 0.38µm Gold (Au) Selective Plating | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 90156-0142       | 2.54mm Pitch C-Grid III™ Crimp Housing Single Row, 2 Circuits   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 015-31-1062      | 4.80mm Pitch Wire-to-Wire Receptacle Housing, 6 Circuits  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 015-91-2140      | 2.54mm Pitch C-Grid® Header, Surface Mount, Dual Row, Vertical, 14 Circuits, Tin (Sn) Plating, without PCB Locator Pegs             | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 02-08-1101       | Clascon™ Crimp Terminal Socket, Tin (Sn) Plated Brass Contact, 16-24 AWG, Reel  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 02-08-1102       | Clascon™ Crimp Terminal Socket, Tin (Sn) Plated Brass Contact, 16-24 AWG, Bag   | ELV and RoHS Compliant        | Contains SVHC: No | Not Reviewed              |
| 02-08-1103       | Clascon™ Crimp Terminal Socket, Tin (Sn) Plated Brass Contact, 24-30 AWG, Reel  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>   | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b> | <b>Low-Halogen Status</b> |
|------------------|---|-------------------------------|-------------------|---------------------------|
| 02-08-1104       | Claspcon™ Crimp Terminal Socket, Tin (Sn) Plated Brass Contact, 24-30 AWG, Bag  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 02-09-1118       | 2.36mm Diameter Standard .093" Crimp Terminal, Dimpled Female, 18-22 AWG, Bag   | ELV and RoHS Compliant        | Contains SVHC: No | Not Reviewed              |
| 03-09-1022       | 2.36mm Diameter Standard .093" Pin and Socket Receptacle Housing, 2 Circuits, without Mounting Ears, with Ramps   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 03-09-1022       | 2.36mm Diameter Standard .093" Pin and Socket Receptacle Housing, 2 Circuits, without Mounting Ears, with Ramps   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 03-09-1027       | 2.36mm Diameter Standard .093" Pin and Socket Receptacle Housing, 2 Circuits, with Pre-bent Mounting Ears, with Ramps                                   | ELV and RoHS Compliant        | Contains SVHC: No | Not Reviewed              |
| 03-09-2022       | 2.36mm Diameter Standard .093" Pin and Socket Plug Housing, 2 Circuits, without Mounting Ears   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 03-09-2040       | 2.36mm Diameter Standard .093" Pin and Socket Plug Housing, 4 Circuits, Dual Row  | ELV and RoHS Compliant        | Contains SVHC: No | Not Reviewed              |
| 03-09-2151       | 2.36mm Diameter Standard .093" Pin and Socket Plug Housing, 15 Circuits, 3 Rows, without Panel Mount Ears, with Pull Tabs, without Passive Lock Windows | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 03-09-2159       | 2.36mm Diameter Standard .093" Pin and Socket Plug Housing, 15 Circuits, 3 Rows   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 03-12-1121       | 3.18mm Diameter, HCS125, Pin and Socket Receptacle Housing, 12 Circuits, 3 Row, with Panel Mount Ears   | ELV and RoHS Compliant        | Contains SVHC: No | Not Reviewed              |
| 08-55-0131       | KK® Crimp Terminal, 22-30 AWG, Bag, Selective Gold (Au), Nickel (Ni) Under Plating  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
|                  |   |                               |                   |                           |
| 106053-3000      | FC Connector, Multimode, 128µm Ferrule, 3.00mm Cable Diameter, Metal Coupling Nut, Black Boot   | RoHS Compliant by Exemption   | Not Reviewed      | Not Reviewed              |
| 106053-3500      | FC Connector, Multimode, 128µm Ferrule, .90mm Buffered Fiber, Metal Coupling Nut, Black Boot  | RoHS Compliant by Exemption   | Not Reviewed      | Not Reviewed              |
| 106053-5000      | FC Connector, Singlemode, 126µm Ferrule, 3.00mm Cable Diameter, Metal Coupling Nut, Yellow Boot   | RoHS Compliant by Exemption   | Not Reviewed      | Not Reviewed              |
| 106053-5500      | FC Connector, Singlemode, 126µm Ceramic PC Ferrule, 900mm Buffered Fiber, Metal Coupling Nut, Yellow Boot   | RoHS Compliant by Exemption   | Not Reviewed      | Not Reviewed              |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b> | <b>RoHS Compliance Status</b>     | <b>REACH SVHC</b> | <b>Low-Halogen Status</b> |
|------------------|-------------------------|-----------------------------------|-------------------|---------------------------|
| 11-02-0001       | Hand Insertion Tool     | Compliance Status<br>Not Reviewed | Not Reviewed      | Not Reviewed              |
| 11-02-0003       | Insertion Tool          | ELV and RoHS<br>Compliant         | Not Reviewed      | Not Reviewed              |
| 11-03-0043       | Extraction Tool         | Compliance Status<br>Not Reviewed | Not Reviewed      | Not Reviewed              |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>  | <b>RoHS Compliance Status</b>  | <b>REACH SVHC</b> | <b>Low-Halogen Status</b> |
|------------------|--|--------------------------------|-------------------|---------------------------|
| 11-26-0006       | Hand Crimp Tool JHTR1031C  | RoHS Compliance Not Required   | -                 | -                         |
| 11-26-0058       | Hand Crimp Tool JHTR5904   | RoHS Compliance Not Required   | -                 | -                         |
| 15-31-1061       | 4.80mm Pitch Wire-to-Wire Plug Housing, 6 Circuits   | ELV and RoHS Compliant         | Contains SVHC: No | Low-Halogen               |
| 19-09-1042       | 2.36mm Diameter, .093" Pin and Socket Receptacle Housing with Positive Latch, 4 Circuits, without Mounting Ears              | ELV and RoHS Compliant         | Contains SVHC: No | Low-Halogen               |
| 19-09-2042       | 2.36mm Diameter, .093" Pin and Socket Plug Housing with Positive Latch, 4 Circuits, without Mounting Ears                    | ELV and RoHS Compliant         | Contains SVHC: No | Low-Halogen               |
| 190020025        | Avikrimp™ Fully Insulated Quick Disconnect, Female, for 14-16 AWG Wire, Mylar Tape   | ELV and RoHS Compliant         | Contains SVHC: No | Not Reviewed              |
| 19003-0040       | InsulKrimp™ Female Quick Disconnect, for 14-16 AWG Wire  | ELV and RoHS Compliant         | Contains SVHC: No | Not Reviewed              |
| 19003-0056       | InsulKrimp™ Quick Disconnect, Female, for 14-16 (2.00-1.30mm <sup>2</sup> ), Box, Tab 4.75 x 0.81mm                          | ELV and RoHS Compliant         | Contains SVHC: No | Not Reviewed              |
| 19003-0126       | InsulKrimp™ Quick Disconnect, Female, Box, Tab 4.75 x 0.51mm   | ELV and RoHS Compliant         | Not Reviewed      | Not Low-Halogen           |
| 19019-0055       | Avikrimp™ Quick Disconnect, Female, for 12-14 (3.30-2.00mm <sup>2</sup> ) Wire, Metal Strip, Tab 4.75 x 0.51mm               | ELV and RoHS Compliant         | Contains SVHC: No | Low-Halogen               |
| 19294-0002       | Economy Cable Tie Tool   | Compliance Status Not Reviewed | Not Reviewed      | Not Reviewed              |
| 22-03-2022       | KK 100 Hdr Flat Vert Tin 2Ckt  | ELV and RoHS Compliant         | Not Reviewed      | Low-Halogen               |
| 22-03-2032       | KK 100 Hdr Flat Vert Tin 3Ckt  | ELV and RoHS Compliant         | Not Reviewed      | Low-Halogen               |
| 22-03-2042       | KK 100 Hdr Flat Vert Tin 4Ckt  | ELV and RoHS Compliant         | Not Reviewed      | Low-Halogen               |
| 35097-9812       | MP-Lock™ Quick Disconnect, Female, for 16-20 AWG (1.30-0.51mm <sup>2</sup> ), Metal Strip, Tab 2.79 x 0.51mm, Pre-Tin Plated | ELV and RoHS Compliant         | Contains SVHC: No | Low-Halogen               |
| 36664-0002       | MLX Crimp Terminal 42024, 10-12 AWG, Loose, Tin (Sn)   | ELV and RoHS Compliant         | Contains SVHC: No | Not Reviewed              |
| 38770-0102       | CB BTS STD 2 ASY   | ELV and RoHS Compliant         | Not Reviewed      | Not Low-Halogen           |
| 38770-0103       | CB BTS STD 3 ASY   | ELV and RoHS Compliant         | Not Reviewed      | Not Reviewed              |
| 38770-0105       | CB BTS STD 5 ASY   | ELV and RoHS Compliant         | -                 | -                         |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>   | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b> | <b>Low-Halogen Status</b> |
|------------------|---|-------------------------------|-------------------|---------------------------|
| 39-00-0074       | Mini-Fit® Female Crimp Terminal, Selective Gold (Au) and Selective Tin (Sn) over Nickel (Ni), 18-24 AWG, Loose  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 39-00-0307       | 2.36mm Diameter, Standard .093" Pin and Socket Crimp Terminal, Series 1381, Female, with Tin (Sn) over Copper Plated Brass Contact, 18-24 AWG, Bag, with Dimple | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 39-00-0324       | 2.36mm Diameter, Standard .093" Pin and Socket Crimp Terminal, Series 1434, Male, with Tin (Sn) over Copper Plated Brass Contact, 24-28 AWG, Bag                | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 39-00-0435       | Mini-Fit® Female Crimp Terminal, Selective Gold (Au) and Selective Tin (Sn) over Nickel (Ni), 22-28 AWG, Bag  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 39-01-3203       | Mini-Fit Jr.™ Plug Housing, 4.20mm Pitch, Dual Row without Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-2, 20 Circuits                                      | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 39543-1006       | 5.00mm Pitch Eurostyle™ Vertical Fixed Mount PCB Terminal Block, with Screw Pressure Clamp, with Standard Imprinting, 6 Circuits                                | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 39543-1006       | 5.00mm Pitch Eurostyle™ Vertical Fixed Mount PCB Terminal Block, with Screw Pressure Clamp, with Standard Imprinting, 6 Circuits                                | ELV and RoHS Compliant        | Not Reviewed      | Not Reviewed              |
| 42819-3213       | 10.00mm Pitch Mini-Fit Sr.™ Header, Single Row, Vertical, 3 Circuits, 1.57mm PCB Thickness, 0.76µm Gold (Au) Selective Plating                                  | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 42819-3223       | 10.00mm Pitch Mini-Fit Sr.™ Header, Single Row, Vertical, 3 Circuits, 2.36mm PCB Thickness, 0.76µm Gold (Au) Selective Plating                                  | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 42819-3233       | 10.00mm Pitch Mini-Fit Sr.™ Header, Single Row, Vertical, 3 Circuits, 3.18mm PCB Thickness, 0.76µm Gold (Au) Selective Plating                                  | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 42819-6213       | 10.00mm Pitch Mini-Fit Sr.™ Header, Single Row, Vertical, 6 Circuits, 1.57mm PCB Thickness, 0.76µm Gold (Au) Selective Plating                                  | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 42819-6233       | 10.00mm Pitch Mini-Fit Sr.™ Header, Single Row, Vertical, 6 Circuits, 3.18mm PCB Thickness, 0.76µm Gold (Au) Selective Plating                                  | ELV and RoHS Compliant        | Contains SVHC: No | Not Low-Halogen           |
| 43025-0408       | 3.00mm Pitch Micro-Fit 3.0™ Receptacle Housing, Dual Row, 4 Circuits, Halogen-Free, Glow Wire Compatible  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>  | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b> | <b>Low-Halogen Status</b> |
|------------------|--|-------------------------------|-------------------|---------------------------|
| 43025-0608       | 3.00mm Pitch Micro-Fit 3.0™ Receptacle Housing, Dual Row, 6 Circuits, Halogen-Free, Glow Wire Compatible   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 43025-1008       | 3.00mm Pitch Micro-Fit 3.0™ Receptacle Housing, Dual Row, 10 Circuits, Halogen-Free, Glow Wire Compatible  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 43650-0426       | 3.00mm Pitch Micro-Fit 3.0™ Header, Surface Mount Compatible, Single Row, Vertical, with Solder Tab, 4 Circuits, 0.76µm Gold (Au) Selective Plating, Glow Wire Compatible                                | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 45750-1211       | Mini-Fit® Plus Crimp Terminal, 18-20 AWG, Reel, Copper (Cu) Alloy, Gold (Au) Selective   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 45750-3212       | Mini-Fit® Plus Crimp Terminal, 16 AWG, Bag, Copper (Cu) Alloy, Gold (Au) Selective   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 46012-1241       | Mini-Fit® Plus Crimp Terminal, 18-20 AWG, Reel, Selective Gold (Au) Plating 0.76µm   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 46015-0603       | Mini-Fit® Plus Header, 4.20mm Pitch, Dual Row, Vertical, 6 Circuits, with Snap-in Plastic Peg PCB Lock, without Drain Holes, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) 1.27µm Over Nickel (Ni) Plating  | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 46015-1003       | Mini-Fit® Plus Header, 4.20mm Pitch, Dual Row, Vertical, 10 Circuits, with Snap-in Plastic Peg PCB Lock, without Drain Holes, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) 1.27µm Over Nickel (Ni) Plating | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 46018-1541       | Mini-Fit® Plus High Mating Cycle Female Crimp Terminal, 18-20 AWG, Reel, Select Gold (Au) Plating with Proprietary Molex Advanced Contact Surface Finish (CSF) in Contact Area                           | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 46018-2541       | Mini-Fit® Plus High Mating Cycle Female Crimp Terminal, 22-24 AWG, Reel, Select Gold (Au) Plating with Proprietary Molex Advanced Contact Surface Finish (CSF) in Contact Area                           | ELV and RoHS Compliant        | Not Reviewed      | Low-Halogen               |
| 46018-3541       | Mini-Fit® Plus High Mating Cycle Female Crimp Terminal, 16 AWG, Reel, Select Gold (Au) Plating with Proprietary Molex Advanced Contact Surface Finish (CSF) in Contact Area                              | ELV and RoHS Compliant        | Not Reviewed      | Low-Halogen               |
| 46235-0002       | Micro-Fit 3.0™ Reduced Mating Force, Crimp Terminal, Female, with .0.76µm Selective Gold (Au) over Nickel (Ni), 20-24 AWG, without Lubricant   | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |



**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>   | <b>RoHS Compliance Status</b>  | <b>REACH SVHC</b> | <b>Low-Halogen Status</b> |
|------------------|---|--------------------------------|-------------------|---------------------------|
| 51110-1051       | 2.00mm Pitch, Milli-Grid™ Crimp Housing, 10 Circuits, with Center Polarization Key, without Locking Ramp, Lead-Free       | ELV and RoHS Compliant         | Contains SVHC: No | Not Low-Halogen           |
| 51198-0200       | 2.50mm Pitch Wire-to-Wire Plug Housing, Positive Lock, Panel Mount, 2 Circuits  | ELV and RoHS Compliant         | Not Reviewed      | Not Low-Halogen           |
| 51198-0500       | 2.50mm Pitch Wire-to-Wire Plug Housing, Positive Lock, Panel Mount, 5 Circuits  | ELV and RoHS Compliant         | Not Reviewed      | Not Low-Halogen           |
| 51198-0600       | 2.50mm Pitch Wire-to-Wire Plug Housing, Positive Lock, Panel Mount, 6 Circuits  | ELV and RoHS Compliant         | Not Reviewed      | Not Low-Halogen           |
| 52465-1029       | 0.8 BtB Hsg Assy SMT 10Ckt  | Compliance Status Not Reviewed | Not Reviewed      | Not Reviewed              |
| 52465-1229       | 0.8 B/B Hsg Assy SMT 12Ckt  | Compliance Status Not Reviewed | Not Reviewed      | Not Reviewed              |
| 52465-1271       | 0.80mm Pitch Board-to-Board Receptacle, Surface Mount, Dual Row, 12 Circuits, Lead-Free                                   | ELV and RoHS Compliant         | Not Reviewed      | Not Low-Halogen           |
| 52465-1629       | 0.8 B/B Hsg Assy SMT 16Ckt  | Compliance Status Not Reviewed | Not Reviewed      | Not Reviewed              |
| 52465-1671       | 0.80mm Pitch Board-to-Board Receptacle, Surface Mount, Dual Row, 16 Circuits, Lead-Free                                   | ELV and RoHS Compliant         | Not Reviewed      | Not Low-Halogen           |
| 52465-1829       | 0.8 B/B Hsg Assy SMT 18Ckt  | Compliance Status Not Reviewed | Not Reviewed      | Not Reviewed              |
| 52465-2429       | 0.8 B/B Hsg Assy SMT 24Ckt  | Compliance Status Not Reviewed | Not Reviewed      | Not Reviewed              |
| 52465-2629       | 0.8 B/B Hsg Assy SMT 26Ckt  | Compliance Status Not Reviewed | Not Reviewed      | Not Reviewed              |
| 52465-3029       | 0.8 B/B Hsg Assy SMT 30Ckt  | Compliance Status Not Reviewed | Not Reviewed      | Not Reviewed              |
| 52465-3829       | 0.8 B/B Hsg Assy SMT 38Ckt  | Compliance Status Not Reviewed | Not Reviewed      | Not Reviewed              |
| 52465-4029       | 0.8 B/B Hsg Assy SMT 40Ckt  | Compliance Status Not Reviewed | Not Reviewed      | Not Reviewed              |
| 52465-4071       | 0.80mm Pitch Board-to-Board Receptacle, Surface Mount, Dual Row, 40 Circuits, Lead-Free                                   | ELV and RoHS Compliant         | Not Reviewed      | Not Low-Halogen           |
| 53048-0410       | 1.25mm Pitch PicoBlade™ Header, Right Angle, 4 Circuits   | ELV and RoHS Compliant         | Not Reviewed      | Not Low-Halogen           |
| 53307-1028       | 0.8 B/B Wafer Assy ST SMT W/O Boss 10Ckt  | Compliance Status Not Reviewed | Not Reviewed      | Not Reviewed              |
| 53307-1228       | 0.8 B/B Wafer Assy ST SMT W/O Boss 12Ckt  | Compliance Status Not Reviewed | Not Reviewed      | Not Reviewed              |
| 53307-1271       | 0.80mm Pitch Header, Surface Mount, Dual Row, Vertical Stacking, 4.50 and 5.50mm Stacking Heights, Lead-Free, 12 Circuits | ELV and RoHS Compliant         | Not Reviewed      | Not Low-Halogen           |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>   | <b>RoHS Compliance Status</b>  | <b>REACH SVHC</b> | <b>Low-Halogen Status</b> |
|------------------|---|--------------------------------|-------------------|---------------------------|
| 53307-1628       | 0.8 B/B Wafer Assy ST SMT W/O Boss 16Ckt  | Compliance Status Not Reviewed | -                 | -                         |
| 53307-1828       | 0.8 B/B Wafer Assy ST SMT W/O Boss 18Ckt  | Compliance Status Not Reviewed | Not Reviewed      | Not Reviewed              |
| 53307-1871       | 0.80mm Pitch Header, Surface Mount, Dual Row, Vertical Stacking, 4.50 and 5.50mm Stacking Heights, Lead-Free, 18 Circuits | ELV and RoHS Compliant         | Not Reviewed      | Not Low-Halogen           |
| 53307-2428       | 0.8 B/B Wafer Assy ST SMT W/O Boss 24Ckt  | Compliance Status Not Reviewed | Not Reviewed      | Not Reviewed              |
| 53307-2628       | 0.8 B/B Wafer Assy ST SMT W/O Boss 26Ckt  | Compliance Status Not Reviewed | Not Reviewed      | Not Reviewed              |
| 53307-3628       | 0.8 B/B Wafer Assy ST SMT W/O Boss 36Ckt  | Compliance Status Not Reviewed | Not Reviewed      | Not Reviewed              |
| 53748-0400       | 0.5 B/B PLUG OVER MOLD  | Compliance Status Not Reviewed | Contains SVHC: No | Not Reviewed              |
|                  |   |                                |                   |                           |
| 63817-0000       | Manual Wire Stripper  | Compliance Status Not Reviewed | -                 | -                         |
| 63817-0300       | Heavy Duty Cable Stripping Tool suitable for cable diameters up to 40.00mm  | Compliance Status Not Reviewed | -                 | -                         |
| 64016-0044       | ServiceGrade™ Hand Crimp Tool - Ratchet   | Compliance Status Not Reviewed | -                 | -                         |
| 67582-0000       | 1.27mm Pitch Crimp Housing for Serial ATA Power Cable Receptacle, 15 Circuits, Black                                      | ELV and RoHS Compliant         | Contains SVHC: No | Not Low-Halogen           |
| 73101-0120       | BNC 75 Ohm, Right Angle PCB Bulkhead Jack Receptacle with Board Locks, Low Profile  | RoHS Compliant RF Product      | Contains SVHC: No | Low-Halogen               |
| 73251-2120       | 50 Ohms, SMA Jack, Edge Mount   | RoHS Compliant RF Product      | Contains SVHC: No | Low-Halogen               |
| 73276-0022       | N JACK TO N JACK ADAPTER 50 OHMS  | RoHS Compliant RF Product      | Not Reviewed      | Not Reviewed              |
| 73391-0070       | SMA PCB Jack Receptacle, with Standoffs   | RoHS Compliant RF Product      | Contains SVHC: No | Low-Halogen               |
| 73415-0971       | MMCX 50 Ohm, Straight Plug, Crimp, RG-178 & RF-196 Cable  | RoHS Compliant RF Product      | Contains SVHC: No | Low-Halogen               |
| 73415-1251       | MMCX Plug RG-174, RG-188 and RG-316 Cable   | RoHS Compliant RF Product      | Contains SVHC: No | Low-Halogen               |
| 73415-2232       | MCX 50 Ohm, Right Angle Plug, Crimp, RD-316 Cable, Mil Gold on Center Contact   | RoHS Compliant RF Product      | -                 | -                         |
| 73415-4193       | 50 Ohms MXC Right Angle Plug, RG-174, RG-188 and RG-316 Cable   | RoHS Compliant RF Product      | -                 | -                         |
| 83000-0083       | Commercial Micro-D Socket Terminal, Loose in Bag  | ELV and RoHS Compliant         | Not Reviewed      | Not Reviewed              |

**Table A**

| <b>Molex P/N</b> | <b>Part Description</b>  | <b>RoHS Compliance Status</b> | <b>REACH SVHC</b> | <b>Low-Halogen Status</b> |
|------------------|--|-------------------------------|-------------------|---------------------------|
| 83041-0005       | Jackpost for Commercial Micro-D PCB Mount Plugs, 2-56 UNC-2B Internal Thread         | ELV and RoHS Compliant        | Contains SVHC: No | Low-Halogen               |
| 91228-3001       | 2.54mm Pitch ChipSIM Connector with Ejector, 6 Circuits, without Pegs, Yellow Button | ELV and RoHS Compliant        | Not Reviewed      | Not Low-Halogen           |
|                  |  |                               |                   |                           |
|                  |  |                               |                   |                           |
|                  |  |                               |                   |                           |