

RoHS Certificate of Compliance

August 11, 2009

Table A provides the RoHS compliance status for the identified part numbers manufactured by Molex, contained in original Molex packaging and labeled with an inventory control date on or after the date of this certificate. Molex part numbers with the RoHS compliance status "*ELV and RoHS Compliant*" do not contain the substances listed in the table below in concentrations exceeding the Maximum Control Value (MCV) ¹.

<u>Substance</u>	<u>Maximum Control Value</u>
Lead	0.1% by weight (1000 ppm) ⁽²⁾
Mercury	0.1% by weight (1000 ppm)
Cadmium	0.01% by weight (100 ppm) ⁽²⁾
Hexavalent Chromium	0.1% by weight (1000 ppm)
Polybrominated Biphenyls (PBB)	0.1% by weight (1000 ppm)
Polybrominated Diphenyl Ethers (PBDE) including deca-BDE	0.1% by weight (1000 ppm)

(2) The MCV does not apply to applications for which exemptions have been granted to the RoHS Directive

Products containing the substances listed in the table above, in concentrations below the MCV, are understood to be in compliance with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronics equipment (RoHS Directive) in accordance with the definitions set forth in the directives.

Molex's sole liability for incorrectly certifying a product as having the substances listed in the table above, in concentrations below the MCV, shall be either replacement of the Molex product or, alternatively and in the sole discretion of Molex, return of the purchase price paid for the relevant Molex product.

For additional information regarding Molex's environmental initiatives, please visit the ECO CARE section of www.molex.com



Jay Williamson
World Wide V.P. of Quality

¹ In order to validate compliance, Molex is evaluating its products to the homogeneous material level. A homogeneous material is defined as either a raw material or a material applied during the construction of the product. For example, in terminals plated with both a nickel and a tin layer, the base metal (copper alloy) and both layers are considered homogeneous materials and therefore must be considered separately. In another example, a cable is constructed of wire, insulation, jacketing and may be marked with ink. All these are considered individual homogeneous materials.

Table A

Molex P/N	Part Description	RoHS Compliance Status
15-99-7426	MOLEX P/N NOT RECOGNIZED	
15-99-3307	MOLEX P/N NOT RECOGNIZED	
15-99-3309	MOLEX P/N NOT RECOGNIZED	
15-99-7430	MOLEX P/N NOT RECOGNIZED	
15-99-3347	MOLEX P/N NOT RECOGNIZED	
15-99-3349	MOLEX P/N NOT RECOGNIZED	
15-99-7434	MOLEX P/N NOT RECOGNIZED	
15-99-3367	MOLEX P/N NOT RECOGNIZED	
15-99-3369	MOLEX P/N NOT RECOGNIZED	
15-99-7436	MOLEX P/N NOT RECOGNIZED	
15-99-3407	MOLEX P/N NOT RECOGNIZED	
15-99-3409	MOLEX P/N NOT RECOGNIZED	
15-99-7440	MOLEX P/N NOT RECOGNIZED	
15-99-3507	MOLEX P/N NOT RECOGNIZED	
15-99-3509	MOLEX P/N NOT RECOGNIZED	
15-99-7450	MOLEX P/N NOT RECOGNIZED	
15-99-3607	MOLEX P/N NOT RECOGNIZED	
15-99-3609	MOLEX P/N NOT RECOGNIZED	
15-99-7460	MOLEX P/N NOT RECOGNIZED	
15-99-3647	MOLEX P/N NOT RECOGNIZED	
15-99-3649	MOLEX P/N NOT RECOGNIZED	
15-99-7464	MOLEX P/N NOT RECOGNIZED	
22-50-3185	WO/B WR PR 18CCT GRN 7720SC18H	ELV and RoHS Compliant
22-50-3195	WO/B WR PR 19CCT GRN 7720SC19H	ELV and RoHS Compliant
22-50-3205	WO/B WR PR 20CCT GRN 7720SC20H	ELV and RoHS Compliant
22-50-3215	CONNECTOR IDT .100IN	ELV and RoHS Compliant
22-50-3225	KK100 IDT ASSEMBLY 7720SC22H	ELV and RoHS Compliant
22-50-3235	WO/B WR PR 23CCT GRN 7720SC23H	ELV and RoHS Compliant
22-50-3245	WO/B WR PR 24CCT GRN 7720SC24H	ELV and RoHS Compliant
22-50-3255	WO/B WR PR 25CCT GRN 7720SC25H	Compliance Status Not Reviewed
22-50-3265	KK100 IDT ASSEMBLY 7720SC26H	ELV and RoHS Compliant
22-50-3275	KK100 IDT ASSEMBLY 7720SC27H	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
22-50-3285	WO/B WR PR 28CCT GRN 7720SC28H	Compliance Status Not Reviewed
38-00-2108	WO/B WR PR 18CCT BRN 7720SC18J	ELV and RoHS Compliant
38-00-2109	WO/B WR PR 19CCT BRN 7720SC19J	Compliance Status Not Reviewed
38-00-2110	WO/B WR PR 20CCT BRN 7720SC20J	ELV and RoHS Compliant
38-00-2111	WO/B WR PR 21CCT BRN 7720SC21J	ELV and RoHS Compliant
38-00-2112	WO/B WR PR 22CCT BRN 7720SC22J	ELV and RoHS Compliant
38-00-2113	CONNECTOR IDT .100IN	ELV and RoHS Compliant
38-00-2114	WO/B WR PR 24CCT BRN 7720SC24J	Compliance Status Not Reviewed
38-00-2115	WO/B WR PR 25CCT GRN 7720SC25J	Compliance Status Not Reviewed
38-00-2116	CONNECTOR IDT .100IN	ELV and RoHS Compliant
38-00-2117	CONNECTOR IDT .100IN	ELV and RoHS Compliant
38-00-2118	WO/B WR PR 28CCT BRN 7720SC28J	Compliance Status Not Reviewed
14-44-2102	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 2 Circuits	ELV and RoHS Compliant
14-44-2103	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 3 Circuits	ELV and RoHS Compliant
14-44-2104	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 4 Circuits	ELV and RoHS Compliant
14-44-2105	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 5 Circuits	ELV and RoHS Compliant
14-44-2106	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 6 Circuits	ELV and RoHS Compliant
14-44-2107	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 7 Circuits	ELV and RoHS Compliant
14-44-2108	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 8 Circuits	ELV and RoHS Compliant
14-44-2109	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 9 Circuits	ELV and RoHS Compliant
14-44-2110	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 10 Circuits	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
14-44-2111	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 11 Circuits	Compliance Status Not Reviewed
14-44-2112	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 12 Circuits	ELV and RoHS Compliant
14-44-2113	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 13 Circuits	ELV and RoHS Compliant
14-44-2114	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 14 Circuits	ELV and RoHS Compliant
14-44-2115	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 15 Circuits	ELV and RoHS Compliant
14-44-2116	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 16 Circuits	ELV and RoHS Compliant
14-44-2117	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 17 Circuits	ELV and RoHS Compliant
14-44-2118	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 18 Circuits	ELV and RoHS Compliant
14-44-2119	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 19 Circuits	ELV and RoHS Compliant
14-44-2120	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 20 Circuits	ELV and RoHS Compliant
14-44-2121	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 21 Circuits	ELV and RoHS Compliant
14-44-2122	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 22 Circuits	ELV and RoHS Compliant
14-44-2123	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 23 Circuits	ELV and RoHS Compliant
14-44-2124	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 24 Circuits	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
14-44-2125	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.38µm (15µ") Gold (Au), 25 Circuits	ELV and RoHS Compliant
14-44-1602	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 2 Circuits	ELV and RoHS Compliant
14-44-1603	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 3 Circuits	ELV and RoHS Compliant
14-44-1604	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 4 Circuits	ELV and RoHS Compliant
14-44-1605	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 5 Circuits	ELV and RoHS Compliant
14-44-1606	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 6 Circuits	ELV and RoHS Compliant
14-44-1607	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 7 Circuits	ELV and RoHS Compliant
14-44-1608	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 8 Circuits	ELV and RoHS Compliant
14-44-1609	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 9 Circuits	ELV and RoHS Compliant
14-44-1610	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 10 Circuits	ELV and RoHS Compliant
14-44-1611	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 11 Circuits	ELV and RoHS Compliant
14-44-1612	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 12 Circuits	ELV and RoHS Compliant
14-44-1613	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 13 Circuits	ELV and RoHS Compliant
14-44-1614	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 14 Circuits	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
14-44-1615	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 15 Circuits	ELV and RoHS Compliant
14-44-1616	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 16 Circuits	ELV and RoHS Compliant
14-44-1617	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 17 Circuits	ELV and RoHS Compliant
14-44-1618	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 18 Circuits	ELV and RoHS Compliant
14-44-1619	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 19 Circuits	ELV and RoHS Compliant
14-44-1620	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 20 Circuits	ELV and RoHS Compliant
14-44-1621	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 21 Circuits	ELV and RoHS Compliant
14-44-1622	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 22 Circuits	ELV and RoHS Compliant
14-44-1623	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 23 Circuits	ELV and RoHS Compliant
14-44-1624	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 24 Circuits	ELV and RoHS Compliant
14-44-1625	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.38µm (15µ") Gold (Au), 25 Circuits	ELV and RoHS Compliant
14-44-1202	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 2 Circuits	ELV and RoHS Compliant
14-44-1203	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 3 Circuits	ELV and RoHS Compliant
14-44-1204	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 4 Circuits	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
14-44-1205	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 5 Circuits	ELV and RoHS Compliant
14-44-1206	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 6 Circuits	ELV and RoHS Compliant
14-44-1207	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 7 Circuits	ELV and RoHS Compliant
14-44-1208	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 8 Circuits	ELV and RoHS Compliant
14-44-1209	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 9 Circuits	ELV and RoHS Compliant
14-44-1210	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 10 Circuits	ELV and RoHS Compliant
14-44-1211	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 11 Circuits	ELV and RoHS Compliant
14-44-1212	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 12 Circuits	ELV and RoHS Compliant
14-44-1213	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 13 Circuits	ELV and RoHS Compliant
14-44-1214	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 14 Circuits	ELV and RoHS Compliant
14-44-1215	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 15 Circuits	ELV and RoHS Compliant
14-44-1216	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 16 Circuits	ELV and RoHS Compliant
14-44-1217	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 17 Circuits	ELV and RoHS Compliant
14-44-1218	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 18 Circuits	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
14-44-1219	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 19 Circuits	ELV and RoHS Compliant
14-44-1220	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 20 Circuits	ELV and RoHS Compliant
14-44-1221	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 21 Circuits	ELV and RoHS Compliant
14-44-1222	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 22 Circuits	ELV and RoHS Compliant
14-44-1223	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 23 Circuits	ELV and RoHS Compliant
14-44-1224	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 24 Circuits	ELV and RoHS Compliant
14-44-1225	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.38µm (15µ") Gold (Au), 25 Circuits	ELV and RoHS Compliant
14-44-5302	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 2 Circuits	ELV and RoHS Compliant
14-44-5303	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 3 Circuits	ELV and RoHS Compliant
14-44-5304	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 4 Circuits	ELV and RoHS Compliant
14-44-5305	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 5 Circuits	ELV and RoHS Compliant
14-44-5306	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 6 Circuits	ELV and RoHS Compliant
14-44-5307	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 7 Circuits	ELV and RoHS Compliant
14-44-5308	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 8 Circuits	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
14-44-5309	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 9 Circuits	ELV and RoHS Compliant
14-44-5310	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 10 Circuits	ELV and RoHS Compliant
14-44-5311	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 11 Circuits	ELV and RoHS Compliant
14-44-5312	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 12 Circuits	ELV and RoHS Compliant
14-44-5313	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 13 Circuits	ELV and RoHS Compliant
14-44-5314	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 14 Circuits	ELV and RoHS Compliant
14-44-5315	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 15 Circuits	ELV and RoHS Compliant
14-44-5316	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 16 Circuits	ELV and RoHS Compliant
14-44-5317	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 17 Circuits	ELV and RoHS Compliant
14-44-5318	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 18 Circuits	ELV and RoHS Compliant
14-44-5319	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 19 Circuits	ELV and RoHS Compliant
14-44-5320	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 20 Circuits	ELV and RoHS Compliant
14-44-5321	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 21 Circuits	ELV and RoHS Compliant
14-44-5322	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 22 Circuits	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
14-44-5323	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 23 Circuits	ELV and RoHS Compliant
14-44-5324	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 24 Circuits	ELV and RoHS Compliant
14-44-5325	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 22, 0.38µm (15µ") Gold (Au), 25 Circuits	ELV and RoHS Compliant
14-44-4902	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 2 Circuits	Compliance Status Not Reviewed
14-44-4903	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 3 Circuits	Compliance Status Not Reviewed
14-44-4904	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 4 Circuits	ELV and RoHS Compliant
14-44-4905	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 5 Circuits	Compliance Status Not Reviewed
14-44-4906	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 6 Circuits	Compliance Status Not Reviewed
14-44-4907	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 7 Circuits	Compliance Status Not Reviewed
14-44-4908	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 8 Circuits	Compliance Status Not Reviewed
14-44-4909	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 9 Circuits	Compliance Status Not Reviewed
14-44-4910	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 10 Circuits	ELV and RoHS Compliant
14-44-4911	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 11 Circuits	Compliance Status Not Reviewed
14-44-4912	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 12 Circuits	Compliance Status Not Reviewed

Table A

Molex P/N	Part Description	RoHS Compliance Status
14-44-4913	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 13 Circuits	ELV and RoHS Compliant
14-44-4914	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 14 Circuits	Compliance Status Not Reviewed
14-44-4915	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 15 Circuits	Compliance Status Not Reviewed
14-44-4916	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 16 Circuits	Compliance Status Not Reviewed
14-44-4917	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 17 Circuits	Compliance Status Not Reviewed
14-44-4918	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 18 Circuits	Compliance Status Not Reviewed
14-44-4919	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 19 Circuits	Compliance Status Not Reviewed
14-44-4920	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 20 Circuits	ELV and RoHS Compliant
14-44-4921	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 21 Circuits	Compliance Status Not Reviewed
14-44-4922	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 22 Circuits	Compliance Status Not Reviewed
14-44-4923	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 23 Circuits	Compliance Status Not Reviewed
14-44-4924	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 24 Circuits	Compliance Status Not Reviewed
14-44-4925	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 28, 0.76µm (30µ") Gold (Au), 25 Circuits	Compliance Status Not Reviewed
14-44-2902	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 2 Circuits	Compliance Status Not Reviewed

Table A

Molex P/N	Part Description	RoHS Compliance Status
14-44-2903	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 3 Circuits	Compliance Status Not Reviewed
14-44-2904	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 4 Circuits	ELV and RoHS Compliant
14-44-2905	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 5 Circuits	ELV and RoHS Compliant
14-44-2906	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 6 Circuits	ELV and RoHS Compliant
14-44-2907	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 7 Circuits	Compliance Status Not Reviewed
14-44-2908	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 8 Circuits	Compliance Status Not Reviewed
14-44-2909	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 9 Circuits	Compliance Status Not Reviewed
14-44-2910	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 10 Circuits	ELV and RoHS Compliant
14-44-2911	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 11 Circuits	Compliance Status Not Reviewed
14-44-2912	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 12 Circuits	Compliance Status Not Reviewed
14-44-2913	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 13 Circuits	Compliance Status Not Reviewed
14-44-2914	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 14 Circuits	Compliance Status Not Reviewed
14-44-2915	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 15 Circuits	Compliance Status Not Reviewed
14-44-2916	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 16 Circuits	Compliance Status Not Reviewed

Table A

Molex P/N	Part Description	RoHS Compliance Status
14-44-2917	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 17 Circuits	Compliance Status Not Reviewed
14-44-2918	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 18 Circuits	Compliance Status Not Reviewed
14-44-2919	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 19 Circuits	Compliance Status Not Reviewed
14-44-2920	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 20 Circuits	Compliance Status Not Reviewed
14-44-2921	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 21 Circuits	Compliance Status Not Reviewed
14-44-2922	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 22 Circuits	Compliance Status Not Reviewed
14-44-2923	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 23 Circuits	Compliance Status Not Reviewed
14-44-2924	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 24 Circuits	Compliance Status Not Reviewed
14-44-2925	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26, 0.76µm (30µ") Gold (Au), 25 Circuits	Compliance Status Not Reviewed
14-44-2502	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.76µm (30µ") Gold (Au), 2 Circuits	ELV and RoHS Compliant
14-44-2503	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.76µm (30µ") Gold (Au), 3 Circuits	ELV and RoHS Compliant
14-44-2504	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.76µm (30µ") Gold (Au), 4 Circuits	ELV and RoHS Compliant
14-44-2505	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.76µm (30µ") Gold (Au), 5 Circuits	ELV and RoHS Compliant
14-44-2506	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.76µm (30µ") Gold (Au), 6 Circuits	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
14-44-2507	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.76µm (30µ") Gold (Au), 7 Circuits	Compliance Status Not Reviewed
14-44-2508	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.76µm (30µ") Gold (Au), 8 Circuits	ELV and RoHS Compliant
14-44-2509	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.76µm (30µ") Gold (Au), 9 Circuits	Compliance Status Not Reviewed
14-44-2510	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.76µm (30µ") Gold (Au), 10 Circuits	ELV and RoHS Compliant
14-44-2511	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.76µm (30µ") Gold (Au), 11 Circuits	Compliance Status Not Reviewed
14-44-2512	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.76µm (30µ") Gold (Au), 12 Circuits	Compliance Status Not Reviewed
14-44-2513	2.54mm (.100") Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 24, 0.76µm (30µ") Gold (Au), 13 Circuits	ELV and RoHS Compliant