

RoHS Certificate of Compliance

August 12, 2009

Table A provides the RoHS compliance status for the identified part numbers manufactured by Molex, contained in original Molex packaging and labeled with an inventory control date on or after the date of this certificate. Molex part numbers with the RoHS compliance status "*ELV and RoHS Compliant*" do not contain the substances listed in the table below in concentrations exceeding the Maximum Control Value (MCV) ¹.


<u>Substance</u>	<u>Maximum Control Value</u>
Lead	0.1% by weight (1000 ppm) ⁽²⁾
Mercury	0.1% by weight (1000 ppm)
Cadmium	0.01% by weight (100 ppm) ⁽²⁾
Hexavalent Chromium	0.1% by weight (1000 ppm)
Polybrominated Biphenyls (PBB)	0.1% by weight (1000 ppm)
Polybrominated Diphenyl Ethers (PBDE) including deca-BDE	0.1% by weight (1000 ppm)

(2) The MCV does not apply to applications for which exemptions have been granted to the RoHS Directive

Products containing the substances listed in the table above, in concentrations below the MCV, are understood to be in compliance with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronics equipment (RoHS Directive) in accordance with the definitions set forth in the directives.

Molex's sole liability for incorrectly certifying a product as having the substances listed in the table above, in concentrations below the MCV, shall be either replacement of the Molex product or, alternatively and in the sole discretion of Molex, return of the purchase price paid for the relevant Molex product.

For additional information regarding Molex's environmental initiatives, please visit the ECO CARE section of www.molex.com



Jay Williamson
World Wide V.P. of Quality

¹ In order to validate compliance, Molex is evaluating its products to the homogeneous material level. A homogeneous material is defined as either a raw material or a material applied during the construction of the product. For example, in terminals plated with both a nickel and a tin layer, the base metal (copper alloy) and both layers are considered homogeneous materials and therefore must be considered separately. In another example, a cable is constructed of wire, insulation, jacketing and may be marked with ink. All these are considered individual homogeneous materials.

Table A

Molex P/N	Part Description	RoHS Compliance Status
35363-1110	2.00mm (.079") Pitch Sherlock™ Wire-to-Board Header, Right Angle, with Positive Lock, 11 Circuits	Not RoHS Compliant
35363-1210	2.00mm (.079") Pitch Sherlock™ Wire-to-Board Header, Right Angle, with Positive Lock, 12 Circuits	Not RoHS Compliant
35363-1310	2.00mm (.079") Pitch Sherlock™ Wire-to-Board Header, Right Angle, with Positive Lock, 13 Circuits	Not RoHS Compliant
35363-1410	2.00mm (.079") Pitch Sherlock™ Wire-to-Board Header, Right Angle, with Positive Lock, 14 Circuits	Not RoHS Compliant
35363-1510	2.00mm (.079") Pitch Sherlock™ Wire-to-Board Header, Right Angle, with Positive Lock, 15 Circuits	Not RoHS Compliant
35363-2010	2.00mm (.079") Pitch Sherlock™ Wire-to-Board Header, Right Angle, with Positive Lock, 20 Circuits	Not RoHS Compliant
09-48-3031	2.54mm (.100") Pitch Transistor Socket, Staggered Row, 3 Circuits	ELV and RoHS Compliant
09-48-3032	MOLEX P/N NOT RECOGNIZED	
10-07-2035	2.50mm (.098") Pitch Receptacle, Through Hole, Single Row, Bottom Entry, 3 Circuits	ELV and RoHS Compliant
10-07-2045	2.50mm (.098") Pitch Receptacle, Through Hole, Single Row, Bottom Entry, 4 Circuits	ELV and RoHS Compliant
10-07-2055	2.50mm (.098") Pitch Receptacle, Through Hole, Single Row, Bottom Entry, 5 Circuits	ELV and RoHS Compliant
10-07-2065	2.50mm (.098") Pitch Receptacle, Through Hole, Single Row, Bottom Entry, 6 Circuits	ELV and RoHS Compliant
10-07-2075	2.50mm (.098") Pitch Receptacle, Through Hole, Single Row, Bottom Entry, 7 Circuits	ELV and RoHS Compliant
10-07-2085	2.50mm (.098") Pitch Receptacle, Through Hole, Single Row, Bottom Entry, 8 Circuits	ELV and RoHS Compliant
10-07-2095	2.50mm (.098") Pitch Receptacle, Through Hole, Single Row, Bottom Entry, 9 Circuits	ELV and RoHS Compliant
10-07-2105	2.50mm (.098") Pitch Receptacle, Through Hole, Single Row, Bottom Entry, 10 Circuits	ELV and RoHS Compliant
10-07-2115	2.50mm (.098") Pitch Receptacle, Through Hole, Single Row, Bottom Entry, 11 Circuits	ELV and RoHS Compliant
10-07-2125	2.50mm (.098") Pitch Receptacle, Through Hole, Single Row, Bottom Entry, 12 Circuits	ELV and RoHS Compliant
10-07-2135	2.50mm (.098") Pitch Receptacle, Through Hole, Single Row, Bottom Entry, 13 Circuits	ELV and RoHS Compliant
10-07-2145	2.50mm (.098") Pitch Receptacle, Through Hole, Single Row, Bottom Entry, 14 Circuits	ELV and RoHS Compliant
10-07-2155	2.50mm (.098") Pitch Receptacle, Through Hole, Single Row, Bottom Entry, 15 Circuits	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
10-88-1041	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 4 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1043	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 4 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1045	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 4 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1046	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 4 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1061	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 6 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1063	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 6 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1065	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 6 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1066	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 6 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1081	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 8 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1083	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 8 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1085	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 8 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1086	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 8 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1103	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 10 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1105	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 10 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
10-88-1106	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 10 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1121	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 12 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1123	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 12 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1125	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 12 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1126	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 12 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1141	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 14 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1143	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 14 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1145	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 14 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1146	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 14 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1161	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 16 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1163	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 16 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1165	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 16 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1166	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 16 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1181	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 18 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
10-88-1183	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 18 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1185	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 18 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1186	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 18 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1201	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 20 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1203	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 20 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1205	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 20 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1206	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 20 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1221	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 22 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1223	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 22 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1225	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 22 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1226	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 22 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1241	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 24 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1243	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 24 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1245	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 24 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
10-88-1246	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 24 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1261	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 26 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1263	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 26 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1265	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 26 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1266	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 26 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1281	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 28 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1283	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 28 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1285	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 28 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1286	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 28 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1301	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 30 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1303	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 30 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1305	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 30 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1306	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 30 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1321	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 32 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1323	.100 C-GRID BREAKAWAY HEADER	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
10-88-1325	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 32 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1326	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 32 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1341	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 34 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1343	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 34 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1345	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 34 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1346	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 34 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1361	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 36 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1363	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 36 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1365	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 36 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1366	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 36 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1381	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 38 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1383	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 38 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1385	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 38 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1386	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 38 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
10-88-1401	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 40 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1403	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 40 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1405	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 40 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1406	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 40 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1421	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 42 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1423	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 42 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1425	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 42 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1426	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 42 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1441	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 44 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1443	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 44 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1445	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 44 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1446	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 44 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1461	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 46 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1463	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 46 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
10-88-1465	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 46 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1466	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 46 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1481	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 48 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1483	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 48 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1485	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 48 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1486	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 48 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1501	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 50 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1503	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 50 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1505	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 50 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1506	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 50 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1521	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 52 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1523	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 52 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1525	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 52 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1526	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 52 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
10-88-1541	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 54 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1543	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 54 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1545	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 54 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1546	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 54 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1561	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 56 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1563	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 56 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1565	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 56 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1566	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 56 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1581	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 58 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1583	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 58 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1585	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 58 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1586	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 58 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1601	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 60 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1603	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 60 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
10-88-1605	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 60 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1606	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 60 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1621	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 62 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1623	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 62 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1625	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 62 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1626	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 62 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1641	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 64 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1643	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 64 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1645	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 64 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1646	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 64 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1661	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 66 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1663	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 66 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1665	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 66 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1666	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 66 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
10-88-1681	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 68 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1683	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 68 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1685	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 68 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1686	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 68 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1701	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 70 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1703	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 70 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1705	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 70 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1706	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 70 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1721	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 72 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1723	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 72 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1725	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 72 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1726	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 72 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1741	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 74 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1743	A-8624-0357	ELV and RoHS Compliant
10-88-1745	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 74 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
10-88-1746	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 74 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1761	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 76 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1763	CGrid Bkwy Hdr DR Str Tin 76Ckt	ELV and RoHS Compliant
10-88-1765	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 76 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1766	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 76 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1781	2.54mm (.100") Pitch C-Grid® Breakaway Header, Dual Row, Vertical, 78 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1783	CGrid Bkwy Hdr DR Str Tin 78Ckt	ELV and RoHS Compliant
10-88-1785	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 78 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1786	CGrid Bkwy Hdr DR RA Tin 78ckt	ELV and RoHS Compliant
10-88-1803	CGrid Bkwy Hdr DR Str Tin 80Ckt	ELV and RoHS Compliant
10-88-1805	2.54mm (.100") Pitch C-Grid® Breakaway Header, Low Profile, Dual Row, Right Angle, 80 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-1806	CGrid Bkwy Hdr DR RA Tin 80Ckt	ELV and RoHS Compliant
10-88-3041	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 4 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3042	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 4 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3061	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 6 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3062	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 6 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3081	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 8 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
10-88-3082	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 8 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3101	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 10 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3102	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 10 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3121	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 12 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3122	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 12 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3141	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 14 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3142	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 14 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3161	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 16 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3162	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 16 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3181	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 18 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3182	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 18 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3201	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 20 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3202	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 20 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3221	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 22 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
10-88-3222	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 22 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3241	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 24 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3242	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 24 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3261	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 26 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3262	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 26 Circuits, 8.13mm (.320") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
10-88-3281	2.54mm (.100") Pitch C-Grid® Breakaway Header, High Profile, Dual Row, Right Angle, 28 Circuits, 6.10mm (.240") Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant