

## Product Compliance Statement

April 29, 2013

Molex is committed to managing the use of chemical substances in accordance with governmental regulations, industry standards, and customer-specific requirements in order to protect the environment. For each part listed, this document provides:

- **EU RoHS Compliance Status.** EU RoHS status is declared per Directive 2011/65/EU and its subsequent amendments. Homogeneous materials of parts that are compliant to this legislation have less than 0.1% by weight each of lead, mercury, hexavalent chromium, PBB, and PBDE, and 0.01% by weight of cadmium. In situations where an exemption applies, the preceding limits, corresponding to the exempted substance(s), may be higher.

Molex's sole liability for incorrectly certifying a product shall be either replacement of the Molex product or, alternatively and in the sole discretion of Molex, return of the purchase price paid for the relevant Molex product.

For additional information regarding Molex's environmental initiatives and further explanation of this information, please visit [www.molex.com](http://www.molex.com)



Joel F. Eurich  
Director, Global Environmental, Health & Safety (EH&S)

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>
73644-3213	MOLEX P/N NOT RECOGNIZED	-
73644-3214	MOLEX P/N NOT RECOGNIZED	-
73644-3215	2.00mm Pitch HDM® Board-to-Board Backplane Header, Vertical, SMC, Press-Fit, Guide Post Location A, Polarizing Key Position H, 144 Circuits	ELV and RoHS Compliant
73644-3218	2.00mm Pitch HDM® Board-to-Board Backplane Header, Vertical, SMC, Press-Fit, Guide Post Location N/A, Polarizing Key Position N/A, 144 Circuits	ELV and RoHS Compliant
95503-2661	6/6 Jack Through Hole No Key Version, Palladium Nickel (PdNi) Plated	ELV and RoHS Compliant
95503-2441	4/4 Jack Through Hole No Key Version, Palladium Nickel (PdNi) Plated	ELV and RoHS Compliant
503154-1090	1.50mm Pitch CLIK-Mate™ Wire-to-Board PCB Receptacle, Dual Row, Vertical, 10 Circuits	ELV and RoHS Compliant
015-92-2253	1.27mm Pitch LFH™ Matrix 50 Shielded Plug, 60 Circuits, Right Angle, 2.64mm Tail Length	ELV and RoHS Compliant
79109-1016	2.00mm Pitch Milli-Grid™ Receptacle, Surface Mount, Vertical, Top/Bottom Entry, without Press-fit Plastic Pegs, without Cap, Tube, 0.38µm Gold (Au) Selective, 34 Circuits, Lead-Free	ELV and RoHS Compliant
79109-8416	2.00mm Pitch Milli-Grid™ Receptacle, Surface Mount, Vertical, Top/Bottom Entry, without Press-fit Plastic Pegs, with Cap, Embossed Tape on Reel, 0.38µm Gold (Au) Selective, 34 Circuits, Lead-Free	ELV and RoHS Compliant
41791-0849	3.96mm Pitch KK® Solid Header, Vertical, Friction Lock, 2 Circuits, 0.76µm Gold (Au) Selective Plating	ELV and RoHS Compliant
41791-0850	3.96mm Pitch KK® Solid Header, Vertical, Friction Lock, 3 Circuits, 0.76µm Gold (Au) Selective Plating	ELV and RoHS Compliant
47018-4001	1.27mm Pitch Serial ATA Host Receptacle, Mating Height 5.15mm, 0.76µm Gold (Au) Plating, Light Tin Solder Area, Surface Mount, Right Angle, Top Mount Type, 22 Circuits, Lead-Free	ELV and RoHS Compliant
47018-4002	1.27mm Pitch Serial ATA Host Receptacle, Mating Height 5.15mm, 0.38µm Gold (Au) Plating, Light Tin Solder Area, Surface Mount, Right Angle, Top Mount Type, 22 Circuits, Lead-Free	ELV and RoHS Compliant

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>
52760-0379	0.635mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical Stacking, 5.00 and 10.00mm Stacking Heights, Tube Packaging, 30 Circuits, Lead-Free	ELV and RoHS Compliant
52760-0678	0.635mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical Stacking, 5.00 and 10.00mm Stacking Heights, Embossed Tape Packaging, 60 Circuits, Lead-Free	ELV and RoHS Compliant
70287-1010	2.54mm Pitch C-Grid® Header, Breakaway, Dual Row, Vertical, with Retention Pin, 24 Circuits, 6.10mm Mating Pin Length, Tin (Sn) Plating	ELV and RoHS Compliant
52271-3079	1.00mm Pitch FFC/FPC Connector, Right Angle, SMT, ZIF, Bottom Contact Style, 30 Circuits, Lead-Free, High Barrier Packaging	ELV and RoHS Compliant
87779-1001	1.27mm Pitch Serial ATA Backplane Receptacle, Through Hole, Vertical, SIL, Standard Height, 0.76µm Gold (Au) Selective, 22 Circuits, Lead-Free	ELV and RoHS Compliant
52837-1679	0.635mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical Stacking, 11.00 to 16.00mm Stacking Heights, 160 Circuits, Lead-Free	ELV and RoHS Compliant
52760-0679	0.635mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical Stacking, 5.00 and 10.00mm Stacking Heights, Tube Packaging, 60 Circuits, Lead-Free	ELV and RoHS Compliant
87833-2052	2.00mm Pitch Milli-Grid™ Header, Right Angle, Shrouded, Lead-Free, 20 Circuits, 0.05µm Gold (Au) Plating, without PCB Locator, with Locking Windows, Center Polarization Slot, Tube	ELV and RoHS Compliant
15-80-0129	2.54mm Pitch C-Grid® Header, Through Hole without Peg, Dual Row, Vertical, Shrouded, High Temperature, 12 Circuits, 0.38µm Gold, (Au) Selective Plating, Tin (Sn) PC Tail Plating, 3.81mm Inside Shroud to End Circuit Spacing	ELV and RoHS Compliant
15-80-0189	2.54mm Pitch C-Grid® Header, Through Hole without Peg, Dual Row, Vertical, Shrouded, High Temperature, 18 Circuits, 0.38µm Gold, (Au) Selective Plating, Tin (Sn) PC Tail Plating, 3.81mm Inside Shroud to End Circuit Spacing	ELV and RoHS Compliant

**Table A**

Molex P/N	Part Description	RoHS Compliance Status
15-80-0289	2.54mm Pitch C-Grid® Header, Through Hole without Peg, Dual Row, Vertical, Shrouded, High Temperature, 28 Circuits, 0.38µm Gold, (Au) Selective Plating, Tin (Sn) PC Tail Plating, 3.81mm Inside Shroud to End Circuit Spacing	ELV and RoHS Compliant
15-80-1061	2.54mm Pitch C-Grid® Header, Through Hole without Peg, Dual Row, Vertical, Shrouded, High Temperature, 6 Circuits, 0.76µm Gold, (Au) Selective Plating, Tin (Sn) PC Tail Plating, 3.81mm Inside Shroud to End Circuit Spacing	ELV and RoHS Compliant
15-80-1501	2.54mm Pitch C-Grid® Header, Through Hole without Peg, Dual Row, Vertical, Shrouded, High Temperature, 50 Circuits, 0.76µm Gold, (Au) Selective Plating, Tin (Sn) PC Tail Plating, 3.81mm Inside Shroud to End Circuit Spacing	ELV and RoHS Compliant
87898-0466	2.54mm SRSW SMT Hdr W/O Cap 2.5SnL 4Ckt	ELV and RoHS Compliant
87914-2016	2.54mm Pitch C-Grid® Header, Through Hole, Dual Row, Vertical, 20 Circuits, 2.50µm Tin (Sn) Overall Plating, Tray Packaging, Lead-Free	ELV and RoHS Compliant
87914-2004	2.54mm Pitch C-Grid® Header, Through Hole, Dual Row, Vertical, 0.38µm Gold (Au) Selective Plating, 20 Circuits, Tray Packaging, Lead-Free	ELV and RoHS Compliant
70247-1052	2.54mm Pitch C-Grid® Header, Dual Row, Low Profile, Right Angle, Shrouded, 10 Circuits, 0.76µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating	ELV and RoHS Compliant
70246-3001	2.54mm Pitch C-Grid® Header, Low Profile, Dual Row, Vertical, Shrouded, 30 Circuits, 0.38µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating	ELV and RoHS Compliant
70246-2002	2.54mm Pitch C-Grid® Header, Low Profile, Dual Row, Vertical, Shrouded, 20 Circuits, 0.76µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating	ELV and RoHS Compliant
70247-4052	2.54mm Pitch C-Grid® Header, Dual Row, Low Profile, Right Angle, Shrouded, 40 Circuits, 0.76µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating	ELV and RoHS Compliant
15-91-3086	CGrid SMT Bkwy Hdr 15"SAu 8Ckt Tubew/VC	ELV and RoHS Compliant

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>
15-91-6045	2.54mm Pitch C-Grid® Header, Surface Mount, Dual Row, Vertical, 4 Circuits, 0.38µm Gold (Au) Selective Plating, with 3.30mm PCB Locator Peg, Tape and Reel	ELV and RoHS Compliant
15-91-6060	2.54mm Pitch C-Grid® Header, Surface Mount, Dual Row, Vertical, 6 Circuits, Tin (Sn) Plating, without PCB Locator Pegs, Tape and Reel	ELV and RoHS Compliant
89485-8002	Universal Serial Bus (USB) Shielded I/O Type A Receptacle, Single Upright, Right Angle, Terminal Length 2.50mm, Without Mylar, Gold (Au) Flash, Tray Package, Lead-Free	ELV and RoHS Compliant
39-00-0317	2.36mm Diameter, Standard .093" Pin and Socket Crimp Terminal, Series 1433, Female, with Tin (Sn) over Copper Plated Brass Contact, 24-28 AWG, Reel	ELV and RoHS Compliant
39-00-0318	2.36mm Diameter, Standard .093" Pin and Socket Crimp Terminal, Series 1433, Female, with Tin (Sn) over Copper Plated Brass Contact, 24-28 AWG, Bag	ELV and RoHS Compliant
42820-3228	10.00mm Pitch Mini-Fit Sr.™ Header, Single Row, Right Angle, 3 Circuits, 2.36mm PCB Thickness, 0.76µm Gold (Au) Selective Plating	ELV and RoHS Compliant
91999-0018	5.00mm Pitch Appli-Mate RAST 5 Header, Vertical, 2 Circuits, Reference K03, Tin (Sn) Plating, Glow Wire Compatible	ELV and RoHS Compliant
91999-0058	RAST 5 VERTICAL HDR 2 CKT SN	ELV and RoHS Compliant
91999-0478	RAST 5 VERTICAL HDR 2 CKT AG	ELV and RoHS Compliant
91999-0482	5.00mm Pitch Appli-Mate RAST 5 Header, Vertical, 2 Circuits, Reference K02, Silver (Ag) Plating, Glow Wire Compatible	ELV and RoHS Compliant
91999-0495	RAST 5 VERTICAL HDR 2 CKT AG	ELV and RoHS Compliant
91999-0499	5.00mm Pitch Appli-Mate RAST 5 Header, Vertical, 2 Circuits, Reference K01, Silver (Ag) Plating, Glow Wire Compatible	ELV and RoHS Compliant
91999-0526	RAST 5 VERTICAL HDR 3 CKT SN	ELV and RoHS Compliant
91999-0531	RAST 5 VERTICAL HDR 3 CKT SN	ELV and RoHS Compliant
91999-0532	RAST 5 VERTICAL HDR 3 CKT SN	ELV and RoHS Compliant
91999-0535	RAST 5 VERTICAL HDR 3 CKT SN	ELV and RoHS Compliant

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>
91999-1238	5.00mm Pitch Appli-Mate RAST 5 Header, Vertical, 3 Circuits, Reference K145, Silver (Ag) Plating, Glow Wire Compatible	ELV and RoHS Compliant
91999-1249	5.00mm Pitch Appli-Mate RAST 5 Header, Vertical, 3 Circuits, Reference K01, Silver (Ag) Plating, Glow Wire Compatible	ELV and RoHS Compliant
91999-1283	5.00mm Pitch Appli-Mate RAST 5 Header, Vertical, 4 Circuits, No Reference, Tin (Sn) Plating, Glow Wire Compatible	ELV and RoHS Compliant
91999-1284	5.00mm Pitch Appli-Mate RAST 5 Header, Vertical, 4 Circuits, No Reference, Tin (Sn) Plating, Glow Wire Compatible	ELV and RoHS Compliant
91999-1982	5.00mm Pitch Appli-Mate RAST 5 Header, Vertical, 4 Circuits, Reference K153, Silver (Ag) Plating, Glow Wire Compatible	ELV and RoHS Compliant
39-01-3025	4.20mm Pitch Mini-Fit Jr.™ Receptacle Housing, Dual Row, PA Polyamide Nylon 6/6, UL 94V-2, 2 Circuits	ELV and RoHS Compliant
52584-0879	1.00mm Pitch Receptacle, Dual Row Surface Mount, Vertical Stacking, Mated Stacking Height 18.00mm, 80 Circuits, Lead-Free	ELV and RoHS Compliant
52584-1279	1.00mm Pitch Receptacle, Dual Row Surface Mount, Vertical Stacking, Mated Stacking Height 18.00mm, 120 Circuits, Lead-Free	ELV and RoHS Compliant
53398-0267	1.25 WtB Wafer Assy 2Ckt EmbsTp Pkg	ELV and RoHS Compliant
53398-0767	MOLEX P/N NOT RECOGNIZED	-
53647-0474	0.635mm Pitch SlimStack™ Header, Surface Mount, Dual Row, Vertical Stacking, 8.00 and 14.00mm Stacking Heights, Lead-Free, 40 Circuits, with Embossed Tape with Cover Packaging	ELV and RoHS Compliant
53647-0674	0.635mm Pitch SlimStack™ Header, Surface Mount, Dual Row, Vertical Stacking, 8.00 and 14.00mm Stacking Heights, Lead-Free, 60 Circuits, with Embossed Tape with Cover Packaging	ELV and RoHS Compliant
53647-0874	0.635mm Pitch SlimStack™ Header, Surface Mount, Dual Row, Vertical Stacking, 8.00 and 14.00mm Stacking Heights, Lead-Free, 80 Circuits, with Embossed Tape with Cover Packaging	ELV and RoHS Compliant

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>
53647-1074	0.635mm Pitch SlimStack™ Header, Surface Mount, Dual Row, Vertical Stacking, 8.00 and 14.00mm Stacking Heights, Lead-Free, 100 Circuits, with Embossed Tape with Cover Packaging	ELV and RoHS Compliant
53780-3070	MOLEX P/N NOT RECOGNIZED	-
54363-0278	0.50mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical, 2.00 and 3.00mm Stacking Heights, with Solder Tabs, 20 Circuits, Lead-Free	ELV and RoHS Compliant
54363-0778	0.50mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical, 2.00 and 3.00mm Stacking Heights, with Solder Tabs, 70 Circuits, Lead-Free	ELV and RoHS Compliant
54363-0289	0.50mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical, 2.00 and 3.00mm Stacking Heights, with Solder Tabs, 20 Circuits, Lead-Free	ELV and RoHS Compliant
54363-0389	0.50mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical, 2.00 and 3.00mm Stacking Heights, with Solder Tabs, 30 Circuits, Lead-Free	ELV and RoHS Compliant
54363-0589	0.50mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical, 2.00 and 3.00mm Stacking Heights, with Solder Tabs, 50 Circuits, Lead-Free	ELV and RoHS Compliant
54363-0689	0.50mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical, 2.00 and 3.00mm Stacking Heights, with Solder Tabs, 60 Circuits, Lead-Free	ELV and RoHS Compliant
54477-0608	0.40mm Pitch Board-to-Board SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical Stacking, 4.00mm Stacking Height, 60 Circuits	ELV and RoHS Compliant
54684-0804	0.40mm Pitch Board-to-Board SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical Stacking, 4.00mm Stacking Height, 80 Circuits	ELV and RoHS Compliant
55526-0808	0.40mm Pitch Board-to-Board SlimStack™ Plug, Surface Mount, Dual Row, Vertical Stacking, 3.50mm Stacking Height, 80 Circuits	ELV and RoHS Compliant
89400-0220	2.00mm Pitch Wire-to-Board Header, Vertical, 2 Circuits, with Kinked PC Tail	ELV and RoHS Compliant
89400-0420	2.00mm Pitch Wire-to-Board Header, Vertical, 4 Circuits, with Kinked PC Tail, Lead-Free	ELV and RoHS Compliant

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>
93070-0001	2.50mm Pitch Appli-Mate RAST 2.5 Header, Vertical, 3 Circuits, Reference K00, Glow Wire Compatible	ELV and RoHS Compliant
93070-0510	RAST 2.5 HDR ASSY 4CKT W/ LTCH	ELV and RoHS Compliant
93070-1501	2.50mm Pitch Appli-Mate RAST 2.5 Header, Vertical, 6 Circuits, Reference K00, Glow Wire Compatible	ELV and RoHS Compliant
93070-1511	2.50mm Pitch Appli-Mate RAST 2.5 Header, Vertical, 6 Circuits, Glow Wire Compatible, with Latch	ELV and RoHS Compliant
93070-0004	2.50mm Pitch Appli-Mate RAST 2.5 Header, Vertical, 3 Circuits, Glow Wire Compatible, with Latch, Positioning Keys B & C	ELV and RoHS Compliant
93070-0514	RAST 2.5 HDR ASSY 4CKT W/ LTCH	ELV and RoHS Compliant
93070-0515	RAST 2.5 HDR ASSY 4CKT W/ LTCH	ELV and RoHS Compliant
93070-0601	2.50mm Pitch Appli-Mate RAST 2.5 Header, Vertical, 4 Circuits, Glow Wire Compatible, with Latch	ELV and RoHS Compliant
93070-2502	2.50mm Pitch Appli-Mate RAST 2.5 Header, Vertical, 8 Circuits, Glow Wire Compatible, with Latch, Positioning Keys C, F, H & I	ELV and RoHS Compliant
87919-0011	1.00mm Pitch DDR-2 DIMM Socket, 25 Degree Reverse Angle, Through Hole, 240 Circuits, 1.8V Voltage Key, 3.18mm Tail Length, 0.76µm Gold (Au) Plating, Lead-Free	ELV and RoHS Compliant
87919-0111	1.00mm Pitch DDR-2 DIMM Socket, 25 Degree Reverse Angle, Through Hole, Natural Latches, 240 Circuits, 1.8V Voltage Key, 3.18mm Tail Length, 0.38µm Gold (Au) Plating, Lead-Free	ELV and RoHS Compliant
87919-1001	1.00mm Pitch DDR-2 DIMM Socket, 25 Degree Reverse Angle, Through Hole, Natural Latches, 240 Circuits, 1.8V Voltage Key, 4.00mm Tail Length, 0.76µm Gold (Au) Plating, Lead-Free	ELV and RoHS Compliant
87919-1002	1mm DDR2 DIMM 25° RvsAng 0.76AuLF 240Ckt	ELV and RoHS Compliant
44661-1002	Modular Jack, Right Angle, Low Profile, 8/8	ELV and RoHS Compliant
95622-4883	Modular Jack, Right Angle, Fully Shielded, SMT, 8/8, Gold (Au)	ELV and RoHS Compliant
95622-4881	Modular Jack, Right Angle, Fully Shielded, SMT, 8/8, Gold (Au)	ELV and RoHS Compliant



**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>
95623-2881	Modular Jack, Top Entry, Fully Shielded, Through Hole, 8/8, Gold (Au)	ELV and RoHS Compliant
95009-7667	Modular Jack, Right Angle, 6/6, Palladium Nickel (PdNi)	ELV and RoHS Compliant
47272-1004	0.50mm Pitch DisplayPort* Male Receptacle, Right Angle, SMT, 0.76µm Gold (Au) Plating, 20 Circuits, without Cover or Mylar; with Flange, Latch Holes, Peg and Solder Tab of Shell, Lead-Free	ELV and RoHS Compliant
47272-1002	0.50mm Pitch DisplayPort* Male Receptacle, Right Angle, SMT, 0.76µm Gold (Au) Plating, 20 Circuits, with Cover, Latch Holes, Peg, Solder Tab of Shell, without Flange or Mylar, Lead-Free	ELV and RoHS Compliant
47272-0003	0.50mm Pitch DisplayPort* Male Receptacle, Right Angle, SMT, 0.76µm Gold (Au) Plating, 20 Circuits, without Cover, Latch Holes, Flange or Mylar; with Peg and Solder Tab of Shell, Lead-Free	ELV and RoHS Compliant
002-08-1003	MLX Crimp Terminal 42024, 14-20 AWG, Reel Tin (Sn)	ELV and RoHS Compliant
08-50-0136	KK® Crimp Terminal 4809, 22-30 AWG, Tin, Bag	ELV and RoHS Compliant
48202-6041	D-subminiature Shielded I/O PCB Male Plug, Right Angle, Through Hole, 9 Circuits, #4-40 Flush Insert, 2 #4-40 Round Inner Thread Screws Included, 0.76µm Gold (Au) Plating, PCB Thickness 1.60mm, Lead-Free	RoHS Compliant by Exemption
48202-6066	D-Subminiature Shielded I/O PCB Male Plug, Right Angle, Through Hole, 9 Circuits, #4-40 Flush Insert, 2 #4-40 Hex Internal Thread Screws Attached, Gold (Au) Flash, PCB Thickness 1.60mm, Lead-Free	RoHS Compliant by Exemption
460101022	4.20mm Pitch Mini-Fit® Plus HCS PCB Receptacle, Dual Row, Vertical, Blind Mating, 10 Circuits, with Snap-in Plastic Peg PCB Lock, PA Polyamide Nylon 6/6, UL 94V-0, Select Gold (Au) Over Nickel (Ni) Plating	ELV and RoHS Compliant
460101021	4.20mm Pitch Mini-Fit® Plus HCS PCB Receptacle, Dual Row, Vertical, Blind Mating, 10 Circuits, with Snap-in Plastic Peg PCB Lock, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) Over Nickel (Ni) Plating	ELV and RoHS Compliant
46984-2221	10.00mm Pitch Mini-Fit Sr.™ Header, Single Row, Right Angle, 2 Circuits, 2.36mm PCB Thickness, Tin (Sn) Plating	ELV and RoHS Compliant

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>
46984-2121	10.00mm Pitch Mini-Fit Sr.™ Header, Single Row, Right Angle, 2 Circuits, 1.57mm PCB Thickness, Tin (Sn) Plating	ELV and RoHS Compliant
46984-2123	10.00mm Pitch Mini-Fit Sr.™ Header, Single Row, Right Angle, 2 Circuits, 1.57mm PCB Thickness, Tin (Sn) Plating	ELV and RoHS Compliant
46984-2223	10.00mm Pitch Mini-Fit Sr.™ Header, Single Row, Right Angle, 2 Circuits, 2.36mm PCB Thickness, Tin (Sn) Plating	ELV and RoHS Compliant
35978-0330	3.96mm Pitch Wire-to-Board Header, Vertical, Low Profile, 3 Circuits, Natural, Polyester Alloy	ELV and RoHS Compliant
35978-0530	3.96mm Pitch Wire-to-Board Header, Vertical, Low Profile, 5 Circuits, Natural, Polyester Alloy	ELV and RoHS Compliant
35978-0430	3.96mm Pitch Wire-to-Board Header, Vertical, Low Profile, 4 Circuits, Natural, Polyester Alloy	ELV and RoHS Compliant
35978-0240	3.96mm Pitch Wire-to-Board Header, Right Angle, Low Profile, 2 Circuits, Natural, Polyester Alloy	ELV and RoHS Compliant
35978-0540	3.96mm Pitch Wire-to-Board Header, Right Angle, Low Profile, 5 Circuits, Natural, Natural, Polyester Alloy	ELV and RoHS Compliant
46015-1603	4.20mm Pitch Mini-Fit® Plus HCS Header, Dual Row, Vertical, 16 Circuits, with Snap-in Plastic Peg PCB Lock, without Drain Holes, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) 1.27µm Over Nickel (Ni) Plating	ELV and RoHS Compliant
46015-0606	4.20mm Pitch Mini-Fit® Plus HCS Header, Dual Row, Vertical, 6 Circuits, without Snap-in Plastic Peg PCB Lock, without Drain Holes, PA Polyamide Nylon 6/6, UL 94V-2, Tin (Sn) 1.27µm Over Nickel (Ni) Plating	ELV and RoHS Compliant
46015-0802	4.20mm Pitch Mini-Fit® Plus HCS Header, Dual Row, Vertical, 8 Circuits, without Snap-in Plastic Peg PCB Lock, without Drain Holes, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) 1.27µm Over Nickel (Ni) Plating	ELV and RoHS Compliant
46015-0803	4.20mm Pitch Mini-Fit® Plus HCS Header, Dual Row, Vertical, 8 Circuits, with Snap-in Plastic Peg PCB Lock, without Drain Holes, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) 1.27µm Over Nickel (Ni) Plating	ELV and RoHS Compliant
46015-1009	4.20mm Pitch Mini-Fit® Plus HCS Header, Dual Row, Vertical, 10 Circuits, with Snap-in Plastic Peg PCB Lock, PA Polyamide Nylon 6/6, UL 94V-0, 0.76µm Gold (Au) Selective Plating	ELV and RoHS Compliant

**Table A**

Molex P/N	Part Description	RoHS Compliance Status
46015-1209	4.20mm Pitch Mini-Fit® Plus HCS Header, Dual Row, Vertical, 12 Circuits, with Snap-in Plastic Peg PCB Lock, PA Polyamide Nylon 6/6, UL 94V-0, 0.76µm Gold (Au) Selective Plating	ELV and RoHS Compliant
452800653	3.00mm Pitch Micro-Fit 3.0 BMI CPI™ Compliant Pin Header, Blind Mate Interface, Dual Row, Vertical, 6 Circuits, PA Polyamide Nylon 4/6, UL 94V-0, 0.76µm Gold (Au) Selective Contact Plating, Tin (Sn) Tail Plating	ELV and RoHS Compliant
452802253	3.00mm Pitch Micro-Fit 3.0 BMI CPI™ Compliant Pin Header, Blind Mate Interface, Dual Row, Vertical, 22 Circuits, PA Polyamide Nylon 4/6, UL 94V-0, 0.76µm Gold (Au) Selective Contact Plating, Tin (Sn) Tail Plating	ELV and RoHS Compliant
452800453	3.00mm Pitch Micro-Fit 3.0 BMI CPI™ Compliant Pin Header, Blind Mate Interface, Dual Row, Vertical, 4 Circuits, PA Polyamide Nylon 4/6, UL 94V-0, 0.76µm Gold (Au) Selective Contact Plating, Tin (Sn) Tail Plating	ELV and RoHS Compliant
452801053	3.00mm Pitch Micro-Fit 3.0 BMI CPI™ Compliant Pin Header, Blind Mate Interface, Dual Row, Vertical, 10 Circuits, PA Polyamide Nylon 4/6, UL 94V-0, 0.76µm Gold (Au) Selective Contact Plating, Tin (Sn) Tail Plating	ELV and RoHS Compliant
452801253	3.00mm Pitch Micro-Fit 3.0 BMI CPI™ Compliant Pin Header, Blind Mate Interface, Dual Row, Vertical, 12 Circuits, PA Polyamide Nylon 4/6, UL 94V-0, 0.76µm Gold (Au) Selective Contact Plating, Tin (Sn) Tail Plating	ELV and RoHS Compliant
452801452	3.00mm Pitch Micro-Fit 3.0 BMI CPI™ Compliant Pin Header, Blind Mate Interface, Dual Row, Vertical, 14 Circuits, PA Polyamide Nylon 4/6, UL 94V-0, 0.38µm Gold (Au) Selective Contact Plating, Tin (Sn) Tail Plating	ELV and RoHS Compliant
452802453	3.00mm Pitch Micro-Fit 3.0 BMI CPI™ Compliant Pin Header, Blind Mate Interface, Dual Row, Vertical, 24 Circuits, PA Polyamide Nylon 4/6, UL 94V-0, 0.76µm Gold (Au) Selective Contact Plating, Tin (Sn) Tail Plating	ELV and RoHS Compliant
67800-8025	1.27mm Pitch Serial ATA High Speed Header, Vertical, Through Hole, with Locking Latch, 7 Circuits, 0.38µm Gold (Au) Selective Plating, for 2.40mm PCB, Black, Footprint A, with PCB Locator Tabs, Lead-Free	ELV and RoHS Compliant

**Table A**

Molex P/N	Part Description	RoHS Compliance Status
52885-0674	0.635mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical Stacking, 5.00 to 10.00mm Stacking Heights, Embossed Tape with Cover Packaging, 60 Circuits, Lead-Free	ELV and RoHS Compliant
52885-0474	0.635mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical Stacking, 5.00 to 10.00mm Stacking Heights, Embossed Tape with Cover Packaging, 40 Circuits, Lead-Free	ELV and RoHS Compliant
52885-0974	0.635mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical Stacking, 5.00 to 10.00mm Stacking Heights, Embossed Tape with Cover Packaging, 90 Circuits, Lead-Free	ELV and RoHS Compliant
52885-1274	0.635mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical Stacking, 5.00 to 10.00mm Stacking Heights, Embossed Tape with Cover Packaging, 120 Circuits, Lead-Free	ELV and RoHS Compliant
94103-5106	2.00mm Pitch SIP Socket with Blind Circuit, SMT Version, 7 Circuit	ELV and RoHS Compliant
79109-8412	2.00mm Pitch Milli-Grid™ Receptacle, Surface Mount, Vertical, Top/Bottom Entry, without Press-fit Plastic Pegs, with Cap, Embossed Tape on Reel, 0.38µm Gold (Au) Selective, 26 Circuits, Lead-Free	ELV and RoHS Compliant
79109-1006	2.00mm Pitch Milli-Grid™ Receptacle, Surface Mount, Vertical, Top/Bottom Entry, without Press-fit Plastic Pegs, without Cap, Tube, 0.38µm Gold (Au) Selective, 14 Circuits, Lead-Free	ELV and RoHS Compliant
79109-1021	2.00mm Pitch Milli-Grid™ Receptacle, Surface Mount, Vertical, Top/Bottom Entry, without Press-fit Plastic Pegs, without Cap, Tube, 0.38µm Gold (Au) Selective, 44 Circuits, Lead-Free	ELV and RoHS Compliant
79109-8403	2.00mm Pitch Milli-Grid™ Receptacle, Surface Mount, Vertical, Top/Bottom Entry, without Press-fit Plastic Pegs, with Cap, Embossed Tape on Reel, 0.38µm Gold (Au) Selective, 8 Circuits, Lead-Free	ELV and RoHS Compliant
79109-8404	2.00mm Pitch Milli-Grid™ Receptacle, Surface Mount, Vertical, Top/Bottom Entry, without Press-fit Plastic Pegs, with Cap, Embossed Tape on Reel, 0.38µm Gold (Au) Selective, 10 Circuits, Lead-Free	ELV and RoHS Compliant

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>
79109-8606	2.00mm Pitch Milli-Grid™ Receptacle, Surface Mount, Vertical, Top/Bottom Entry, with Press-fit Plastic Pegs, with Cap, Embossed Tape on Reel, 0.38µm Gold (Au) Selective, 14 Circuits, Lead-Free	ELV and RoHS Compliant
79109-8424	2.00mm Pitch Milli-Grid™ Receptacle, Surface Mount, Vertical, Top/Bottom Entry, without Press-fit Plastic Pegs, with Cap, Embossed Tape on Reel, 0.38µm Gold (Au) Selective, 50 Circuits, Lead-Free	ELV and RoHS Compliant
79109-1012	2.00mm Pitch Milli-Grid™ Receptacle, Surface Mount, Vertical, Top/Bottom Entry, without Press-fit Plastic Pegs, without Cap, Tube, 0.38µm Gold (Au) Selective, 26 Circuits, Lead-Free	ELV and RoHS Compliant
79109-1203	2.00mm Pitch Milli-Grid™ Receptacle, Surface Mount, Vertical, Top/Bottom Entry, with Press-fit Plastic Pegs, without Cap, Tube, 0.38µm Gold (Au) Selective, 8 Circuits, Lead-Free	ELV and RoHS Compliant
79109-1205	2.00mm Pitch Milli-Grid™ Receptacle, Surface Mount, Vertical, Top/Bottom Entry, with Press-fit Plastic Pegs, without Cap, Tube, 0.38µm Gold (Au) Selective, 12 Circuits, Lead-Free	ELV and RoHS Compliant
79109-1209	2.00mm Pitch Milli-Grid™ Receptacle, Surface Mount, Vertical, Top/Bottom Entry, with Press-fit Plastic Pegs, without Cap, Tube, 0.38µm Gold (Au) Selective, 20 Circuits, Lead-Free	ELV and RoHS Compliant
09-52-3083	KK 156 PCB Assy Top 08 Ckt Tin	ELV and RoHS Compliant
09-52-3123	KK 156 PCB Assy Top 12 Ckt Tin	ELV and RoHS Compliant
47309-3351	1.10mm Pitch microSD Card Header with Detect Switch, Height 3.35mm, Lead-Free, Gold (Au) Plated 0.762µm	ELV and RoHS Compliant
47309-5251	1.10mm Pitch microSD Card Header, with Detect Switch, Height 5.25mm, Lead-Free, Gold (Au) Plated 0.762µm	ELV and RoHS Compliant
73138-5033	BNC 50 Ohm, Right Angle, PCB Bulkhead Jack Receptacle, Die Cast Zinc Alloy Body, Nickel Plated	RoHS Compliant RF Product
52207-2085	1.00mm Pitch FFC/FPC Connector, SMT, Right Angle, ZIF, Top Contact Style Receptacle, 20 Circuits, Lead-Free, High Barrier Packaging	ELV and RoHS Compliant

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>
52207-0585	1.00mm Pitch FFC/FPC Connector, SMT, Right Angle, ZIF, Top Contact Style Receptacle, 5 Circuits, Lead-Free, High Barrier Packaging	ELV and RoHS Compliant
501951-3000	0.5 FPC HsgAssyE/OStr30CktEmbsTpPkg	ELV and RoHS Compliant
501951-3010	0.50mm Pitch Easy-On™ FFC/FPC Connector, Vertical, SMT, Gold Plating, 30 Circuits	ELV and RoHS Compliant
501951-4010	0.50mm Pitch Easy-On™ FFC/FPC Connector, Vertical, SMT, Gold Plating, 40 Circuits	ELV and RoHS Compliant
501951-4510	0.50mm Pitch Easy-On™ FFC/FPC Connector, Vertical, SMT, Gold Plating, 45 Circuits	ELV and RoHS Compliant
501951-6010	0.50mm Pitch Easy-On™ FFC/FPC Connector, Vertical, SMT, Gold Plating, 60 Circuits	ELV and RoHS Compliant
501951-2410	0.50mm Pitch Easy-On™ FFC/FPC Connector, Vertical, SMT, Gold Plating, 24 Circuits	ELV and RoHS Compliant
501951-2419	0.5 FPC Hsg Assy Easy On ST 24Ckt	ELV and RoHS Compliant
501951-3210	0.50mm Pitch Easy-On™ FFC/FPC Connector, Vertical, SMT, Gold Plating, 32 Circuits	ELV and RoHS Compliant
501951-5010	0.50mm Pitch Easy-On™ FFC/FPC Connector, Vertical, SMT, Gold Plating, 50 Circuits	ELV and RoHS Compliant
501951-5019	0.5 FPC Hsg Assy Easy On ST 50Ckt	ELV and RoHS Compliant
501951-6019	0.5 FPC Hsg Assy Easy On ST 60Ckt	ELV and RoHS Compliant
51441-0872	0.50mm Pitch Easy-On™ Type FFC/FPC Connector, Right Angle, SMT, ZIF, Bottom Contact Style, 1.10mm Mated Height, 8 Circuits, Lead-Free, Gold Contact Plating	ELV and RoHS Compliant
52207-1882	1.0 FPC Hsg Assy ZIF SMT 18Ckt EmbsTpPkg	Compliance Status Not Reviewed
52808-1971	1.00mm Pitch FFC/FPC Connector, Housing Assembly, Vertical, Non-ZIF Receptacle, 19 Circuits, Lead-Free	ELV and RoHS Compliant
87977-0021	1.00mm Pitch Fully Buffered DIMM Socket, Vertical, Press-Fit, 240 Circuits, 1.8V Center Voltage Key, with Plastic Locating Peg and Press-Fit Metal Pins, with Off-White Latches, 0.38µm Gold (Au) Plating, Lead-Free	ELV and RoHS Compliant

**Table A**

Molex P/N	Part Description	RoHS Compliance Status
87977-0051	1.00mm Pitch Fully Buffered DIMM Socket, Vertical, Press-Fit, 240 Circuits, 1.8V Center Voltage Key, with Plastic Locating Peg and Press-Fit Metal Pins, with Off-White Latches, 0.76µm Gold (Au) Plating, Lead-Free	ELV and RoHS Compliant
43860-3004	Modjack RA LoPro 50AU Inv w/ shield 8/8	ELV and RoHS Compliant
75462-5001	Small Form-factor Pluggable (SFP) Stacked 2-by-1 Multi-Port Connector with Press-fit PC Tails, 40 Circuits, Lead-Free	ELV and RoHS Compliant
52018-6646	Modular Jack Hsg Assy 6Ckt	ELV and RoHS Compliant
52018-6636	Modular Jack Hsg Assy 6Ckt	ELV and RoHS Compliant
95622-3882	Modular Jack, Right Angle, Fully Shielded, Through Hole, LCP, 8/8, Gold (Au)	ELV and RoHS Compliant
95551-7667	Modular Jack, High Profile Top Entry Shunted Jack with Ribs, Tray, Palladium Nickel (PdNi)	ELV and RoHS Compliant
48258-0002	Universal Serial Bus (USB) Shielded I/O Receptacle, Type A, Right Angle, Sink Reverse Type, Mid Mount with side flange and Beveled Metal Pins, 0.76µm Gold (Au) Plating, Lead-Free	ELV and RoHS Compliant
47151-1101	0.50mm Pitch HDMI* Receptacle, Right Angle, Front Solder Tab Length 1.45mm, Shell Nickel (Ni) Plated, with Back Cover, Tape and Reel Package, Lead-Free	ELV and RoHS Compliant
54819-1572	USB On-The-Go (OTG) Mini-B Receptacle, Right Angle, SMT Solder Tails and Shell Tabs, with Cover Tape, Lead-Free, LCP Housing	ELV and RoHS Compliant
15-80-0169	2.54mm Pitch C-Grid® Header, Through Hole without Peg, Dual Row, Vertical, Shrouded, High Temperature, 16 Circuits, 0.38µm Gold, (Au) Selective Plating, Tin (Sn) PC Tail Plating, 3.81mm Inside Shroud to End Circuit Spacing	ELV and RoHS Compliant
15-80-1321	2.54mm Pitch C-Grid® Header, Through Hole without Peg, Dual Row, Vertical, Shrouded, High Temperature, 32 Circuits, 0.76µm Gold, (Au) Selective Plating, Tin (Sn) PC Tail Plating, 3.81mm Inside Shroud to End Circuit Spacing	ELV and RoHS Compliant

**Table A**

Molex P/N	Part Description	RoHS Compliance Status
15-80-1401	2.54mm Pitch C-Grid® Header, Through Hole without Peg, Dual Row, Vertical, Shrouded, High Temperature, 40 Circuits, 0.76µm Gold, (Au) Selective Plating, Tin (Sn) PC Tail Plating, 3.81mm Inside Shroud to End Circuit Spacing	ELV and RoHS Compliant
50-29-1620	KK 100 Hdr Assy Bkwy 08 Ckt 30 SGold	ELV and RoHS Compliant
50-29-1692	KK 100 Hdr Assy Bkwy 02 Ckt 15 SGold	ELV and RoHS Compliant
50-29-1621	KK 100 Hdr Assy Bkwy 08 Ckt 15 SGold	ELV and RoHS Compliant
50-29-1760	KK 100 Hdr Assy Bkwy 09 Ckt Tin	ELV and RoHS Compliant
50-29-1761	KK 100 Hdr Assy Bkwy 12 Ckt Tin	ELV and RoHS Compliant
50-29-1883	KK 100 Hdr Assy Bkwy 02 Ckt 15 SGold	ELV and RoHS Compliant
43045-5212	Microfit 3.0 Vert Thrhole Hdr DR Tin2Ckt	ELV and RoHS Compliant
43045-5414	Microfit 3.0 Vert Thrhole DR 30Au 4 Ckt	ELV and RoHS Compliant
43045-5814	Microfit 3.0 Vert Thrhole DR 30Au 8 Ckt	ELV and RoHS Compliant
43045-6014	Microfit 3.0 Vert Thrhole DR 30Au 10 Ckt	ELV and RoHS Compliant
43045-6214	Microfit 3.0 Vert Thrhole DR 30Au 12 Ckt	ELV and RoHS Compliant
43045-6814	Microfit 3.0 Vert Thrhole DR 30Au 18 Ckt	ELV and RoHS Compliant
43045-5614	Microfit 3.0 Vert Thrhole DR 30Au 6 Ckt	ELV and RoHS Compliant
43045-6412	Microfit 3.0 Vert Thrhole DR HdrTin14Ckt	ELV and RoHS Compliant
43045-6812	Microfit 3.0 Vert Thrhole DR HdrTin18Ckt	ELV and RoHS Compliant
43045-7412	Microfit 3.0 Vert Thrhole DR HdrTin24Ckt	ELV and RoHS Compliant
42819-2243	10.00mm Pitch Mini-Fit Sr.™ Header, Single Row, Vertical, 2 Circuits, 6.35mm PCB Thickness, 0.76µm Gold (Au) Selective Plating	ELV and RoHS Compliant
53553-1679	0.635mm Pitch SlimStack™ Header, Surface Mount, Dual Row, Vertical Stacking, 10.00 and 16.00mm Stacking Heights, Lead-Free, 160 Circuits, with Tube Packaging	ELV and RoHS Compliant



**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>
53748-0804	0.50mm Pitch SlimStack™ Plug, Surface Mount, Dual Row, Vertical, 3.00mm Stack Height, 80 Circuits, with Vacuum Pick-up Tape	ELV and RoHS Compliant
473065025	1.27mm Pitch Serial ATA High Speed Header, Vertical, Surface Mount, with Locking Latches, 7 Circuits, 0.38µm Gold (Au) Plating, Metal Post Length 3.45mm, with Mylar, Tape on Reel Package, Lead-Free	ELV and RoHS Compliant
78320-0001	1.27mm Pitch High Speed Micro Serial ATA Device Receptacle for 45.72mm HDD/SSD, SMT, Right Angle, Top Mount, 16 Circuits, Tray, Lead-Free	ELV and RoHS Compliant
78320-0002	1.27mm Pitch High Speed Micro Serial ATA Device Receptacle for 45.72mm HDD/SSD, SMT, Right Angle, Top Mount, with Support Rib, Tape on Reel, Lead-Free	ELV and RoHS Compliant