

Product Compliance Statement

April 29, 2013

Molex is committed to managing the use of chemical substances in accordance with governmental regulations, industry standards, and customer-specific requirements in order to protect the environment. For each part listed, this document provides:

- **EU RoHS Compliance Status.** EU RoHS status is declared per Directive 2011/65/EU and its subsequent amendments. Homogeneous materials of parts that are compliant to this legislation have less than 0.1% by weight each of lead, mercury, hexavalent chromium, PBB, and PBDE, and 0.01% by weight of cadmium. In situations where an exemption applies, the preceding limits, corresponding to the exempted substance(s), may be higher.

Molex's sole liability for incorrectly certifying a product shall be either replacement of the Molex product or, alternatively and in the sole discretion of Molex, return of the purchase price paid for the relevant Molex product.

For additional information regarding Molex's environmental initiatives and further explanation of this information, please visit www.molex.com



Joel F. Eurich
Director, Global Environmental, Health & Safety (EH&S)

Table A

Molex P/N	Part Description	RoHS Compliance Status
87537-0100	1.27mm Pitch EBBI™ 50D Receptacle, Through Hole, Right Angle, Blind Mate, with Beveled Metal Pin and Plastic Peg, 0.76µm Gold (Au) Selective Plating, 68 Circuits, 3.12mm PC Tail Length, Lead-Free	ELV and RoHS Compliant
53625-0474	0.635mm Pitch SlimStack™ Header, Surface Mount, Dual Row, Vertical Stacking, 13.00mm Stack Height, Lead-Free, 40 Circuits, with Embossed Tape with Cover Packaging	ELV and RoHS Compliant
53625-0874	0.635mm Pitch SlimStack™ Header, Surface Mount, Dual Row, Vertical Stacking, 13.00mm Stack Height, Lead-Free, 80 Circuits, with Embossed Tape with Cover Packaging	ELV and RoHS Compliant
53625-0974	0.635mm Pitch SlimStack™ Header, Surface Mount, Dual Row, Vertical Stacking, 13.00mm Stack Height, Lead-Free, 90 Circuits, with Embossed Tape with Cover Packaging	ELV and RoHS Compliant
53625-1274	0.635mm Pitch SlimStack™ Header, Surface Mount, Dual Row, Vertical Stacking, 13.00mm Stack Height, Lead-Free, 120 Circuits, with Embossed Tape with Cover Packaging	ELV and RoHS Compliant
53625-1474	0.635mm Pitch SlimStack™ Header, Surface Mount, Dual Row, Vertical Stacking, 13.00mm Stack Height, Lead-Free, 140 Circuits, with Embossed Tape with Cover Packaging	ELV and RoHS Compliant
55650-0788	0.50mm Pitch SlimStack™ Plug, Surface Mount, Dual Row, Vertical, 2.00mm Stack Height, with Solder Tab, 70 Circuits, Lead-Free	ELV and RoHS Compliant
55650-3078	0.5 BtB Plg Nail Assy 30Ckt EmbsTp Pkg	ELV and RoHS Compliant
87437-0342	1.50mm Pitch Pico-SPOX™ Wire-to-Board Header, Surface Mount, Vertical, Shrouded, 3 Circuits, Tube Packaging, Lead-Free	ELV and RoHS Compliant
87437-0643	1.50mm Pitch Pico-SPOX™ Wire-to-Board Header, Surface Mount, Vertical, Shrouded, 6 Circuits, Embossed Tape on Reel Packaging, Lead-Free	ELV and RoHS Compliant
87437-0673	1.5mm WtB VHdr SMT T&R/Cap 2.54SnLF 6Ckt	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
87437-0343	1.50mm Pitch Pico-SPOX™ Wire-to-Board Header, Surface Mount, Vertical, Shrouded, 3 Circuits, Embossed Tape on Reel Packaging, Lead-Free	ELV and RoHS Compliant
87437-0373	1.5mm WtB VHdr SMT T&R/Cap 2.54SnLF 3Ckt	ELV and RoHS Compliant
87437-0642	1.50mm Pitch Pico-SPOX™ Wire-to-Board Header, Surface Mount, Vertical, Shrouded, 6 Circuits, Tube Packaging, Lead-Free	ELV and RoHS Compliant
87437-0273	1.5mm WtB VHdr SMT T&R/Cap 2.54SnLF 2Ckt	ELV and RoHS Compliant
87438-0343	1.50mm Pitch Pico-SPOX™ Wire-to-Board Header, Surface Mount, Right Angle, Shrouded, 3 Circuits, Embossed Tape on Reel, Lead-Free	ELV and RoHS Compliant
87438-1043	1.50mm Pitch Pico-SPOX™ Wire-to-Board Header, Surface Mount, Right Angle, Shrouded, 10 Circuits, Embossed Tape on Reel, Lead-Free	ELV and RoHS Compliant
87438-0642	1.50mm Pitch Pico-SPOX™ Wire-to-Board Header, Surface Mount, Right Angle, Shrouded, 6 Circuits, Tube Packaging, Lead-Free	ELV and RoHS Compliant
87438-0643	1.50mm Pitch Pico-SPOX™ Wire-to-Board Header, Surface Mount, Right Angle, Shrouded, 6 Circuits, Embossed Tape on Reel, Lead-Free	ELV and RoHS Compliant
87832-1414	2.00mm Pitch Milli-Grid™ Header, Surface Mount, Vertical, Shrouded, Lead-Free, 14 Circuits, 0.38µm Gold (Au) Plating, with Locking Windows, Center Polarization Slot, with Cap, without PCB Locator, Embossed Tape & Reel	ELV and RoHS Compliant
87832-6522	2.00mm Pitch Milli-Grid™ Header, Surface Mount, Vertical, Shrouded, Lead-Free, 32 Circuits, 0.38µm Gold (Au) Plating, with Pick-and-Place Cap, with Side and Center Locking Windows, with Center Polarization Slot, with PCB Locator, Embossed Tape & Reel	ELV and RoHS Compliant
87831-1010	2.00mm Pitch Milli-Grid™ Header, Vertical, Through Hole, Shrouded, Lead-Free, 10 Circuits, 0.38µm Gold (Au) Plating, with Center Polarization Slot and Locking Windows, Tube	ELV and RoHS Compliant
87831-1429	2.00mm Pitch Milli-Grid™ Header, Vertical, Through Hole, Shrouded, Lead-Free, 14 Circuits, 0.76µm Gold (Au) Plating, Center Polarization Slot, with Locking Windows, PCB Locator, Tube	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
87831-2629	2.00mm Pitch Milli-Grid™ Header, Vertical, Through Hole, Shrouded, Lead-Free, 26 Circuits, 0.76µm Gold (Au) Plating, Center Polarization Slot, with Locking Windows, PCB Locator, Tube	ELV and RoHS Compliant
87831-5029	MOLEX P/N NOT RECOGNIZED	-
87759-1050	2.00mm Pitch Milli-Grid™ Header, Surface Mount, Vertical, 10 Circuits, 0.38µm Gold (Au) Selective Plating, with Press-fit Plastic Pegs, Lead-Free	ELV and RoHS Compliant
87831-0642	2.00mm Pitch Milli-Grid™ Header, Vertical, Through Hole, Shrouded, Lead-Free, 6 Circuits, 0.76µm Gold (Au) Plating, with Locking Window, without PCB Locator, without Center Polarization Slot, Tube	ELV and RoHS Compliant
87833-1233	2.00mm Pitch Milli-Grid™ Header, Right Angle, Shrouded, Lead-Free, 12 Circuits, 0.38µm Gold (Au) Plating, without PCB Locator, with Locking Window, without Center Polarization Slot, Tube	ELV and RoHS Compliant
70541-9036	2.54mm Pitch SL™ Header, Single Row, Vertical, 3.05mm Pocket, Shrouded, with Straight Plastic Peg, 2 Circuits, 0.38µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating	ELV and RoHS Compliant
70541-9038	2.54mm Pitch SL™ Header, Single Row, Vertical, 3.05mm Pocket, Shrouded, with Straight Plastic Peg, 4 Circuits, 0.38µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating	ELV and RoHS Compliant
70541-9041	2.54mm Pitch SL™ Header, Single Row, Vertical, 3.05mm Pocket, Shrouded, with Straight Plastic Peg, 7 Circuits, 0.38µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating	ELV and RoHS Compliant
70541-9043	2.54mm Pitch SL™ Header, Single Row, Vertical, 3.05mm Pocket, Shrouded, with Straight Plastic Peg, 9 Circuits, 0.38µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating	ELV and RoHS Compliant
87898-0454	2.54mm SRSW SMT/Cap O/Pg T&R .38AuLF 4Ckt	ELV and RoHS Compliant
87898-0456	2.54mm Pitch C-Grid® / SL™ Header, Surface Mount, Breakaway, Vertical, 4 Circuits, Tin (Sn) Overall Plating, Embossed Tape on Reel Packaging, with Cap, Lead-Free	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
87898-0204	2.54mm Pitch C-Grid® / SL™ Header, Surface Mount, Breakaway, Vertical, 2 Circuits, 0.38µm Gold (Au) Plating, Tray Packaging, without Cap, Lead-Free	ELV and RoHS Compliant
87898-0306	2.54mm Pitch C-Grid® / SL™ Header, Surface Mount, Breakaway, Vertical, 3 Circuits, Tin (Sn) Overall Plating, Tray Packaging, without Cap, Lead-Free	ELV and RoHS Compliant
87898-0455	2.54mm Pitch C-Grid® / SL™ Header, Surface Mount, Breakaway, Vertical, 4 Circuits, 0.38µm Gold (Au) Plating, Embossed Tape on Reel Packaging, with Cap, Lead-Free	ELV and RoHS Compliant
87898-0526	2.54mm Pitch C-Grid® / SL™ Header, Surface Mount, Breakaway, Vertical, 5 Circuits, Tin (Sn) Overall Plating, Tube Packaging, without Cap, Lead-Free	ELV and RoHS Compliant
87898-0556	2.54mm Pitch C-Grid® / SL™ Header, Surface Mount, Breakaway, Vertical, 5 Circuits, 2.50µm Tin (Sn) Plating, Tape on Reel Packaging, with Cap, Lead-Free	ELV and RoHS Compliant
87914-0001	2.54mm Pitch C-Grid® Header, Through Hole, Dual Row, Vertical, 10 Circuits, 0.38µm Gold (Au) Plating, Tray Packaging, Lead-Free	ELV and RoHS Compliant
87914-1013	2.54mm Pitch C-Grid® Header, Through Hole, Dual Row, Vertical, 10 Circuits, 0.63µm Gold (Au) Selective Plating, Tray Packaging, Lead-Free	ELV and RoHS Compliant
87914-1014	2.54mm Pitch C-Grid® Header, Through Hole, Dual Row, Vertical, 10 Circuits, 0.38µm Gold (Au) Selective Plating, Tray Packaging, Lead-Free	ELV and RoHS Compliant
87914-1616	2.54mm Pitch C-Grid® Header, Through Hole, Dual Row, Vertical, 16 Circuits, 2.50µm Tin (Sn) Overall Plating, Tray Packaging, Lead-Free	ELV and RoHS Compliant
45608-0012	2.50mm Pitch SPOX™ BMI Header Assembly, Dual Row, Right Angle, 12 Circuits	ELV and RoHS Compliant
87898-0654	2.54mm Pitch C-Grid® / SL™ Header, Surface Mount, Breakaway, Vertical, 6 Circuits, 0.38µm Gold (Au) Plating, Tape on Reel Packaging, with Cap, Lead-Free	ELV and RoHS Compliant
48074-9001	Modular Jack, Right Angle, SMT, 10/100, with Integrated Magnetics and LED, 8/8, Lead-Free	ELV and RoHS Compliant
75640-5001	Small Form-factor Pluggable (SFP) Stacked 2-by-1 Multi-Port Connector with 4 Lightpipes, with Press-fit PC Tails, 40 Circuits, Lead-Free	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
75640-0003	Small Form-factor Pluggable (SFP) Stacked 2-by-1 Multi-Port Connector with 2 Outer Lightpipes, with Press-fit PC Tails, 40 Circuits	Not RoHS Compliant
75640-5003	Small Form-factor Pluggable (SFP) Stacked 2-by-1 Multi-Port Connector with 2 Outer Lightpipes, with Press-fit PC Tails, 40 Circuits, Lead-Free	ELV and RoHS Compliant
95522-2647	Modular Jack, High Profile Top Entry with Ribs, 6/4 Circuits, Gold (Au)	ELV and RoHS Compliant
95522-2667	Modular Jack, High Profile Top Entry with Ribs, 6/6 Circuits, Gold (Au)	ELV and RoHS Compliant
95522-2887	Modular Jack, High Profile Top Entry with Ribs, 8/8 Circuits, Gold (Au)	ELV and RoHS Compliant
48146-0011	Modular Jack, Right Angle, Low Profile, Inverted, Shielded, with LEDs, 8/8, LED Color: Left (Green); Right (Amber), Lead-Free	ELV and RoHS Compliant
67068-8010	Universal Serial Bus (USB), Shielded I/O, Type B Receptacle, Right Angle with Straight Tabs, Color Black, Gold (Au) Flash Plating, Tray Pack, Lead-Free	ELV and RoHS Compliant
67068-8100	Universal Serial Bus (USB), Shielded I/O, Type B Receptacle, Right Angle with Kinked Pins, Color Black, Gold (Au) Flash Plating, Tube Pack, Lead-Free	ELV and RoHS Compliant
67068-8101	MOLEX P/N NOT RECOGNIZED	-
67068-8110	Universal Serial Bus (USB), Shielded I/O, Type B Receptacle, Right Angle with Straight Tabs, Color Black, Gold (Au) Flash Plating, Tube Pack, Lead-Free	ELV and RoHS Compliant
67068-9001	Universal Serial Bus (USB) Shielded I/O Type B Receptacle, Right Angle, with Kinked Solder Tabs, Color White, 0.76µm Gold (Au)Plating, Tray Pack, Lead-Free	ELV and RoHS Compliant
67068-9011	Universal Serial Bus (USB), Shielded I/O, Type B Receptacle, Right Angle with Straight Tabs, Color White, 0.76µm Gold (Au) Plating, Tray Pack, Lead-Free	ELV and RoHS Compliant
67068-9100	USB B CONN.WITH KINK BOARD LOCK LEAD FRE	ELV and RoHS Compliant
48258-0001	Universal Serial Bus (USB) Shielded I/O Receptacle, Type A, Right Angle, Reverse Type, Mid Mount with side flange and Beveled Metal Pins, Gold (Au) Plated, Lead-Free	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
94512-0200	Quick Disconnect, High Reliability Terminal (HRT), Female for (1.00-2.50mm ²) 10-18 AWG Wire, Accepts 6.30 x 0.81mm Tab , Unplated	ELV and RoHS Compliant
501193-2000	1.00mm Pitch Pico-Clasp™ Wire-to-Board Crimp Terminal, 28-32 AWG, Lead-free, Gold Plating	ELV and RoHS Compliant
19417-0030	MX150L™ Male Terminal for 18-22 AWG Wire, Length 26.16mm , Metal Strip Carrier, Gold Plated	ELV and RoHS Compliant
75134-1000	1.27mm Pitch DMS-59® Receptacle, Shielded, Right Angle	ELV and RoHS Compliant
75134-1001	1.27mm Pitch DMS-59® Receptacle, Shielded, Right Angle	ELV and RoHS Compliant
87439-0601	1.50mm Pitch Pico-SPOX™ Wire-to-Board Housing, 6 Circuits, Black Housing	ELV and RoHS Compliant
87439-1001	1.50mm Pitch Pico-SPOX™ Wire-to-Board Housing, 10 Circuits, Black Housing	ELV and RoHS Compliant
87439-0401	1.50mm Pitch Pico-SPOX™ Wire-to-Board Housing, 4 Circuits, Black Housing	ELV and RoHS Compliant
501646-2000	2.00mm Pitch iGrid™ Wire-to-Board Housing, Dual Row, Positive Lock, 20 Circuits	ELV and RoHS Compliant
501646-3800	2.00mm Pitch iGrid™ Wire-to-Board Housing, Dual Row, Positive Lock, 38 Circuits	ELV and RoHS Compliant
501646-1000	2.00mm Pitch iGrid™ Wire-to-Board Housing, Dual Row, Positive Lock, 10 Circuits	ELV and RoHS Compliant
501646-1600	2.00mm Pitch iGrid™ Wire-to-Board Housing, Dual Row, Positive Lock, 16 Circuits	ELV and RoHS Compliant
36633-0008	Mini Fit Jr, Vert Header, T&R, 2ckt	ELV and RoHS Compliant
36633-0009	Mini Fit Jr, Vert Header, T&R, 4ckt	ELV and RoHS Compliant
36633-0010	Mini Fit Jr, Vert Header, T&R, 6ckt	ELV and RoHS Compliant
44914-5603	3.00mm Pitch Micro-Fit 3.0 CPI™ Header, Dual Row, Vertical, Compliant Pin Interface, 6 Circuits, LCP, Glass-Filled, UL 94V-0, 0.76µm Gold (Au) Selective Contact Plating, Tin (Sn) Plated Tails, Glow Wire Compatible	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
44914-6603	3.00mm Pitch Micro-Fit 3.0 CPI™ Header, Dual Row, Vertical, Compliant Pin Interface, 16 Circuits, LCP, Glass-Filled, UL 94V-0, 0.76µm Gold (Au) Selective Contact Plating, Tin (Sn) Plated Tails, Glow Wire Compatible	ELV and RoHS Compliant
44914-7002	3.00mm Pitch Micro-Fit 3.0 CPI™ Header, Dual Row, Vertical, Compliant Pin Interface, 20 Circuits, LCP, Glass-Filled, UL 94V-0, 0.38µm Gold (Au) Selective Contact Plating, Tin (Sn) Plated Tails, Glow Wire Compatible	ELV and RoHS Compliant
44914-5202	3.00mm Pitch Micro-Fit 3.0 CPI™ Header, Dual Row, Vertical, Compliant Pin Interface, 2 Circuits, LCP, Glass-Filled, UL 94V-0, 0.38µm Gold (Au) Selective Contact Plating, Tin (Sn) Plated Tails, Glow Wire Compatible	ELV and RoHS Compliant
44914-5203	3.00mm Pitch Micro-Fit 3.0 CPI™ Header, Dual Row, Vertical, Compliant Pin Interface, 2 Circuits, LCP, Glass-Filled, UL 94V-0, 0.76µm Gold (Au) Selective Contact Plating, Tin (Sn) Plated Tails, Glow Wire Compatible	ELV and RoHS Compliant
44914-5402	3.00mm Pitch Micro-Fit 3.0 CPI™ Header, Dual Row, Vertical, Compliant Pin Interface, 4 Circuits, LCP, Glass-Filled, UL 94V-0, 0.38µm Gold (Au) Selective Contact Plating, Tin (Sn) Plated Tails, Glow Wire Compatible	ELV and RoHS Compliant
44914-6202	3.00mm Pitch Micro-Fit 3.0 CPI™ Header, Dual Row, Vertical, Compliant Pin Interface, 12 Circuits, LCP, Glass-Filled, UL 94V-0, 0.38µm Gold (Au) Selective Contact Plating, Tin (Sn) Plated Tails, Glow Wire Compatible	ELV and RoHS Compliant
44914-6203	3.00mm Pitch Micro-Fit 3.0 CPI™ Header, Dual Row, Vertical, Compliant Pin Interface, 12 Circuits, LCP, Glass-Filled, UL 94V-0, 0.76µm Gold (Au) Selective Contact Plating, Tin (Sn) Plated Tails, Glow Wire Compatible	ELV and RoHS Compliant
44914-6602	3.00mm Pitch Micro-Fit 3.0 CPI™ Header, Dual Row, Vertical, Compliant Pin Interface, 16 Circuits, LCP, Glass-Filled, UL 94V-0, 0.38µm Gold (Au) Selective Contact Plating, Tin (Sn) Plated Tails, Glow Wire Compatible	ELV and RoHS Compliant
45984-4182	1.27mm, 12.00mm Pitch, EXTreme LPHPower™ Receptacle Header, Right Angle, 4 Power Contacts, 40 Signal Contacts, Select Gold (Au) Plating, for 2.36mm Thick PC Board	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
45984-4141	1.27mm, 12.00mm Pitch, EXTreme LPHPower™ Receptacle Header, Right Angle, 4 Power Contacts, 24 Signal Contacts, Select Gold (Au) Plating, for 3.18mm Thick PC Board	ELV and RoHS Compliant
45984-4343	1.27mm, 12.00mm Pitch, EXTreme LPHPower™ Receptacle Header, Right Angle, 4 Power Contacts, 24 Signal Contacts, Select Gold (Au) Plating, for 1.57mm Thick PC Board, with Press-fit Plastic Pegs	ELV and RoHS Compliant
45984-4422	1.27mm, 12.00mm Pitch, EXTreme LPHPower™ Receptacle Header, Right Angle, 4 Power Contacts, 16 Signal Contacts, Select Gold (Au) Plating, for 2.36mm Thick PC Board, with Guide Posts, with Press-fit Plastic Pegs	ELV and RoHS Compliant
78399-1022	Impact™ 3 Pair, Vertical Power Header, 2.00mm Pitch, Blade A1 & A2, B1 & B2 4.0mm, Press-Fit, LCP, Glass Filled UL94-V0, Black, Tray Packaging, Lead-Free	ELV and RoHS Compliant
55091-1075	0.635mm Pitch SlimStack™ Header, Surface Mount, Dual Row, Vertical Stacking, 6.00 and 12.00mm Stacking Heights, Black, Lead-Free, 100 Circuits, Robotic Placement Metal Cap, with Tube Packaging	ELV and RoHS Compliant
71439-0264	1.00mm Pitch Mezzanine IEEE 1386 Receptacle, Surface Mount, Dual Row, Vertical Stacking, Embossed Tape on Reel, 1.27µm Gold (Au), 64 Circuits Pick and Place Cap	ELV and RoHS Compliant
55450-1069	1.25mm Pitch Mi II™ System Wire-to-Board Header, SMT, Single Row, Vertical, without Plastic Peg, Lead-Free, 10 Circuits	ELV and RoHS Compliant
55454-1470	1.25mm Pitch Mi II™ System Wire-to-Board Header, Single Row, Right Angle, Lead-Free, 14 Circuits	ELV and RoHS Compliant
67800-8205	1.27mm Pitch Serial ATA High Speed Header, Vertical, Through Hole, with Locking Latch, 7 Circuits, 0.38µm Gold (Au) Plating, for 1.60mm PCB, High Temperature, Black, Footprint A, with PCB Locator Tabs, Lead-Free	ELV and RoHS Compliant
35362-0550	2.00mm Pitch Sherlock™ Wire-to-Board Header, Vertical, with Positive Lock, 5 Circuits, with Kinked PC Tails, Natural	ELV and RoHS Compliant
35362-0850	2.00mm Pitch Sherlock™ Wire-to-Board Header, Vertical, with Positive Lock, 8 Circuits, with Kinked PC Tails, Natural	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
74993-4009	2.00mm Pitch HDM® Board-to-Board Stacking Header, High Rise Vertical, SMC, Double End Wall Option, Solder Tail, 72 Circuits, Lead-Free	ELV and RoHS Compliant
89400-0810	2.00mm Pitch Wire-to-Board Header, Vertical, 8 Circuits, without Kinked PC Tail	ELV and RoHS Compliant
35363-0250	2.00mm Pitch Sherlock™ Wire-to-Board Header, Right Angle, with Positive Lock, 2 Circuits, Lead-Free, White, Glass-field	ELV and RoHS Compliant
71349-5036	2.54mm Pitch C-Grid® Header, Surface Mount, Dual Row, Vertical, Shrouded, 8 Circuits, 0.76µm Gold (Au) Selective Plating, without Press-fit Plastic Pegs	ELV and RoHS Compliant
74162-0220	2.54mm Pitch C-Grid® Receptacle, Right Angle, Through Hole, Dual Row, Shrouded, Version A, High-Temperature, 20 Circuits, 0.40µm Gold (Au)	ELV and RoHS Compliant
74162-0416	2.54mm Pitch C-Grid® Receptacle, Right Angle, Through Hole, Dual Row, Shrouded, Version A, High-Temperature, 16 Circuits, 0.80µm Gold (Au)	ELV and RoHS Compliant
74162-0014	2.54mm Pitch C-Grid® Receptacle, Right Angle, Through Hole, Dual Row, Shrouded, Version A, High-Temperature, 14 Circuits, Tin (Sn)	ELV and RoHS Compliant
74162-0424	2.54mm Pitch C-Grid® Receptacle, Right Angle, Through Hole, Dual Row, Shrouded, Version A, High-Temperature, 24 Circuits, 0.80µm Gold (Au)	ELV and RoHS Compliant
87898-1366	2.54mm Pitch C-Grid® / SL™ Header, Surface Mount, Breakaway, Vertical, 13 Circuits, 2.50µm Tin (Sn) Overall Plating, Tube Packaging, without Cap, Lead-Free	ELV and RoHS Compliant
015-91-3146	CGrid SMT Bkwy Hdr 15"SAu 14Ckt Tubew/VC	ELV and RoHS Compliant
015-91-1048	CGrid SMT Hdr w/S.Peg 30"SAu 4Ckt Tube	ELV and RoHS Compliant
015-91-6047	CGrid SMT Hdr w/S.Peg 30"SAu 4Ckt T&R	ELV and RoHS Compliant
015-91-0200	2.54mm Pitch C-Grid® Header, Surface Mount, Dual Row, Vertical, 20 Circuits, 0.38µm Gold (Au) Selective Plating	ELV and RoHS Compliant
70541-9039	2.54mm Pitch SL™ Header, Single Row, Vertical, 3.05mm Pocket, Shrouded, with Straight Plastic Peg, 5 Circuits, 0.38µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
70541-9040	2.54mm Pitch SL™ Header, Single Row, Vertical, 3.05mm Pocket, Shrouded, with Straight Plastic Peg, 6 Circuits, 0.38µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating	ELV and RoHS Compliant
70541-9042	2.54mm Pitch SL™ Header, Single Row, Vertical, 3.05mm Pocket, Shrouded, with Straight Plastic Peg, 8 Circuits, 0.38µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating	ELV and RoHS Compliant
91716-1022	5CCT APPLI-M FEM CONN WO RIB	ELV and RoHS Compliant
91716-1023	2.5 APPLI-M 5CKT OEW V2,3,4	ELV and RoHS Compliant
91716-1553	2.5 APPLI-M 6CKT OEW V2,5 BLACK	ELV and RoHS Compliant
91716-1554	2.5 APPLI-M 6CKT OEW V2,4 RED	ELV and RoHS Compliant
91716-1555	2.5 APPLI-M 6CKT OEW	ELV and RoHS Compliant
91716-2522	8CCT RAST 2.5 APPLI-M OEW	ELV and RoHS Compliant
70280-0365	CGrid VT Bkwy Hdr Tin 12Ckt (435/145)	ELV and RoHS Compliant
70280-0367	CGrid VT Bkwy Hdr Tin 16Ckt (435/145)	ELV and RoHS Compliant
70280-0371	CGrid VT Bkwy Hdr Tin 24Ckt (435/145)	ELV and RoHS Compliant
70280-0368	CGrid VT Bkwy Hdr Tin 18Ckt (435/145)	ELV and RoHS Compliant
70227-8243	CGrid Shrd DR VHdr RPg 15"SAu 24Ckt	ELV and RoHS Compliant
15-80-1481	2.54mm Pitch C-Grid® Header, Through Hole without Peg, Dual Row, Vertical, Shrouded, High Temperature, 48 Circuits, 0.76µm Gold, (Au) Selective Plating, Tin (Sn) PC Tail Plating, 3.81mm Inside Shroud to End Circuit Spacing	ELV and RoHS Compliant
22-23-5024	2.54mm Pitch KK® Solid Header, Vertical, 2 Circuits, without Kinked PC Tails	ELV and RoHS Compliant
42376-0426	KK 100 Hdr Assy RA Bkwy 06 Ckt Tin	ELV and RoHS Compliant
44499-0078	Mini Fit BMI Rt An Hdr 18Ckt MF/BL	ELV and RoHS Compliant
44499-0100	MiniFit BMI RA Hdr Assy Sel MFBL 24Ckt	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
53266-0829	7.0 WtB Wafer Assy RA 8Ckt	ELV and RoHS Compliant
53266-0729	7.0 WtB Wafer Assy RA 7Ckt	ELV and RoHS Compliant
73251-2200	50 Ohms, SMA Jack, Right Angle PCB, Nickel	RoHS Compliant RF Product
73171-0560	75 Ohm BNC Right Angle PCB Receptacle	RoHS Compliant RF Product
73171-0700	BNC 75 Ohm, Right Angle, Low Profile, PCB Jack Receptacle	RoHS Compliant RF Product
73171-0950	BNC 75 Ohm, Vertical PCB, Compliant Pin, Bulkhead Jack Receptacle, Brass Body, Nickel Plated	RoHS Compliant RF Product
73171-3357	BNC JACK R/A PCB 75 OHMS BULKHEAD	RoHS Compliant RF Product
73171-3350	3 Ghz BNC Right Angle Jack with Low Profile Jam Nut, 75 Ohms	RoHS Compliant RF Product
73251-1150	SMA Edge Mount Jack Receptacle	RoHS Compliant RF Product
73251-1851	Precision Test Connector, Optimized SMA Jack, Two Hole Flange with 2 Screws 4.76mm, 0-80 Threads, 50 Ohms	RoHS Compliant RF Product
73251-1853	Precision Test Connector, Optimized SMA Jack, Two Hole Flange with 2 Screws 6.35mm, 0-80 Threads, 50 Ohms	RoHS Compliant RF Product
73254-0460	QMA Jack, Bulkhead Edge Mount, 50 Ohms EWR-4591	RoHS Compliant RF Product
73415-2121	MMCX Vertical Plug, PCB	RoHS Compliant RF Product
73415-1691	MCX 50 Ohm, Vertical Surface Mount Jack Receptacle, Body Gold Plated	RoHS Compliant RF Product
78119-1368	0.50mm Pitch FFC/FPC Connector, SMT, Non ZIF, Vertical, Gold Plating, 36 Circuits, Lead-Free	ELV and RoHS Compliant
78119-1168	0.50mm Pitch FFC/FPC Connector, SMT, Non ZIF, Vertical, Gold Plating, 16 Circuits, Lead-Free	ELV and RoHS Compliant
501864-3091	0.50mm Pitch FFC-to-Board Connector, Receptacle Housing Assembly, Right Angle, SMT, with Grounding terminals, 30 Circuits	ELV and RoHS Compliant
78065-8001	1.00mm Pitch DDR2 DIMM Socket, Very Low Profile, Vertical, Press-fit, 1.8V Center Keys, 3.30mm Tail Length, Black Latches, 240 Circuits, 0.76µm Gold (Au) Plating, Lead-Free	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
78079-0001	1.00mm Pitch DDR3 DIMM Socket, Vertical, Through Hole, with Beveled Metal Pins, Black Housing and Latches, 0.38µm Gold (Au) Plating, 2.67mm Solder tail, 240 Circuits, Lead-Free	ELV and RoHS Compliant
78079-0052	1.00mm Pitch DDR3 DIMM Socket, Vertical, Through Hole, with Beveled Metal Pins, Black Housing, Off-White Latches, 0.38µm Gold (Au) Plating, 3.18mm Solder tail, 240 Circuits, Lead-Free	ELV and RoHS Compliant
78079-0062	1.00mm Pitch DDR3 DIMM Socket, Vertical, Through Hole, with Beveled Metal Pins, Black Housing, Off-White Latches, 0.76µm Gold (Au) Plating, 3.18mm Solder tail, 240 Circuits, Lead-Free	ELV and RoHS Compliant
78079-0113	1.00mm Pitch DDR3 DIMM Socket, Vertical, Through Hole, with Beveled Metal Pins, Off-White Housing and Latches, 0.76µm Gold (Au) Plating, 3.00mm Solder tail, 240 Circuits, Lead-Free	ELV and RoHS Compliant
78315-0001	1.00mm Pitch Aerodynamic DDR3 DIMM Socket, Very Low Profile, Vertical, Press-Fit, with Pegs, Black Housing and Latches, 0.76µm Gold (Au) Plating, 1.85mm Compliant Pin Length, 2.40mm PCB Thickness, 240 Circuits, Lead-Free	ELV and RoHS Compliant
78315-0051	1.00mm Pitch Aerodynamic DDR3 DIMM Socket, Very Low Profile, Vertical, Press-Fit, with Pegs, Blue Housing and Latches, 0.76µm Gold (Au) Plating, 2.85mm Compliant Pin Length, 2.60mm PCB Thickness, 240 Circuits, Lead-Free	ELV and RoHS Compliant
78315-0011	1.00mm Pitch Aerodynamic DDR3 DIMM Socket, Very Low Profile, Vertical, Press-Fit, with Pegs, Black Housing and Latches, 0.76µm Gold (Au) Plating, 2.85mm Compliant Pin Length, 2.60mm PCB Thickness, 240 Circuits, Lead-Free	ELV and RoHS Compliant
78321-0012	1.00mm Pitch DDR3 DIMM Socket, LLCR, Vertical, Through Hole, with Beveled Metal Pins, Black Housing and Latches, 0.76µm Gold (Au) Plating, 3.18mm Solder Tail Length, 2.36mm PCB Thickness, 240 Circuits, Lead-Free	ELV and RoHS Compliant
78373-0011	1mm DDR3 DIMM 25° TH O/ Lub.76AuLF 240Ckt	ELV and RoHS Compliant
78373-0111	1mm DDR3 DIMM 25° TH O/ Lub.76AuLF 240Ckt	ELV and RoHS Compliant
78079-0212	MOLEX P/N NOT RECOGNIZED	-

Table A

Molex P/N	Part Description	RoHS Compliance Status
87916-0001	1.00mm Pitch DDR-2 DIMM Socket, 22.5 Degree Angle, Through Hole, 240 Circuits, 1.8V Voltage Key, 0.76µm Gold (Au) Plating, 2.79mm Tail Length, with Off-White Latches, Lead-Free	ELV and RoHS Compliant
87916-0011	1.00mm Pitch DDR-2 DIMM Socket, 22.5 Degree Angle, Through Hole, 240 Circuits, 1.8V Voltage Key, 0.76µm Gold (Au) Plating, 3.18mm Tail Length, with Off-White Latches, Lead-Free	ELV and RoHS Compliant
87916-0111	1.00mm Pitch DDR-2 DIMM Socket, 22.5 Degree Angle, Through Hole, 240 Circuits, 1.8V Voltage Key, 0.76µm Gold (Au) Plating, 4.00mm Tail Length, with Off-White Latches, Lead-Free	ELV and RoHS Compliant
85511-5002	Modular Jack, High Speed, Vertical, Short Top, 8/8, Cat 5e, Special Version, Gold (Au), Tin (Sn) over Nickel (Ni)	ELV and RoHS Compliant
85506-5002	Modular Jack, Vertical, High Profile, 8/8, Cat 5e, without Ribs, Through Hole, Gold (Au), Tin (Sn) over Nickel (Ni)	ELV and RoHS Compliant
85543-7001	Modular Jack, Right Angle, Fully Shielded, SMT, 8 Circuits, Palladium Nickel (PdNi)	ELV and RoHS Compliant
95540-6880	Modular Jack, Right Angle, Shielded, Low Profile, SMT, 8/8, Gold (Au)	ELV and RoHS Compliant
48307-8022	0.50mm Pitch HDMI* Receptacle, Vertical, SMT, with Flange, Gold (Au) Flash Plating, Pick-and-Place Cover, 19 Circuits, Tape on Reel Packaging, Lead-Free	ELV and RoHS Compliant
54819-0519	USB On-The-Go (OTG) Mini-B Receptacle, Right Angle, Through Hole Solder Tails and Shell Tabs, Lead-Free	ELV and RoHS Compliant
67643-0980	Universal Serial Bus (USB) Shielded I/O Receptacle, Right Angle, Type A, High-Temperature Black Nylon, Gold (Au) Flash Plating, PCB Thickness 1.20mm, with Upper Flange, for IR Reflow Process, Lead-Free	ELV and RoHS Compliant
67643-3990	Universal Serial Bus (USB) Shielded I/O Receptacle, Right Angle, Type A, High-Temperature White Nylon, Gold (Au) Flash, PCB Thickness 1.60mm, with Upper Flange, for IR Reflow Process, Lead-Free	ELV and RoHS Compliant
02-08-1201	Disk Drive Power Connection System, Female Crimp Terminal, Reel, Phosphor Bronze, AWG 14-20	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
56134-8000	2.00mm Pitch Crimp Terminal 56134, Female, 22-26 AWG, Reel, Phosphor Bronze, for 51242/51353/51382 Housings	ELV and RoHS Compliant
501648-1000	2.00mm Pitch iGrid™ Wire-to-Board Crimp Terminal, Female, 26-28 AWG, Reel	ELV and RoHS Compliant
71718-2900	1.27mm Pitch LFH™ Matrix 50 Receptacle, Shielded, 200 Circuits, Right Angle, PC Tail Length 2.00mm	RoHS Compliant by Exemption
71430-0013	0.80mm Pitch Ultra+™ VHDCI Receptacle, Right Angle, 68 Circuits, PC Tail Length 2.08mm, Shield with Enhanced Ground Tabs, No Screwlocks	RoHS Compliant by Exemption
71430-0050	VHDCI .8MM RA Rec W/Screwlocks 68Ckt	RoHS Compliant by Exemption
022-55-2102	2.54mm Pitch SL™ Crimp Housing, Dual Row, Version B, Polarized, 10 Circuits	ELV and RoHS Compliant
46991-4004	4.20mm Pitch Mini-Fit® RTC Reflow High Temperature Compatible Header, Right Angle, Dual Row, 4 Circuits, without Mounting Peg, Tin (Sn) Over Nickel (Ni) Plating, Glow Wire Compliant	ELV and RoHS Compliant
46991-1024	4.20mm Pitch Mini-Fit® RTC Reflow High Temperature Compatible Header, Right Angle, Dual Row, 24 Circuits, without Mounting Peg, Tin (Sn) Over Nickel (Ni) Plating, Glow Wire Compliant	ELV and RoHS Compliant
41671-3446	KK 156 Header Assy FrLk Bkwy 06 ckt Tin	ELV and RoHS Compliant
026481146	3.96mm (.156") Pitch KK® Header, Breakaway, Right Angle, with Friction Lock, 14 Circuits, Tin (Sn) Plating	ELV and RoHS Compliant
026482046	3.96mm (.156") Pitch KK® Header, Breakaway, Right Angle, with Friction Lock, 4 Circuits, Gold (Au) Plating	ELV and RoHS Compliant
026482049	KK 156 Header Assy FrLk Break 04 Ckt Tin	ELV and RoHS Compliant
026482059	KK 156 Header Assy FrLk Break 05 Ckt Tin	ELV and RoHS Compliant
41672-0228	KK 156 Hdr Assy FrLk BA 05 Ckt Tin void	ELV and RoHS Compliant
27-62-4087	KK 156 Hdr FrLk Peg 08 Ckt Tin	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
15-97-7105	4.20mm Pitch Mini-Fit® TPA Header, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, 10 Circuits, Gold (Au) Plating, without Drain Holes	ELV and RoHS Compliant
26-01-3093	4.20mm Pitch Mini-Fit Jr.™ Plug Housing, Single Row, without Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, 4 Circuits, Glow Wire Compatible	ELV and RoHS Compliant
50-36-1699	4.20mm Pitch Mini-Fit Jr.™ Header, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, without Drain Holes, 2 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) Over Nickel (Ni) Plating, Glow Wire Compatible	ELV and RoHS Compliant
50-36-1809	4.20mm Pitch Mini-Fit Jr.™ Header, Single Row, Vertical, with Snap-in Plastic Peg PCB lock, without Drain Holes, 3 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) Over Nickel (Ni) Plating, Glow Wire Compatible	ELV and RoHS Compliant
50-36-1819	4.20mm Pitch Mini-Fit Jr.™ Header, Dual Row, Vertical, with Snap-in Plastic Peg PCB lock, without Drain Holes, 5 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) Over Nickel (Ni) Plating, Glow Wire Compatible	ELV and RoHS Compliant
50-36-1702	4.20mm Pitch Mini-Fit Jr.™ Header, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, without Drain Holes, 4 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) Over Nickel (Ni) Plating, Glow Wire Compatible	ELV and RoHS Compliant
50-36-1704	4.20mm Pitch Mini-Fit Jr.™ Header, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, without Drain Holes, 6 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) Over Nickel (Ni) Plating, Glow Wire Compatible	ELV and RoHS Compliant
50-36-1706	4.20mm Pitch Mini-Fit Jr.™ Header, Dual Row, Vertical, with Snap-in Plastic Peg PCB Lock, without Drain Holes, 8 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, Tin (Sn) Over Nickel (Ni) Plating, Glow Wire Compatible	ELV and RoHS Compliant
26-01-3096	4.20mm Pitch Mini-Fit Jr.™ Plug Housing, Dual Row, without Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, Panel Mount, 12 Circuits, Glow Wire Compatible	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
50-36-1675	4.20mm Pitch Mini-Fit Jr.™ Plug Housing, Dual Row, without Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, 6 Circuits, Glow Wire Compatible	ELV and RoHS Compliant
50-36-1678	4.20mm Pitch Mini-Fit Jr.™ Plug Housing, Dual Row, without Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, Panel Mount, 2 Circuits, Glow Wire Compatible	ELV and RoHS Compliant
50-36-1679	4.20mm Pitch Mini-Fit Jr.™ Plug Housing, Dual Row, without Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, 4 Circuits, Glow Wire Compatible	ELV and RoHS Compliant
50-36-1734	4.20mm Pitch Mini-Fit Jr.™ Plug Housing, Dual Row, with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, 2 Circuits, Glow Wire Compatible	ELV and RoHS Compliant
50-36-1735	4.20mm Pitch Mini-Fit Jr.™ Plug Housing, Dual Row, with Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, 4 Circuits, Glow Wire Compatible	ELV and RoHS Compliant
50-36-1737	4.20mm Pitch Mini-Fit Jr.™ Plug Housing, Dual Row, without Panel Mount Ears, PA Polyamide Nylon 6/6, UL 94V-0, Panel Mount, 8 Circuits, Glow Wire Compatible	ELV and RoHS Compliant