

Product Compliance Statement

April 29, 2013

Molex is committed to managing the use of chemical substances in accordance with governmental regulations, industry standards, and customer-specific requirements in order to protect the environment. For each part listed, this document provides:

• EU RoHS Compliance Status. EU RoHS status is declared per Directive 2011/65/EU and its subsequent amendments. Homogeneous materials of parts that are compliant to this legislation have less than 0.1% by weight each of lead, mercury, hexavalent chromium, PBB, and PBDE, and 0.01% by weight of cadmium. In situations where an exemption applies, the preceding limits, corresponding to the exempted substance(s), may be higher.

Molex's sole liability for incorrectly certifying a product shall be either replacement of the Molex product or, alternatively and in the sole discretion of Molex, return of the purchase price paid for the relevant Molex product.

For additional information regarding Molex's environmental initiatives and further explanation of this information, please visit www.molex.com

Joel F. Eurich

Director, Global Environmental, Health & Safety (EH&S)

Table A

Table A		
Molex P/N	Part Description	RoHS Compliance Status
74323-2133	MicroCross™ DVI-I Integrated Digital/Analog Dual Channel High Volume Plug Connector Sub- assembly, for PCB Mount, Vertical, Gold (Au) Flash, 29 Circuits, Lead- Free	ELV and RoHS Compliant
73386-0320	RF Adapter SMA Plug to MMCX Reverse Polarized Plug	RoHS Compliant RF Product
0016-02-0069	SL™ Crimp Terminal, Series 70058, Female, with Tin (Sn) Plated Contact, 24-30 AWG, Reel	ELV and RoHS Compliant
19002-0024	Avikrimp™ Fully Insulated Quick Disconnect, Female, for 14-16 AWG Wire, Box	ELV and RoHS Compliant
19003-0050	InsulKrimp™ Quick Disconnect, Female, for 14-16 (2.00-1.30mm²), Box, Tab 4.75 x 0.51mm	ELV and RoHS Compliant
19005-0001	InsulKrimp™ Fully Insulated Coupler, Female, for 18-22 AWG Wire, Box	ELV and RoHS Compliant
457501212	Mini-Fit® Plus HCS Crimp Terminal 45750, 18-20 AWG, Bag, Copper (Cu) Alloy, Gold (Au) Selective	ELV and RoHS Compliant
457503111	Mini-Fit® Plus HCS Crimp Terminal 45750, 16 AWG, Reel, Copper (Cu) Alloy, Tin (Sn)	ELV and RoHS Compliant
457503112	Mini-Fit® Plus HCS Crimp Terminal 45750, 16 AWG, Bag, Copper (Cu) Alloy, Tin (Sn)	ELV and RoHS Compliant
502381-0000	1.25mm Pitch CLIK-Mate™ Wire-to- Board Crimp Terminal, Reel	ELV and RoHS Compliant
19001-0003	Avikrimp™ Quick Disconnect, Male, for 18-22 (0.80-0.35mm²), Box, Tab 4.75 x 0.51mm	ELV and RoHS Compliant
19002-0005	Avikrimp™ Fully Insulated Quick Disconnect, Female, for 18-22 AWG Wire, Box	ELV and RoHS Compliant
0190020001	Avikrimp™ Fully Insulated Quick Disconnect, Female for 18-22 AWG Wire, Box	ELV and RoHS Compliant
19002-0001	Avikrimp™ Fully Insulated Quick Disconnect, Female for 18-22 AWG Wire, Box	ELV and RoHS Compliant
19006-0001	Avikrimp™ Quick Disconnect, for 18-22 AWG Wire, Female Flag, Tab 6.35 x 0.81mm	ELV and RoHS Compliant
015-92-2468	1.27mm Pitch EBBI™ 50D Plug, Vertical, without Latch, 68 Circuits, 2.79mm PC Tail Length	ELV and RoHS Compliant
085009-0854	2.54mm Pitch DIN 41612/EIC 603-2 Mixed Layout Connector, Male Style M, Right Angle, Through Hole, 1µm Selective Gold (Au), 48 Circuits	ELV and RoHS Compliant

Table A

	Table A	
Molex P/N	Part Description	RoHS Compliance Status
85042-1079	2.54mm Pitch DIN 41612 Receptacle, Style C, 96 Circuits	ELV and RoHS Compliant
502380-0300	1.25mm Pitch CLIK-Mate™ Wire-to- Board Housing, Single Row, Positive Lock, 3 Circuits	ELV and RoHS Compliant
087568-4044	2.00mm Pitch Milli-Grid™ Cable-to- Board Receptacle, Dual Row, IDT, Lead-Free, 40 Circuits, 0.76µm Gold (Au) Selective Plating, with Center Polarization Key, without Locking Friction Ramp	ELV and RoHS Compliant
087568-4444	2.00mm Pitch Milli-Grid™ Cable-to- Board Receptacle, Dual Row, IDT, Lead-Free, 44 Circuits, 0.76µm Gold (Au) Selective Plating, with Center Polarization Key, without Locking Friction Ramp	ELV and RoHS Compliant
0050-57-9402	2.54mm Pitch SL™ Crimp Housing, Single Row, Version G, Positive Latch, 2 Circuits	ELV and RoHS Compliant
0050-57-9408	2.54mm Pitch SL™ Crimp Housing, Single Row, Version G, Positive Latch, 8 Circuits	ELV and RoHS Compliant
19418-0022	MX150L [™] 8 Circuit Receptacle for 18-22 AWG Wire, without CPA	ELV and RoHS Compliant
15-31-1023	4.80mm Pitch Wire-to-Wire Plug Housing, 2 Circuits	ELV and RoHS Compliant
03-09-2158	2.36mm Diameter Standard .093" Pin and Socket Plug Housing, 15 Circuits, 3 Rows	ELV and RoHS Compliant
75341-7644	1.85mm by 1.85mm Pitch 4-Pair GbX® Backplane Connector System, Power Module, 12 Circuits, 1.27µm Gold (Au)	ELV and RoHS Compliant
87663-9004	6.35mm Pitch Power (DC), 7.62mm Pitch Power (AC), 2.54mm Pitch Signal, EXTreme PowerPlus™ Board-to-Board Header, Through Hole, Right Angle, 29 Circuits, Power Alpha 3, Signal 24, Power Beta 2, Long Contact, with Bevel	ELV and RoHS Compliant
47018-2002	1.27mm Pitch Serial ATA Host Receptacle, Mating Height 4.30mm, 0.38µm Gold (Au) Plating, Light Tin Solder Area, Surface Mount, Right Angle, Top Mount Type, 22 Circuits, Lead-Free	ELV and RoHS Compliant
67492-9221	1.27mm Pitch Serial ATA Host Receptacle, Right Angle, SMT, Mating Height 6.74mm, 0.76µm Gold (Au) Plating, Tray Packaging, 22 Circuits, Lead-Free	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS Compliance Status
678005002	1.27mm Pitch Serial ATA High Speed Header, Vertical, Surface Mount, with Locking Latch, 7 Circuits, 0.76µm Gold (Au) Plating, for 1.60mm PCB, with PCB Locator Pegs, Lead-Free	ELV and RoHS Compliant
71436-2264	1.00mm Pitch Mezzanine IEEE 1386 Plug, Surface Mount, Dual Row, Vertical Stacking, 64 Circuits, 8.35mm Unmated Height, without PCB Locator Pegs, with Robotic Placement Metal Cap, 1.27µm Gold (Au) Selective Plating, Embossed Tape on Reel	ELV and RoHS Compliant
71436-2464	1.00mm Pitch Mezzanine IEEE 1386 Plug, Surface Mount, Dual Row, Vertical Stacking, 64 Circuits, 8.35mm Unmated Height, with PCB Locator Pegs, with Robotic Placement Metal Cap, 0.76µm Gold (Au) Selective Plating, Embossed	ELV and RoHS Compliant
55451-4070	1.25mm Pitch Mi II™ System Wire- to-Board Header, Dual Row, Vertical, Lead-Free, 40 Circuits	ELV and RoHS Compliant
55560-0307	0.50mm Pitch SlimStack™ Plug, Surface Mount, Dual Row, Vertical, 1.50mm Stack Height, 30 Circuits	ELV and RoHS Compliant
55560-0607	0.50mm Pitch SlimStack™ Plug, Surface Mount, Dual Row, Vertical, 1.50mm Stack Height, 60 Circuits	ELV and RoHS Compliant
55604-5070	0.40mm Pitch Board-to-Board SlimStack™ Plug, Surface Mount, Dual Row, Vertical Stacking, 1.50mm Stacking Height, with Solder Tab and Mating Guide, Lead-Free, without PCB Locator, 50 Circuits	ELV and RoHS Compliant
53398-1271	1.25mm Pitch PicoBlade™ Header, Surface Mount, Vertical, Lead-Free, 12 Circuits	ELV and RoHS Compliant
53398-1471	1.25mm Pitch PicoBlade™ Header, Surface Mount, Vertical, Lead-Free, 14 Circuits	ELV and RoHS Compliant
55450-2069	1.25mm Pitch Mi II™ System Wireto-Board Header, SMT, Single Row, Vertical, without Plastic Peg, Lead-Free, 20 Circuits	ELV and RoHS Compliant
52465-1871	0.80mm Pitch Board-to-Board Receptacle, Surface Mount, Dual Row, 18 Circuits, Lead-Free	ELV and RoHS Compliant
52465-3071	0.80mm Pitch Board-to-Board Receptacle, Surface Mount, Dual Row, 30 Circuits, Lead-Free	ELV and RoHS Compliant

Table A

Table A		
Molex P/N	Part Description	RoHS Compliance Status
52885-1074	0.635mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical Stacking, 5.00 to 10.00mm Stacking Heights, Embossed Tape with Cover Packaging, 100 Circuits, Lead-Free	ELV and RoHS Compliant
52901-0374	0.635mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical Stacking, 11.00 to 16.00mm Stacking Heights, Embossed Tape with Cover Packaging, 30 Circuits, Lead-Free	ELV and RoHS Compliant
53307-1071	0.80mm Pitch Header, Surface Mount, Dual Row, Vertical Stacking, 4.50 and 5.50mm Stacking Heights, Lead-Free, 10 Circuits	ELV and RoHS Compliant
53307-1671	0.80mm Pitch Header, Surface Mount, Dual Row, Vertical Stacking, 4.50 and 5.50mm Stacking Heights, Lead-Free, 16 Circuits	ELV and RoHS Compliant
53307-2471	0.80mm Pitch Header, Surface Mount, Dual Row, Vertical Stacking, 4.50 and 5.50mm Stacking Heights, Lead-Free, 24 Circuits	ELV and RoHS Compliant
53307-4071	0.80mm Pitch Header, Surface Mount, Dual Row, Vertical Stacking, 4.50 and 5.50mm Stacking Heights, Lead-Free, 40 Circuits	ELV and RoHS Compliant
53309-4070	0.80mm Pitch Board-to-Board Header, Surface Mount, Dual Row, Right Angle, Lead-Free, 40 Circuits	ELV and RoHS Compliant
55447-0270	1.25mm Pitch Mi II™ System Wireto-Board Header, Single Row, Vertical, with Positive Lock, Lead-Free, 2 Circuits	ELV and RoHS Compliant
55447-0470	1.25mm Pitch Mi II™ System Wireto-Board Header, Single Row, Vertical, with Positive Lock, Lead-Free, 4 Circuits	ELV and RoHS Compliant
55447-0870	1.25mm Pitch Mi II™ System Wireto-Board Header, Single Row, Vertical, with Positive Lock, Lead-Free, 8 Circuits	ELV and RoHS Compliant
501331-0407	1.00mm Pitch Pico-Clasp™ Wire- to-Board Header, Surface Mount, Single Row, Vertical, with Friction Lock, 4 Circuits, with Cover Tape, Lead-Free	ELV and RoHS Compliant
501331-0507	1.00mm Pitch Pico-Clasp™ Wire- to-Board Header, Surface Mount, Single Row, Vertical, with Friction Lock, 5 Circuits, with Cover Tape, Lead-Free	ELV and RoHS Compliant
501568-0307	1.00mm Pitch Pico-Clasp™ Wire- to-Board Header, Surface Mount, Single Row, Right Angle, with Friction Lock, 3 Circuits, Lead-Free	ELV and RoHS Compliant

Table A

Table A		
Molex P/N	Part Description	RoHS Compliance Status
74441-5010	0.80mm Pitch SFP Plus (SFP+) Host Connector, Right Angle, SMT, 20 Circuits, 0.76µm Gold (Au) Plating Over Nickel (Ni), Solder Area Tin (Sn) Over Nickel (Ni)	ELV and RoHS Compliant
502382-0370	1.25mm Pitch CLIK-Mate™ Wire-to- Board PCB Receptacle, Single Row, Vertical, 3 Circuits	ELV and RoHS Compliant
501331-0607	1.00mm Pitch Pico-Clasp™ Wire- to-Board Header, Surface Mount, Single Row, Vertical, with Positive Lock, 6 Circuits, with Cover Tape, Lead-Free	ELV and RoHS Compliant
501331-1007	1.00mm Pitch Pico-Clasp™ Wire- to-Board Header, Surface Mount, Single Row, Vertical, with Positive Lock, 10 Circuits, with Cover Tape, Lead-Free	ELV and RoHS Compliant
52760-1079	0.635mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical Stacking, 5.00 and 10.00mm Stacking Heights, Tube Packaging, 100 Circuits, Lead-Free	ELV and RoHS Compliant
87438-0242	1.50mm Pitch Pico-SPOX™ Wire-to- Board Header, Surface Mount, Right Angle, Shrouded, 2 Circuits, Tube Packaging, Lead-Free	ELV and RoHS Compliant
87437-0243	1.50mm Pitch Pico-SPOX™ Wire- to-Board Header, Surface Mount, Vertical, Shrouded, 2 Circuits, Embossed Tape on Reel Packaging, Lead-Free	ELV and RoHS Compliant
35362-0250	2.00mm Pitch Sherlock™ Wire-to- Board Header, Vertical, with Positive Lock, 2 Circuits, with Kinked PC Tails, Natural	ELV and RoHS Compliant
35362-0350	2.00mm Pitch Sherlock™ Wire-to- Board Header, Vertical, with Positive Lock, 3 Circuits, with Kinked PC Tails, Natural	ELV and RoHS Compliant
35362-0750	2.00mm Pitch Sherlock™ Wire-to- Board Header, Vertical, with Positive Lock, 7 Circuits, with Kinked PC Tails, Natural	ELV and RoHS Compliant
35363-0460	2.00mm Pitch Sherlock™ Wire-to- Board Header, Right Angle, with Positive Lock, 4 Circuits, Lead-Free	ELV and RoHS Compliant
35363-0660	2.00mm Pitch Sherlock™ Wire-to- Board Header, Right Angle, with Positive Lock, 6 Circuits, Lead-Free, White	ELV and RoHS Compliant
55917-3630	2.00mm Pitch MicroClasp™ Wire-to- Board Header, Dual Row, Vertical, 36 Circuits, without PCB Locator	ELV and RoHS Compliant

Table A

Table A		
Molex P/N	Part Description	RoHS Compliance Status
55917-0830	2.00mm Pitch MicroClasp™ Wire-to- Board Header, Dual Row, Vertical, 8 Circuits, without PCB Locator	ELV and RoHS Compliant
55935-0430	2.00mm Pitch MicroClasp™ Wire- to-Board Header, Single Row, Right Angle, 4 Circuits, without PCB Locator	ELV and RoHS Compliant
53325-0860	2.00mm Pitch Mi II™ System Wireto-Board Header, Single Row, Right Angle, Lead-Free, 8 Circuits	ELV and RoHS Compliant
087760-1416	2.00mm Pitch Milli-Grid™ Header, Right Angle, Through Hole, 14 Circuits, 0.38µm Gold (Au) Selective Plating, Tray, Lead-Free	ELV and RoHS Compliant
54603-0952	2.00mm Pitch MZP™ Hard Metric Board-to-Board PCB Receptacle, Right Angle, Type B, CompactPCI*, with Upper Shield, 95 Circuits	Not RoHS Compliant
87831-1241	2.00mm Pitch Milli-Grid™ Header, Vertical, Through Hole, Shrouded, Lead-Free, 12 Circuits, 0.38µm Gold (Au) Plating, with Locking Window, without PCB Locator, without Center Polarization Slot, Tube	ELV and RoHS Compliant
87831-2021	2.00mm Pitch Milli-Grid™ Header, Vertical, Through Hole, Shrouded, Lead-Free, 20 Circuits, 0.76µm Gold (Au) Plating, Center Polarization Slot, with Locking Windows, without PCB Locator, Tube	ELV and RoHS Compliant
55501-1331	2.00mm Pitch MZP™ Hard Metric Board-to-Board PCB Plug, Vertical, Type B, CompactPCI*, Short Tail, 133 Circuits	ELV and RoHS Compliant
70246-4001	2.54mm Pitch C-Grid® Header, Low Profile, Dual Row, Vertical, Shrouded, 40 Circuits, 0.38µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating	ELV and RoHS Compliant
070246-4002	2.54mm Pitch C-Grid® Header, Low Profile, Dual Row, Vertical, Shrouded, 40 Circuits, 0.76µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating	ELV and RoHS Compliant
070246-2401	2.54mm Pitch C-Grid® Header, Low Profile, Dual Row, Vertical, Shrouded, 24 Circuits, 0.38µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating, Lead-Free	ELV and RoHS Compliant
070287-1155	2.54mm Pitch C-Grid® Header, Breakaway, Dual Row, Vertical, with Retention Pin, 20 Circuits, 8.13mm Mating Pin Length, 0.38µm Gold (Au) Selective Plating	ELV and RoHS Compliant

Table A

	Table A	
Molex P/N	Part Description	RoHS Compliance Status
70246-1602	2.54mm Pitch C-Grid® Header, Low Profile, Dual Row, Vertical, Shrouded, 16 Circuits, 0.76µm Gold (Au) Selective Plating, Tin (Sn) PC Tail Plating	ELV and RoHS Compliant
42819-4213	10.00mm Pitch Mini-Fit Sr.™ Header, Single Row, Vertical, 4 Circuits, 1.57mm PCB Thickness, 0.76µm Gold (Au) Selective Plating	ELV and RoHS Compliant
42819-4223	10.00mm Pitch Mini-Fit Sr.™ Header, Single Row, Vertical, 4 Circuits, 2.36mm PCB Thickness, 0.76µm Gold (Au) Selective Plating	ELV and RoHS Compliant
43160-4102	Sabre 2Ckt Ver V0 Hdr 093Lk ShtTail	ELV and RoHS Compliant
43160-4103	Sabre 3Ckt Ver V0 Hdr 093Lk ShtTail	ELV and RoHS Compliant
43160-4104	Sabre 4Ckt Ver V0 Hdr 093Lk ShtTail	ELV and RoHS Compliant
43650-0324	3.00mm Pitch Micro-Fit 3.0 [™] Header, Surface Mount Compatible, Single Row, Vertical, with Solder Tab, 3 Circuits, Tin (Sn) Plating, Glow Wire Compatible	ELV and RoHS Compliant
53259-0220	2CKT 3.5MM W-B R/A CONN WAFER ASSY	Not RoHS Compliant
1060555500	FC Connector, APC, Singlemode, 126µm Angled Ferrule, .90mm Buffered Fiber, Metal Coupling Nut, Green Boot, Tight Fit Key	RoHS Compliant by Exemption
86024-5500	LC Connector, Singlemode, 126µm Ceramic Ferrule, 900µm Buffered Fiber, Blue Housing, White Boot	Not RoHS Compliant
475531001	1.27mm Pitch SIM Card Holder with 2 Detect Pins, 6 Circuits, Push-Push Style, Housing Height 1.80mm, with Pegs, Lead-Free	ELV and RoHS Compliant
503182-0852	1.10mm Pitch microSD Memory Card Connector, Normal Mount SMT, Push-Push Type, 1.45mm Height, Anti-card fly-out	ELV and RoHS Compliant
73169-7001	BNC 75 Ohm, Plug, 1/4 W Resistive Termination	RoHS Compliant RF Product
731713680	BNC JACK BULK REAR MOUNT IP68 RD316	RoHS Compliant RF Product
73216-2060	TNC PLUG R/A RG223 50 OHM	RoHS Compliant RF Product
73251-3680	SMA PLUG STR CRIMP/CRIMP RD316	RoHS Compliant RF Product
73276-1760	N PLUG BLKHD IP68 REAR MOUNT CLAMP RD316	RoHS Compliant RF Product

Table A

Molex P/N	Part Description	RoHS Compliance Status
73397-0022	SSMB R/A PLUG FOR RG316/U	RoHS Compliant RF Product
73404-0292	SMB PLUG, R/A, 50 OHM, RD316	RoHS Compliant RF Product
73404-2740	SMB PLUG STR RD316 50 OHM	RoHS Compliant RF Product
73415-4194	50 Ohms MXC Right Angle Plug, RG-174, RG-188 and RG-316 Cable	RoHS Compliant RF Product
73171-2730	75 Ohms Mini BNC, Straight Jack, Nickel	RoHS Compliant RF Product
73171-3510	BNC JACK R/A PCB 75 OHMS	RoHS Compliant RF Product
73174-0850	1.0/2.3 Jack, vertical TH, PCB, 75 ohms	RoHS Compliant RF Product
73251-2201	50 Ohms, SMA Jack, Right Angle PCB, Gold	RoHS Compliant RF Product
052435-3071	0.50mm Pitch SMT Right-Angle FFC/ FPC Connector, 30 Circuits, Gold (Au) Contact Plating	ELV and RoHS Compliant
52089-0419	1.00mm Pitch FFC/FPC Connector, Through-Hole, Right Angle, Low Profile, ZIF, Top Contact Style Receptacle, 4 Circuits, Lead-Free	ELV and RoHS Compliant
52207-3085	1.00mm Pitch FFC/FPC Connector, SMT, Right Angle, ZIF, Top Contact Style Receptacle, 30 Circuits, Lead- Free, High Barrier Packaging	ELV and RoHS Compliant
52271-1679	1.00mm Pitch FFC/FPC Connector, Right Angle, SMT, ZIF, Bottom Contact Style, 16 Circuits, Lead- Free, High Barrier Packaging	ELV and RoHS Compliant
052559-2270	0.50mm Pitch FFC/FPC Connector, Vertical, SMT, ZIF, 22 Circuits, Lead- Free	ELV and RoHS Compliant
87715-9206	1.00mm Pitch, PCI Express* Connector, 98 Circuits, Nylon 4/6 Glass-filled, Black Housing, Phosphor Bronze, 0.76µm Gold Soldertail, Lead-Free	ELV and RoHS Compliant
39100-1008	10.00mm Pitch Beau™ Eurostyle™ Two-Screw Terminal Strips, 8 Circuits	ELV and RoHS Compliant
38280-0112	BTS STD 12 ASY	ELV and RoHS Compliant
38720-0203	SR BTS CB 3 ASY	ELV and RoHS Compliant
38720-3212	SR BTS TT 12 ASY	ELV and RoHS Compliant
38760-0104	CB BTS STD 4 ASY	ELV and RoHS Compliant

Table A

l able A		
Molex P/N	Part Description	RoHS Compliance Status
38760-0106	CB BTS STD 6 ASY	ELV and RoHS Compliant
38760-0130	CB BTS STD 30 ASY	ELV and RoHS Compliant
38770-0104	CB BTS STD 4 ASY	ELV and RoHS Compliant
38770-0106	CB BTS STD 6 ASY	ELV and RoHS Compliant
38770-0110	CB BTS STD 10 ASY	ELV and RoHS Compliant
38770-0112	CB BTS STD 12 ASY	ELV and RoHS Compliant
38770-0120	CB BTS STD 20 ASY	ELV and RoHS Compliant
38780-0106	CB BTS STD 6 ASY	ELV and RoHS Compliant
38780-0108	CB BTS STD 8 ASY	ELV and RoHS Compliant
39970-0104	10.16mm Beau [™] Eurostyle [™] Fixed Mount PCB Terminal Block, High Power 60A, 4 Circuits	RoHS Compliant by Exemption
84700-0001	Modular Jack, Inline, Industrial, 8/8	ELV and RoHS Compliant
84700-0002	Modular Plug, Industrial, 8/8, Panel Stops	ELV and RoHS Compliant
48025-1090	Modular Jack, Right Angle, 10/100, with Integrated Magnetic and LED, 8/8, Lead-Free	ELV and RoHS Compliant
48025-1091	Modular Jack, Right Angle, 10/100, with Integrated Magnetic and LED, 8/8, without EMI Fingers, Lead-Free	ELV and RoHS Compliant
95501-2661	Modular Jack, Right Angle, Low Profile, Through Hole, 6/6, Gold (Au)	ELV and RoHS Compliant
95501-6889	Modular Jacks, Low Profile, SMT, 8/8 Circuits, Gold (Au)	ELV and RoHS Compliant
52018-8846	Modular Jack, Right Angle, Inverted, 8/8 Lead Free, 1.27μm Gold (Au) Plating	ELV and RoHS Compliant
85503-5001	Modular Jack, High Speed, Right Angle, 8/8, Cat 5e, Through Hole, Gold (Au), Tin (Sn) over Nickel (Ni)	ELV and RoHS Compliant
847290009	USB Type A Panel Mount PCB Receptacle	ELV and RoHS Compliant
95501-2441	Modular Jack, Right Angle, Low Profile, Through Hole, 4/4, Gold (Au)	ELV and RoHS Compliant
95501-7441	Modular Jack, Right Angle, Low Profile, Through Hole, 4/4, Cat 3 Jack with Palladium Nickel (PdNi) + Gold (Au) flash over Tin (Sn) Plating	ELV and RoHS Compliant

Table A

Malas D/N	Part Passalistian	D - 110
Molex P/N	Part Description	RoHS Compliance Status
95501-2641	Modular Jack, Right Angle, Low Profile, Through Hole, 6/4, Gold (Au)	ELV and RoHS Compliant
95501-7641	Modular Jack, Right Angle, Low Profile, Through Hole, 6/4, Cat 3 Jack with Palladium Nickel (PdNi) + Gold (Au) flash over Tin (Sn) Plating	ELV and RoHS Compliant
95501-2881	Modular Jack, Right Angle, Low Profile, Through Hole, 8/8, Gold (Au)	ELV and RoHS Compliant
95501-7881	Modular Jack, Right Angle, Low Profile, Through Hole, 8/8, Cat 3 Jack with Palladium Nickel (PdNi) + Gold (Au) flash over Tin (Sn) Plating	ELV and RoHS Compliant
95501-2882	Modular Jack, Right Angle, Low Profile, Through Hole, 8/8, Gold (Au), Keyed	ELV and RoHS Compliant
95501-7882	Modular Jack, Right Angle, Low Profile, Through Hole, 8/8, Cat 3 Jack with Palladium Nickel (PdNi) + Gold (Au) flash over Tin (Sn) Plating, Keyed	ELV and RoHS Compliant
95501-7661	Modular Jack, Right Angle, Low Profile, Through Hole, 6/6, Cat 3 Jack with Palladium Nickel (PdNi) + Gold (Au) flash over Tin (Sn) Plating	ELV and RoHS Compliant
70928-2008	1.27mm Pitch LFH™ Matrix 50 Receptacle, Shielded, Right Angle, 2.34mm PC Tail Length, 4-40 Hex Screw Kit, Gold Plating, 60 Circuits	ELV and RoHS Compliant
83612-9020	1.27mm Pitch Commercial Micro D, PCB Mount, Right Angle Plug, 15 Circuits	ELV and RoHS Compliant
46015-0809	4.20mm Pitch Mini-Fit® Plus HCS Header, Dual Row, Vertical, 8 Circuits, with Snap-in Plastic Peg PCB Lock, PA Polyamide Nylon 6/6, UL 94V-0, 0.76µm Gold (Au) Selective Plating	ELV and RoHS Compliant
44914-6403	3.00mm Pitch Micro-Fit 3.0 CPI™ Header, Dual Row, Vertical, Compliant Pin Interface, 14 Circuits, LCP, Glass-Filled, UL 94V-0, 0.76μm Gold (Au) Selective Contact Plating, Tin (Sn) Plated Tails, Glow Wire Compatible	ELV and RoHS Compliant
87680-2001	6.35mm Pitch, Power, EXTreme PowerPlus™ All Power Receptacle, Press-fit, Vertical, 0.76µm Gold (Au), 2 Circuits, Tin	ELV and RoHS Compliant
78011-0011	1.27mm Pitch Serial ATA Host Receptacle, 8.15mm Height, SMT, Vertical, with 1.00mm Plastic Locating Peg, Pick-and-Place Cap, 0.76µm Gold (Au) Selective Plating, 22 Circuits, Lead-Free	ELV and RoHS Compliant

Table A

Molex P/N	Part Description	RoHS
		Compliance Status
67491-0020	1.27mm Pitch Serial ATA High Speed Header, Through Hole, Vertical, 7 Circuits, Gold (Au) Flash, with 2.05mm PC Tail Length, Lead- Free	ELV and RoHS Compliant
87831-1042	2.00mm Pitch Milli-Grid™ Header, Vertical, Through Hole, Shrouded, Lead-Free, 10 Circuits, 0.76µm Gold (Au) Plating, with Locking Window, without PCB Locator, without Center Polarization Slot, Tube	ELV and RoHS Compliant
462071204	4.20mm Pitch Mini-Fit® RTC Reflow High Temperature Compatible Header, Dual Row, Vertical, 4 Circuits, 3.18mm PCB Thickness, No PCB Pegs, LCP Housing, with Tin (Sn) Over Nickel (Ni) Plating, Glow Wire Compliant	ELV and RoHS Compliant
462071224	4.20mm Pitch Mini-Fit® RTC Reflow High Temperature Compatible Header, Dual Row, Vertical, 6 Circuits, 3.18mm PCB Thickness, No PCB Pegs, LCP Housing, with Tin (Sn) Over Nickel (Ni) Plating, Glow Wire Compliant	ELV and RoHS Compliant
44914-6003	3.00mm Pitch Micro-Fit 3.0 CPI™ Header, Dual Row, Vertical, Compliant Pin Interface, 10 Circuits, LCP, Glass-Filled, UL 94V-0, 0.76μm Gold (Au) Selective Contact Plating, Tin (Sn) Plated Tails, Glow Wire Compatible	ELV and RoHS Compliant
95503-6891	8/8 Low Profile Jack, SMT Version, Tin (Sn) Plated	ELV and RoHS Compliant
47391-3001	1.27mm Pitch External Serial ATA Shelled Plug without Flange, Bottom Mount, Right Angle, Unmating Height 5.35mm, 0.76µm Gold (Au) Plating, 7 Circuits, with Vacuum Pick-Up Tape, Lead-Free	ELV and RoHS Compliant
89485-8001	Universal Serial Bus (USB) Shielded I/O Type A Receptacle, Single Upright, Right Angle, Terminal Length 2.00mm, Without Mylar, 0.76µm Gold (Au) Plating, Tray Package, Lead-Free	ELV and RoHS Compliant
87630-1011	1.27mm Pitch DIMM 4-Byte Socket, Vertical, Multi-Key, 3.3V Center Voltage Key, with Plastic Pegs, 0.38µm Gold (Au) Plating, 100 Circuits, Lead-Free, Tube	ELV and RoHS Compliant
87587-2050	1.27mm Pitch DIMM 8-Byte Socket, Low Profile (25°), Multi-Key, with Beveled Metal Pins and Plastic Peg, Right Function Key, 2.79mm Tail Length, 0.38µm Gold (Au) Selective Plating, 168 Circuits, Lead-Free	ELV and RoHS Compliant
73415-3593	SMP Edge Mount PCB Plug, Leg Length 1.27mm	RoHS Compliant RF Product

Table A

Moley D/N	Part Description	Dalle
Molex P/N	Part Description	RoHS Compliance Status
73415-3591	SMP Edge Mount PCB Plug, Leg Length 1.27mm, Bag	RoHS Compliant RF Product
501568-1407	1.00mm Pitch Pico-Clasp™ Wire- to-Board Header, Surface Mount, Single Row, Right Angle, with Positive Lock, 14 Circuits, Lead-Free	ELV and RoHS Compliant
67068-8001	Universal Serial Bus (USB) Shielded I/O Type B Receptacle, Right Angle, with Kinked Solder Tabs, Color Black, 0.76µm Gold (Au) Plating, Tray Pack, Lead-Free	ELV and RoHS Compliant
39-30-7165	4.20mm Pitch Mini-Fit Jr.™ Header, Dual Row, Right Angle, with Snap- in Plastic Peg PCB Lock, 16 Circuits, PA Polyamide Nylon 6/6, 94V-2, Tin (Sn) Over Nickel (Ni) Plating	ELV and RoHS Compliant
39-30-7185	4.20mm Pitch Mini-Fit Jr.™ Header, Dual Row, Right Angle, with Snap- in Plastic Peg PCB Lock, 18 Circuits, PA Polyamide Nylon 6/6, 94V-2, Tin (Sn) Over Nickel (Ni) Plating	ELV and RoHS Compliant
39-00-0022	SPOX™ Crimp Terminal 5194, 18-24 AWG, Phosphor Bronze, Bag	ELV and RoHS Compliant
02-09-2133	2.36mm Diameter, Standard .093" Pin and Socket PC Tail Terminal, Series 1376, Male, with Tin/Lead (Sn/Pb) Plated Contact, With Detent, Bag Packaged	ELV and RoHS Compliant
08-58-0127	3.96mm Pitch KK® Crimp Terminal 2878, 18-20 AWG, Reel, Phosphor Bronze, 0.51µm Selective Gold (Au), Bifurcated	ELV and RoHS Compliant
0039000090	4.20mm Pitch Mini-Fit® Crimp Terminal, Female, Brass, Gold (Au), 16 AWG, Bag	ELV and RoHS Compliant
019002-0009	Avikrimp™ Fully Insulated Quick Disconnect, Female, for 18-22 AWG Wire, Box	ELV and RoHS Compliant
19002-0028	Avikrimp™ Fully Insulated Quick Disconnect, Female, for 14-16 AWG Wire, Box	ELV and RoHS Compliant
190020044	Avikrimp™ Quick Disconnect, Female, for 10-12 (5.00-3.30mm²) Wire, Box, Tab 6.35 x 0.81mm	ELV and RoHS Compliant
19003-0017	InsulKrimp™ Quick Disconnect, Female, for 18-22 (0.80-0.35mm²), Box, Tab 4.75 x 0.81mm	ELV and RoHS Compliant
19006-0011	Avikrimp™ Quick Disconnect, for 14-16 AWG Wire, Female Flag, Tab 6.35 x 0.81mm	ELV and RoHS Compliant
19007-0029	Flag InsulKrimp™ Quick Disconnect, Female, for 14-16 (2.00-1.30mm²) Wire, Box, Tab 4.75 x 0.51mm	ELV and RoHS Compliant

Table A

I able A		
Molex P/N	Part Description	RoHS Compliance Status
190070041	Flag InsulKrimp™ Quick Disconnect, Female, for 10-12 (5.00-3.30mm²) Wire, Metal Strip, Tab 6.35 x 0.81mm	ELV and RoHS Compliant
19016-0085	Krimptite™ Quick Disconnect, Female, for 12-14 (3.30-2.00mm²) Wire, Box, Tab 6.35 x 0.81mm	ELV and RoHS Compliant
19019-0001	Avikrimp™ Quick Disconnect, Female, for 18-22 (0.80-0.35mm²) Wire, Box, Tab 2.79 x 0.51mm	ELV and RoHS Compliant
19019-0004	Avikrimp™ Quick Disconnect, Female, for 18-22 (0.80-0.35mm²) Wire, Box, Tab 2.79 x 0.81mm	ELV and RoHS Compliant
19019-0022	Avikrimp™ Quick Disconnect, Female, for 14-16 (2.00-1.30mm²) Wire, Box, Tab 2.79 x 0.51mm	ELV and RoHS Compliant
44485-1212	Mini-Fit® Crimp Terminal, 18-24 AWG, Bag, Phosphor Bronze, Select Gold (Au)	ELV and RoHS Compliant
0561349100	2.00mm Pitch Crimp Terminal 56134, Female, 22-28 AWG, Bag, Copper Alloy, for 51242/51353/51382/500915 Housings	ELV and RoHS Compliant
08-55-0130	KK® Crimp Terminal, 22-30 AWG, Selective Gold (Au), Nickel (Ni) Under Plating	ELV and RoHS Compliant
19005-0010	InsulKrimp™ Fully Insulated Female Quick Disconnect, for 10-12 AWG Wire, Box	ELV and RoHS Compliant
501330-1200	1.00mm Pitch Pico-Clasp™ Wire-to- Board Female Housing, Single Row, with Positive Lock, 12 Circuits	ELV and RoHS Compliant
5013301500	1.00mm Pitch Pico-Clasp™ Wire-to- Board Female Housing, Single Row, with Positive Lock, 15 Circuits	ELV and RoHS Compliant
51382-0400	2.00mm Pitch MicroClasp™ Wire-to- Board Receptacle Housing, Positive Lock, Single Row, 4 circuits	ELV and RoHS Compliant
51382-0200	2.00mm Pitch MicroClasp™ Wire-to- Board Receptacle Housing, Positive Lock, Single Row, 2 circuits	ELV and RoHS Compliant
15-31-1022	4.80mm Pitch Wire-to-Wire Receptacle Housing, 2 Circuits	ELV and RoHS Compliant
19-09-2031	2.36mm Diameter, .093" Pin and Socket Plug Housing with Positive Latch, 3 Circuits, with Pre-bent Mounting Ears	ELV and RoHS Compliant
194180001	MX150L™ 8 Circuit Receptacle for 18-22 AWG Wire, with CPA	ELV and RoHS Compliant
19-09-1030	1991 Rcpt Hsg PeBntEar 3Ckt	ELV and RoHS Compliant

Table A

1000			
Molex P/N	Part Description	RoHS Compliance Status	
050-84-1065	2.13mm Diameter MLX [™] Power Crimp Housing Plug, 6 Circuits	ELV and RoHS Compliant	
52465-2471	0.80mm Pitch Board-to-Board Receptacle, Surface Mount, Dual Row, 24 Circuits, Lead-Free	ELV and RoHS Compliant	
09-52-3062	KK 156 PCB Assy Bottom 06 Ckt Tin	ELV and RoHS Compliant	
501616-4585	0.30mm Pitch Easy-On™ Type FPC Connector, 1.10mm Mated Height, Right Angle, SMT, ZIF, Top Contact Style, 45 Circuits, Lead-Free	ELV and RoHS Compliant	
501951-6000	0.50mm Pitch Easy-On™ FFC/ FPC Connector, Vertical, SMT, Tin- Bismuth Plating, 60 Circuits	ELV and RoHS Compliant	
39100-0803	8.00mm Pitch Beau [™] Eurostyle [™] Two-Screw Terminal Strips, 3 Circuits	RoHS Compliant by Exemption	
39100-0912	8.00mm Pitch Beau [™] Eurostyle [™] Two-Screw Terminal Strips, 12 Circuits, Low Profile	ELV and RoHS Compliant	