



注)  
NOTE.

- 各部のそりは0.5最大  
WARPING:0.5MAX.
- サーキットNO. はNO. " 1" のみ表示  
CIRCUIT NO. : "1" ONLY
- ELV 及び RoHS適合品  
ELV AND RoHS COMPLIANT.

10-22-1092	5198-09	45.72	50.72	9
↑ -1082	↑ -08	40.64	45.64	8
-1072	-07	35.56	40.56	7
-1062	-06	30.48	35.48	6
-1052	-05	25.4	30.4	5
-1042	-04	20.32	25.32	4
↓ -1032	↓ -03	15.24	20.24	3
10-22-1022	5198-02	10.16	15.16	2
EDP.NO.	ENG.NO.	B	(A)	極数 CKT.

MATERIAL  
NYLON66, 94V-2

REVISED  
EC NO: J2008-4096  
DRWN:MNABEI  
CHKD:THARUYAMA  
APPR:NUKITA

DESCRIPTION  
GENERAL TOLERANCES (UNLESS SPECIFIED)  
10 UNDER ±0.2  
10 OVER 30 UNDER ±0.25  
30 OVER ±0.3  
ANGULAR ±3 °  
DRAFT WHERE APPLICABLE  
MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE  
MM ONLY  
DRAWN BY DATE  
K. KOHAMA '00/03/28  
CHECKED BY DATE  
T. YAMAGUCHI '00/03/30  
APPROVED BY DATE  
M. FUKUSHIMA '00/03/30  
MATERIAL NO.  
5198-\*\*

SCALE  
2:1  
DESIGN UNITS  
METRIC  
THIRD ANGLE PROJECTION  
SPOX 10.16/5.08 PITCH  
REC HSG  
MOLEX INCORPORATED  
DOCUMENT NO.  
SD-5198-001  
SHEET NO.  
1 OF 1  
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION