Register | Login
Register | Login
Register | Login
Wy Parts (0 items)

Finder Part No. or K Go

Cross-Ref
Catalog
Literature
Industries
Standards
Contact Us
About Us
Investors
Careers
Careers
Connectors Sockets | //O Connectors Cable Fiber Optics Printed Circuit Industrial Lighting Products

Switch Language

English

Need Assistance?

Contact Us
Find a Distributor
Order Samples
Tech Library
Ecocare
Electrical Models

Printer-friendly page

Email this page

Home

Quick Disconnects

Datasheet

Part Number:

0190020024

Status:

Active


Description:

Avikrimp™ Fully Insulated Quick Disconnect, Female, for 14-16 AWG Wire, Box

Documents: Note - Please disable browser pop-up blockers for documents on www.molex.com

Drawing (PDF)

Datasheet (PDF)



EU RoHS

ELV and RoHS Compliant

REACH SVHC

Not Reviewed

Halogen-Free Status

Not Reviewed

China RoHS



Need more information on product
environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, click here

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

19002Series

Use With

<u>19001-0006</u>, <u>19001-0007</u>

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below . Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description

Product #

Hand Crimp Tool

0640011100

Crimp Head for the AT-

0640051100

200™ Pneumatic Hand

Tool

Crimp Quality Equipment

Molex also offers wire strippers, pull testers, shut-height gauges, micrometers and more

Click here for details

RoHS Certificate of Compliance (PDF)

Order Products:

Part Detail: (show all)

GeneralPhysicalElectricalAgency CertificationMaterial InfoReference - Drawing Numbers

General

Product Family	Quick Disconnects
Series	<u>19002</u>
Product Name	Avikrimp™
Туре	Quick Disconnect

Physical

Barrel Type	Closed
Flammability	94V-2
Gender	Female
Glow-Wire Compliant	No
Insulation	Nylon (PA)
Lock to Mating Part	None
Material - Metal	Brass
Orientation	Straight
Packaging Type	Bag
Polarized to Mating Part	No
Tab Thickness	0.81mm (.032")
Tab Width	6.35mm (.250")
Temperature Range - Operating	-40°C to +105°C
Wire Insulation Diameter	3.94mm (.155") max.
Wire Size AWG	14, 16
Wire Size mm²	1.30 - 2.00

Electrical(Please review the Product Specification for specific details.)

Voltage - Maximum	300V	

Agency Certification

CSA	LR18689
UL	E79133

Material Info

Old Part Number	BB-5263	
-----------------	---------	--

Reference - Drawing Numbers

Sales Drawing	SD-19002-004
---------------	--------------

Feedback Privacy Legal Site Map Help

