

This document was generated on 12/17/2012

### PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 93071-2001

Status: Active

Overview: RAST 2.5 Connector System

Description: 5.00mm Pitch Appli-Mate RAST 2.5 Header, Vertical, 4 Circuits, Reference K00, Glow

Wire Compatible

**Documents:** 

3D ModelProduct Specification PS-93070-001 (PDF)Drawing (PDF)RoHS Certificate of Compliance (PDF)

**Agency Certification** 

CSA LR19980 UL E29179

General

Product Family PCB Headers

Series <u>93071</u>

Application Power, Wire-to-Board Comments "This Molex product is

"This Molex product is manufactured from material that has the following ratings, tested by independent agencies:. a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13.. b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety, section 30 Resistance to heat and fire. <P><P> The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test

end-use standard(s). <P> If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for

standard IEC 60695-2-11 and any applicable product


possible product options."

Overview RAST 2.5 Connector System

Product Name RAST 2.5 UPC 883906320850

**Physical** 

**Breakaway** No Circuits (Loaded) 4 Circuits (maximum) 4 Color - Resin Natural Durability (mating cycles max) 10 First Mate / Last Break No Flammability 94V-0 **Glow-Wire Compliant** Yes Guide to Mating Part No Keying to Mating Part Yes Lock to Mating Part Yes Material - Metal **Brass** Material - Plating Mating Tin Material - Plating Termination Tin Material - Resin Nylon



Series

image - Reference only

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Low-Halogen Status
Not Low-Halogen



# Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

## Search Parts in this Series

93071 Series

#### **Mates With**

Appli-Mate RAST 2.5 Female Connector 93051, Appli-Mate RAST 2.5 IDT Housing 91717, Appli-Mate® RAST Power IDT Housing 91627

### **Use With**

**RAST Standard Interface** 

Net Weight 1.660/g Number of Rows Orientation Vertical **PCB** Locator Yes **PCB** Retention None PCB Thickness - Recommended 1.50mm Packaging Type Carton Pitch - Mating Interface 5.00mm Plating min - Mating 3.048µm Plating min - Termination 3.048µm Polarized to Mating Part Yes Polarized to PCB Yes Shrouded Fully Stackable No Surface Mount Compatible (SMC) No

Temperature Range - Operating -20C to +120C
Termination Interface: Style Through Hole

**Electrical** 

Current - Maximum per Contact 6A Voltage - Maximum 250V

**Material Info** 

**Reference - Drawing Numbers** 

Product Specification PS-93070-001

Sales Drawing SD-93071-001, SD-93073-001

This document was generated on 12/17/2012

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION