

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

22-28-3155

Status:


Active

Overview:

KK® Interconnection System

Description:

2.54mm Pitch KK® Header, Breakaway, Vertical, with Polarizing Wall, 15 Circuits, 0.76µm Gold (Au) Selective Plating, with Kinked PC Tails



Series

image - Reference only

Documents:

- [3D Model](#)
- [Drawing \(PDF\)](#)
- [Product Specification PS-10-07 \(PDF\)](#)
- [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA

LR19980

UL

E29179

General

Product Family

PCB Headers

Series

42225

Application

Signal, Wire-to-Board

Application Tooling Part Link

011201230

Overview

KK® Interconnection System

Product Name

KK®

UPC

800753816633

Physical

Breakaway

Yes

Circuits (Loaded)

15

Circuits (maximum)

15

Color - Resin

Black

Durability (mating cycles max)

100

Flammability

94V-0

Glow-Wire Compliant

No

Lock to Mating Part

None

Material - Metal

Brass

Material - Plating Mating

Gold

Material - Plating Termination

Tin

Material - Resin

Nylon

Net Weight

2.061/g

Number of Rows

1

Orientation

Vertical

PC Tail Length

3.43mm

PCB Locator

No

PCB Retention

Yes

PCB Thickness - Recommended

1.60mm

Packaging Type

Bag

Pitch - Mating Interface

2.54mm

Plating min - Mating

0.762µm

Plating min - Termination

2.540µm

Polarized to Mating Part

Yes

Polarized to PCB

No

Shrouded

Partial

Stackable

No

Temperature Range - Operating

See Product Specification

Termination Interface: Style

Through Hole

Electrical

Current - Maximum per Contact

4A

EU RoHS

ELV and RoHS  
Compliant

REACH SVHC

Not Reviewed

Low-Halogen Status

Not Low-Halogen

China RoHS



Need more information on product  
environmental compliance?

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
For a multiple part number RoHS Certificate of  
Compliance, [click here](#)

Please visit the [Contact Us](#) section for any  
non-product compliance questions.

Search Parts in this Series

42225Series

Mates With

KK® Crimp Housing [2695](#) , [6471](#) , [7880](#) ,  
KK® PC Board Connector [4455](#)

|                                                |                        |
|------------------------------------------------|------------------------|
| Voltage - Maximum                              | 250V                   |
| <b>Solder Process Data</b>                     |                        |
| Duration at Max. Process Temperature (seconds) | 5                      |
| Lead-free Process Capability                   | Wave Capable (TH only) |
| Max. Cycles at Max. Process Temperature        | 1                      |
| Process Temperature max. C                     | 235                    |
| <b>Material Info</b>                           |                        |
| Old Part Number                                | 42225-0190             |
| <b>Reference - Drawing Numbers</b>             |                        |
| Product Specification                          | PS-10-07               |
| Sales Drawing                                  | SD-42225-001           |

This document was generated on 02/22/2013

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**