


Pin Header Sandwich 2,00 mm

Series

151




Rated current	1,5 A
Rated voltage	150 V _{RMS} / V _{DC}
Withstand voltage	500 V _{RMS} for one minute
Material contact	Copper alloy
Material insulator	High temp. thermoplast UL94V-0
Operating temperature	-40°C to +105°C
Max. processing temper.	260°C for 10 seconds

All dimensions in mm.


pitch	2,00
termination	
contact size	□ 0,50
max. pincount	040 / 080

Product group
3

Variation





1



2

PCB Layout



see figure left	see figure left	see figure left	see figure left	available in variation	
A	B	C	L	1	2
14,50	2,50	4,00	8,00	1	2
16,85	2,40	2,45	12,00	1	2
20,50	4,00	2,50	14,00	1	2

Plating:
T = Sn
F = Au
S = Selective Au

* No. of contacts:
Variation 1 = 002 - 040
Variation 2 = 004 - 080

Variation (1,2)

No. of contacts *
(002,... - 080)

Plating contact (T,F,S)

A (1/100 mm)
e.g. 1000 = 10,00 mm



www.mpe-connector.de

Order code:

151-2-2-2-2-0-2-XS0-2-2-2

Mating series	156	159	422	158	413	160
see page	4-14	4-15	4-16	4-17	4-18	6-8