

Pin Header SMD Sandwich 1,27 mm										Series		179	
				Rated current1,0 A Rated voltage100 VRMS / VDC Withstand voltage300 VRMS for one minute Material contactCopper alloy Material insulatorHigh temp. thermoplast UL94V-0 Operating temperature-40°C to +105°C Max. processing temper. 260°C for 10 seconds						pitch		1,27	
										termination			
										contact size		□ 0,40	
										max. pincount		100	
Variation				All dimensions in mm.						PCB Layout			
1													
Positioning peg: 0 = Without peg 1 = With peg Plating: T = Sn F = Au S = Selective Au Cap: 0 = Without cap 1 = With cap				Variation No. of contacts (006,... - 100) Positioning peg (0,1) Plating contact (T,F,S) Cap (0,1) A (1/100 mm) e.g. 1000 = 10,00 mm				see figure left		see figure left			
								A		B			
								5,60		3,00			
								5,68		3,00			
								10,18		7,50			
								6,58		3,00			
								12,75		3,00			
								13,41		3,00			
								5,50		5,50			
								2,60		2,68			
2,68		3,58											
9,75		10,41											
Order code: 179-1-?-?-?-?-XS?-?-?-?													
Mating series		187	185	349									
see page		4-5	4-7	4-8									