

**RADIATION HARDENED
NPN POWER SILICON TRANSISTOR**
Qualified per MIL-PRF-19500/544

*Qualified Levels:
JANSM, JANSJ,
JANSK, JANSL,
JANSR, JANSF*


DESCRIPTION

These RHA level 2N5152L and 2N5154L silicon transistor devices are military Radiation Hardness Assurance qualified up to a JANSF level for high-reliability applications. Microsemi also offers numerous other products to meet higher and lower power voltage regulation applications.

Important: For the latest information, visit our website <http://www.microsemi.com>.


FEATURES


- JEDEC registered 2N5152 and 2N5154.
- JANS RHA qualifications are available per MIL-PRF-19500/544.



TO-5 Package

Also available in:

 **TO-39 Package**
(leaded)
JANS_2N5152 &
JANS_2N5154

 **U3 Package**
(surface mount)
JANS_2N5152U3 &
JANS_2N5154U3

APPLICATIONS / BENEFITS

- High frequency operation.
- Lightweight.
- High-speed power-switching applications.
- High-reliability applications.

MAXIMUM RATINGS

Parameters/Test Conditions	Symbol	Value	Unit
Junction and Storage Temperature	T_J and T_{STG}	-65 to +200	°C
Thermal Resistance Junction-to-Ambient	$R_{\theta JA}$	175	°C/W
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	10	°C/W
Reverse Pulse Energy ⁽¹⁾		15	mJ
Collector Current (dc)	I_C	2	A
Collector to base voltage (static), emitter open	V_{CBO}	100	V
Collector to emitter voltage (static) base open	V_{CEO}	80	V
Emitter to base voltage (static) collector open	V_{EBO}	5.5	V
Steady-State Power Dissipation @ $T_A = +25$ °C	P_D	1	W
Steady-State Power Dissipation @ $T_C = +25$ °C	P_D	10	W

Notes: 1. This rating is based on the capability of the transistors to operate safely in the unclamped inductive load energy test circuit.


MSC – Lawrence
6 Lake Street,
Lawrence, MA 01841
Tel: 1-800-446-1158 or
(978) 620-2600
Fax: (978) 689-0803

MSC – Ireland
Gort Road Business Park,
Ennis, Co. Clare, Ireland
Tel: +353 (0) 65 6840044
Fax: +353 (0) 65 6822298

Website:
www.microsemi.com

MECHANICAL and PACKAGING

- CASE: Hermetically sealed, kovar base, nickel cap.
- TERMINALS: Leads are kovar, nickel plated, and finish is solder dip (Sn63/Pb37).
- MARKING: Part number, date code, manufacturer's ID.
- POLARITY: NPN (see package outline).
- WEIGHT: Approximately 1.14 grams.
- See [Package Dimensions](#) on last page.

PART NOMENCLATURE

SYMBOLS & DEFINITIONS

Symbol	Definition
C_{obo}	Common-base open-circuit output capacitance
I_{CEO}	Collector cutoff current, base open
I_{CEX}	Collector cutoff current, circuit between base and emitter
I_{EBO}	Emitter cutoff current, collector open
h_{FE}	Common-emitter static forward current transfer ratio
V_{CEO}	Collector-emitter voltage, base open
V_{CBO}	Collector-emitter voltage, emitter open
V_{EBO}	Emitter-base voltage, collector open

ELECTRICAL CHARACTERISTICS @ $T_A = +25\text{ }^\circ\text{C}$ unless otherwise noted.
OFF CHARACTERISTICS

Parameters / Test Conditions	Symbol	Min.	Max.	Unit
Collector-Emitter Breakdown Voltage $I_C = 100\text{ mA}, I_B = 0$	$V_{(BR)CEO}$	80		V
Emitter-Base Cutoff Current $V_{EB} = 4.0\text{ V}, I_C = 0$ $V_{EB} = 5.5\text{ V}, I_C = 0$	I_{EBO}		1.0 1.0	μA mA
Collector-Emitter Cutoff Current $V_{CE} = 60\text{ V}, V_{BE} = 0$ $V_{CE} = 100\text{ V}, V_{BE} = 0$	I_{CES}		1.0 1.0	μA mA
Collector-Emitter Cutoff Current $V_{CE} = 40\text{ V}, I_B = 0$	I_{CEO}		50	μA

ON CHARACTERISTICS

Parameters / Test Conditions	Symbol	Min.	Max.	Unit
Forward-Current Transfer Ratio $I_C = 50\text{ mA}, V_{CE} = 5\text{ V}$	h_{FE}	20	--	
2N5152L		50	--	
$I_C = 2.5\text{ A}, V_{CE} = 5\text{ V}$		30	90	
2N5154L		70	200	
$I_C = 5\text{ A}, V_{CE} = 5\text{ V}$		20	--	
2N5154L		40	--	
Collector-Emitter Saturation Voltage $I_C = 2.5\text{ A}, I_B = 250\text{ mA}$ $I_C = 5.0\text{ A}, I_B = 500\text{ mA}$	$V_{CE(sat)}$		0.75 1.5	V
Base-Emitter Voltage Non-Saturation $I_C = 2.5\text{ A}, V_{CE} = 5\text{ V}$	V_{BE}		1.45	V
Base-Emitter Saturation Voltage $I_C = 2.5\text{ A}, I_B = 250\text{ mA}$ $I_C = 5.0\text{ A}, I_B = 500\text{ mA}$	$V_{BE(sat)}$		1.45 2.2	V


DYNAMIC CHARACTERISTICS

Parameters / Test Conditions	Symbol	Min.	Max.	Unit
Magnitude of Common Emitter Small-Signal Short-Circuit Forward Current Transfer Ratio $I_C = 500\text{ mA}, V_{CE} = 5\text{ V}, f = 10\text{ MHz}$	$ h_{fe} $	6		
2N5152L 2N5154L		7		
Small-signal short Circuit Forward-Current Transfer Ratio $I_C = 100\text{ mA}, V_{CE} = 5\text{ V}, f = 1\text{ KHz}$	h_{fe}	20		
2N5152L 2N5154L		50		
Output Capacitance $V_{CB} = 10\text{ V}, I_E = 0, f = 1.0\text{ MHz}$	C_{obo}		250	pF

ELECTRICAL CHARACTERISTICS @ $T_A = +25\text{ }^\circ\text{C}$ unless otherwise noted. (continued)
SWITCHING CHARACTERISTICS

Parameters / Test Conditions	Symbol	Min.	Max.	Unit
Turn-On Time $I_C = 5\text{ A}$, $I_{B1} = 500\text{ mA}$	t_{on}		0.5	μs
Turn-Off Time $R_L = 6\Omega$	t_{off}		1.5	μs
Storage Time $I_{B2} = -500\text{ mA}$	t_s		1.4	μs
Fall Time $V_{BE(OFF)} = 3.7\text{ V}$	t_f		0.5	μs

SAFE OPERATING AREA (See SOA graph below and [MIL-STD-750, method 3053](#))
DC Tests
 $T_C = +25\text{ }^\circ\text{C}$, $t_p = 1.0\text{ s}$, 1 Cycle

Test 1
 $V_{CE} = 5.0\text{ V}$, $I_C = 2.0\text{ A}$
Test 2
 $V_{CE} = 32\text{ V}$, $I_C = 310\text{ mA}$
Test 3
 $V_{CE} = 80\text{ V}$, $I_C = 12.5\text{ mA}$


Maximum Safe Operating Area

ELECTRICAL CHARACTERISTICS @ $T_A = +25\text{ }^\circ\text{C}$, unless otherwise noted (continued)
POST RADIATION ELECTRICAL CHARACTERISTICS

Parameters / Test Conditions	Symbol	Min.	Max.	Unit
Collector to Emitter Cutoff Current $V_{CE} = 40\text{ V}$	I_{CEO}		100	μA
Emitter to Base Cutoff Current $V_{EB} = 4\text{ V}$	I_{EBO}		2.0	μA
Breakdown Voltage, Collector to Emitter $I_C = 100\text{ mA}$	$V_{(BR)CEO}$	80		V
Collector to Emitter Cutoff Current $V_{CE} = 60\text{ V}$	I_{CES}		2.0	μA
Emitter to Base Cutoff Current $V_{EB} = 5.5\text{ V}$	I_{EBO}		2.0	mA
Forward-Current Transfer Ratio ⁽¹⁾ $I_C = 50\text{ mA}$, $V_{CE} = 5\text{ V}$		[10]		
		[25]		
$I_C = 2.5\text{ A}$, $V_{CE} = 5\text{ V}$	$[h_{FE}]$	[15]	90	
		[35]	200	
$I_C = 5\text{ A}$ pulsed, $V_{CE} = 5\text{ V}$		[10]		
		[20]		
Base to Emitter voltage (non-saturated) $V_{CE} = 5\text{ V}$, $I_C = 2.5\text{ A}$, pulsed	V_{BE}		1.45	V
Collector-Emitter Saturation Voltage $I_C = 2.5\text{ mA}$, $I_B = 250\text{ mA}$, pulsed $I_C = 500\text{ mA}$, $I_B = 500\text{ mA}$, pulsed	$V_{CE(sat)}$		0.86 1.73	V
Base-Emitter Saturation Voltage $I_C = 2.5\text{ A}$, $I_B = 250\text{ mA}$, pulsed $I_C = 5\text{ A}$, $I_B = 500\text{ mA}$, pulsed	$V_{BE(sat)}$		1.67 2.53	V

- (1) See method 1019 of MIL-STD-750 for how to determine $[h_{FE}]$ by first calculating the delta ($1/h_{FE}$) from the pre- and post-radiation h_{FE} . Notice the $[h_{FE}]$ is not the same as h_{FE} and cannot be measured directly. The $[h_{FE}]$ value can never exceed the pre-radiation minimum h_{FE} that it is based upon.


GRAPHS


FIGURE 1
Temperature-Power Derating Curve




FIGURE 2
Temperature-Power Derating Curve


GRAPHS (continued)


FIGURE 3
Thermal Impedance ($R_{\theta JA}$)






FIGURE 4
Thermal Impedance ($R_{\theta JC}$)

PACKAGE DIMENSIONS


Symbol	Dimensions				Note
	Inch		Millimeters		
	Min	Max	Min	Max	
CD	.305	.335	7.75	8.51	6
CH	.240	.260	6.10	6.60	
HD	.335	.370	8.51	9.40	
LC	.200 TP		5.08 TP		7
LD	.016	.019	0.41	0.48	8,9
LL	See note 14				
LU	.016	.019	0.41	0.48	8,9
L1		.050		1.27	8,9
L2	.250		6.35		8,9
P	.100		2.54		7
Q		.030		0.76	5
TL	.029	.045	0.74	1.14	3,4
TW	.028	.034	0.71	0.86	3
r		.010		0.25	10
α	45° TP		45° TP		7

NOTES:

- Dimensions are in inches.
- Millimeters are given for general information only.
- Beyond r (radius) maximum, TW shall be held for a minimum length of .011 (0.28 mm).
- Dimension TL measured from maximum HD.
- Body contour optional within zone defined by HD, CD, and Q.
- CD shall not vary more than .010 inch (0.25 mm) in zone P. This zone is controlled for automatic handling.
- Leads at gauge plane .054 +.001 -.000 inch (1.37 +0.03 -0.00 mm) below seating plane shall be within .007 inch (0.18 mm) radius of true position (TP) at maximum material condition (MMC) relative to tab at MMC. The device may be measured by direct methods or by gauging procedure.
- Dimension LU applies between L1 and L2. Dimension LD applies between L2 and LL minimum. Diameter is uncontrolled in and beyond LL minimum.
- All three leads.
- The collector shall be internally connected to the case.
- Dimension r (radius) applies to both inside corners of tab.
- In accordance with ASME Y14.5M, diameters are equivalent to Φx symbology.
- Lead 1 = emitter, lead 2 = base, lead 3 = collector.
- TO-5 dimension LL = 1.5 inches (38.10 mm) min. and 1.75 inches (44.45 mm) max.