miRata

Product Search Data Sheet

Note: This datasheet may be out of date.

Please download the latest datasheet of NCP03XH223J05RL from the official website of Murata Manufacturing Co., Ltd.


https://www.murata.com/en-global/products/productdetail?partno=NCP03XH223J05RL

# NCP03XH223J05RL

In Production Recommended RoHS REACH

### Appearance & Shape





### Applications

Limited Usage	Mobile Application, Tablet PC, Wearable		
Other Usage	<ol> <li>Temperature compensation for transistor, IC and crystal oscillator in mobile communications</li> <li>Temperature sensor for rechargeable batteries</li> </ol>		

### Packaging Information

Packaging	Specifications	Minimum Order Quantity
RL	180mm Paper Tape	15000



- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-Constant
- 4. Reflow soldering possible
- 5. Lead is not contained in the product.
- 6. NCP series are recognized by UL/cUL (UL1434, File No.E137188).



#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



muRata INNOVATOR IN ELECTRONICS

Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of NCP03XH223J05RL from the official website of Murata Manufacturing

Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=NCP03XH223J05RL

# NCP03XH223J05RL

## Specifications

Resistance (25°C)	22kΩ
Resistance Value Tolerance (at 25°C)	±5%
B-Constant (25/50°C)	3380K
B-Constant (25/50°C) Tolerance	±1%
B-Constant(25/80°C)(Reference Value)	3428K
B-Constant(25/85°C)(Reference Value)	3434K
B-Constant(25/100°C)(Reference Value)	3455K
Max. Voltage	5V
Permissive Operating Current (25°C)	0.21mA
Rated Electric Power (25°C)	100.0mW
Typical Dissipation Constant (25°C)	1mW/°C
Operating Temperature Range	-40℃ to 125℃
Size Code (in mm)	0.6x0.3mm
Size Code (in inch)	0.2x0.1inch
Shape	SMD
Mass	0.00026g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

Product Search Data Sheet

Note: This datasheet may be out of date Please download the latest datasheet of

Please download the latest datasheet of NCP03XH223J05RL from the official website of Murata Manufacturing


Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=NCP03XH223J05RL


## NCP03XH223J05RL

Product Data

Rai

INNOVATOR IN ELECTRONI





Resistance-Temperature Characteristics

Maximum Operating Voltage Reduction Characteristics

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
 This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

3 of 3