

Product Search Data Sheet

.

Note: This datasheet may be out of date.

Please download the latest datasheet of DSS1NB32A223Q55# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=DSS1NB32A223Q55%23

DSS1NB32A223Q55#

"#" indicates a package specification code.

In Production RoHS REACH

< List of part numbers with package codes > DSS1NB32A223Q55B





Features

DSS1 series is a compact, high performance lead type 3 terminal capacitor which can be mounted in 2.54mm pitch. Its three terminal structure enables nice high frequency performance. Wide capacitance variation enables flexible selection for various noise frequencies. High speed mounting is available with automatic insertion machine.



Other Usage For general



Packaging	Specifications	Minimum Order Quantity
В	Bulk(Bag)	250

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of DSS1NB32A223Q55# from the official website of Murata Manufacturing Co., Ltd.

Co., Ltd. http://www.murata.com/en-us/products/productdetail?partno=DSS1NB32A223Q55%23

DSS1NB32A223Q55#

"#" indicates a package specification code.

Specifications

muRata

INNOVATOR IN ELECTRONICS

Shape	Lead	
Length	8.5mm	
Length Tolerance	max.	
Width	3.5mm	
Width Tolerance	max.	
Thickness	7.5mm	
Thickness Tolerance	max.	
Rated Current	6A	
Operating Temperature Range	-40°C to 85°C	
Mass(typ.)	0.45g	
Number of Circuit	1	
Insulation Resistance(min.)	1000ΜΩ	
Rated Voltage	100Vdc	
Withstanding Voltage	250Vdc	
Capacitance	22000pF	
Capacitance Tolerance	±10%	
Structure/Shape	Small type beads inside(straight)	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Product Search Data Shee

Note: This datasheet may be out of date

Please download the latest datasheet of DSS1NB32A223Q55# from the official website of Murata Manufacturing Co. Ltd.

Co., Ltd. http://www.murata.com/en-us/products/productdetail?partno=DSS1NB32A223Q55%23

DSS1NB32A223Q55#

"#" indicates a package specification code.



INNOVATOR IN FLECT





Insertion Loss Characteristics

Insertion Loss Characteristics (Main Items)



Equivalent Circuit

3 of 3

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

