muRata Inductor Data Sheet





< List of part numbers with package codes >

LQM21FN4R7M80L , LQM21FN4R7M80K , LQM21FN4R7M80B



References

Packaging code	Specifications	Minimum quantity
L	ф180mm Embossed taping	3000
к	ф330mm Embossed taping	10000
В	Packing in bulk	1000

Mass (Typ.)	
1 piece	0.016g

Specifications

Inductance	4.7μH ±20%
Inductance test frequency	1MHz
Rated current (Itemp) (Based on Temperature rise)	120mA
Max. of DC resistance	0.234Ω
Avg. of DC resistance	0.18Ω±30%
Self resonance frequency (min.)	25MHz
Operating temperature range (Self-temperature rise is not included)	-55~125°C
Class of magnetic shield	Ferrite Core
Series	LQM21FN_80

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Chart of characteristic data (The charts below may show another part number which shares its characteristics.)



10000 10µĤ

Impedance-Frequency characteristics (Typ.)



🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.