Note: This datasheet may be out of date.

Please download the latest datasheet of NXRT15XH103FA5B from the official website of Murata

Manufacturing Co., Ltd.

https://www.murata.com/en-global/products/productdetail?partno=NXRT15XH103FA5B_

NXRT15XH103FA5B_












Appearance & Shape








Features

- 1. NXR series can accurately detect temperature with NCP15 series on the head of parts.
- 2. The insulation coat with polyule than on the surface of lead wire : $100 \mbox{VDC}$.
- 3. You can choose NTC characteristics from NCP15 series.
- 4. The resistance drift is small in the reliability test.
- 5. The production capacity is bigger and NXR is produced in almost all automation line.
- 6. Adopt to Sb regulation







Packaging Information

Packaging	Specifications	Minimum Order Quantity
В	Bulk(Bag)	500

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2018/07/30



Note: This datasheet may be out of date. Please download the latest datasheet of NXRT15XH103FA5B from the official website of Murata

Manufacturing Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=NXRT15XH103FA5B____

NXRT15XH103FA5B____



Resistance (25°C)	10kΩ
Resistance Value Tolerance (at 25°C)	±1%
B-Constant (25/50°C)	3380K
B-Constant (25/50°C) Tolerance	±1%
B-Constant(25/80°C)(Reference Value)	3428K
B-Constant(25/85°C)(Reference Value)	3434K
B-Constant(25/100°C)(Reference Value)	3455K
Maximum Operating Current (25°C)	0.16mA
Rated Electric Power (25°C)	13.0mW
Typical Dissipation Constant (25°C)	2.6mW/°C
Thermal Time Constant	4s
Operating Temperature Range	-40°C to 125°C
Lead Shape	Insulation type
Shape	Lead
Mass	0.09g to 0.15g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering




URL: https://www.murata.com/

NXRT15XH103FA5B_







Resistance-Temperature Characteristics

Temperature Tolenrance VS. Temp.

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

