Note: This datasheet may be out of date.

Please download the latest datasheet of XRCGB48M000F0L00R0 from the official website of Murata

Manufacturing Co., Ltd.

https://www.murata.com/en-global/products/productdetail?partno=XRCGB48M000F0L00R0

XRCGB48M000F0L00R0










Appearance & Shape







Features

The crystal unit that realized small package and highly accurate frequency.

Based on Murata's excellent package technology and high grade quartz crystal elements, achieving small size and high accuracy resonators.

Features

- 1. The series is available in the applications to be necessary for high accuracy resonator. Especially, it is the best for the communication clocks such as S-ATA and USB2.0.
- 2. The resonator is extremerly small size $(2.0 \times 1.6 \times 0.7 \text{ (mm)})$, and contribute to reduction in mounting area.
- 3. The series complies to RoHS directive, being lead-free (phase 3).



Other Usage

Consumer



Packaging Information

Packaging	Specifications	Minimum Order Quantity
R0	180mm Plastic Tape	3000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date.

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ XRCGB48M000F0L00R0 \ from \ the \ official \ website \ of \ Murata}$ $\label{eq:manufacturing} \underline{\text{Co., Ltd.}} \\ \text{https://www.murata.com/en-global/products/productdetail?partno=XRCGB48M000F0L00R0} \\$

XRCGB48M000F0L00R0



Product Type	Crystal Unit	
Series	XRCGB	
Туре	HCR2016	
Frequency	48.0MHz	
Frequency Tolerance	+/-100ppm max. (25+/-3°C)	
Operating Temperature Range	-30℃ to 85℃	
Frequency Shift by Temperature	+/-50ppm max.	
Frequency Aging	+/-50ppm max.	
Equivalent Series Resistance (ESR)	100ohm max.	
Drive Level (DL)	150μW (300μW max.)	
Load Capacitance (Cs)	6pF	
Shape	SMD	
Wash	Not available	
L x W (size)	2.0x1.6mm	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering




URL: https://www.murata.com/

Last updated : 2018/12/04

XRCGB48M000F0L00R0





Temperature Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2018/12/04