muRata	Capacitor Data Sheet	
GRM155R61A225KE01#		"#" indicates a package specification code.

In Production General 85 Cmax. Reflow RoHS REACH 1

GRM155R61A225KE01D , GRM155R61A225KE01W , GRM155R61A225KE01J

Shape		
L size	1.0 ±0.05mm	
W size	0.5 ±0.05mm	
T size	0.5 ±0.05mm	
External terminal width e	0.15 to 0.35mm	
Distance between external terminals g	0.3mm min.	
Size code in inch(mm)	0402 (1005M)	

	NI COLOR
	Notes
5	110103

Derating1

## References

Packaging	Specifications	Minimum quantity
D	φ180mm Paper taping	10000
J	φ330mm Paper taping	50000
W	φ180mm Paper taping (W8P1*) * Width : 8mm, Pocket pitch : 1mm	20000

Mass (typ.)	
1 piece	1.6mg
φ180mm Reel	118g


# Specifications

Capacitance	2.2µF ±10%
Rated voltage	10Vdc
Temperature characteristics (complied standard)	X5R(EIA)
Capacitance change rate	±15.0%
Temperature range of temperature characteristics	-55 to 85℃
Operating temperature range	-55 to 85℃

### \rm Attention

This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

1 of 2



#### 2 of 2

### 🔔 Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.