

Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of DLW43MH201XK2#from the official website of Murata Manufacturing Co., Ltd.

https://www.murata.com/en-global/products/productdetail?partno=DLW43MH201XK2%23

DLW43MH201XK2#

"#" indicates a package specification code.

In Production RoHS REACH AEC-

< List of part numbers with package codes > DLW43MH201XK2K DLW43MH201XK2L DLW43MH201XK2B



Appearance & Shape





(in mm)

Features

- 1. Small size: L4.5xW3.2xT2.7mm (ElAcode: 1812) Tolerance: 0.2mm
- 2. It realized common mode inductance of 200microH (at 0.1MHz) though it is small size.
- 3. Transfer mode conversion characteristics is properly improved.

Applications

Noise countermeasures for the automotive market, in particular for the vehicle LAN BroadR-Reach $\ensuremath{\mathbb{R}}$

Applications

Automotive Usage Powertrain/Safety

Packaging Information

Packaging	Specifications	Minimum Order Quantity
К	330mm Embossed Tape	2500
L	180mm Embossed Tape	500
В	Bulk(Bag)	100

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date

Please download the latest datasheet of DLW43MH201XK2#from the official website of Murata Manufacturing Co., Ltd.

DLW43MH201XK2#

"#" indicates a package specification code.

Specifications

Shape	SMD	Number of Circuit	1
Size Code (in mm)	4532	Common Mode Inductance	200µH-25%/+50% (at 0.1MHz)
Size Code (in inch)	1812	Operating Temperature Range(Self- temperature rise is included)	No
Length	4.5mm		
Length Tolerance	±0.2mm		
Width	3.2mm		
Width Tolerance	±0.2mm		
Thickness	2.7mm		
Thickness Tolerance	±0.2mm		
Rated Current	110mA		
Rated Voltage	20Vdc		
Withstanding Voltage	50Vdc		
DC Resistance(max.)	4.5Ω		
DC Resistance	4.5Ω max.		
Insulation Resistance(min.)	10ΜΩ		
Operating Temperature Range	-40℃ to 105℃		
Mass(typ.)	0.16g		

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date

Please download the latest datasheet of DLW43MH201XK2#from the official website of Murata Manufacturing Co. Ltd.

Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=DLW43MH201XK2%23

DLW43MH201XK2#

"#" indicates a package specification code.







Impedance-Frequency Characteristics

Equivalent Circuit

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

3 of 3