

Note: This datasheet may be out of date.

Please download the latest datasheet of DLW5BTZ142TQ2#from the official website of Murata Manufacturing

Co., Ltd.

https://www.murata.com/en-global/products/productdetail?partno=DLW5BTZ142TQ2%23

DLW5BTZ142TQ2#

"#" indicates a package specification code.










< List of part numbers with package codes >

DLW5BTZ142TQ2K DLW5BTZ142TQ2L DLW5BTZ142TQ2B



Appearance & Shape







Features

- 1. Low profile (h=2.5mm)
- 2. Small size (5.0x5.0mm) and high rated current (1.5 to 4A)
- 3. High common mode Impedance (max. 1400 ohm, at 100MHz)
- 4 ·Operating Temperature Range -40°C to +105°C

Applications

Automotive
Usage

Infotainment



Packaging Information

Packaging	Specifications	Minimum Order Quantity
K	330mm Embossed Tape	2500
L	180mm Embossed Tape	700
В	Bulk(Bag)	100

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/07/18



Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=DLW5BTZ142TQ2%23

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ DLW5BTZ142TQ2\# from \ the \ official \ website \ of \ Murata \ Manufacturing} }$

DLW5BTZ142TQ2#

"#" indicates a package specification code.

Note: This datasheet may be out of date



Shape	SMD
Size Code (in mm)	5050
Size Code (in inch)	2020
Length	5.0mm
Length Tolerance	±0.3mm
Width	5.0mm
Width Tolerance	±0.3mm
Thickness	2.35mm
Thickness Tolerance	±0.15mm
Common Mode Impedance (at 100MHz)	1400Ω
Common Mode Impedance (at 100MHz) Tolerance	(Тур.)
Common Mode Impedance (at 10MHz)	100Ω
Common Mode Impedance (at 10MHz) Tolerance	min.
Rated Current	1.5A
Rated Voltage	50Vdc
Withstanding Voltage	125Vdc
DC Resistance(max.)	0.056Ω

DC Resistance	0.056Ω max.
Insulation Resistance(min.)	10ΜΩ
Operating Temperature Range	-40℃ to 105℃
Mass(typ.)	0.21g
Number of Circuit	1
Operating Temperature Range(Self-temperature rise is included)	No

2 of 3

Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/07/18


^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


https://www.murata.com/en-global/products/productdetail?partno=DLW5BTZ142TQ2%23

DLW5BTZ142TQ2#

"#" indicates a package specification code.








Impedance-Frequency Characteristics

Impedance-Frequency Characteristics (Main Items)



Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/07/18