Note: This datasheet may be out of date

Please download the latest datasheet of NFA21SL207X1A45# from the official website of Murata Manufacturing

https://www.murata.com/en-global/products/productdetail?partno=NFA21SL207X1A45%23

### NFA21SL207X1A45#

"#" indicates a package specification code.








< List of part numbers with package codes > NFA21SL207X1A45B NFA21SL207X1A45L



### Appearance & Shape







### **Features**

- 1. Steep insertion loss characteristics
- 2. Suitable for noise suppression in 800MHz or higher frequency
- 3. Size: 2.0x1.25mm
- 4. 4 circuits in one package

**Applications** 

Noise suppression for LCD line



Other Usage

For general



# Packaging Information

Packaging	Specifications	Minimum Order Quantity
В	Bulk(Bag)	1000
L	180mm Embossed Tape	4000

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2019/07/18

Note: This datasheet may be out of date.


 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ NFA21SL207X1A45\# from \ the \ official \ website \ of \ Murata \ Manufacturing} }$ 

Insertion Loss

 $\underline{\text{Co., Ltd.}} \\ \text{https://www.murata.com/en-global/products/productdetail?partno=NFA21SL207X1A45\%23} \\$ 

### NFA21SL207X1A45#

"#" indicates a package specification code.



Shape	SMD
Size Code (in mm)	2012
Size Code (in inch)	0805
Length	2.0mm
Length Tolerance	±0.1mm
Width	1.25mm
Width Tolerance	±0.1mm
Thickness	0.5mm
Thickness Tolerance	±0.1mm
Rated Current	100mA
Operating Temperature Range	-55℃ to 125℃
Mass(typ.)	0.007g
Number of Circuit	4
Rated Voltage	10Vdc
Withstanding Voltage	30Vdc
Insulation Resistance(min.)	1000ΜΩ
Nominal Cut-off Frequency	200MHz

2dB to 7dB(at Cut-off Frequency) 13dB min.(at 500MHz) 25dB min.(at 800MHz) 25dB min.(at 1000MHz)

2 of 3

#### Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/07/18

<sup>1.</sup> This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


Note: This datasheet may be out of date  $\underline{ \text{Please download the latest datasheet of NFA21SL207X1A45\# from the official website of Murata Manufacturing} \\$ 


https://www.murata.com/en-global/products/productdetail?partno=NFA21SL207X1A45%23

# NFA21SL207X1A45#

"#" indicates a package specification code.








Insertion Loss Characteristics

Insertion Loss Characteristics (Main Items)



**Equivalent Circuit** 

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/07/18