

Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of BLM21AG331SH1# from the official website of Murata Manufacturing Co., Ltd.

https://www.murata.com/en-global/products/productdetail?partno=BLM21AG331SH1%23

BLM21AG331SH1#

"#" indicates a package specification code.

Features

connection to ground.

The chip ferrite beads BLM series is designed to

function nearly as a resistor at noise frequencies, which greatly reduces the possibility of resonance and

BLM series is effective in circuits without stable

ground lines because BLM series does not need a

electrodes provides excellent solder heat resistance.

relatively low frequencies. Therefore BLM_Aseries is

effective in noise suppression in a wide frequency

BLM_Aseries generates an impedance from the

leaves signal wave forms undistorted.

The nickel barrier structure of the external

range (30MHz to several hundred MHz).




< List of part numbers with package codes > BLM21AG331SH1J BLM21AG331SH1D BLM21AG331SH1B



Appearance & Shape





(in mm)



Automotive Usage Powertrain/Safety

Packaging Information

Packaging	Specifications	Minimum Order Quantity
J	330mm Paper Tape	10000
D	180mm Paper Tape	4000
В	Bulk(Bag)	1000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date

Please download the latest datasheet of BLM21AG331SH1# from the official website of Murata Manufacturing Co. Ltd.

Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=BLM21AG331SH1%23

BLM21AG331SH1#

"#" indicates a package specification code.

Specifications

Shape	SMD
Size Code (in mm)	2012
Size Code (in inch)	0805
Length	2.0mm
Length Tolerance	±0.2mm
Width	1.25mm
Width Tolerance	±0.2mm
Thickness	0.85mm
Thickness Tolerance	±0.2mm
Impedance (at 100MHz)	330Ω
Impedance (at 100MHz) Tolerance	±25%
Rated Current (at 85°C)	800mA
Rated Current (at 125°C)	800mA
DC Resistance(max.)	0.15Ω
Operating Temperature Range	-55℃ to 125℃
Mass(typ.)	0.01g
Number of Circuit	1

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance onlice. Please check with our sales representatives or product engineers before ordering

without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Product Search Data Sheet

Note: This datasheet may be out of date.


Please download the latest datasheet of BLM21AG331SH1# from the official website of Murata Manufacturing Co., Ltd.


Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=BLM21AG331SH1%23

BLM21AG331SH1#

"#" indicates a package specification code.

Product Data





Impedance-Frequency Characteristics

Equivalent Circuit

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



3 of 3