

Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of NFE31PT152Z1E9# from the official website of Murata Manufacturing Co., Ltd.

https://www.murata.com/en-global/products/productdetail?partno=NFE31PT152Z1E9%23

NFE31PT152Z1E9#

"#" indicates a package specification code.

In Production RoHS REACH

< List of part numbers with package codes > NFE31PT152Z1E9L NFE31PT152Z1E9K NFE31PT152Z1E9B

0.7±0.2

(1)

1.0±0.2

(2)

3.2±0.35

0.7±0.2 (3)

1.6±0.15

1.6±0.15

: Electrode

(in mm)





The chip "EMIFIL" NFE31PT is a small size T-type circuit EMI suppression filter.

Features

- 1. Its large rated current of 6A and low voltage drop due to small DC resistance are suitable for DC power line use.
- 2. The feedthrough capacitor realizes excellent high frequency characteristics.
- 3. The structure incorporates built-in ferrite beads which minimize resonance with surrounding circuits.
- 4. 22 to 2,200pF lineups can be used in signal lines.



Packaging Information

Packaging	Specifications	Minimum Order Quantity
L	180mm Embossed Tape	2000
К	330mm Embossed Tape	8000
В	Bulk(Bag)	500

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date

Please download the latest datasheet of NFE31PT152Z1E9# from the official website of Murata Manufacturing Co. Ltd.

Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=NFE31PT152Z1E9%23

NFE31PT152Z1E9#

"#" indicates a package specification code.

Specifications

Shape	SMD	Capacitance Tolerance	50/-20%
Size Code (in mm)	3216		
Size Code (in inch)	1206		
Length	3.2mm		
Length Tolerance	±0.35mm		
Width	1.6mm		
Width Tolerance	±0.15mm		
Thickness	1.6mm		
Thickness Tolerance	±0.15mm		
Rated Current	6A		
Operating Temperature Range	-40℃ to 85℃		
Mass(typ.)	0.034g		
Number of Circuit	1		
Insulation Resistance(min.)	1000ΜΩ		
Rated Voltage	25Vdc		
Withstanding Voltage	62.5Vdc		
Capacitance	1500pF		

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date

Please download the latest datasheet of NFE31PT152Z1E9# from the official website of Murata Manufacturing Co., Ltd.


https://www.murata.com/en-global/products/productdetail?partno=NFE31PT152Z1E9%23


NFE31PT152Z1E9#

"#" indicates a package specification code.




INNOVATOR IN FLECT





Insertion Loss Characteristics

Insertion Loss Characteristics (Main Items)



Equivalent Circuit

3 of 3

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

