Note: This datasheet may be out of date

Please download the latest datasheet of DLW5ATZ501MQ2#from the official website of Murata Manufacturing

https://www.murata.com/en-global/products/productdetail?partno=DLW5ATZ501MQ2%23

DLW5ATZ501MQ2#

"#" indicates a package specification code.










< List of part numbers with package codes >

DLW5ATZ501MQ2K DLW5ATZ501MQ2L DLW5ATZ501MQ2B



Appearance & Shape







- 1. Low profile(h=2.35mm max.)
- 2. Small size(5.0x3.6mm)
- 3 Large Current Available (1.5Ato 4A)
- 4 ·Operating Temperature Range -40°C to +105°C
- 5 ·Reflow and Flow soldering Available

Applications

Automotive
Usage

Infotainment



Packaging Information

Packaging	Specifications	Minimum Order Quantity
K	330mm Embossed Tape	2500
L	180mm Embossed Tape	700
В	Bulk(Bag)	100

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2019/07/18

Note: This datasheet may be out of date

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ DLW5ATZ501MQ2\# from \ the \ official \ website \ of \ Murata \ Manufacturing} }$ Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=DLW5ATZ501MQ2%23

DLW5ATZ501MQ2#

"#" indicates a package specification code.



Shape	SMD
Size Code (in mm)	5036
Size Code (in inch)	2014
Length	5.0mm
Length Tolerance	±0.3mm
Width	3.6mm
Width Tolerance	±0.3mm
Thickness	2.2mm
Thickness Tolerance	±0.15mm
Common Mode Impedance (at 100MHz)	500Ω
Common Mode Impedance (at 100MHz) Tolerance	(Тур.)
Common Mode Impedance (at 10MHz)	35Ω
Common Mode Impedance (at 10MHz) Tolerance	min.
Rated Current	2A
Rated Voltage	50Vdc
Withstanding Voltage	125Vdc
DC Resistance(max.)	0.034Ω

DC Resistance	0.034Ω max.		
Insulation Resistance(min.)	10ΜΩ		
Operating Temperature Range	-40°C to 105°C		
Mass(typ.)	0.14g		
Number of Circuit	1		
Operating Temperature Range(Self- temperature rise is included)	No		

2 of 3

Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/07/18


^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


https://www.murata.com/en-global/products/productdetail?partno=DLW5ATZ501MQ2%23

DLW5ATZ501MQ2#

"#" indicates a package specification code.








Impedance-Frequency Characteristics

Impedance-Frequency Characteristics (Main Items)



Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/