Note: This datasheet may be out of date

Please download the latest datasheet of NFE31ZT101C1E9# from the official website of Murata Manufacturing

https://www.murata.com/en-global/products/productdetail?partno=NFE31ZT101C1E9%23

### NFE31ZT101C1E9#

"#" indicates a package specification code.










< List of part numbers with package codes >

NFE31ZT101C1E9L NFE31ZT101C1E9K NFE31ZT101C1E9B



### Appearance & Shape









## **Features**

The chip "EMIFIL" NFE31ZT is a small size T-type circuit EMI suppression filter.

- 1. Its large rated current of 6A and low voltage drop due to small DC resistance are suitable for DC power line use.
- 2. The feedthrough capacitor realizes excellent high frequency characteristics.
- 3. The structure incorporates built-in ferrite beads which minimize resonance with surrounding circuits.
- 4. 22 to 2,200pF lineups can be used in signal lines.

# Applications

Automotive
Usage

Infotainment



### Packaging Information

Packaging	Specifications	Minimum Order Quantity
L	180mm Embossed Tape	2000
К	330mm Embossed Tape	8000
В	Bulk(Bag)	500

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2019/07/18

 $\underline{\text{Co., Ltd.}} \\ \text{https://www.murata.com/en-global/products/productdetail?partno=NFE31ZT101C1E9\%23} \\$ 

## NFE31ZT101C1E9#

"#" indicates a package specification code.

Capacitance Tolerance



Shape	SMD
Size Code (in mm)	3216
Size Code (in inch)	1206
Length	3.2mm
Length Tolerance	±0.35mm
Width	1.6mm
Width Tolerance	±0.15mm
Thickness	1.6mm
Thickness Tolerance	±0.15mm
Rated Current	6A
Operating Temperature Range	-40℃ to 85℃
Mass(typ.)	0.034g
Number of Circuit	1
Insulation Resistance(min.)	1000ΜΩ
Rated Voltage	25Vdc
Withstanding Voltage	62.5Vdc
Capacitance	100pF

80/-20%

2 of 3

### Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/07/18

<sup>1.</sup> This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


Note: This datasheet may be out of date  $\underline{ \text{Please download the latest datasheet of NFE31ZT101C1E9\# from the official website of Murata Manufacturing} \\$ 


https://www.murata.com/en-global/products/productdetail?partno=NFE31ZT101C1E9%23

## NFE31ZT101C1E9#

"#" indicates a package specification code.








Insertion Loss Characteristics

Insertion Loss Characteristics (Main Items)



**Equivalent Circuit** 

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/