

Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of NFA21SL287V1A45# from the official website of Murata Manufacturing Co., Ltd.


https://www.murata.com/en-global/products/productdetail?partno=NFA21SL287V1A45%23


NFA21SL287V1A45#

"#" indicates a package specification code.

In Production RoHS REACH

< List of part numbers with package codes > NFA21SL287V1A45B NFA21SL287V1A45L





- 1. Steep insertion loss characteristics
- 2. Suitable for noise suppression in 800MHz or higher frequency

3. Size: 2.0x1.25mm

4.4 circuits in one package

Applications Noise suppression for LCD line

Applications

Other Usage

For general

Packaging Information

Packaging	Specifications	Minimum Order Quantity
В	Bulk(Bag)	1000
L	180mm Embossed Tape	4000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date.

Please download the latest datasheet of NFA21SL287V1A45# from the official website of Murata Manufacturing Co. Ltd.

Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=NFA21SL287V1A45%23

NFA21SL287V1A45#

"#" indicates a package specification code.

Specifications

Shape	SMD	Insertion Loss	6dB max.(at Cut-off Frequency 25dB min.(at 800MHz)
Size Code (in mm)	2012		25dB min.(at 900MHz)
Size Code (in inch)	0805		
Length	2.0mm		
Length Tolerance	±0.1mm		
Width	1.25mm		
Width Tolerance	±0.1mm		
Thickness	0.5mm		
Thickness Tolerance	±0.1mm		
Rated Current	100mA		
Operating Temperature Range	-55℃ to 125℃		
Mass(typ.)	0.007g		
Number of Circuit	4]	
Rated Voltage	10Vdc]	
Withstanding Voltage	30Vdc]	
Insulation Resistance(min.)	1000ΜΩ]	
Nominal Cut-off Frequency	280MHz		

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



INNOVATOR IN ELECTRONICS


Note: This datasheet may be out of date. <u>Please download the latest datasheet of NFA21SL287V1A45# from the official website of Murata Manufacturing</u> Co., Ltd.


https://www.murata.com/en-global/products/productdetail?partno=NFA21SL287V1A45%23

NFA21SL287V1A45#

"#" indicates a package specification code.


Product Data





Insertion Loss Characteristics

Insertion Loss Characteristics (Main Items)



Equivalent Circuit

3 of 3

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

