

Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of NFE61PT102E1H9# from the official website of Murata Manufacturing Co., Ltd.

https://www.murata.com/en-global/products/productdetail?partno=NFE61PT102E1H9%23

NFE61PT102E1H9#

"#" indicates a package specification code.

In Production REACH RoHS

< List of part numbers with package codes > NFE61PT102E1H9L NFE61PT102E1H9K NFE61PT102E1H9B

0.7±0.2

0.7±0.2

(3)

1.6±0.3

: Electrode

(in mm)

2.6±0.3

(2)

6.8±0.5





The chip "EMIFIL" NFE61PT is a T-type circuit EMI suppression filter.

Features

- 1. Its large rated current of 2A and low voltage drop due to small DC resistance are suitable for DC power line use.
- 2. The feedthrough capacitor realizes excellent high frequency characteristics.
- 3. The structure incorporates built-in ferrite beads which minimize resonance with surrounding circuits.
- 4.33 to 4,700pF lineups can be used in signal lines.



Applications

Packaging Information

Packaging	Specifications	Minimum Order Quantity
L	180mm Embossed Tape	2500
К	330mm Embossed Tape	8000
В	Bulk(Bag)	500

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date

Please download the latest datasheet of NFE61PT102E1H9# from the official website of Murata Manufacturing Co. Ltd.

Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=NFE61PT102E1H9%23

NFE61PT102E1H9#

"#" indicates a package specification code.

Specifications

Shape	SMD	Capacitance Tolerance	80/-20%
Size Code (in mm)	6816		
Size Code (in inch)	2706		
Length	6.8mm		
Length Tolerance	±0.5mm		
Width	1.6mm		
Width Tolerance	±0.3mm		
Thickness	1.6mm		
Thickness Tolerance	±0.3mm		
Rated Current	2A		
Operating Temperature Range	-40℃ to 85℃		
Mass(typ.)	0.062g		
Number of Circuit	1		
Insulation Resistance(min.)	1000ΜΩ		
Rated Voltage	50Vdc		
Withstanding Voltage	125Vdc		
Capacitance	1000pF		

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date

Please download the latest datasheet of NFE61PT102E1H9# from the official website of Murata Manufacturing Co., Ltd.


https://www.murata.com/en-global/products/productdetail?partno=NFE61PT102E1H9%23


NFE61PT102E1H9#

"#" indicates a package specification code.




INNOVATOR IN ELECTRON





Insertion Loss Characteristics

Insertion Loss Characteristics (Main Items)



Equivalent Circuit

3 of 3

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

