Note: This datasheet may be out of date

Please download the latest datasheet of DSS1NB32A681Q55# from the official website of Murata Manufacturing

https://www.murata.com/en-global/products/productdetail?partno=DSS1NB32A681Q55%23

DSS1NB32A681Q55#

"#" indicates a package specification code.








< List of part numbers with package codes > DSS1NB32A681Q55B



Appearance & Shape





Features

DSS1 series is a compact, high performance lead type 3 terminal capacitor which can be mounted in 2.54mm pitch.

Its three terminal structure enables nice high frequency performance.

Wide capacitance variation enables flexible selection for various noise frequencies. High speed mounting is available with automatic insertion machine.

Applications

Other Usage

For general



Packaging Information

Packaging	Specifications	Minimum Order Quantity
В	Bulk(Bag)	250

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ DSS1NB32A681Q55\# from \ the \ official \ website \ of \ Murata \ Manufacturing} }$ $\underline{Co., Ltd.} \\ https://www.murata.com/en-global/products/productdetail?partno=DSS1NB32A681Q55\%23$

DSS1NB32A681Q55#

"#" indicates a package specification code.



Shape	Lead	
Length	8.5mm	
Length Tolerance	max.	
Width	3.5mm	
Width Tolerance	max.	
Thickness	7.5mm	
Thickness Tolerance	max.	
Rated Current	6A	
Operating Temperature Range	-40°C to 85°C	
Mass(typ.)	0.45g	
Number of Circuit	1	
Insulation Resistance(min.)	1000ΜΩ	
Rated Voltage	100Vdc	
Withstanding Voltage	250Vdc	
Capacitance	680pF	
Capacitance Tolerance	±10%	
Structure/Shape	Small type beads inside(straight)	

2 of 3

Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/07/18

^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Note: This datasheet may be out of date


 $\underline{ \text{Please download the latest datasheet of DSS1NB32A681Q55\# from the official website of Murata Manufacturing} \\$


https://www.murata.com/en-global/products/productdetail?partno=DSS1NB32A681Q55%23

DSS1NB32A681Q55#

"#" indicates a package specification code.








Insertion Loss Characteristics

Insertion Loss Characteristics (Main Items)



Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/07/18