Note: This datasheet may be out of date

Please download the latest datasheet of NFE61PT680B1H9# from the official website of Murata Manufacturing Co., Ltd.

https://www.murata.com/en-global/products/productdetail?partno=NFE61PT680B1H9%23

NFE61PT680B1H9#

"#" indicates a package specification code.








< List of part numbers with package codes >

NFE61PT680B1H9L NFE61PT680B1H9K NFE61PT680B1H9B



Appearance & Shape





: Electrode



The chip "EMIFIL" NFE61PT is a T-type circuit EMI suppression filter.

Features

- Its large rated current of 2A and low voltage drop due to small DC resistance are suitable for DC power line use.
- 2. The feedthrough capacitor realizes excellent high frequency characteristics.
- 3. The structure incorporates built-in ferrite beads which minimize resonance with surrounding circuits.
- 4. 33 to 4,700pF lineups can be used in signal lines.



Other Usage

For general



Packaging Information

Packaging	Specifications	Minimum Order Quantity
L	180mm Embossed Tape	2500
К	330mm Embossed Tape	8000
В	Bulk(Bag)	500

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/07/18

Note: This datasheet may be out of date $\underline{ Please \ download \ the \ latest \ datasheet \ of \ NFE61PT680B1H9\# \ from \ the \ official \ website \ of \ Murata \ Manufacturing} }$

±30%

 $\underline{\text{Co., Ltd.}} \\ \text{https://www.murata.com/en-global/products/productdetail?partno=NFE61PT680B1H9\%23} \\$

NFE61PT680B1H9#

"#" indicates a package specification code.

Capacitance Tolerance



Shape	SMD
Size Code (in mm)	6816
Size Code (in inch)	2706
Length	6.8mm
Length Tolerance	±0.5mm
Width	1.6mm
Width Tolerance	±0.3mm
Thickness	1.6mm
Thickness Tolerance	±0.3mm
Rated Current	2A
Operating Temperature Range	-40°C to 85°C
Mass(typ.)	0.062g
Number of Circuit	1
Insulation Resistance(min.)	1000ΜΩ
Rated Voltage	50Vdc
Withstanding Voltage	125Vdc
Capacitance	68pF

2 of 3

Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/07/18

^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


https://www.murata.com/en-global/products/productdetail?partno=NFE61PT680B1H9%23


NFE61PT680B1H9#

"#" indicates a package specification code.

Note: This datasheet may be out of date








Insertion Loss Characteristics

Insertion Loss Characteristics (Main Items)



Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/07/18