

Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of BLM18BB100SZ1# from the official website of Murata Manufacturing Co., Ltd.

https://www.murata.com/en-global/products/productdetail?partno=BLM18BB100SZ1%23

BLM18BB100SZ1#


"#" indicates a package specification code.



< List of part numbers with package codes > BLM18BB100SZ1J BLM18BB100SZ1D BLM18BB100SZ1B

0.4±0.2

1.6±0.15





0.8±0.

: Electrode

(in mm)

0.8±0.15

The chip ferrite beads BLM series is designed to work nearly as a resistor at noise frequencies, which greatly reduces the possibility of resonance and leaves signal wave forms undistorted. BLM series is effective in circuits without stable ground lines because BLM series does not need a connection to ground.

BLM_B series can minimize attenuation of the signal waveform due to its sharp impedance characteristics. Various impedances are available to match signal frequency.

The nickel barrier structure of the external electrodes provides excellent solder heat resistance.



Automotive Usage	Infotainment
---------------------	--------------

Packaging Information

Packaging	Specifications	Minimum Order Quantity
J	330mm Paper Tape	10000
D	180mm Paper Tape	4000
В	Bulk(Bag)	1000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date.

Please download the latest datasheet of BLM18BB100SZ1# from the official website of Murata Manufacturing

Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=BLM18BB100SZ1%23

BLM18BB100SZ1#

"#" indicates a package specification code.



D_

SMD Shape 1608 Size Code (in mm) Length 1.6mm Length Tolerance ±0.15mm Width 0.8mm Width Tolerance ±0.15mm Thickness 0.8mm Thickness Tolerance ±0.15mm Impedance (at 100MHz) 10Ω Impedance (at 100MHz) Tolerance ±25% Rated Current (at 85°C) 700mA 700mA Rated Current (at 125°C) DC Resistance(max.) 0.1Ω Operating Temperature Range -55℃ to 125℃ Mass(typ.) 0.005g Number of Circuit 1

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Product Search Data Sheet

Note: This datasheet may be out of date.


Please download the latest datasheet of BLM18BB100SZ1# from the official website of Murata Manufacturing Co. Ltd.


Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=BLM18BB100SZ1%23

BLM18BB100SZ1#

"#" indicates a package specification code.







Impedance-Frequency Characteristics

Equivalent Circuit

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



3 of 3