Note: This datasheet may be out of date

Please download the latest datasheet of BLE32PN260SH1# from the official website of Murata Manufacturing

Co., Ltd

https://www.murata.com/en-global/products/productdetail?partno=BLE32PN260SH1%23

### BLE32PN260SH1#

"#" indicates a package specification code.










< List of part numbers with package codes >

BLE32PN260SH1L BLE32PN260SH1K BLE32PN260SH1B



### Appearance & Shape







- 1.Bead inductor BLE series is designed to function nearly as a resistor at noise frequencies, which greatly reduces the possibility of resonance and leaves signal wave forms undistorted.
- 2.The nickel barrier structure of the external electrodes provides excellent solder heat resistance.
- 3.BLE32PN series can be used in high current circuits due to its low DC resistance. It can match power lines to a maximum of 10ADC.

# Applications

| Automotive |
|------------|
| Usage      |

Powertrain/Safety



## Packaging Information

| Packaging | Specifications      | Minimum<br>Order Quantity |
|-----------|---------------------|---------------------------|
| L         | 180mm Embossed Tape | 1500                      |
| K         | 330mm Embossed Tape | 7000                      |
| В         | Bulk(Bag)           | 1000                      |

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2019/09/05

### Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=BLE32PN260SH1%23

# BLE32PN260SH1#

"#" indicates a package specification code.



| Shape                           | SMD           |
|---------------------------------|---------------|
| Size Code (in mm)               | 3225          |
| Size Code (in inch)             | 1210          |
| Length                          | 3.2mm         |
| Length Tolerance                | ±0.2mm        |
| Width                           | 2.5mm         |
| Width Tolerance                 | ±0.2mm        |
| Thickness                       | 1.5mm         |
| Thickness Tolerance             | +0.1mm/-0.2mm |
| Impedance (at 100MHz)           | 26Ω           |
| Impedance (at 100MHz) Tolerance | ±10Ω          |
| Rated Current (at 85°C)         | 10A           |
| Rated Current (at 125°C)        | 10A           |
| DC Resistance(max.)             | 1.6mΩ         |
| Operating Temperature Range     | -55℃ to 125℃  |
| Mass(typ.)                      | 0.06g         |
| Number of Circuit               | 1             |

2 of 3

#### Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/09/05


<sup>1.</sup> This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=BLE32PN260SH1%23

# BLE32PN260SH1#

"#" indicates a package specification code.







Impedance-Frequency Characteristics

**Equivalent Circuit** 

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

