

Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of BLM15HB221SH1# from the official website of Murata Manufacturing Co., Ltd.


https://www.murata.com/en-global/products/productdetail?partno=BLM15HB221SH1%23


BLM15HB221SH1#

"#" indicates a package specification code.

In Production RoHS REACH AEC-

< List of part numbers with package codes > BLM15HB221SH1J BLM15HB221SH1B BLM15HB221SH1D





1. Small size: 1.0x0.5mm

(in mm)

- 2. Suitable for noise suppression in 1GHz or higher frequency.
- 3. No Lead production using Ni+Sn plating in termination.

Applications

Automotive Usage	Powertrain/Safety
---------------------	-------------------

Packaging Information

Packaging	Specifications	Minimum Order Quantity
J	330mm Paper Tape	50000
В	Bulk(Bag)	1000
D	180mm Paper Tape	10000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date

Please download the latest datasheet of BLM15HB221SH1# from the official website of Murata Manufacturing Co. Ltd.

Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=BLM15HB221SH1%23

BLM15HB221SH1#

"#" indicates a package specification code.

Specifications

Shape	SMD	Mass(typ.)	0.001g
Size Code (in mm)	1005	Number of Circuit	1
Size Code (in inch)	0402		*
Length	1.0mm		
Length Tolerance	±0.05mm		
Width	0.5mm		
Width Tolerance	±0.05mm		
Thickness	0.5mm		
Thickness Tolerance	±0.05mm		
Impedance (at 100MHz)	220Ω		
Impedance (at 100MHz) Tolerance	±25%		
Impedance (at 1GHz)	900Ω		
Impedance (at 1GHz) Tolerance	±40%		
Rated Current (at 85°C)	250mA		
Rated Current (at 125°C)	250mA		
DC Resistance(max.)	1Ω		
Operating Temperature Range	-55℃ to 125℃		
		-	

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

2 of 3



Product Search Data Sheet

Note: This datasheet may be out of date.


Please download the latest datasheet of BLM15HB221SH1# from the official website of Murata Manufacturing Co. Ltd.


Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=BLM15HB221SH1%23

BLM15HB221SH1#

"#" indicates a package specification code.







Impedance-Frequency Characteristics

Equivalent Circuit

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

3 of 3