

Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of BLM15GG221SZ1# from the official website of Murata Manufacturing Co., Ltd.


https://www.murata.com/en-global/products/productdetail?partno=BLM15GG221SZ1%23

BLM15GG221SZ1#

"#" indicates a package specification code.

In Production RoHS REACH AEC-

< List of part numbers with package codes > BLM15GG221SZ1J BLM15GG221SZ1B BLM15GG221SZ1D





Chip ferrite beads for high frequency noise suppression over a wide frequency range.

Features

0.5±0.05

: Electrode

(in mm)

- 1. High impedance characteristic in 1GHz or higher frequency.
- 2. High impedance characteristic over a wide frequency band range of 100MHz to 6GHz.
- 3. Small decrease in impedance during current loading, resulting in small impedance fluctuation during equipment operation.
- 4. Reflow soldering only.

Applications

Automotive Usage	Infotainment
---------------------	--------------

Packaging Information

Packaging	Specifications	Minimum Order Quantity
J	330mm Paper Tape	50000
В	Bulk(Bag)	1000
D	180mm Paper Tape	10000

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Please download the latest datasheet of BLM15GG221SZ1# from the official website of Murata Manufacturing

Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=BLM15GG221SZ1%23

BLM15GG221SZ1#

"#" indicates a package specification code.

Specifications

Chana	SMD	_	
Shape	SMD		Mass(typ.)
Size Code (in mm)	1005		Number of Circuit
Size Code (in inch)	0402		
Length	1.0mm		
Length Tolerance	±0.05mm		
Width	0.5mm		
Width Tolerance	±0.05mm		
Thickness	0.5mm		
Thickness Tolerance	±0.05mm		
Impedance (at 100MHz)	220Ω		
Impedance (at 100MHz) Tolerance	±25%		
Impedance (at 1GHz)	600Ω		
Impedance (at 1GHz) Tolerance	±40%		
Rated Current (at 85°C)	300mA		
Rated Current (at 125°C)	300mA		
DC Resistance(max.)	0.7Ω		
Operating Temperature Range	-55℃ to 125℃		

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance onlice. Please check with our sales representatives or product engineers before ordering

without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date. Please download the latest datasheet of BLM15GG221SZ1# from the official website of Murata Manufacturing


Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=BLM15GG221SZ1%23


BLM15GG221SZ1#

"#" indicates a package specification code.

Product Data

Ų_





Impedance-Frequency Characteristics

Equivalent Circuit

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

3 of 3